

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

DINITROL 447 Light Grey

UFI: 7Y3F-Y0NK-400R-2S33

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Anti-corrosive coating

1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
e-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

1.4. Emergency telephone number: Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 2; H225
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H336
STOT RE 2; H373
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
xylene
ethyl acetate
Hydrocarbons, C9, aromatics

Signal word: Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 2 of 16

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves and eye/face protection.
- P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml**Signal word:**

Danger

Pictograms:**2.3. Other hazards**

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 3 of 16

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			25 - < 30 %
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
1330-20-7	xylene			10 - < 15 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
141-78-6	ethyl acetate			5 - < 10 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
64742-95-6	Hydrocarbons, C9, aromatics			1 - < 5 %
	918-668-5	649-356-00-4	01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
7779-90-0	trizinc bis(orthophosphate)			1 - < 5 %
	231-944-3	030-011-00-6	01-2119485044-40	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
13463-67-7	Titanium dioxide			< 1 %
	236-675-5			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	25 - < 30 %
	inhalation: LC50 = > 25 mg/l (vapours); dermal: LD50 = >2920 mg/kg; oral: LD50 = > 5840 mg/kg		
1330-20-7	215-535-7	xylene	10 - < 15 %
	inhalation: LC50 = 10-20 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 8700 mg/kg		
141-78-6	205-500-4	ethyl acetate	5 - < 10 %
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = > 2000 mg/kg		
64742-95-6	918-668-5	Hydrocarbons, C9, aromatics	1 - < 5 %
	inhalation: LC50 = >6193 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = 3492 mg/kg		
7779-90-0	231-944-3	trizinc bis(orthophosphate)	1 - < 5 %
	inhalation: LC50 = > 5,7 mg/l (dusts or mists); oral: LD50 = > 5000 mg/kg M acute; H400: M=1 M chron.; H410: M=1		
13463-67-7	236-675-5	Titanium dioxide	< 1 %
	dermal: LD50 = > 10000 mg/kg; oral: LD50 = > 20000 mg/kg		

Further Information

The homogeneous mixing of this product is controlled by continuous physical tests. Formerly dusty raw materials are completely integrated into the liquid/pasty mass. Possible AGW-values for solid substances are

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 4 of 16

therefore not given, as there is no longer any risk of inhalation of these substances (when handling this mixture).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious but breathing normally, place in recovery position and seek medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.
Wash with plenty of water/Soap.
If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.
Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.
Wear personal protection equipment.
Avoid contact with skin, eyes and clothes.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 5 of 16

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Do not store together with: Oxidizing agents. Strong acid, strong alkalis

7.3. Specific end use(s)

Anti-corrosive coating

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 6 of 16

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 7 of 16

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Worker DNEL, long-term	inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day
1330-20-7	xylene		
Consumer DNEL, long-term	oral	systemic	1,6 mg/kg bw/day
Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	108 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	77 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	14,8 mg/m ³
141-78-6	ethyl acetate		
Worker DNEL, long-term	inhalation	systemic	734 mg/m ³
Worker DNEL, acute	inhalation	systemic	1468 mg/m ³
Worker DNEL, long-term	inhalation	local	734 mg/m ³
Worker DNEL, acute	inhalation	local	1468 mg/m ³
Worker DNEL, long-term	dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	367 mg/m ³
Consumer DNEL, acute	inhalation	systemic	734 mg/m ³
Consumer DNEL, long-term	dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4,5 mg/kg bw/day
64742-95-6	Hydrocarbons, C9, aromatics		
Worker DNEL, long-term	inhalation	systemic	150 mg/m ³
Worker DNEL, long-term	dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	32 mg/m ³
Consumer DNEL, long-term	dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	11 mg/kg bw/day
7779-90-0	trizinc bis(orthophosphate)		
Worker DNEL, long-term	inhalation	systemic	5 mg/m ³
Worker DNEL, long-term	dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	2,5 mg/m ³
Consumer DNEL, long-term	dermal	systemic	83 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	0,83 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 8 of 16

PNEC values

CAS No	Substance	Value
Environmental compartment		
1330-20-7	xylene	
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		0,20 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg
7779-90-0	trizinc bis(orthophosphate)	
Freshwater		0,0206 mg/l
Marine water		0,0061 mg/l
Freshwater sediment		117,8 mg/kg
Marine sediment		56,5 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,100 mg/l
Soil		35,6 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time:: 480 min.

PVA (Polyvinyl alcohol), Breakthrough time:: 480 min.

NBR (Nitrile rubber), Breakthrough time:: 30 min.

Butyl caoutchouc (butyl rubber) Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 9 of 16

gas filtering equipment (EN 141), Filter material/medium: A/P2

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light grey
Odour:	characteristic
Odour threshold:	not determined

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	80 °C
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Flash point:	-5 °C

Flammability

Solid/liquid:	not applicable
Gas:	not applicable

Explosive properties

not determined

Lower explosion limits:	0,8 vol. %
Upper explosion limits:	7,7 vol. %
Auto-ignition temperature:	200 °C

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: not determined

Viscosity / dynamic: (at 20 °C) 400-600 mPa·s

Viscosity / kinematic: not determined

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: (at 20 °C) 61 hPa

Density (at 20 °C): 1,04-1,08 g/cm³

Relative vapour density: not determined

9.2. Other information**Information with regard to physical hazard classes**Oxidizing properties
not determined**Other safety characteristics**

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 10 of 16

Solvent separation test:	not determined
Solvent content:	52,00 %
Solid content:	46-50 %
Evaporation rate:	not determined

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 11 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 > 5840 mg/kg	Rat		
	dermal	LD50 >2920 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 25 mg/l	Rat		
1330-20-7	xylene				
	oral	LD50 8700 mg/kg	Rat		
	dermal	LD50 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 10-20 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
141-78-6	ethyl acetate				
	oral	LD50 > 2000 mg/kg	Rabbit		
	dermal	LD50 >20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 30 mg/l	Rat		
64742-95-6	Hydrocarbons, C9, aromatics				
	oral	LD50 3492 mg/kg	Rat		
	dermal	LD50 >3160 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >6193 mg/l	Rat		
7779-90-0	trizinc bis(orthophosphate)				
	oral	LD50 > 5000 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 > 5,7 mg/l	Rat		
13463-67-7	Titanium dioxide				
	oral	LD50 > 20000 mg/kg	Rat		
	dermal	LD50 > 10000 mg/kg	Rabbit		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 12 of 16

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards
Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information
12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50 mg/l	10-100	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	30-100	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna (Big water flea)	
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss (Rainbow trout)	
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	
1330-20-7	xylene					
	Acute fish toxicity	LC50	86 mg/l	96 h	Leuciscus idus (golden orfe)	
	Acute algae toxicity	ErC50	2-8 mg/l		Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 mg/l	1-10	48 h		
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	3300		Desmodesmus subspicatus	48 h
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	(EC50 mg/l)	2900		Pseudomonas putida	16 h
64742-95-6	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50	9,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	2,9 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	3,2 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 13 of 16

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	OECD 301F	98%	28	
	Readily biodegradable (according to OECD criteria).			
141-78-6	ethyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	100 %	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	3,4-5,2
141-78-6	ethyl acetate	0,73

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 14 of 16

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: Coating solution, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 640D
 Limited quantity: 5 L
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Other applicable information (land transport)

E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; Hydrocarbons, C9, aromatics), MARINE POLLUTANT
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Marine pollutant: yes
 Special Provisions: -
 Limited quantity: 5 L
 EmS: F-E, S-E

Other applicable information (marine transport)

E2

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 1 L
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2

Passenger-LQ: Y341

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 15 of 16

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Hydrocarbons, C9, aromatics
trizinc bis(orthophosphate)

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

2004/42/EC (VOC): 52,0 %
540 g/l

Information according to 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

Additional information: P5c

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C9, aromatics

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,9,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

Safety Data Sheet

according to UK REACH Regulation

DINITROL 447 Light Grey

Revision date: 19.10.2021

Product code: 5101

Page 16 of 16

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)