

according to UK REACH Regulation

DINITROL 3125 HS

Revision date: 16.05.2024

Product code: 21661

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 3125 HS

UFI:

9QYW-K1SH-8001-A01G

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	
1.4. Emergency telephone	Giftnotruf Berlin: +49 30 30686 70	0 (Beratung in Deutsch und Englisch)
1.4. Emergency telephone	Giftnotruf Berlin: +49 30 30686 70	0 (Beratung in Deutsch und Englisch)

<u>number:</u>

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

Warning

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Pictograms:



Hazard statements

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P280	Wear protective gloves and eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P403+P235	Store in a well-ventilated place. Keep cool.



according to UK REACH Regulation

DINITROL 3125 HS

Revision date: 16.05.2024

Product code: 21661

Page 2 of 11

P405 Store locked up.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking. Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Pictograms:



2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name EC No Index No REACH No		Quantity	
			REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9-C11, n-alkanes,	isoalkanes, cyclics, <2% aromatics		45 - < 50 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
	barium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)			1 - < 5 %
	939-718-2		01-2119980986-14	
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H332 H302 H315			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	45 - < 50 %
	inhalation: LC50 = 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
	939-718-2	barium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	1 - < 5 %
	inhalation: AT 500 mg/kg	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 =	

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious but breathing normally, place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

DINITROL 3125 HS

Revision date: 16.05.2024

Product code: 21661

Page 3 of 11

After contact with skin

Change contaminated clothing. Wash with plenty of water/Soap. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure. Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Wear personal protection equipment. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

according to UK REACH Regulation

DINITROL 3125 HS Product code: 21661

Revision date: 16.05.2024

For cleaning up

Provide adequate ventilation. Clear contaminated areas thoroughly. Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking. Vapours are heavier than air and will spread at floor level. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Wash hands before breaks and after work. Avoid contact with skin and eyes. Remove contaminated, saturated clothing immediately. Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep container dry.

Keep away from heat.Protect from direct sunlight.

Hints on joint storage

No further relevant information available.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Anti-corrosive coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Page 4 of 11



DINITROL 3125 HS

Revision date: 16.05.2024

Product code: 21661

Page 5 of 11

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	aromatics	-	
Consumer DNE	EL, long-term	oral	systemic	125 mg/kg bw/day
Worker DNEL,	long-term	dermal	systemic	208 mg/kg bw/day
Consumer DNE	EL, long-term	dermal	systemic	125 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	871 mg/m³
Consumer DNE	EL, long-term	inhalation	systemic	185 mg/m³

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation.

- If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
- If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time:: > 480min.

PVA (Polyvinyl alcohol), Breakthrough time:: > 480min.

NBR (Nitrile rubber), Breakthrough time:: > 480min.

Butyl caoutchouc (butyl rubber) Breakthrough time:: > 480min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	beige
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point: Boiling point or initial boiling point and boiling range: Test method

not determined 154-193 °C



according to UK REACH Regulation

	DINITROL 3125 HS	
Revision date: 16.05.2024	Product code: 21661	Page 6 of 11
Flammability:	Flammable liquid and vapour.	
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	7 vol. %	
Flash point:	41 °C	DIN 53213
Auto-ignition temperature:	> 200 °C	
Decomposition temperature:	not determined	
pH-Value:	The study does not need to be	
	conducted because the substance is	
	known to be insoluble in water.	
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined Partition coefficient n-octanol/water:	u et eleterne in e el	
Vapour pressure:	not determined 3 hPa	
(at 20 °C)	ЭПГА	
Vapour pressure:	13 hPa	
(at 50 °C)		
Density (at 20 °C):	-	DIN 51757
Relative vapour density:	not determined	
9.2. Other information		
Information with regard to physical hazard classes	;	
Explosive properties		
not determined	.	
Sustaining combustion:	No data available	
Self-ignition temperature Solid:	not applicable	
Gas:	not applicable not applicable	
Oxidizing properties		
not determined		
Other safety characteristics		
Evaporation rate:	not determined	
Solvent separation test:	not determined	
Solvent content:	28,0 %	
Solid content:	69,7 %	
Viscosity / dynamic:	not determined	
Flow time:	55s	4 DIN EN ISO 2431
(at 20 °C)		
Further Information		
No information available		

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat.

DINITROL 3125 HS

Revision date: 16.05.2024

Product code: 21661

Page 7 of 11

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix tested			
	Dose	Species	Source
LD50, oral	15688 mg/kg		
LC50, inhalation (vapour) (4 h)	47,1 mg/l		

ATEmix calculated

ATE (dermal) > 2000 mg/kg; ATE (inhalation dust/mist) 30,61 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
	Hydrocarbons, C9-C11,	n-alkanes, is	soalkanes, cy	clics, <2% aromatics		
	oral	LD50 mg/kg	> 5000	Rat		
	dermal	LD50 mg/kg	> 5000	Rabbit		
	inhalation (4 h) vapour	LC50	5000 mg/l	Rat		
	barium bis (di C8-C10, b	ranched, C9	rich, alkylna	ohthalenesulphonate)		
	oral	LD50 mg/kg	500			
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.



DINITROL 3125 HS

Revision date: 16.05.2024

Product code: 21661

Page 8 of 11

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% ard	omatics		
		80%		
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes. List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information



	DINITROL 3125 HS	
Revision date: 16.05.2024	Product code: 21661	Page 9 of 11
Land transport (ADR/RID)		
14.1. UN number or ID number:	UN 1139	
14.2. UN proper shipping name:	COATING SOLUTION	
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
	3	
Classification code:	F1	
Limited quantity:	5 L	
Excepted quantity:	E1	
Transport category:	3	
Hazard No:	30	
Tunnel restriction code:	D/E	
Inland waterways transport (ADN)		
14.1. UN number or ID number:	UN 1139	
14.2. UN proper shipping name:	Coating solution	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	III	
Hazard label:	3	
	3	
Classification code:	F1	
Limited quantity:	5 L	
Excepted quantity:	E1	
Marine transport (IMDG)		
14.1. UN number or ID number:	UN 1139	
14.2. UN proper shipping name:	COATING SOLUTION	
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
Marine pollutant:	no	
Special Provisions:	955	
Limited quantity:	955 5 L	
Excepted quantity:	5 L E1	
Excepted quantity: EmS:	EI F-E, S-E	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number or ID number:</u>	UN 1139	
14.1. UN number of 1D number. 14.2. UN proper shipping name:	COATING SOLUTION	
	3	
14.3. Transport hazard class(es):		
14.4. Packing group:		
Hazard label:	3	
	3	
	•	



according to UK REACH Regulation

DINITROL 3125 HS		
Revision date: 16.05.2024	Product code: 21661	Page 10 of 11
Special Provisions: Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	A3 10 L Y344 E1 355 60 L 366 220 L	
14.5. Environmental hazards ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user Warning: Flammable liquids 14.7. Maritime transport in bulk according to not applicable		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or	mixture
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 75 Directive 2004/42/EC on VOC in paints and varnishes: Information according to Directive 2012/18/EU (SEVESO III):	28,04 % 274,8 g/l P5c FLAMMABLE LIQUIDS	
Additional information Observe in addition any national regula Directive 98/24/EC of 7 April 1998 on th chemical agents at work	tions! ne protection of the health and safety of workers f	rom the risks related to
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	
Water hazard class (D): Additional information	1 - slightly hazardous to water	
	stances of very high concern (SVHC) which are ir f REACH: none	ncluded in the
15.2. Chemical safety assessment		
Chemical safety assessments for subst	ances in this mixture were not carried out.	
Chemical safety assessments for subst	ances in this mixture were not carried out.	

Changes

This data sheet contains changes from the previous version in section(s): 2,8,9,11.



according to UK REACH Regulation

DINITROL 3125 HS

Revision date: 16.05.2024

Product code: 21661

Page 11 of 11

Abbreviations and acronyms

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation STOT SE: Specific target organ toxicity - single exposure ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)