

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 410 UV NF Black

Revision date: 02/15/2024

Product code: 82115

Page 1 of 9

1. Identification

Product identifier

DINITROL 410 UV NF Black

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Adhesives, sealants

Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980
E-mail: msds@dinol.com
Contact person: Labor
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

Supplier

Company name: DINOL U.S. Inc.
Street: 8500 Cotter Street, Lewis Center
Place: USA-43035 Ohio
Telephone: 740-548-1656
E-mail: info@dinolus.com
Internet: www.dinol.com

Telefax: 740-548-1657

Emergency phone number: 3E Company Emergency +1-866-404-4230

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Respiratory or skin sensitization: Resp. Sens. 1

Respiratory or skin sensitization: Skin Sens. 1

Carcinogenicity: Carc. 2

Specific target organ toxicity repeated or prolonged exposure: STOT RE 2

Label elements

29 CFR Part 1910.1200

Signal word: Danger

Pictograms:



Hazard statements

May cause an allergic skin reaction

May cause allergy or asthma symptoms or breathing difficulties if inhaled

Suspected of causing cancer

May cause damage to organs through prolonged or repeated exposure

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

DINITROL 410 UV NF Black

Revision date: 02/15/2024

Product code: 82115

Page 2 of 9

Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
Wear respiratory protection.
If on skin: Wash with plenty of water.
Wash contaminated clothing before reuse.
If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
If experiencing respiratory symptoms: Call a poison center/doctor.
If exposed or concerned: Get medical advice/attention.
Store locked up.

Hazards not otherwise classified

No information available.

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Components	Quantity
	reaction mass of ethylbenzene and xylene	9.9 %
25686-28-6	Methylenediphenyl diisocyanate, modified	0.9 %
101-68-8	diphenylmethane-4,4'-diisocyanate	0.9 %

Further Information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

4. First-aid measures

Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleansing agent and water. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Do NOT induce vomiting.
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.

Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

Indication of any immediate medical attention and special treatment needed

No information available.

5. Fire-fighting measures

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 410 UV NF Black

Revision date: 02/15/2024

Product code: 82115

Page 3 of 9

Extinguishing media**Suitable extinguishing media**Water spray jet, alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂).**Unsuitable extinguishing media**

Full water jet.

Specific hazards arising from the chemicalIn case of fire may be liberated: Hydrogen chloride (HCl), Nitrogen oxides (NO_x), Sulphur oxides, Carbon monoxide**Special protective equipment and precautions for fire-fighters**

Do not inhale explosion and combustion gases. In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Suppress gases/vapors/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.
Wear personal protection equipment.
Avoid contact with skin, eyes and clothes.
Avoid breathing dust/fume/gas/mist/vapors/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow uncontrolled discharge of product into the environment.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.
Clear contaminated areas thoroughly.
Do not rinse down with water.

Other information

No information available.

Reference to other sections

Safe handling: see section 7
Personal protection equipment (PPE): see section 8
Disposal: see section 13

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 410 UV NF Black

Revision date: 02/15/2024

Product code: 82115

Page 4 of 9

Advice on protection against fire and explosion

Vapors may form explosive mixtures with air. Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Protect from moisture.

Hints on joint storage

Store away from foodstuffs.

Further information on storage conditions

Keep container tightly closed and dry. Keep in a cool, well-ventilated place.

Protect against: Frost, Heat, UV-radiation/sunlight.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No	Substance	ppm	mg/m ³	f/cc	Category	Origin
101-68-8	Methylene bisphenyl isocyanate (MDI)	C 0.02	C 0.2		Ceiling	PEL
101-68-8	Methylene bisphenyl isocyanate	0.005	0.05		TWA (8 h)	REL
		C 0.02	C 0.2		10 min	REL
101-68-8	Methylene bisphenyl isocyanate	0.005			TWA (8 h)	ACGIH-2023

Exposure controls



Appropriate engineering controls

The usual precautionary measures are to be adhered to when handling chemicals.

Provide adequate ventilation. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) - (0,7mm), Breakthrough time:: 240 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Protective clothing

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 410 UV NF Black

Revision date: 02/15/2024

Product code: 82115

Page 5 of 9

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
gas filtering equipment (EN 141), Filter material/medium: A2

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Paste	
Color:	black	
Odor:	like: Solvent	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not applicable
Flammability:		not applicable
Flash point:		not applicable
Decomposition temperature:		not determined
pH-Value:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:		not determined
Density (at 20 °C):		1,22 g/cm ³
Relative vapour density:		not determined

Other information

Information with regard to physical hazard classes

Explosive properties	not determined	
Self-ignition temperature		
Solid:		not applicable
Gas:		not applicable

Other safety characteristics

Evaporation rate:	not determined
-------------------	----------------

10. Stability and reactivity

Reactivity

The product has not been tested.

Chemical stability

Stability:	Stable
The product is stable under storage at normal ambient temperatures.	

Possibility of hazardous reactions

Hazardous reactions:	Will not occur
Reacts with : Alcohol, Amines, Acid, alkali	
After contact with water: Formation of: Methanol, Carbon dioxide.	
Heating causes rise in pressure with risk of bursting.	

Conditions to avoid

Protect from moisture.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 410 UV NF Black

Revision date: 02/15/2024

Product code: 82115

Page 6 of 9

Incompatible materials

No information available.

Hazardous decomposition products

Possible in traces: Isocyanates.

11. Toxicological information

Route(s) of Entry

No information available.

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 43434 mg/kg; ATE (dermal) 25253 mg/kg; ATE (inhalation vapour) 202,0 mg/l; ATE (inhalation dust/mist) 15,15 mg/l

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
	reaction mass of ethylbenzene and xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 20 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
25686-28-6	Methylenediphenyl diisocyanate, modified				
	oral	LD50 >5000 mg/kg	Rat		
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
101-68-8	diphenylmethane-4,4'-diisocyanate				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >9400 mg/kg	Rabbit		
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitizing effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled (Methylenediphenyl diisocyanate, modified; diphenylmethane-4,4'-diisocyanate)

May cause an allergic skin reaction (Methylenediphenyl diisocyanate, modified; diphenylmethane-4,4'-diisocyanate)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer (Methylenediphenyl diisocyanate, modified; diphenylmethane-4,4'-diisocyanate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 410 UV NF Black

Revision date: 02/15/2024

Product code: 82115

Page 7 of 9

Specific target organ toxicity (STOT) - repeated exposure

May cause damage to organs through prolonged or repeated exposure (reaction mass of ethylbenzene and xylene)

Carcinogenicity (IARC): 4,4'-Methylenediphenyl diisocyanate (CAS 101-68-8) is listed in group 3.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information

Persistence and degradability

There are no data available on the mixture itself.

Bioaccumulative potential

There are no data available on the mixture itself.

Mobility in soil

There are no data available on the mixture itself.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

Contaminated packaging

Remove according to the regulations.

14. Transport information

U.S. DOT 49 CFR 172.101

Proper shipping name:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

UN number or ID number:

No dangerous good in sense of this transport regulation.

UN proper shipping name:

No dangerous good in sense of this transport regulation.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 410 UV NF Black

Revision date: 02/15/2024

Product code: 82115

Page 8 of 9

Transport hazard class(es): No dangerous good in sense of this transport regulation.

Packing group: No dangerous good in sense of this transport regulation.

Marine pollutant: no

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: No dangerous good in sense of this transport regulation.

UN proper shipping name: No dangerous good in sense of this transport regulation.

Transport hazard class(es): No dangerous good in sense of this transport regulation.

Packing group: No dangerous good in sense of this transport regulation.

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

No dangerous good in sense of this transport regulation.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No dangerous good in sense of this transport regulation.

Other applicable information

Fire test in accordance with 33.2.1.4 "Manual of test and criteria" (recommendations on the TRANSPORT OF DANGEROUS GOODS [United Nations]): burn rate: $\leq 2, 2 \text{ mm / s}$ (no hazardous goods according to class 4.1 [ADR])

15. Regulatory information

U.S. Regulations

National Inventory TSCA

Substance/product listed in the following inventories: TSCA

National regulatory information

SARA Section 304 CERCLA:

Methylenebis(phenylisocyanate)(MDI) (101-68-8): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:

reaction mass of ethylbenzene and xylene (-): Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Methylenediphenyl diisocyanate, modified (25686-28-6): Delayed (chronic) health hazard, Immediate (acute) health hazard

Methylenebis(phenylisocyanate)(MDI) (101-68-8): Delayed (chronic) health hazard, Immediate (acute) health hazard

SARA Section 313 Toxic release inventory:

Methylenebis(phenylisocyanate)(MDI) (101-68-8): De minimis limit = 1.0 %, Reportable threshold = Standard

Clean Air Act Section 112(b):

Methylenebis(phenylisocyanate)(MDI) (101-68-8)

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Directive 2004/42/EC on VOC in 8,0 %
paints and varnishes: 97,6 g/l

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

16. Other information

Revision date: 02/15/2024

Revision No: 1,3

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 410 UV NF Black

Revision date: 02/15/2024

Product code: 82115

Page 9 of 9

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)