

Revision date: 10.11.2023

DINITROL 445

Product code: 5104

Page 1 of 11

1. Identification

Product identifier

DINITROL 445

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980
E-mail: msds@dinol.com
Contact person: Labor
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

Supplier

Company name: DINOL U.S. Inc.
Street: 8500 Cotter Street, Lewis Center
Place: USA-43035 Ohio
Telephone: 740-548-1656
E-mail: info@dinolus.com
Internet: www.dinol.com

Telefax: 740-548-1657

Emergency telephone number: 3E Company Emergency +1-866-404-4230

2. Hazard identification

Classification of the substance or mixture

WHMIS 2015

Flammable liquid: Flam. Liq. 2
Skin corrosion/irritation: Skin Irrit. 2
Respiratory or skin sensitization: Skin Sens. 1A
Reproductive toxicity: Repr. 2
Specific target organ toxicity - single exposure: STOT SE 3 (narcotic effects)
Specific target organ toxicity - repeated exposure: STOT RE 1
Specific target organ toxicity - repeated exposure: STOT RE 2

Label elements

WHMIS 2015

Signal word: Danger

Pictograms:



Hazard statements

Highly flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.

DINITROL 445

Revision date: 10.11.2023

Product code: 5104

Page 2 of 11

Causes damage to organs through prolonged or repeated exposure.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash water thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves and eye/face protection.
IF ON SKIN: Wash with plenty of water.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
Take off contaminated clothing and wash it before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
In case of fire: Use water to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.

Other hazards

No information available.

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	10 - < 30% (*)
108-88-3	toluene	5 - < 10% (*)
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	5 - < 10% (*)
1330-20-7	xylene	3 - < 7% (*)
141-78-6	ethyl acetate	1 - < 5% (*)
100-41-4	ethylbenzene	0.5 - < 1.5% (*)
147900-93-4	Fatty acids, C18-unsatd. , trimers, compds. with oleylamine	0.1 - < 1% (*)
85711-55-3	Fatty acids, tall-oil, compds. with oleylamine	0.1 - < 1% (*)

(*) The actual concentration is withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General information

If unconscious but breathing normally, place in recovery position and seek medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
In all cases of doubt, or when symptoms persist, seek medical advice.

DINITROL 445

Revision date: 10.11.2023

Product code: 5104

Page 3 of 11

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

Wash with plenty of water/Soap.

If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

Most important symptoms and effects, whether acute or delayed

Nausea, Dizziness, Headache.

Indication of immediate medical attention and special treatment needed

No information available.

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

Specific hazards arising from the hazardous product

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

Special protective equipment and precautions for fire-fighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

DINITROL 445

Revision date: 10.11.2023

Product code: 5104

Page 4 of 11

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Do not store together with: Oxidizing agents. Strong acid, strong alkalis

8. Exposure controls/Personal protection**Control parameters**

DINITROL 445

Revision date: 10.11.2023

Product code: 5104

Page 5 of 11

Exposure limits (ACGIH)

CAS No	Chemical name	ppm	mg/m ³	F/ml	Category	Origin
141-78-6	Ethyl acetate	400			TWA (8 h)	ACGIH-2023
100-41-4	Ethyl benzene	20			TWA (8 h)	ACGIH-2023
14807-96-6	Talc containing no asbestos fibers (respirable fraction)		2		TWA (8 h)	ACGIH-2023
108-88-3	Toluene	20	-		TWA (8 h)	ACGIH-2023
1330-20-7	Xylene: mixed isomers	20			TWA (8 h)	ACGIH-2023

Biological limit values

CAS No	Chemical name	Parameter	Value	Test material	Sampling time
108-88-3	TOLUENE (ACGIH 2023)	Toluene	0.02 mg/L	blood	Prior to last shift of workweek
1330-20-7	XYLENES (technical or commercial grade) (ACGIH 2023)	Methylhippuric acids (creatinine)	1.5 g/g	urine	End of shift
100-41-4	ETHYLBENZENE (ACGIH 2023)	Sum of mandelic acid and phenylglyoxylic acid (creatinine)	0.15 g/g	urine	End of shift

Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber) Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: A/P2

DINITROL 445

Revision date: 10.11.2023

Product code: 5104

Page 6 of 11

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	black	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		> 77 °C
Flammability:		not applicable
Lower explosive limits:		0,8 vol. %
Upper explosive limits:		7,7 vol. %
Flash point:		- 4 °C
Auto-ignition temperature:		> 200 °C
Decomposition temperature:		not determined
pH-Value:		not applicable
Viscosity / kinematic:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		61 hPa
(at 20 °C)		
Density (at 20 °C):		1,14 - 1,18 g/cm³
Relative vapour density:		not determined

Other information

Information with regard to physical hazard classes

Explosive properties	
not determined	
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
not determined	

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	43,6 %
Solid content:	55-59 %
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Viscosity / dynamic:	900 - 1100 mPa·s
(at 20 °C)	

Further Information

No information available.

10. Stability and reactivity

DINITROL 445

Revision date: 10.11.2023

Product code: 5104

Page 7 of 11

Reactivity

No hazardous reaction when handled and stored according to provisions.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid

Keep away from heat.

Incompatible materials

No information available.

Hazardous decomposition products

Carbon monoxide

11. Toxicological information**Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 36811 mg/kg; ATE (dermal) 8282 mg/kg; ATE (inhalation vapour) 63,62 mg/l; ATE (inhalation dust/mist) 21,55 mg/l

DINITROL 445

Revision date: 10.11.2023

Product code: 5104

Page 8 of 11

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat		
108-88-3	toluene				
	oral	LD50 5580 mg/kg	Rat		
	dermal	LD50 12124 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 31 mg/l	Rat		
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	oral	LD50 >15000 mg/kg	Rat		
	dermal	LD50 >3400 mg/kg	Rat		
1330-20-7	xylene				
	oral	LD50 8700 mg/kg	Rat		
	dermal	LD50 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 10-20 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
141-78-6	ethyl acetate				
	oral	LD50 5620 mg/kg	Rat		
	dermal	LD50 >20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 50 mg/l	Rat		
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
147900-93-4	Fatty acids, C18-unsatd., trimers, compds. with oleylamine				
	oral	LD50 > 1570 mg/kg	Rat		
85711-55-3	Fatty acids, tall-oil, compds. with oleylamine				
	oral	LD50 > 2000 mg/kg	Rat		

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Revision date: 10.11.2023

DINITROL 445

Product code: 5104

Page 9 of 11

Sensitizing effects

May cause an allergic skin reaction. (Fatty acids, C18-unsatd. , trimers, compds. with oleylamine; Fatty acids, tall-oil, compds. with oleylamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging fertility or the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

May cause damage to organs through prolonged or repeated exposure. (toluene; xylene; ethylbenzene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on other hazards**Endocrine disrupting properties**

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information**Persistence and degradability**

There are no data available on the mixture itself.

Bioaccumulative potential

There are no data available on the mixture itself.

Mobility in soil

There are no data available on the mixture itself.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meet the criteria.

Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

13. Disposal considerations**Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes. No discharge of substance into waste water

List of proposed waste codes/waste designations in accordance with EWC:

Contaminated packaging

Remove according to the regulations.

14. Transport information**Canadian TDG****UN number:**

UN 1139

Safety Data Sheet

according to WHMIS

DINITROL 445

Revision date: 10.11.2023

Product code: 5104

Page 10 of 11

Proper shipping name: Coating solution
Hazard classes: 3
Packing group: II
 Hazard label: 3
 Limited quantity: 5L



Marine transport (IMDG)

UN number or ID number: UN 1139
United Nations proper shipping name: Coating solution
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Marine pollutant: no
 Special Provisions: -
 Limited quantity: 5 L
 EmS: F-E, S-E

Other applicable information (marine transport)
 E2

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1139
United Nations proper shipping name: COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under-coating, drum or barrel lining)
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 1 L
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)
 E2
 Passenger-LQ: Y341

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

15. Regulatory information

Canadian regulations

Safety Data Sheet

according to WHMIS

DINITROL 445

Revision date: 10.11.2023

Product code: 5104

Page 11 of 11

DSL/NDSL inventory status

Substance/product listed in the following inventories: DSL/NDSL

Directive 2004/42/EC on VOC in paints and varnishes: 43,6 % (510 g/l)

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

16. Other information**Abbreviations and acronyms**ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)