

## DINITROL 538 PLUS

Revision date: 13.12.2023

Product code: 10730

Page 1 of 11

### 1. Identification

#### Product identifier

DINITROL 538 PLUS

#### Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Adhesion promoter

#### Details of the supplier of the safety data sheet

##### Manufacturer

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

##### Supplier

Company name: DINOL U.S. Inc.  
Street: 8500 Cotter Street, Lewis Center  
Place: USA-43035 Ohio  
Telephone: 740-548-1656  
E-mail: info@dinolus.com  
Internet: www.dinol.com

Telefax: 740-548-1657

**Emergency telephone number:** 3E Company Emergency +1-866-404-4230

### 2. Hazard identification

#### Classification of the substance or mixture

##### WHMIS 2015

Flammable liquid: Flam. Liq. 2  
Serious eye damage/eye irritation: Eye Irrit. 2A  
Respiratory or skin sensitization: Resp. Sens. 1  
Respiratory or skin sensitization: Skin Sens. 1  
Carcinogenicity: Carc. 2  
Specific target organ toxicity - single exposure: STOT SE 3 (narcotic effects)

#### Label elements

##### WHMIS 2015

**Signal word:** Danger

**Pictograms:**



##### Hazard statements

Highly flammable liquid and vapour.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.

## DINITROL 538 PLUS

Revision date: 13.12.2023

Product code: 10730

Page 2 of 11

### Precautionary statements

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Ground and bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use non-sparking tools.  
Take action to prevent static discharges.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
Wash hands thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Wear respiratory protection.  
IF ON SKIN: Wash with plenty of water.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
Take off contaminated clothing and wash it before reuse.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If experiencing respiratory symptoms: Call a POISON CENTER/doctor.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF exposed or concerned: Get medical advice/attention.  
In case of fire: Use Water spray jet, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>) to extinguish.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

### Other hazards

Endocrine disrupting properties: butanone; ethyl methyl ketone.  
No information available.

## 3. Composition/information on ingredients

### Mixtures

#### Hazardous components

CAS No	Chemical name	Quantity
78-93-3	butanone; ethyl methyl ketone	45 - < 70% (*)
108-65-6	2-methoxy-1-methylethyl acetate	5 - < 10% (*)
28182-81-2	Hexamethylene diisocyanate, oligomers	5 - < 10% (*)
1333-86-4	Carbon Black	3 - < 7% (*)
123-86-4	n-butyl acetate	1 - < 5% (*)
1330-20-7	xylene	1 - < 5% (*)
100-41-4	ethylbenzene	0.1 - < 1% (*)
9016-87-9	Diphenylmethanediisocyanate, isomeres and homologues	0.1 - < 1% (*)

(\*) The actual concentration is withheld as a trade secret.

### Further Information

Full text of H- and EUH-statements: see section 16.

## 4. First-aid measures

### Description of first aid measures

**DINITROL 538 PLUS**

Revision date: 13.12.2023

Product code: 10730

Page 3 of 11

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice.  
Never give anything by mouth to an unconscious person or a person with cramps.  
If unconscious but breathing normally, place in recovery position and seek medical advice.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

Change contaminated clothing.  
After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious).  
Do NOT induce vomiting.  
Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.

**Most important symptoms and effects, whether acute or delayed**

No information available.

**Indication of immediate medical attention and special treatment needed**

Treat symptomatically.

**5. Fire-fighting measures****Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), Extinguishing powder. Water spray jet  
In case of major fire and large quantities: Water spray jet, alcohol resistant foam.

**Unsuitable extinguishing media**

High power water jet.

**Specific hazards arising from the hazardous product**

No further relevant information available.

**Special protective equipment and precautions for fire-fighters**

No special measures are necessary.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.  
Wear personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Avoid breathing dust/fume/gas/mist/vapours/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.

**DINITROL 538 PLUS**

Revision date: 13.12.2023

Product code: 10730

Page 4 of 11

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

**Other information**

No information available.

**Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**7. Handling and storage****Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed.

Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

No special measures are necessary.

**Further information on storage conditions**

maximum storage temperature: < 40°C

minimum storage temperature: > 4°C

storage temperature: 4 - 40°C

**8. Exposure controls/Personal protection****Control parameters**

## DINITROL 538 PLUS

Revision date: 13.12.2023

Product code: 10730

Page 5 of 11

### Exposure limits (ACGIH)

CAS No	Chemical name	ppm	mg/m <sup>3</sup>	F/ml	Category	Origin
1333-86-4	Carbon black (inhalable fraction)		3		TWA (8 h)	ACGIH-2023
100-41-4	Ethyl benzene	20			TWA (8 h)	ACGIH-2023
78-93-3	Methyl ethyl ketone	200			TWA (8 h)	ACGIH-2023
		300			STEL (15 min)	ACGIH-2023
123-86-4	n-Butyl acetate	50			TWA (8 h)	ACGIH-2023
		150			STEL (15 min)	ACGIH-2023
1330-20-7	Xylene: mixed isomers	20			TWA (8 h)	ACGIH-2023

### Biological limit values

CAS No	Chemical name	Parameter	Value	Test material	Sampling time
78-93-3	METHYL ETHYL KETONE (ACGIH 2023)	Methyl ethyl ketone	2 mg/L	urine	End of shift
1330-20-7	XYLENES (technical or commercial grade) (ACGIH 2023)	Methylhippuric acids (creatinine)	1.5 g/g	urine	End of shift
100-41-4	ETHYLBENZENE (ACGIH 2023)	Sum of mandelic acid and phenylglyoxylic acid (creatinine)	0.15 g/g	urine	End of shift

### Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (DIN EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

##### Skin protection

Wear anti-static footwear and clothing

##### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: A

## DINITROL 538 PLUS

Revision date: 13.12.2023

Product code: 10730

Page 6 of 11

### 9. Physical and chemical properties

#### Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	black
Odour:	characteristic
Odour threshold:	not determined
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	79 - 80,5 °C
Flammability:	Highly flammable liquid and vapour.
Lower explosive limits:	1,8 vol. %
Upper explosive limits:	11,5 vol. %
Flash point:	-4 °C
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	Immiscible
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	105 hPa
(at 20 °C)	
Density (at 20 °C):	0,92 - 0,93 g/cm³
Relative vapour density:	not determined
Particle characteristics:	not applicable

#### Other information

##### Information with regard to physical hazard classes

###### Explosive properties

The product is: not explosive.. In use, may form flammable/explosive vapour-air mixture.

###### Self-ignition temperature

Solid: not applicable

Gas: not applicable

###### Oxidizing properties

not determined

##### Other safety characteristics

Evaporation rate: not determined

Solvent content: 72,3 %

Softening point: not determined

Viscosity / dynamic: not determined

##### Further Information

No information available.

### 10. Stability and reactivity

#### Reactivity

No further relevant information available.

#### Chemical stability

No hazardous reaction when handled and stored according to provisions.

#### Possibility of hazardous reactions

**DINITROL 538 PLUS**

Revision date: 13.12.2023

Product code: 10730

Page 7 of 11

No known hazardous reactions.

**Conditions to avoid**

No further relevant information available.

**Incompatible materials**

No further relevant information available.

**Hazardous decomposition products**

No known hazardous decomposition products.

**11. Toxicological information****Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix tested**

	Dose	Species	Source
LD50, dermal	150638 mg/kg	Rabbit	
LC50, inhalation (vapour) (4 h)	130 mg/l		

**ATEmix calculated**

ATE (oral) 5012 mg/kg; ATE (inhalation dust/mist) 16,67 mg/l

## DINITROL 538 PLUS

Revision date: 13.12.2023

Product code: 10730

Page 8 of 11

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 mg/kg 3300	Rat		
	dermal	LD50 mg/kg 5000	Rabbit		
	inhalation (4 h) vapour	LC50 12 mg/l	Rat		
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 mg/kg 8500	Rat		
	inhalation (4 h) vapour	LC50 35,7 mg/l	Rat		
28182-81-2	Hexamethylene diisocyanate, oligomers				
	oral	LD50 mg/kg >5000	Rat		
	inhalation (4 h) vapour	LC50 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
1333-86-4	Carbon Black				
	oral	LD50 mg/kg > 15400	Rat	GESTIS	
	dermal	LD50 mg/kg > 3000	Rabbit	GESTIS	
123-86-4	n-butyl acetate				
	oral	LD50 mg/kg 10760	Rat		
	dermal	LD50 mg/kg > 14112	Rabbit		
	inhalation vapour	LC50 > 21 mg/l	Rat		
	inhalation (4 h) dust/mist	LC50 >21 mg/l	Rat		
1330-20-7	xylene				
	dermal	ATE mg/kg 1100			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	oral	LD50 mg/kg 3500	Rat	GESTIS	
	dermal	LD50 mg/kg 15400	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
9016-87-9	Diphenylmethanediisocyanate, isomeres and homologues				
	oral	LD50 mg/kg >10000	Rat		
	dermal	LD50 mg/kg >9400	Rabbit		
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			



**Safety Data Sheet**

according to WHMIS

**DINITROL 538 PLUS**

Revision date: 13.12.2023

Product code: 10730

Page 9 of 11

**Irritation and corrosivity**

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

**Sensitizing effects**

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Diphenylmethanediisocyanate, isomeres and homologues)

May cause an allergic skin reaction. (Hexamethylene diisocyanate, oligomers; Diphenylmethanediisocyanate, isomeres and homologues)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of causing cancer. (Carbon Black; ethylbenzene; Diphenylmethanediisocyanate, isomeres and homologues)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (butanone; ethyl methyl ketone)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No information available.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**Information on other hazards****Endocrine disrupting properties**

Endocrine disrupting properties: butanone; ethyl methyl ketone.

-

**Further information**

There are no data available on the preparation/mixture itself.

**12. Ecological information****Persistence and degradability**

No further relevant information available.

**Bioaccumulative potential**

No further relevant information available.

**Mobility in soil**

No further relevant information available.

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other adverse effects**

No further relevant information available.

**Further information**

There are no data available on the mixture itself.

## DINITROL 538 PLUS

Revision date: 13.12.2023

Product code: 10730

Page 10 of 11

### 13. Disposal considerations

#### Waste treatment methods

##### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

##### Contaminated packaging

Remove according to the regulations.

### 14. Transport information

#### Canadian TDG

**UN number:** UN 1866  
**Proper shipping name:** Resin solution  
**Hazard classes:** 3  
**Packing group:** II  
Hazard label: 3  
Limited quantity: 5 L



#### Marine transport (IMDG)

**UN number or ID number:** UN 1866  
**United Nations proper shipping name:** RESIN SOLUTION  
**Transport hazard class(es):** 3  
**Packing group:** II  
Hazard label: 3



Marine pollutant: no  
Special Provisions: -  
Limited quantity: 5 L  
Excepted quantity: E2  
EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

**UN number or ID number:** UN 1866  
**United Nations proper shipping name:** RESIN SOLUTION  
**Transport hazard class(es):** 3  
**Packing group:** II  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353

# Safety Data Sheet

according to WHMIS

## DINITROL 538 PLUS

Revision date: 13.12.2023

Product code: 10730

Page 11 of 11

IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

### Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## 15. Regulatory information

### Canadian regulations

#### DSL/NDSL inventory status

Substance/product listed in the following inventories: DSL/NDSL

Directive 2004/42/EC on VOC in	72,34 %
paints and varnishes:	665,5 - 672,8 g/l

#### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

## 16. Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,3,7,8,9,11.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*