

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 1 of 17

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 550

UFI: AAQX-H0MJ-H00X-8QUA

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Adhesion promoter

##### Uses advised against

No further relevant information available.

#### 1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Flam. Liq. 2; H225  
 Eye Irrit. 2; H319  
 Resp. Sens. 1; H334  
 Skin Sens. 1; H317  
 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

butanone; ethyl methyl ketone  
 Hexamethylene diisocyanate, oligomers  
 Isocyanic acid, polymethylenepolyphenylene ester  
 Dibutyltin dilaurate  
 diphenylmethane-4,4'-diisocyanate  
 diphenylmethane-2,4'-diisocyanate

Signal word: Danger

##### Pictograms:



##### Hazard statements

H225	Highly flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 2 of 17

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H336 May cause drowsiness or dizziness.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.  
Restricted to professional users.  
As from 24 August 2023 adequate training is required before industrial or professional use.

### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



### Hazard statements

H317-H334

### Precautionary statements

P280-P302+P352

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 3 of 17

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
78-93-3	butanone; ethyl methyl ketone			80 - < 85 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
28182-81-2	Hexamethylene diisocyanate, oligomers			5 - < 10 %
	931-274-8		01-2119485796-17	
	Acute Tox. 4, Skin Sens. 1, STOT SE 3; H332 H317 H335			
108-65-6	2-methoxy-1-methylethyl acetate			5 - < 10 %
	203-603-9	607-195-00-7		
	Flam. Liq. 3; H226			
9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester			< 1 %
	618-498-9			
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
77-58-7	Dibutyltin dilaurate			< 1 %
	201-039-8		01-2119496068-27	
	Muta. 2, Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1, STOT SE 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H341 H360FD H314 H318 H317 H370 H372 H400 H410			
101-68-8	diphenylmethane-4,4'-diisocyanate			< 0.1 %
	202-966-0	615-005-00-9	01-2119457014-47	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
5873-54-1	diphenylmethane-2,4'-diisocyanate			< 0.1 %
	227-534-9	615-005-00-9	01-2119480143-45	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			

Full text of H and EUH statements: see section 16.

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 4 of 17

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
78-93-3	201-159-0	butanone; ethyl methyl ketone	80 - < 85 %
		dermal: LD50 = 6480 mg/kg; oral: LD50 = 2740 mg/kg	
28182-81-2	931-274-8	Hexamethylene diisocyanate, oligomers	5 - < 10 %
		inhalation: LC50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = >5000 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	5 - < 10 %
		dermal: LD50 = 7500 mg/kg; oral: LD50 = 8532 mg/kg	
9016-87-9	618-498-9	Isocyanic acid, polymethylenepolyphenylene ester	< 1 %
		inhalation: LC50 = 310 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 10000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	
77-58-7	201-039-8	Dibutyltin dilaurate	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 2071 mg/kg	
101-68-8	202-966-0	diphenylmethane-4,4'-diisocyanate	< 0.1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >9400 mg/kg; oral: LD50 = >2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	
5873-54-1	227-534-9	diphenylmethane-2,4'-diisocyanate	< 0.1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >9400 mg/kg; oral: LD50 = >2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	

### Further Information

Full text of H- and EUH-statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 550**

Revision date: 13.12.2023

Product code: 10731

Page 5 of 17

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder. Water fog.**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

No further relevant information available.

**5.3. Advice for firefighters**

No special measures are necessary.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 6 of 17

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

### Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

#### Hints on joint storage

Not required.

#### Further information on storage conditions

Keep container tightly closed. Keep container tightly closed and dry.

maximum storage temperature : &lt; 40°C

minimum storage temperature : &gt; 4 °C

storage temperature: : 4 - 40 °C

### 7.3. Specific end use(s)

No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 7 of 17

### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
77-58-7	Dibutyltin dilaurate			
Worker DNEL, long-term		inhalation	systemic	0,02 mg/m³
Worker DNEL, long-term		dermal	systemic	0,42 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	2,08 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,006 mg/m³
Consumer DNEL, acute		inhalation	systemic	0,04 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,16 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	1 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,004 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,02 mg/kg bw/day
,				
101-68-8	diphenylmethane-4,4'-diisocyanate			
Worker DNEL, long-term		inhalation	local	0,05 mg/m³
Worker DNEL, acute		inhalation	local	0,10 mg/m³
Consumer DNEL, long-term		inhalation	local	0,025 mg/m³
Consumer DNEL, acute		inhalation	local	0,05 mg/m³
5873-54-1	diphenylmethane-2,4'-diisocyanate			
Worker DNEL, long-term		inhalation	systemic	0,05 mg/m³
Worker DNEL, acute		inhalation	systemic	0,10 mg/m³
Worker DNEL, long-term		inhalation	local	0,05 mg/m³
Worker DNEL, acute		inhalation	local	0,10 mg/m³
Worker DNEL, acute		dermal	systemic	50,0 mg/kg bw/day
Worker DNEL, acute		dermal	local	28,7 mg/person/day
Consumer DNEL, long-term		inhalation	systemic	0,025 mg/m³
Consumer DNEL, acute		inhalation	systemic	0,05 mg/m³
Consumer DNEL, long-term		inhalation	local	0,025 mg/m³
Consumer DNEL, acute		inhalation	local	0,05 mg/m³
Consumer DNEL, acute		dermal	systemic	25,0 mg/kg bw/day
Consumer DNEL, acute		dermal	local	17,2 mg/person/day
Consumer DNEL, acute		oral	systemic	20,0 mg/kg bw/day

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 8 of 17

### PNEC values

CAS No	Substance	
Environmental compartment		Value
77-58-7	Dibutyltin dilaurate	
Freshwater		0,000463 mg/l
Marine water		0,0000463 mg/l
Freshwater sediment		0,05 mg/kg
Marine sediment		0,005 mg/kg
Secondary poisoning		0,2 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,0407 mg/kg
101-68-8	diphenylmethane-4,4'-diisocyanate	
Freshwater		1,0 mg/l
Marine water		0,1 mg/l
Micro-organisms in sewage treatment plants (STP)		1,0 mg/l
Soil		1,0 mg/kg
5873-54-1	diphenylmethane-2,4'-diisocyanate	
Freshwater		1,0 mg/l
Marine water		0,1 mg/l
Micro-organisms in sewage treatment plants (STP)		1,0 mg/l
Soil		1,0 mg/kg

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (DIN EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

##### Skin protection

Wear anti-static footwear and clothing

##### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.



## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 9 of 17

gas filtering equipment (EN 141). Filter material/medium : A

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	black	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		79 - 80,5 °C
Flammability:	Highly flammable liquid and vapour.	
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		- 4 °C
Auto-ignition temperature:		> 300 °C
Decomposition temperature:		not applicable
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		Immiscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		not determined
Density (at 20 °C):		0,94 - 0,95 g/cm³
Relative vapour density:		not determined
Particle characteristics:		not applicable

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosive properties

The product is: not explosive.. In use may form flammable/explosive vapour-air mixture.

##### Sustaining combustion:

No data available

##### Oxidizing properties

not determined

#### Other safety characteristics

##### Solvent content:

65,6 %

##### Softening point:

not determined

##### Viscosity / dynamic:

not determined

#### Further Information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 550**

Revision date: 13.12.2023

Product code: 10731

Page 10 of 17

**10.4. Conditions to avoid**

No further relevant information available.

**10.5. Incompatible materials**

No further relevant information available.

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix tested**

	Dose	Species	Source
LC50, inhalation (dust/mist) (4 h)	113 mg/l		

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) 134,5 mg/l

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 11 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 2740 mg/kg	Rat		
	dermal	LD50 6480 mg/kg	Rabbit		
28182-81-2	Hexamethylene diisocyanate, oligomers				
	oral	LD50 >5000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 8532 mg/kg	Rat	RTECS	
	dermal	LD50 7500 mg/kg	Rabbit		
9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester				
	oral	LD50 > 10000 mg/kg	Rat		
	dermal	LD50 > 9400 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 310 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
77-58-7	Dibutyltin dilaurate				
	oral	LD50 2071 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
101-68-8	diphenylmethane-4,4'-diisocyanate				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >9400 mg/kg	Rabbit		
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
5873-54-1	diphenylmethane-2,4'-diisocyanate				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >9400 mg/kg	Rabbit		
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

### Sensitising effects

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 550**

Revision date: 13.12.2023

Product code: 10731

Page 12 of 17

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Isocyanic acid, polymethylenepolyphenylene ester; diphenylmethane-4,4'-diisocyanate; diphenylmethane-2,4'-diisocyanate)

May cause an allergic skin reaction. (Hexamethylene diisocyanate, oligomers; Isocyanic acid, polymethylenepolyphenylene ester; Dibutyltin dilaurate; diphenylmethane-4,4'-diisocyanate; diphenylmethane-2,4'-diisocyanate)

Contains isocyanates. May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (butanone; ethyl methyl ketone)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No information available.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**11.2. Information on other hazards****Endocrine disrupting properties**

Endocrine disrupting potential No information available.

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 13 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
28182-81-2	Hexamethylene diisocyanate, oligomers					
	Acute fish toxicity	LC50 >100 mg/l	96 h			
	Acute crustacea toxicity	EC50 >100 mg/l	48 h			
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 161 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 408 mg/l	48 h	Daphnia magna		
77-58-7	Dibutyltin dilaurate					
	Acute fish toxicity	LC50 3,1 mg/l	96 h	fish		
	Acute algae toxicity	ErC50 1 mg/l	72 h			
	Acute crustacea toxicity	EC50 <0,463 mg/l	48 h	Daphnia magna (Big water flea)		
101-68-8	diphenylmethane-4,4'-diisocyanate					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50 >1640 mg/l	72 h	Scenedesmus subspicatus		
	Crustacea toxicity	NOEC >10 mg/l	21 d	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	EC50 >100 mg/l ( )	3 h	Activated sludge		
5873-54-1	diphenylmethane-2,4'-diisocyanate					
	Acute fish toxicity	LC50 55 mg/l	96 h	Cyprinus carpio (Common Carp)		

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
101-68-8	diphenylmethane-4,4'-diisocyanate			
	OECD 302C	0%	28	
	Not readily biodegradable (according to OECD criteria)			

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-93-3	butanone; ethyl methyl ketone	0,29
108-65-6	2-methoxy-1-methylethyl acetate	0,43
77-58-7	Dibutyltin dilaurate	4,44

#### BCF

CAS No	Chemical name	BCF	Species	Source
101-68-8	diphenylmethane-4,4'-diisocyanate	200	Cyprinus carpio (Common Carp)	

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 14 of 17

### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

### Further information

There are no data available on the mixture itself.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Dispose of waste according to applicable legislation.

Do not mix with other wastes.

#### Contaminated packaging

Dispose according to legislation.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	RESIN SOLUTION
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D
Limited quantity:	5 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

### Inland waterways transport (ADN)

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D
Limited quantity:	5 L

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 15 of 17

Excepted quantity: E2

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1866  
**14.2. UN proper shipping name:** RESIN SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: -  
Limited quantity: 5 L  
Excepted quantity: E2  
EmS: F-E, S-E

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1866  
**14.2. UN proper shipping name:** RESIN SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

Warning : Flammable liquids

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30, Entry 40, Entry 74, Entry 75

Directive 2004/42/EC on VOC in 65,61 %  
paints and varnishes: 616,8 - 623,3 g/l  
Information according to Directive P5c FLAMMABLE LIQUIDS  
2012/18/EU (SEVESO III):

#### Additional information

Observe in addition any national regulations!  
Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 550

Revision date: 13.12.2023

Product code: 10731

Page 16 of 17

#### National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

#### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 4,7,9,15.

#### Abbreviations and acronyms

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Skin Corr: Skin corrosion

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Eye Irrit: Eye irritation

Resp. Sens: Respiratory sensitisation

Skin Sens: Skin sensitisation

Muta: Germ cell mutagenicity

Carc: Carcinogenicity

Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H336	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.



**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 550**

Revision date: 13.12.2023

Product code: 10731

Page 17 of 17

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H360FD	May damage fertility. May damage the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*