

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 1 of 11

1. Identification

Product identifier

DINITROL 550

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Adhesion promoter

Uses advised against

No further relevant information available.

Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980
E-mail: msds@dinol.com
Contact person: Labor
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

Supplier

Company name: DINOL U.S. Inc.
Street: 8500 Cotter Street, Lewis Center
Place: USA-43035 Ohio
Telephone: 740-548-1656
E-mail: info@dinolus.com
Internet: www.dinol.com

Telefax: 740-548-1657

Emergency phone number: 3E Company Emergency +1-866-404-4230

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Flammable liquids: Flam. Liq. 2
Serious eye damage/eye irritation: Eye Irrit. 2A
Respiratory or skin sensitization: Resp. Sens. 1
Respiratory or skin sensitization: Skin Sens. 1
Carcinogenicity: Carc. 2
Reproductive toxicity: Repr. 1B
Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects)

Label elements

29 CFR Part 1910.1200

Signal word: Danger

Pictograms:



Hazard statements

Highly flammable liquid and vapor
May cause an allergic skin reaction
Causes serious eye irritation

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 2 of 11

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause drowsiness or dizziness

Suspected of causing cancer

May damage fertility or the unborn child

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash water thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

Wear respiratory protection.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a poison center/doctor.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

In case of fire: Use water to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Hazards not otherwise classified

No information available.

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Components	Quantity
78-93-3	butanone; ethyl methyl ketone	82.6 %
28182-81-2	Hexamethylene diisocyanate, oligomers	8.18 %
9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	0.818 %
77-58-7	Dibutyltin dilaurate	0.19 %

Further Information

Full text of H statements: see section 16.

4. First-aid measures

Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 3 of 11

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder. Water fog.

Unsuitable extinguishing media

High power water jet.

Specific hazards arising from the chemical

No further relevant information available.

Special protective equipment and precautions for fire-fighters

No special measures are necessary.

Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Suppress gases/vapors/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapors/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow to enter into surface water or drains.

Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 4 of 11

For cleaning up

Provide adequate ventilation.
Clear contaminated areas thoroughly.
Do not rinse down with water.

Other information

No information available.

Reference to other sections

Safe handling: see section 7
Personal protection equipment (PPE): see section 8
Disposal: see section 13

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed. Keep container tightly closed and dry.
maximum storage temperature : < 40 °C
minimum storage temperature : > 4 °C
storage temperature: : 4 - 40 °C

8. Exposure controls/personal protection**Control parameters**

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 5 of 11

Exposure limits

CAS No	Substance	ppm	mg/m ³	f/cc	Category	Origin
78-93-3	2-Butanone (Methyl ethyl ketone)	200	590		TWA (8 h)	REL
78-93-3	2-Butanone	200	590		TWA (8 h)	REL
		300	885		STEL (15 min)	REL
78-93-3	Methyl ethyl ketone	200			TWA (8 h)	ACGIH-2023
		300			STEL (15 min)	ACGIH-2023
101-68-8	Methylene bisphenyl isocyanate (MDI)	C 0.02	C 0.2		Ceiling	REL
101-68-8	Methylene bisphenyl isocyanate	0.005	0.05		TWA (8 h)	REL
		C 0.02	C 0.2		10 min	REL
101-68-8	Methylene bisphenyl isocyanate	0.005			TWA (8 h)	ACGIH-2023

Biological Exposure Indices (BEI-ACGIH)

CAS No	Substance	Determinant	Value	Test material	Sampling time
78-93-3	METHYL ETHYL KETONE	Methyl ethyl ketone	2 mg/L	urine	End of shift

Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141). Filter material/medium : A

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Liquid
Color: black

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 6 of 11

Odor:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		79 - 80,5 °C
Flammability:	Highly flammable liquid and vapor.	
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	- 4 °C	
Auto-ignition temperature:	> 300 °C	
Decomposition temperature:	not applicable	
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	Immiscible	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapor pressure:	not determined	
Density (at 20 °C):	0,94 - 0,95 g/cm ³	
Relative vapour density:	not determined	
Particle characteristics:	not applicable	

Other information

Information with regard to physical hazard classes

Explosive properties

The product is: not explosive. In use, may form flammable/explosive vapor-air mixture.

Sustaining combustion:

No data available

Oxidizing properties

not determined

Other safety characteristics

Solvent content:

65,6 %

Softening point:

not determined

Viscosity / dynamic:

not determined

Further Information

No information available.

10. Stability and reactivity

Reactivity

No hazardous reaction when handled and stored according to provisions.

Chemical stability

Stability:

Stable

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Hazardous reactions:

Will not occur

No known hazardous reactions.

Conditions to avoid

No further relevant information available.

Incompatible materials

No further relevant information available.

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 7 of 11

Hazardous decomposition products

No known hazardous decomposition products.

11. Toxicological information

Route(s) of Entry

No information available.

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix tested

	Dose	Species	Source
LC50, inhalation (dust/mist) (4 h)	113 mg/l		

ATEmix calculated

ATE (oral) 3307 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 134,5 mg/l

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 2740 mg/kg	Rat		
	dermal	LD50 6480 mg/kg	Rabbit		
28182-81-2	Hexamethylene diisocyanate, oligomers				
	oral	LD50 >5000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester				
	oral	LD50 > 10000 mg/kg	Rat		
	dermal	LD50 > 9400 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 310 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
77-58-7	Dibutyltin dilaurate				
	oral	LD50 2071 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		

Irritation and corrosivity

Causes serious eye irritation

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled (Isocyanic acid, polymethylenepolyphenylene ester)

May cause an allergic skin reaction (Hexamethylene diisocyanate, oligomers; Isocyanic acid, polymethylenepolyphenylene ester; Dibutyltin dilaurate)

Carcinogenic/mutagenic/toxic effects for reproduction

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 8 of 11

Suspected of causing cancer (Isocyanic acid, polymethylenepolyphenylene ester)
May damage fertility or the unborn child (Dibutyltin dilaurate)
Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (butanone; ethyl methyl ketone)

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (OSHA): No ingredient of this mixture is listed.

Carcinogenicity (IARC): Polymethylene polyphenyl isocyanate (CAS 9016-87-9) is listed in group 3.

Carcinogenicity (NTP): No ingredient of this mixture is listed.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information

Persistence and degradability

There are no data available on the mixture itself.

Bioaccumulative potential

There are no data available on the mixture itself.

Mobility in soil

There are no data available on the mixture itself.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No information available.

Further information

There are no data available on the mixture itself.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.
Do not mix with other wastes.

Contaminated packaging

Dispose according to legislation.

14. Transport information

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 9 of 11

U.S. DOT 49 CFR 172.101

UN number or ID number: UN 1866
Proper shipping name: RESIN SOLUTION
Transport hazard class(es): 3
Packing group: II
Hazard label: 3



Marine transport (IMDG)

UN number or ID number: UN 1866
UN proper shipping name: RESIN SOLUTION
Transport hazard class(es): 3
Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 5 L
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1866
UN proper shipping name: RESIN SOLUTION
Transport hazard class(es): 3
Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

Warning : Flammable liquids

15. Regulatory information

U.S. Regulations

National Inventory TSCA

Substance/product listed in the following inventories: TSCA

National regulatory information

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 10 of 11

SARA Section 304 CERCLA:

Methyl ethyl ketone (78-93-3): Reportable quantity = 5,000 (2270) lbs. (kg)

Methylenebis(phenylisocyanate)(MDI) (101-68-8): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:

Methyl ethyl ketone (78-93-3): Fire hazard, Immediate (acute) health hazard

Hexamethylene diisocyanate, oligomers (28182-81-2): Immediate (acute) health hazard

Methylenebis(phenylisocyanate)(MDI) (9016-87-9): Delayed (chronic) health hazard, Immediate (acute) health hazard

Dibutyltin dilaurate (77-58-7): Immediate (acute) health hazard, Delayed (chronic) health hazard

SARA Section 313 Toxic release inventory:

Methylenebis(phenylisocyanate)(MDI) (101-68-8): De minimis limit = 1.0 %, Reportable threshold = Standard

Clean Air Act Section 112(b):

Methyl ethyl ketone (78-93-3), Methylenebis(phenylisocyanate)(MDI) (101-68-8)

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Directive 2004/42/EC on VOC in
paints and varnishes: 65,61 %
616,8 - 623,3 g/l

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

16. Other information

Hazardous Materials Identification System (HMIS)

Health: 2
Flammability: 3
Physical Hazard: 0

NFPA Hazard Ratings

Health: 2
Flammability: 3
Reactivity: 0
Unique Hazard: none



Changes

Revision date: 12/13/2023

Revision No: 1,5

This data sheet contains changes from the previous version in section(s): 4,7,9.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

DINITROL 550

Revision date: 12/13/2023

Product code: 10731

Page 11 of 11

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)