

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 6030

UFI: XQPH-50VC-P00G-MWF1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Bodyfiller/stopper

1.3. Details of the supplier of the safety data sheet

| | | | |
|-------------------------|----------------------|----------|-----------------------|
| Company name: | DINOL GmbH | | |
| Street: | Pyrmonter Strasse 76 | | |
| Place: | D-32676 Luegde | | |
| Telephone: | + 49 (0) 5281 982980 | Telefax: | + 49 (0) 5281 9829860 |
| E-mail: | msds@dinol.com | | |
| Contact person: | Labor | | |
| Responsible Department: | msds@dinol.com | | |

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

Further Information
160369

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Repr. 2; H361d
STOT RE 1; H372
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

styrene

Signal word: Danger

Pictograms:



Hazard statements

| | |
|-------|---|
| H226 | Flammable liquid and vapour. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H361d | Suspected of damaging the unborn child. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H412 | Harmful to aquatic life with long lasting effects. |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 2 of 14

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H361d-H372-H412

Precautionary statements

P260-P280

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|-------------|---|--------------|------------------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (GB CLP Regulation) | | | |
| 100-42-5 | styrene | | | 15 - < 20 % |
| | 202-851-5 | 601-026-00-0 | 01-2119457861-32 | |
| | Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H226 H361d H332 H315 H319 H335 H372 H304 H412 | | | |
| 128601-23-0 | Hydrocarbons, C9, aromatics | | | 1 - < 5 % |
| | 918-668-5 | | 01-2119455851-35 | |
| | Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066 | | | |
| 130-15-4 | 1,4-naphthoquinone | | | < 0.1 % |
| | 204-977-6 | | 01-2120760462-57 | |
| | Acute Tox. 1, Acute Tox. 3, Skin Corr. 1C, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H330 H301 H314 H319 H317 H335 H400 H410 | | | |

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|-------------|-----------|---|-------------|
| | | Specific Conc. Limits, M-factors and ATE | |
| 100-42-5 | 202-851-5 | styrene | 15 - < 20 % |
| | | inhalation: LC50 = < 10 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = > 5000 mg/kg | |
| 128601-23-0 | 918-668-5 | Hydrocarbons, C9, aromatics | 1 - < 5 % |
| | | dermal: LD50 = > 3160 mg/kg; oral: LD50 = > 2000 mg/kg | |
| 130-15-4 | 204-977-6 | 1,4-naphthoquinone | < 0.1 % |
| | | inhalation: ATE = 0,05 mg/l (vapours); inhalation: LC50 = 0,046 mg/l (dusts or mists); oral: LD50 = 124 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1 | |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

After inhalation

Provide fresh air. In case of irregular breathing or respiratory arrest provide artificial respiration. If unconscious but breathing normally, place in recovery position and seek medical advice. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately. Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water fog.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure. Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 4 of 14

with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

- Provide adequate ventilation.
- Wear personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

- Do not allow uncontrolled discharge of product into the environment.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For containment**

- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
- Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

- Provide adequate ventilation.
- Clear contaminated areas thoroughly.
- Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

- Keep away from sources of ignition - No smoking.
- Take precautionary measures against static discharges.
- Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs.
- When using do not eat or drink.
- Wash hands before breaks and after work.
- Avoid contact with skin and eyes.
- Remove contaminated, saturated clothing immediately.
- Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 5 of 14

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

Further information on storage conditions

Keep container tightly closed and in a well-ventilated place. Keep container dry.

Protect from direct sunlight.

storage temperature: 15 - 25 °C

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|------------|----------------------------------|-----|-------------------|-----------|---------------|--------|
| 7429-90-5 | Aluminium metal, respirable dust | - | 4 | | TWA (8 h) | WEL |
| 100-42-5 | Styrene | 100 | 430 | | TWA (8 h) | WEL |
| | | 250 | 1080 | | STEL (15 min) | WEL |
| 14807-96-6 | Talc respirable dust | - | 1 | | TWA (8 h) | WEL |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 6 of 14

DNEL/DMEL values

| CAS No | Substance | Exposure route | Effect | Value |
|--------------------------|-------------------------------|----------------|--------------------------|-------|
| 100-42-5 | styrene | | | |
| Worker DNEL, acute | inhalation | local | 289 mg/m ³ | |
| Worker DNEL, long-term | inhalation | systemic | 306 mg/m ³ | |
| Worker DNEL, long-term | inhalation | local | 85 mg/m ³ | |
| Worker DNEL, long-term | dermal | local | 406 mg/person/day | |
| Consumer DNEL, acute | inhalation | local | 182,75 mg/m ³ | |
| Consumer DNEL, acute | inhalation | systemic | 174,25 mg/m ³ | |
| Consumer DNEL, long-term | inhalation | systemic | 10,2 mg/m ³ | |
| Consumer DNEL, long-term | dermal | systemic | 343 mg/kg bw/day | |
| Consumer DNEL, long-term | oral | systemic | 2,1 mg/kg bw/day | |
| 7429-90-5 | aluminium powder (stabilised) | | | |
| Worker DNEL, long-term | inhalation | systemic | 3,72 mg/m ³ | |
| Worker DNEL, long-term | inhalation | local | 3,72 mg/m ³ | |
| Consumer DNEL, long-term | oral | systemic | 3,95 mg/kg bw/day | |
| | | | | |
| 128601-23-0 | Hydrocarbons, C9, aromatics | | | |
| Worker DNEL, long-term | inhalation | systemic | 150 mg/m ³ | |
| Worker DNEL, long-term | dermal | systemic | 25 mg/kg bw/day | |
| Consumer DNEL, long-term | inhalation | systemic | 32 mg/m ³ | |
| Consumer DNEL, long-term | dermal | systemic | 11 mg/kg bw/day | |
| Consumer DNEL, long-term | oral | systemic | 11 mg/kg bw/day | |
| 130-15-4 | 1,4-naphthoquinone | | | |
| Worker DNEL, long-term | inhalation | systemic | 0,033 mg/m ³ | |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 7 of 14

PNEC values

| CAS No | Substance | |
|---------------------------|--|--------------|
| Environmental compartment | | Value |
| 100-42-5 | styrene | |
| | | |
| | Freshwater | 0,028 mg/l |
| | Marine water | 0,014 mg/l |
| | Freshwater sediment | 0,614 mg/kg |
| | Marine sediment | 0,307 mg/kg |
| | Micro-organisms in sewage treatment plants (STP) | 5 mg/l |
| | Soil | 0,2 mg/kg |
| 7429-90-5 | aluminium powder (stabilised) | |
| | Freshwater | 0,0749 mg/l |
| | Micro-organisms in sewage treatment plants (STP) | 20 mg/l |
| 130-15-4 | 1,4-naphthoquinone | |
| | Freshwater | 0,0261 mg/l |
| | Marine water | 0,00261 mg/l |
| | Freshwater sediment | 0,0321 mg/l |
| | Soil | 0,049 mg/kg |

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time:: 480 min.

NBR (Nitrile rubber), Breakthrough time:: 30 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141),. Filter material/medium: A

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 8 of 14

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|------------------|----------------|
| Physical state: | Paste |
| Colour: | silver |
| Odour: | characteristic |
| Odour threshold: | not determined |

Test method

| | | |
|---|--|-----------|
| Melting point/freezing point: | not determined | |
| Boiling point or initial boiling point and boiling range: | 140 °C | |
| Flammability: | not applicable | |
| Lower explosion limits: | 1,2 vol. % | |
| Upper explosion limits: | 8,9 vol. % | |
| Flash point: | 31 °C | DIN 51755 |
| Auto-ignition temperature: | 480 °C | |
| Decomposition temperature: | not determined | |
| pH-Value: | not determined | |
| Viscosity / kinematic: | not determined | |
| Water solubility: | The study does not need to be conducted because the substance is known to be insoluble in water. | |
| Solubility in other solvents | not determined | |
| Partition coefficient n-octanol/water: | not determined | |
| Vapour pressure: | 6,7 hPa | |
| (at 20 °C) | | |
| Density (at 20 °C): | 1,70 g/cm³ | ISO 2811 |
| Relative vapour density: | not determined | |

9.2. Other information

Information with regard to physical hazard classes

| | |
|---------------------------|----------------|
| Explosive properties | not determined |
| Self-ignition temperature | |
| Solid: | not applicable |
| Gas: | not applicable |
| Oxidizing properties | |
| not determined | |

Other safety characteristics

| | |
|--------------------------|---------------------|
| Evaporation rate: | not determined |
| Solvent separation test: | <3 % (ADR/RID) |
| Solvent content: | 15,5 % |
| Solid content: | 84,5 % |
| Sublimation point: | not determined |
| Softening point: | not determined |
| Pour point: | not determined |
| Viscosity / dynamic: | 110000-130000 mPa·s |
| (at 20 °C) | |

Further Information

No information available.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 9 of 14

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

In case of warming: Danger of polymerisation

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 70,46 mg/l; ATE (inhalation dust/mist) 9,609 mg/l

| CAS No | Chemical name | | | | |
|-------------|-----------------------------|-------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 100-42-5 | styrene | | | | |
| | oral | LD50 > 5000 mg/kg | Rat | | |
| | inhalation vapour | LC50 < 10 mg/l | Rat | | |
| | inhalation dust/mist | ATE 1,5 mg/l | | | |
| 128601-23-0 | Hydrocarbons, C9, aromatics | | | | |
| | oral | LD50 > 2000 mg/kg | Rat | | |
| | dermal | LD50 > 3160 mg/kg | Rabbit | | |
| 130-15-4 | 1,4-naphthoquinone | | | | |
| | oral | LD50 124 mg/kg | Rat | | |
| | inhalation vapour | ATE 0,05 mg/l | | | |
| | inhalation (4 h) dust/mist | LC50 0,046 mg/l | Rat | | |

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 10 of 14

Suspected of damaging the unborn child. (styrene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (styrene)

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

| CAS No | Chemical name | | | | | |
|-------------|-----------------------------|--------------|-----------|---------|--------|--------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 100-42-5 | styrene | | | | | |
| | Acute fish toxicity | LC50 mg/l | > 1- < 10 | 96 h | | |
| | Acute crustacea toxicity | EC50 mg/l | >1- < 10 | 48 h | | |
| 128601-23-0 | Hydrocarbons, C9, aromatics | | | | | |
| | Acute fish toxicity | LC50 mg/l | 1 - 10 | 96 h | | |

12.2. Persistence and degradability

There are no data available on the mixture itself.

| There are no data available on the mixture itself. | | | | |
|--|---|-------|----|--------|
| CAS No | Chemical name | | | |
| | Method | Value | d | Source |
| | Evaluation | | | |
| 100-42-5 | styrene | | | |
| | | 70,9% | 28 | |
| | Readily biodegradable (according to OECD criteria). | | | |

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|----------|---------------|---------|
| 100-42-5 | styrene | 2,96 |

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 11 of 14

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.
List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 640E
Limited quantity: 5 L
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Other applicable information (land transport)

E1

No good of class 3 according to ADR/RID chapter 2.2.3.1.5.

Marine transport (IMDG)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 12 of 14

14.4. Packing group:

III

Hazard label:

3



Marine pollutant:

no

Special Provisions:

223, 955

Limited quantity:

5 L

EmS:

F-E, S-E

Other applicable information (marine transport)

E1

Transport in accordance with paragraph 2.3.2.5 of the IMDG Code.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

UN 1866

14.2. UN proper shipping name:

Resin solution

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Special Provisions:

A3

Limited quantity Passenger:

10 L

IATA-packing instructions - Passenger:

355

IATA-max. quantity - Passenger:

60 L

IATA-packing instructions - Cargo:

366

IATA-max. quantity - Cargo:

220 L

Other applicable information (air transport)

E1

Passenger-LQ: Y344

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in

15,5 % (< 250 g/l)

paints and varnishes:

Subcategory according to

Bodyfiller/stopper - All types, VOC limit value: 250 g/l

Directive 2004/42/EC:

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

Additional information

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 13 of 14

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronyms

Water-react: Substances and mixtures which in contact with water emit flammable gases

Flam. Liq: Flammable liquids

Flam. Sol: Flammable solids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Corr: Skin corrosion

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Safety Data Sheet

according to UK REACH Regulation

DINITROL 6030

Revision date: 21.11.2023

Product code: 5006

Page 14 of 14

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Flam. Liq. 3; H226 | On basis of test data |
| Skin Irrit. 2; H315 | Calculation method |
| Eye Irrit. 2; H319 | Calculation method |
| Repr. 2; H361d | Calculation method |
| STOT RE 1; H372 | Calculation method |
| Aquatic Chronic 3; H412 | Calculation method |

Relevant H and EUH statements (number and full text)

| | |
|--------|---|
| H226 | Flammable liquid and vapour. |
| H301 | Toxic if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361d | Suspected of damaging the unborn child. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)