

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 1 of 13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 6070

UFI: X2VE-E051-Y007-7CG5

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Bodyfiller/stopper

#### 1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH		
Street:	Pyrmonter Strasse 76		
Place:	D-32676 Luegde		
Telephone:	+ 49 (0) 5281 982980	Telefax:	+ 49 (0) 5281 9829860
E-mail:	msds@dinol.com		
Contact person:	Labor		
Responsible Department:	msds@dinol.com		

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Flam. Liq. 3; H226  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
Repr. 2; H361d  
STOT RE 1; H372

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

styrene

Signal word: Danger

##### Pictograms:



##### Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

##### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 2 of 13

- P303+P361+P353 protection.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P403+P235 Store in a well-ventilated place. Keep cool.

### Special labelling of certain mixtures

- EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust. Restricted to professional users.

### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



### Hazard statements

H361d-H372

### Precautionary statements

P260-P280

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
100-42-5	styrene			15 - < 20 %
	202-851-5	601-026-00-0	01-2119457861-32	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H226 H361d H332 H315 H319 H335 H372 H304 H412			
13463-67-7	titanium dioxide			5 - < 10 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351			
130-15-4	1,4-Naphthoquinone			< 0.1 %
	204-977-6		01-2120760462-57	
	Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H330 H301 H314 H318 H317 H335 H400 H410			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 3 of 13

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
100-42-5	202-851-5	styrene	15 - < 20 %
		inhalation: LC50 = < 10 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = > 5000 mg/kg	
13463-67-7	236-675-5	titanium dioxide	5 - < 10 %
		dermal: LD50 = > 10000 mg/kg; oral: LD50 = > 20000 mg/kg	
130-15-4	204-977-6	1,4-Naphthoquinone	< 0.1 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); oral: ATE = 100 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1	

#### Further Information

The homogeneous mixing of this product is controlled by continuous physical tests. Formerly dusty raw materials are completely integrated into the liquid/pasty mass. Possible AGW-values for solid substances are therefore not given, as there is no longer any risk of inhalation of these substances (when handling this mixture).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

##### After inhalation

Provide fresh air. In case of irregular breathing or respiratory arrest provide artificial respiration.

If unconscious but breathing normally, place in recovery position and seek medical advice.

In all cases of doubt, or when symptoms persist, seek medical advice.

##### After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention.

##### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

##### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately. Put victim at rest, cover with a blanket and keep warm.

#### 4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water fog.

##### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 6070**

Revision date: 21.11.2023

Product code: 5009

Page 4 of 13

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

**5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Vapours may form explosive mixtures with air.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 5 of 13

Avoid contact with skin and eyes.  
Remove contaminated, saturated clothing immediately.  
Do not breathe gas/vapour/aerosol.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place.

#### Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

#### Further information on storage conditions

Keep container tightly closed and in a well-ventilated place. Keep container dry.  
Protect from direct sunlight.  
storage temperature: 15 - 25 °C

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
7727-43-7	Barium sulphate, inhalable dust	-	10		TWA (8 h)	WEL
100-42-5	Styrene	100	430		TWA (8 h)	WEL
		250	1080		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL

#### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
100-42-5	styrene			
Worker DNEL, acute		inhalation	local	289 mg/m³
Worker DNEL, long-term		inhalation	systemic	306 mg/m³
Worker DNEL, long-term		inhalation	local	85 mg/m³
Worker DNEL, long-term		dermal	local	406 mg/person/day
Consumer DNEL, acute		inhalation	local	182,75 mg/m³
Consumer DNEL, acute		inhalation	systemic	174,25 mg/m³
Consumer DNEL, long-term		inhalation	systemic	10,2 mg/m³
Consumer DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2,1 mg/kg bw/day
7727-43-7	Barium sulfate			
Worker DNEL, long-term		inhalation	systemic	10 mg/m³
Worker DNEL, long-term		inhalation	local	10 mg/m³
Consumer DNEL, long-term		inhalation	systemic	10 mg/m³
Consumer DNEL, long-term		oral	systemic	13000 mg/kg bw/day

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 6 of 13

### PNEC values

CAS No	Substance	
Environmental compartment		Value
100-42-5	styrene	
Freshwater		0,028 mg/l
Marine water		0,014 mg/l
Freshwater sediment		0,614 mg/kg
Marine sediment		0,307 mg/kg
Micro-organisms in sewage treatment plants (STP)		5 mg/l
Soil		0,2 mg/kg
7727-43-7	Barium sulfate	
Freshwater		0,115 mg/l
Freshwater sediment		600,4 mg/kg
Micro-organisms in sewage treatment plants (STP)		62,2 mg/l
Soil		207,7 mg/kg

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time:: 480 min.

NBR (Nitrile rubber), Breakthrough time:: 30 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

##### Skin protection

Wear anti-static footwear and clothing

##### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: A

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:

Paste

Colour:

dark grey

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 7 of 13

Odour: characteristic  
Odour threshold: not determined

### Test method

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	145 °C	
Flammability:	not applicable	
Lower explosion limits:	1,2 vol. %	
Upper explosion limits:	8,9 vol. %	
Flash point:	31 °C	DIN 51755
Auto-ignition temperature:	480 °C	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	6,7 hPa	
(at 20 °C)		
Density (at 20 °C):	1,80 g/cm <sup>3</sup>	ISO 2811
Relative vapour density:	not determined	

## 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties  
not determined

Self-ignition temperature

Solid: not applicable  
Gas: not applicable

Oxidizing properties  
not determined

### Other safety characteristics

Evaporation rate: not determined

Solvent separation test: <3 % (ADR/RID)

Solvent content: 13,5 %

Solid content: 86,5 %

Sublimation point: not determined

Softening point: not determined

Pour point: not determined

Viscosity / dynamic: 110000 - 130000 mPa·s  
(at 20 °C)

### Further Information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 8 of 13

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

In case of warming: Danger of polymerisation

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

Carbon monoxide

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) 60,69 mg/l; ATE (inhalation dust/mist) 8,277 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
100-42-5	styrene				
	oral	LD50 > 5000 mg/kg	Rat		
	inhalation vapour	LC50 < 10 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
13463-67-7	titanium dioxide				
	oral	LD50 > 20000 mg/kg	Rat		
	dermal	LD50 > 10000 mg/kg	Rabbit		
130-15-4	1,4-Naphthoquinone				
	oral	ATE 100 mg/kg			
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (styrene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (styrene)



# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 9 of 13

### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Endocrine disrupting potential No information available.

### Further information

There are no data available on the preparation/mixture itself.

## SECTION 12: Ecological information

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
100-42-5	styrene					
	Acute fish toxicity	LC50 mg/l	> 1- < 10	96 h		
	Acute crustacea toxicity	EC50 mg/l	>1- < 10	48 h		

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

There are no data available on the mixture itself				
CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
100-42-5	styrene			
		70,9%	28	
	Readily biodegradable (according to OECD criteria).			

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-42-5	styrene	2,96

### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

### Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 10 of 13

### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

### Contaminated packaging

Remove according to the regulations.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Special Provisions: 640E  
Limited quantity: 5 L  
Transport category: 3  
Hazard No: 30  
Tunnel restriction code: D/E

### Other applicable information (land transport)

E1

No good of class 3 according to ADR/RID chapter 2.2.3.1.5.

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: no  
Special Provisions: 223, 955  
Limited quantity: 5 L  
EmS: F-E, S-E

### Other applicable information (marine transport)

E1

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 11 of 13

Transport in accordance with paragraph 2.3.2.5 of the IMDG Code.

### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Special Provisions:	A3	
Limited quantity Passenger:	10 L	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

### Other applicable information (air transport)

E1  
Passenger-LQ: Y344

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

Warning: Flammable liquids

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes:

Subcategory according to  
Directive 2004/42/EC: Bodyfiller/stopper - All types, VOC limit value: 250 g/l

#### Additional information

Observe in addition any national regulations!  
Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

#### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6070

Revision date: 21.11.2023

Product code: 5009

Page 12 of 13

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,9.

### Abbreviations and acronyms

Flam. Liq: Flammable liquids  
 Acute Tox: Acute toxicity  
 Asp. Tox: Aspiration hazard  
 Skin Corr: Skin corrosion  
 Skin Irrit: Skin irritation  
 Eye Dam: Eye damage  
 Eye Irrit: Eye irritation  
 Skin Sens: Skin sensitisation  
 Carc: Carcinogenicity  
 Repr: Reproductive toxicity  
 STOT SE: Specific target organ toxicity - single exposure  
 STOT RE: Specific target organ toxicity - repeated exposure  
 Aquatic Acute: Acute aquatic hazard  
 Aquatic Chronic: Chronic aquatic hazard  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT RE 1; H372	Calculation method

### Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.  
 H301 Toxic if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H330 Fatal if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H351 Suspected of causing cancer.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 6070**

Revision date: 21.11.2023

Product code: 5009

Page 13 of 13

H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH212	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*