

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

DINITROL 540

UFI: 794X-70P6-7001-C1FS

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Activator

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

1.4. Emergency telephone number: Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

ethyl acetate

Signal word: Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 2 of 11

- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.

Special labelling of certain mixtures

- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction. Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
141-78-6	ethyl acetate			90 - < 95 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
4151-51-3	Tris(p-isocyanatophenyl) thiophosphate			5 - < 10 %
	223-981-9		01-2119948848-16	
	Acute Tox. 4; H302			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
141-78-6	205-500-4	ethyl acetate	90 - < 95 %
		inhalation: LC50 = 1600 mg/l (vapours); dermal: LD50 = 180000 mg/kg; oral: LD50 = 4935 mg/kg	
4151-51-3	223-981-9	Tris(p-isocyanatophenyl) thiophosphate	5 - < 10 %
		oral: ATE = 500 mg/kg	

Further Information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

- Remove contaminated, saturated clothing immediately.
- In all cases of doubt, or when symptoms persist, seek medical advice.
- Never give anything by mouth to an unconscious person or a person with cramps.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 3 of 11

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

No further relevant information available.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 4 of 11

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

- Provide adequate ventilation.
- Clear contaminated areas thoroughly.
- Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Advice on general occupational hygiene

- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Not required.

Further information on storage conditions

- Keep container tightly closed in a cool, well-ventilated place.
- maximum storage temperature : < 40 °C
- minimum storage temperature : > 4 °C
- storage temperature: : 4 - 40 °C

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 5 of 11

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
141-78-6	ethyl acetate		
Worker DNEL, long-term	inhalation	systemic	734 mg/m ³
Worker DNEL, acute	inhalation	systemic	1468 mg/m ³
Worker DNEL, long-term	inhalation	local	734 mg/m ³
Worker DNEL, acute	inhalation	local	1468 mg/m ³
Worker DNEL, long-term	dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	367 mg/m ³
Consumer DNEL, acute	inhalation	systemic	734 mg/m ³
Consumer DNEL, long-term	dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4,5 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
141-78-6	ethyl acetate	
Freshwater	0,24 mg/l	
Marine water	0,024 mg/l	
Freshwater sediment	1,15 mg/kg	
Marine sediment	0,115 mg/kg	
Secondary poisoning	0,20 mg/kg	
Micro-organisms in sewage treatment plants (STP)	650 mg/l	
Soil	0,148 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment
Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 6 of 11

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
gas filtering equipment (EN 141). Filter material/medium : A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	transparent light yellow	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		36 °C
Flammability:		not applicable
Lower explosion limits:		2,1 vol. %
Upper explosion limits:		11,5 vol. %
Flash point:		-5 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		Immiscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		97 hPa
(at 20 °C)		
Density (at 20 °C):		0,93 g/cm ³
Relative vapour density:		not determined
Particle characteristics:		not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not determined

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate:

not determined

Solvent content:

89,9

Softening point:

not determined

Viscosity / dynamic:

not determined

Further Information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 7 of 11

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in GB CLP Regulation
Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix tested

	Dose	Species	Source
LD50, oral	5005 mg/kg		

ATEmix calculated

ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
141-78-6	ethyl acetate				
	oral	LD50 mg/kg	4935	Rabbit	
	dermal	LD50 mg/kg	180000	Rabbit	
	inhalation (4 h) vapour	LC50	1600 mg/l	Rat	
4151-51-3	Tris(p-isocyanatophenyl) thiophosphate				
	oral	ATE mg/kg	500		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains isocyanates. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 8 of 11

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50 230 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 3300 mg/l		Desmodesmus subspicatus	48 h	
	Acute crustacea toxicity	EC50 717 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	EC50 2900 mg/l ()		Pseudomonas putida	16 h	

12.2. Persistence and degradability

No further relevant information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
141-78-6	ethyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	100 %	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No further relevant information available.

Further information

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 9 of 11

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Dispose of waste according to applicable legislation.
Do not mix with other wastes.

Contaminated packaging

Dispose according to legislation.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: RESIN SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 640D
 Limited quantity: 5 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 640D
 Limited quantity: 5 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: RESIN SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Marine pollutant: no

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 10 of 11

Special Provisions: -
 Limited quantity: 5 L
 Excepted quantity: E2
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: RESIN SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning : Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 89,94 %
 836,4 g/l
 Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

Safety Data Sheet

according to UK REACH Regulation

DINITROL 540

Revision date: 12.12.2023

Product code: 10521

Page 11 of 11

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 11,13.

Abbreviations and acronyms

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)