

# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 535

Revision date: 06/10/2024

Product code: 11001

Page 1 of 11

### 1. Identification

#### Product identifier

DINITROL 535

#### Recommended use of the chemical and restrictions on use

##### Use of the substance/mixture

Adhesion promoter

##### Uses advised against

No further relevant information available.

#### Details of the supplier of the safety data sheet

##### Manufacturer

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

##### Supplier

Company name: DINOL U.S. Inc.  
Street: 8500 Cotter Street, Lewis Center  
Place: USA-43035 Ohio  
Telephone: 740-548-1656  
E-mail: info@dinolus.com  
Internet: www.dinol.com

Telefax: 740-548-1657

**Emergency phone number:** 3E Company Emergency +1-866-404-4230

### 2. Hazard(s) identification

#### Classification of the chemical

##### 29 CFR Part 1910.1200

Flammable liquids: Flam. Liq. 2  
Serious eye damage/eye irritation: Eye Irrit. 2A  
Carcinogenicity: Carc. 2  
Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects)

#### Label elements

##### 29 CFR Part 1910.1200

**Signal word:** Danger

**Pictograms:**



##### Hazard statements

Highly flammable liquid and vapor  
Causes serious eye irritation  
May cause drowsiness or dizziness  
Suspected of causing cancer

##### Precautionary statements

Obtain special instructions before use.

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### DINITROL 535

Revision date: 06/10/2024

Product code: 11001

Page 2 of 11

Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Keep container tightly closed.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Wash water thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 If exposed or concerned: Get medical advice/attention.  
 In case of fire: Use water to extinguish.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.

#### Special labelling of certain mixtures

Restricted to professional users.

#### Hazards not otherwise classified

No information available.

### 3. Composition/information on ingredients

#### Mixtures

##### Hazardous components

CAS No	Components	Quantity
123-86-4	n-butyl acetate	30 %
78-93-3	butanone; ethyl methyl ketone	17 %
141-78-6	ethyl acetate	9.9 %
26426-91-5	Benzene, 2,4-diisocyanato-1-methyl-, polymer with 1,6-diisocyanatohexane	9.9 %
1333-86-4	Carbon Black	4.9 %
4151-51-3	Tris(p-isocyanatophenyl) thiophosphate	4.9 %
82985-35-1	Bis(trimethoxysilylpropyl)amine	1.9 %

#### Further Information

Full text of H statements: see section 16.

### 4. First-aid measures

#### Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice.  
 Never give anything by mouth to an unconscious person or a person with cramps.  
 If unconscious but breathing normally, place in recovery position and seek medical advice.

##### After inhalation

Remove casualty to fresh air and keep warm and at rest.

##### After contact with skin

Change contaminated clothing.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 535**

Revision date: 06/10/2024

Product code: 11001

Page 3 of 11

After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious).  
Do NOT induce vomiting.  
Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.

**Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**Indication of any immediate medical attention and special treatment needed**

No information available.

**5. Fire-fighting measures****Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder. Water fog.

**Unsuitable extinguishing media**

High power water jet.

**Specific hazards arising from the chemical**

No further relevant information available.

**Special protective equipment and precautions for fire-fighters**

No further relevant information available.

**Additional information**

Use water spray/stream to protect personnel and to cool endangered containers. Suppress gases/vapors/mists with water spray jet.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.  
Wear personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Avoid breathing dust/fume/gas/mist/vapors/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).  
Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.  
Clear contaminated areas thoroughly.  
Do not rinse down with water.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 535**

Revision date: 06/10/2024

Product code: 11001

Page 4 of 11

**Other information**

No information available.

**Reference to other sections**

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13

**7. Handling and storage****Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.

**Hints on joint storage**

Not required.

**Further information on storage conditions**

maximum storage temperature : &lt; 40 °C

minimum storage temperature : &gt; 4 °C

storage temperature: : 4 - 40 °C

**8. Exposure controls/personal protection****Control parameters**

# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 535

Revision date: 06/10/2024

Product code: 11001

Page 5 of 11

### Exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	f/cc	Category	Origin
78-93-3	2-Butanone (Methyl ethyl ketone)	200	590		TWA (8 h)	REL
78-93-3	2-Butanone	200	590		TWA (8 h)	REL
		300	885		STEL (15 min)	REL
1333-86-4	Carbon black (in presence of polycyclic aromatic hydrocarbons (PAHs)) (as PAHs)	-	0.1		TWA (8 h)	REL
1333-86-4	Carbon black (inhalable fraction)		3		TWA (8 h)	ACGIH-2023
1333-86-4	Carbon black	-	3.5		TWA (8 h)	REL
141-78-6	Ethyl acetate	400	1400		TWA (8 h)	REL
		400	1400		TWA (8 h)	REL
		400			TWA (8 h)	ACGIH-2023
78-93-3	Methyl ethyl ketone	200			TWA (8 h)	ACGIH-2023
		300			STEL (15 min)	ACGIH-2023
123-86-4	n-Butyl acetate	150	710		TWA (8 h)	REL
		200	950		STEL (15 min)	REL
123-86-4	n-Butyl acetate	50			TWA (8 h)	ACGIH-2023
		150			STEL (15 min)	ACGIH-2023
123-86-4	n-Butyl-acetate	150	710		TWA (8 h)	REL

### Biological Exposure Indices (BEI-ACGIH)

CAS No	Substance	Determinant	Value	Test material	Sampling time
78-93-3	METHYL ETHYL KETONE	Methyl ethyl ketone	2 mg/L	urine	End of shift

### Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (DIN EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

## DINITROL 535

Revision date: 06/10/2024

Product code: 11001

Page 6 of 11

### Skin protection

Wear anti-static footwear and clothing

### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.  
gas filtering equipment (EN 141). Filter material/medium : A

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Physical state:	Liquid	
Color:	black	
Odor:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		79 - 80,5 °C
Flammability:		not applicable
Lower explosion limits:		1,8 vol. %
Upper explosion limits:		11,5 vol. %
Flash point:		- 4 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not applicable
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		completely miscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapor pressure:		105 hPa
(at 20 °C)		
Density (at 20 °C):		0,98 - 0,99 g/cm³
Relative vapour density:		not determined
Particle characteristics:		not applicable

### Other information

#### Information with regard to physical hazard classes

Explosive properties

not determined

Oxidizing properties

not determined

#### Other safety characteristics

Solvent content:

78,7 %

Softening point:

not determined

Viscosity / dynamic:

not determined

#### Further Information

No information available.

## 10. Stability and reactivity

### Reactivity

No hazardous reaction when handled and stored according to provisions.

### Chemical stability

Stability:

Stable

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 535**

Revision date: 06/10/2024

Product code: 11001

Page 7 of 11

The product is stable under storage at normal ambient temperatures.

**Possibility of hazardous reactions**

Hazardous reactions:

Will not occur

No known hazardous reactions.

**Conditions to avoid**

No further relevant information available.

**Incompatible materials**

No information available.

**Hazardous decomposition products**

No known hazardous decomposition products.

**11. Toxicological information****Route(s) of Entry**

No information available.

**Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix tested**

	Dose	Species	Source
LD50, oral	24534 mg/kg		

**ATEmix calculated**

ATE (dermal) 51020 mg/kg; ATE (inhalation vapour) 505,1 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 535

Revision date: 06/10/2024

Product code: 11001

Page 8 of 11

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
123-86-4	n-butyl acetate				
	oral	LD50 10760 mg/kg	Rat		
	dermal	LD50 > 14112 mg/kg	Rabbit		
	inhalation vapour	LC50 > 21 mg/l	Rat		
	inhalation (4 h) dust/mist	LC50 >21 mg/l	Rat		
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 2740 mg/kg	Rat		
	dermal	LD50 6480 mg/kg	Rabbit		
141-78-6	ethyl acetate				
	oral	LD50 5620 mg/kg	Rat		
	dermal	LD50 >20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 50 mg/l	Rat		
26426-91-5	Benzene, 2,4-diisocyanato-1-methyl-, polymer with 1,6-diisocyanatohexane				
	oral	LD50 > 5000 mg/kg	Rat		
1333-86-4	Carbon Black				
	oral	LD50 > 15400 mg/kg	Rat	GESTIS	
	dermal	LD50 > 3000 mg/kg	Rabbit	GESTIS	
4151-51-3	Tris(p-isocyanatophenyl) thiophosphate				
	oral	ATE 500 mg/kg			

### Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

### Sensitizing effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer (Carbon Black)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (n-butyl acetate)

### Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (IARC): Carbon black (CAS 1333-86-4) is listed in group 2B.

### Aspiration hazard

Based on available data, the classification criteria are not met.



# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 535

Revision date: 06/10/2024

Product code: 11001

Page 9 of 11

### Specific effects in experiment on an animal

No information available.

### Additional information on tests

No information available.

### Practical experience

No information available.

### Information on other hazards

#### Endocrine disrupting properties

Endocrine disrupting potential No information available.

### Further information

There are no data available on the preparation/mixture itself.

## 12. Ecological information

### Persistence and degradability

There are no data available on the mixture itself.

### Bioaccumulative potential

There are no data available on the mixture itself.

### Mobility in soil

There are no data available on the mixture itself.

### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### Other adverse effects

No information available.

### Further information

There are no data available on the mixture itself.

## 13. Disposal considerations

### Waste treatment methods

#### Disposal recommendations

Dispose of waste according to applicable legislation.  
Do not mix with other wastes.

#### Contaminated packaging

Dispose according to legislation.

## 14. Transport information

### U.S. DOT 49 CFR 172.101

#### UN number or ID number:

UN 1866

#### Proper shipping name:

RESIN SOLUTION

#### Transport hazard class(es):

3

#### Packing group:

II

#### Hazard label:

3



### Marine transport (IMDG)

#### UN number or ID number:

UN 1866

# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 535

Revision date: 06/10/2024

Product code: 11001

Page 10 of 11

**UN proper shipping name:** RESIN SOLUTION  
**Transport hazard class(es):** 3  
**Packing group:** II  
Hazard label: 3



Marine pollutant: no  
Special Provisions: -  
Limited quantity: 5 L  
Excepted quantity: E2  
EmS: F-E, S-E

### Air transport (ICAO-TI/IATA-DGR)

**UN number or ID number:** UN 1866  
**UN proper shipping name:** RESIN SOLUTION  
**Transport hazard class(es):** 3  
**Packing group:** II  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

### Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## 15. Regulatory information

### U.S. Regulations

#### National Inventory TSCA

Substance/product listed in the following inventories: TSCA

#### National regulatory information

SARA Section 304 CERCLA:

Butyl acetate (123-86-4): Reportable quantity = 5,000 (2270) lbs. (kg)  
Methyl ethyl ketone (78-93-3): Reportable quantity = 5,000 (2270) lbs. (kg)  
Ethyl acetate (141-78-6): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:

Butyl acetate (123-86-4): Fire hazard, Immediate (acute) health hazard  
Methyl ethyl ketone (78-93-3): Fire hazard, Immediate (acute) health hazard  
Ethyl acetate (141-78-6): Fire hazard, Immediate (acute) health hazard  
Benzene, 2,4-diisocyanato-1-methyl-, polymer with 1,6-diisocyanatohexane (26426-91-5): Immediate (acute) health hazard  
Carbon Black (1333-86-4): Delayed (chronic) health hazard  
Tris(p-isocyanatophenyl) thiophosphate (4151-51-3): Immediate (acute) health hazard  
Bis(trimethoxysilylpropyl)amine (82985-35-1): Immediate (acute) health hazard

Clean Air Act Section 112(b):

# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 535

Revision date: 06/10/2024

Product code: 11001

Page 11 of 11

Methyl ethyl ketone (78-93-3)

### State Regulations

#### Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

WARNING: This product can expose you to chemicals including Carbon black (airborne, unbound particles of respirable size) (cancer), which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Directive 2004/42/EC on VOC in paints and varnishes: 78,72 %  
771,5 - 779,4 g/l

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

### 16. Other information

#### Hazardous Materials Identification System (HMIS)

Health: 2  
Flammability: 3  
Physical Hazard: 0

#### NFPA Hazard Ratings

Health: 2  
Flammability: 3  
Reactivity: 0  
Unique Hazard:



#### Changes

Revision date: 06/10/2024  
Revision No: 1,4

This data sheet contains changes from the previous version in section(s): 9.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

#### Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*