

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

UFI: NE91-WKFG-N00H-12S3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

1.3. Details of the supplier of the safety data sheet

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76

Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980

Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229

Asp. Tox. 1; H304

STOT SE 3; H336

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
pentane

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 2 of 14

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains calcium sulfonate. May produce an allergic reaction.
Restricted to professional users.

Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229-H412

Precautionary statements

P210-P211-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 3 of 14

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			20 - < 25 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304			
106-97-8	butane			10 - < 15 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1A, Press. Gas (Comp.), Acute Tox. 3; H220 H280 H331			
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Press. Gas (Comp.); H220 H280			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			5 - < 10 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
109-66-0	pentane			5 - < 10 %
	203-692-4	601-006-00-1		
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			5 - < 10 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304			
61789-86-4	calcium sulfonate			1 - < 5 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	20 - < 25 %
		dermal: LD50 = >3000 mg/kg; oral: LD50 = > 5000 mg/kg	
106-97-8	203-448-7	butane	10 - < 15 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists)	
	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	5 - < 10 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = 5000 mg/kg; oral: LD50 = 4951 mg/kg	
109-66-0	203-692-4	pentane	5 - < 10 %
		inhalation: LC50 = 364 mg/l (vapours)	
	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	5 - < 10 %
		inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
61789-86-4	263-093-9	calcium sulfonate	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5000 mg/kg Skin Sens. 1B; H317: >= 10 - 100	

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 4 of 14

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Change contaminated clothing.
Wash with plenty of water/Soap.
If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂) Extinguishing powder Water spray jet

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wear personal protection equipment.
Avoid contact with skin, eyes and clothes.

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 5 of 14

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only in well-ventilated areas.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Do not open container by force.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Do not keep the container sealed. Keep container dry.

Keep away from heat. Protect from direct sunlight.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 6 of 14

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
109-66-0	Pentane	600	1800		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m ³
Worker DNEL, long-term		dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m ³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	125 mg/kg bw/day
61789-86-4	calcium sulfonate			
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm ²
Consumer DNEL, long-term		oral	systemic	0,8333 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m ³

PNEC values

CAS No	Substance	Value
	Environmental compartment	
61789-86-4	calcium sulfonate	
	Freshwater	1 mg/l
	Marine water	1 mg/l
	Freshwater sediment	226000000 mg/kg
	Marine sediment	226000000 mg/kg
	Secondary poisoning	16667 mg/kg
	Micro-organisms in sewage treatment plants (STP)	1000 mg/l
	Soil	271000000 mg/kg

8.2. Exposure controls



DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 7 of 14

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Recommended glove articles :

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber), Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: AX

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	brown
Odour:	characteristic
Odour threshold:	not determined

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	36,1 °C
Flammability:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	- 97 °C
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	8300 hPa
(at 20 °C)	

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 8 of 14

Vapour pressure:	13 hPa
(at 50 °C)	
Density (at 20 °C):	0,722 g/cm ³ DIN 51757
Relative vapour density:	not determined

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties	
not determined	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
not determined	

Other safety characteristics

Evaporation rate:	not determined
Solvent content:	77,2 %
Solid content:	23,9 %
Viscosity / dynamic:	not determined

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 27,27 mg/l; ATE (inhalation dust/mist) 4,545 mg/l

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rat		
106-97-8	butane				
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
109-66-0	pentane				
	inhalation (4 h) vapour	LC50 364 mg/l	Rat	GESTIS	
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >5000 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.
Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.
Contains calcium sulfonate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 10 of 14

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
109-66-0	pentane					
	Acute crustacea toxicity	EC50 9,74 mg/l	48 h	Daphnia magna	IUCLID	
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36
109-66-0	pentane	3,39

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 11 of 14

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Marine pollutant: no
Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 12 of 14

IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

Other applicable information (air transport)

E0

Passenger-LQ: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Gases under pressure

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in	75.42 %
paints and varnishes:	544,5 g/l
Information according to Directive	P3a FLAMMABLE AEROSOLS
2012/18/EU (SEVESO III):	

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 13 of 14

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9.

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Press. Gas (Comp.): Compressed gas

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains calcium sulfonate. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Safety Data Sheet

according to UK REACH Regulation

DINITROL HIGH PERFORMANCE WAX BROWN SPRAY

Revision date: 22.02.2024

Product code: 20195

Page 14 of 14

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)