

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 444 Spray

UFI: M88E-NY8D-7003-SRXM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Paints and varnishes

1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229
 Eye Irrit. 2; H319
 STOT SE 3; H335
 STOT SE 3; H336
 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

acetone; propan-2-one; propanone
 Hydrocarbons, C9, aromatics
 reaction mass of ethylbenzene and xylene

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	--

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 2 of 16

P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist/vapours/spray.
P273	Avoid release to the environment.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Restricted to professional users.

Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229

Precautionary statements

P210-P211-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 3 of 16

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
115-10-6	dimethyl ether			25 - < 50%
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280			
67-64-1	acetone; propan-2-one; propanone			20 - < 25%
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
128601-23-0	Hydrocarbons, C9, aromatics			12,5 - < 20%
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411			
7440-66-6	zinc powder - zinc dust (stabilized)			5 - < 10%
	231-175-3	030-001-01-9	01-2119467174-37	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
7429-90-5	aluminium powder (stabilised)			2,5 - < 5 %
	231-072-3	013-002-00-1	01-2119455851-35	
	Flam. Sol. 1, Water-react. 2; H228 H261			
	reaction mass of ethylbenzene and xylene			2,5 - < 5 %
	905-588-0		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha			< 2,5 %
	265-150-3	649-327-00-6		
	Asp. Tox. 1; H304			
1314-13-2	zinc oxide			< 0,5 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 4 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	20 - < 25%
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800 mg/kg	
128601-23-0	918-668-5	Hydrocarbons, C9, aromatics	12,5 - < 20%
		inhalation: LC50 = 10,2 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >6800 mg/kg	
7429-90-5	231-072-3	aluminium powder (stabilised)	2,5 - < 5 %
		inhalation: LC50 = >5 mg/l (dusts or mists)	
	905-588-0	reaction mass of ethylbenzene and xylene	2,5 - < 5 %
		inhalation: LC50 = 29000 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = 2000 mg/kg; oral: LD50 = 3523 mg/kg	
1314-13-2	215-222-5	zinc oxide	< 0,5 %
		inhalation: LC50 = > 2500 mg/l (dusts or mists); oral: LD50 = > 7950 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Change contaminated clothing.

Wash with plenty of water/Soap.

If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Let water be drunken in little sips (dilution effect).

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Extinguishing powder, alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 5 of 16

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 6 of 16

a shower if necessary. When using do not eat or drink.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Do not keep the container sealed. Keep container dry.

Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
7429-90-5	Aluminium metal, respirable dust	-	4		TWA (8 h)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 7 of 16

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m ³
Worker DNEL, acute		inhalation	local	2420 mg/m ³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m ³
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
,				
128601-23-0	Hydrocarbons, C9, aromatics			
Worker DNEL, long-term		inhalation	systemic	150 mg/m ³
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m ³
Consumer DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	11 mg/kg bw/day
,				
7429-90-5	aluminium powder (stabilised)			
Worker DNEL, long-term		inhalation	systemic	3,72 mg/m ³
Worker DNEL, long-term		inhalation	local	3,72 mg/m ³
Consumer DNEL, long-term		oral	systemic	3,95 mg/kg bw/day
,				
1314-13-2	zinc oxide			
Worker DNEL, long-term		inhalation	systemic	5 mg/m ³
Worker DNEL, long-term		inhalation	local	0,5 mg/m ³
Worker DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,5 mg/m ³
Consumer DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,83 mg/kg bw/day
,				

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 8 of 16

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg
7429-90-5	aluminium powder (stabilised)	
Freshwater		0,0749 mg/l
Micro-organisms in sewage treatment plants (STP)		20 mg/l
1314-13-2	zinc oxide	
Freshwater		0,0206 mg/l
Marine water		0,0061 mg/l
Freshwater sediment		117,8 mg/kg
Marine sediment		56,5 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,100 mg/l
Soil		35,6 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time:: 120 min.

Butyl caoutchouc (butyl rubber), Breakthrough time:: 120 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: A2/P3

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 9 of 16

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	silver grey	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not applicable
Flammability:		not applicable
Lower explosion limits:		0,7 vol. %
Upper explosion limits:		26,2 vol. %
Flash point:		not applicable
Auto-ignition temperature:		240 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		4000 hPa
(at 20 °C)		
Density (at 20 °C):		0,8 g/cm ³
Relative vapour density:		not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
not determined	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
not determined	

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	82,8 %
Solid content:	17,2 %
Viscosity / dynamic:	not determined

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 10 of 16

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Hazardous decomposition products: none

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) 25500 mg/kg; ATE (inhalation gas) 57375 ppm

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat	RTECS	
	dermal	LD50 7426-15800 mg/kg	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
128601-23-0	Hydrocarbons, C9, aromatics				
	oral	LD50 >6800 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 10,2 mg/l	Rat		
7429-90-5	aluminium powder (stabilised)				
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
	reaction mass of ethylbenzene and xylene				
	oral	LD50 3523 mg/kg	Rat		
	dermal	LD50 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 29000 mg/l	Rat		
	inhalation gas	ATE 4500 ppm			
1314-13-2	zinc oxide				
	oral	LD50 > 7950 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 > 2500 mg/l	Rat		

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 11 of 16

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Hydrocarbons, C9, aromatics)

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone; Hydrocarbons, C9, aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna	
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum	
128601-23-0	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50	9,2 mg/l	96 h	Onchorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	2,9 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	3,2 mg/l	48 h	Daphnia magna (Big water flea)	
	reaction mass of ethylbenzene and xylene					
	Acute fish toxicity	LC50 mg/l	13,5	96 h	fish	
	Acute crustacea toxicity	EC50	7,4 mg/l	48 h	Daphnia magna (Big water flea)	
1314-13-2	zinc oxide					
	Acute fish toxicity	LC50 mg/l	1120	96 h	fish	GESTIS
	Acute crustacea toxicity	EC50 mg/l	12,3	48 h		GESTIS

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 12 of 16

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	acetone; propan-2-one; propanone			
	OECD 301 B	91%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1
67-64-1	acetone; propan-2-one; propanone	-0,24

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 13 of 16

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 1950

14.2. UN proper shipping name:

AEROSOLS, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es):

2

14.4. Packing group:

-

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

Transport category:

2

Tunnel restriction code:

D

Marine transport (IMDG)

14.1. UN number or ID number:

UN 1950

14.2. UN proper shipping name:

AEROSOLS (zinc powder - zinc dust (stabilized), Solvent naphtha (petroleum), light arom.), MARINE POLLUTANT

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Hazard label:

2.1



Marine pollutant:

yes

Special Provisions:

63, 190, 277, 327, 344, 959

Limited quantity:

1000 mL

Excepted quantity:

E0

EmS:

F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

UN 1950

14.2. UN proper shipping name:

AEROSOLS, flammable

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Hazard label:

2.1



Special Provisions:

A145 A167 A802

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y203

Excepted quantity:

E0

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

14.5. Environmental hazards

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 14 of 16

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: zinc powder - zinc dust (stabilized)

14.6. Special precautions for user

Warning: Gases under pressure

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75

Directive 2004/42/EC on VOC in	82,8 %
paints and varnishes:	685,6 g/l
Subcategory according to Directive	Special finishes - All types, VOC limit value: 840 g/l
2004/42/EC:	

Information according to Directive	P3a FLAMMABLE AEROSOLS
2012/18/EU (SEVESO III):	

Additional information:	E2
-------------------------	----

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	---

Water hazard class (D):	2 - obviously hazardous to water
-------------------------	----------------------------------

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 15 of 16

Hydrocarbons, C9, aromatics

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9.

Abbreviations and acronyms

Water-react: Substances and mixtures which in contact with water emit flammable gases

Flam. Gas: Flammable gases

Aerosol: Aerosols

Press. Gas (Liq.): Liquefied gas

Flam. Liq: Flammable liquids

Flam. Sol: Flammable solids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H335	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H229	Pressurised container: May burst if heated.
H261	In contact with water releases flammable gases.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 444 Spray

Revision date: 30.10.2023

Product code: 34059

Page 16 of 16

H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)