

# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 6085

Revision date: 11/21/2023

Product code: 5303

Page 1 of 11

### 1. Identification

#### Product identifier

DINITROL 6085

#### Recommended use of the chemical and restrictions on use

##### Use of the substance/mixture

Bodyfiller/stopper

#### Details of the supplier of the safety data sheet

##### Manufacturer

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

##### Supplier

Company name: DINOL U.S. Inc.  
Street: 8500 Cotter Street, Lewis Center  
Place: USA-43035 Ohio  
Telephone: 740-548-1656  
E-mail: info@dinolus.com  
Internet: www.dinol.com

Telefax: 740-548-1657

**Emergency phone number:** 3E Company Emergency +1-866-404-4230

### 2. Hazard(s) identification

#### Classification of the chemical

##### 29 CFR Part 1910.1200

Flammable liquids: Flam. Liq. 3  
Skin corrosion/irritation: Skin Irrit. 2  
Serious eye damage/eye irritation: Eye Irrit. 2A  
Respiratory or skin sensitization: Skin Sens. 1  
Carcinogenicity: Carc. 1A  
Reproductive toxicity: Repr. 2  
Specific target organ toxicity repeated or prolonged exposure: STOT RE 1

#### Label elements

##### 29 CFR Part 1910.1200

**Signal word:** Danger

**Pictograms:**



##### Hazard statements

Flammable liquid and vapor  
Causes skin irritation  
May cause an allergic skin reaction  
Causes serious eye irritation  
May cause cancer

## DINITROL 6085

Revision date: 11/21/2023

Product code: 5303

Page 2 of 11

Suspected of damaging fertility or the unborn child  
Causes damage to organs through prolonged or repeated exposure

### Precautionary statements

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Do not eat, drink or smoke when using this product.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin: Wash with plenty of water.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
Take off contaminated clothing and wash it before reuse.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
If exposed or concerned: Get medical advice/attention.  
In case of fire: Use water to extinguish.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

### Hazards not otherwise classified

No information available.

## 3. Composition/information on ingredients

### Mixtures

#### Hazardous components

CAS No	Components	Quantity
100-42-5	styrene	19.64 %
13463-67-7	titanium dioxide	2.037 %
108-31-6	Maleic anhydride	0.005988 %

### Further Information

The homogeneous mixing of this product is controlled by continuous physical tests. Formerly dusty raw materials are completely integrated into the liquid/pasty mass. Possible AGW-values for solid substances are therefore not given, as there is no longer any risk of inhalation of these substances (when handling this mixture).

## 4. First-aid measures

### Description of first aid measures

#### General information

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

#### After inhalation

Provide fresh air. In case of irregular breathing or respiratory arrest provide artificial respiration.  
If unconscious but breathing normally, place in recovery position and seek medical advice.  
In all cases of doubt, or when symptoms persist, seek medical advice.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 6085**

Revision date: 11/21/2023

Product code: 5303

Page 3 of 11

**After contact with skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower. If skin irritation occurs: Get medical advice/attention.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately. Put victim at rest, cover with a blanket and keep warm.

**Most important symptoms and effects, both acute and delayed**

Nausea, Dizziness, Headache.

**Indication of any immediate medical attention and special treatment needed**

No information available.

**5. Fire-fighting measures****Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water fog.

**Unsuitable extinguishing media**

Full water jet

**Specific hazards arising from the chemical**

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure. Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

**Special protective equipment and precautions for fire-fighters**

Use water spray/stream to protect personnel and to cool endangered containers.

**Additional information**

Use water spray/stream to protect personnel and to cool endangered containers. Suppress gases/vapors/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.  
Wear personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Avoid breathing dust/fume/gas/mist/vapors/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).  
Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.

**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 6085**

Revision date: 11/21/2023

Product code: 5303

Page 4 of 11

Clear contaminated areas thoroughly.

Do not rinse down with water.

**Other information**

No information available.

**Reference to other sections**

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13

**7. Handling and storage****Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Vapours may form explosive mixtures with air.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

**Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place.

**Hints on joint storage**

Do not store together with: Material, rich in oxygen, oxidizing.

**Further information on storage conditions**

Keep container tightly closed and in a well-ventilated place. Keep container dry.

Protect from direct sunlight.

storage temperature: 15 - 25 °C

**8. Exposure controls/personal protection****Control parameters**

# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 6085

Revision date: 11/21/2023

Product code: 5303

Page 5 of 11

### Exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	f/cc	Category	Origin
108-31-6	Maleic anhydride (inhalable fraction and vapor)		0.01		TWA (8 h)	ACGIH-2023
108-31-6	Maleic anhydride	0.25	1		TWA (8 h)	REL
		0.25	1		TWA (8 h)	REL
100-42-5	Styrene	100	-		TWA (8 h)	REL
		C 200	-		Ceiling	REL
		600	-		5 min	REL
100-42-5	Styrene	50	215		TWA (8 h)	REL
		100	425		STEL (15 min)	REL
100-42-5	Styrene	10			TWA (8 h)	ACGIH-2023
		20			STEL (15 min)	ACGIH-2023
14807-96-6	Talc (containing no asbestos and less than 1% quartz) (resp)	-	2		TWA (8 h)	REL
14807-96-6	Talc (containing no asbestos) respirable dust	706 mp/m <sup>3</sup>	-		TWA (8 h)	REL
14807-96-6	Talc containing no asbestos fibers (respirable fraction)		2		TWA (8 h)	ACGIH-2023
13463-67-7	Titanium dioxide Total dust	-	15		TWA (8 h)	REL
13463-67-7	Titanium dioxide: Finescale particles (Respirable particulate matter)		2.5		TWA (8 h)	ACGIH-2023
13463-67-7	Titanium dioxide				as low as possible	REL

### Biological Exposure Indices (BEI-ACGIH)

CAS No	Substance	Determinant	Value	Test material	Sampling time
100-42-5	Styrene	Mandelic acid plus phenylglyoxylic acid (creatinine)	150 mg/g	urine	End of shift

### Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time:: 480 min.

NBR (Nitrile rubber), Breakthrough time:: 30 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 6085

Revision date: 11/21/2023

Product code: 5303

Page 6 of 11

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

### Skin protection

Wear anti-static footwear and clothing

### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: A

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Physical state:	Paste
Color:	whitish
Odor:	characteristic
Odour threshold:	not determined

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	145 °C
Flammability:	not applicable
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	8,9 vol. %
Flash point:	31 °C
Auto-ignition temperature:	480 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents  
not determined

Partition coefficient n-octanol/water:

Vapor pressure: 6,7 hPa

(at 20 °C)

Density (at 20 °C): 1,70 g/cm<sup>3</sup> ISO 2811

Relative vapour density: not determined

### Test method

DIN 51755

### Other information

#### Information with regard to physical hazard classes

Explosive properties

not determined

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

#### Other safety characteristics

Evaporation rate: not determined

Solvent separation test: <3 % (ADR/RID)

Solvent content: 17,0 %

Solid content: 83,0 %

Sublimation point: not determined

Softening point: not determined

## DINITROL 6085

Revision date: 11/21/2023

Product code: 5303

Page 7 of 11

Pour point:

not determined

Viscosity / dynamic:  
(at 20 °C)

not determined

### Further Information

No information available.

## 10. Stability and reactivity

### Reactivity

No hazardous reaction when handled and stored according to provisions.

### Chemical stability

Stability:

Stable

The product is stable under storage at normal ambient temperatures.

### Possibility of hazardous reactions

Hazardous reactions:

Will not occur

No known hazardous reactions.

### Conditions to avoid

In case of warming: Danger of polymerisation

### Incompatible materials

No information available.

### Hazardous decomposition products

Carbon monoxide

## 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) 43752037 mg/kg; ATE (inhalation vapour) 55,97 mg/l; ATE (inhalation dust/mist) 7,636 mg/l

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
100-42-5	styrene				
	oral	LD50 > 5000 mg/kg	Rat		
	inhalation vapour	LC50 < 10 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
13463-67-7	titanium dioxide				
	oral	LD50 > 20000 mg/kg	Rat		
	dermal	LD50 > 10000 mg/kg	Rabbit		
108-31-6	Maleic anhydride				
	oral	LD50 1090 mg/kg	Rat		
	dermal	LD50 2620 mg/kg	Rabbit		

## Safety Data Sheet

according to 29 CFR 1910.1200(g)

### DINITROL 6085

Revision date: 11/21/2023

Product code: 5303

Page 8 of 11

#### Irritation and corrosivity

- Causes skin irritation
- Causes serious eye irritation

#### Sensitizing effects

- May cause an allergic skin reaction (Maleic anhydride)

#### Carcinogenic/mutagenic/toxic effects for reproduction

- May cause cancer
- Suspected of damaging fertility or the unborn child (styrene)
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (STOT) - single exposure

- Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (STOT) - repeated exposure

- Causes damage to organs through prolonged or repeated exposure (styrene)

Carcinogenicity (OSHA): No ingredient of this mixture is listed.

Carcinogenicity (IARC): Talc not containing asbestos or asbestiform fibres (CAS 14807-96-6) is listed in group 3. Styrene (CAS 100-42-5) is listed in group 2A. Titanium dioxide (CAS 13463-67-7) is listed in group 2B.

Carcinogenicity (NTP): Styrene (CAS 100-42-5) is listed in group RAHC.

#### Aspiration hazard

- Based on available data, the classification criteria are not met.

#### Information on other hazards

##### Endocrine disrupting properties

- Endocrine disrupting potential No information available.

#### Further information

- There are no data available on the preparation/mixture itself.

## 12. Ecological information

#### Persistence and degradability

- There are no data available on the mixture itself.

#### Bioaccumulative potential

- There are no data available on the mixture itself.

#### Mobility in soil

- There are no data available on the mixture itself.

#### Endocrine disrupting properties

- This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### Other adverse effects

- No information available.

#### Further information

- There are no data available on the preparation/mixture itself.
- Do not allow to enter into surface water or drains.

## 13. Disposal considerations

#### Waste treatment methods

##### Disposal recommendations

- Dispose of waste according to applicable legislation. Do not mix with other wastes.
- List of proposed waste codes/waste designations in accordance with EWC:

##### Contaminated packaging

- Remove according to the regulations.



# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 6085

Revision date: 11/21/2023

Product code: 5303

Page 9 of 11

### 14. Transport information

#### U.S. DOT 49 CFR 172.101

**UN number or ID number:** UN3269  
**Proper shipping name:** Polyester resin kit  
**Transport hazard class(es):** 3  
**Hazard label:** 3



#### Marine transport (IMDG)

**UN number or ID number:** UN 1866  
**UN proper shipping name:** Resin solution  
**Transport hazard class(es):** 3  
**Packing group:** III  
**Hazard label:** 3



**Marine pollutant:** no  
**Special Provisions:** 223, 955  
**Limited quantity:** 5 L  
**EmS:** F-E, S-E

#### Other applicable information (marine transport)

E1

Transport in accordance with paragraph 2.3.2.5 of the IMDG Code.

#### Air transport (ICAO-TI/IATA-DGR)

**UN number or ID number:** UN 1866  
**UN proper shipping name:** Resin solution  
**Transport hazard class(es):** 3  
**Packing group:** III  
**Hazard label:** 3



**Special Provisions:** A3  
**Limited quantity Passenger:** 10 L  
**IATA-packing instructions - Passenger:** 355  
**IATA-max. quantity - Passenger:** 60 L  
**IATA-packing instructions - Cargo:** 366  
**IATA-max. quantity - Cargo:** 220 L

#### Other applicable information (air transport)

E1

Passenger-LQ: Y344

#### Environmental hazards

**ENVIRONMENTALLY HAZARDOUS:** No

#### Special precautions for user

Warning: Flammable liquids

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

# Safety Data Sheet

according to 29 CFR 1910.1200(g)

## DINITROL 6085

Revision date: 11/21/2023

Product code: 5303

Page 10 of 11

## 15. Regulatory information

### U.S. Regulations

#### National Inventory TSCA

Substance/product listed in the following inventories: TSCA

#### National regulatory information

SARA Section 304 CERCLA:

Styrene (100-42-5): Reportable quantity = 1,000 (454) lbs. (kg)

Maleic anhydride (108-31-6): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:

Styrene (100-42-5): Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

titanium dioxide (13463-67-7): Delayed (chronic) health hazard

Maleic anhydride (108-31-6): Immediate (acute) health hazard, Delayed (chronic) health hazard

SARA Section 313 Toxic release inventory:

Styrene (100-42-5): De minimis limit = 0.1 %, Reportable threshold = Standard

Maleic anhydride (108-31-6): De minimis limit = 1.0 %, Reportable threshold = Standard

Clean Air Act Section 112(b):

Styrene (100-42-5), Maleic anhydride (108-31-6)

### State Regulations

#### Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

WARNING: This product can expose you to chemicals including Styrene (cancer), which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Directive 2004/42/EC on VOC in paints and varnishes: 17,0 % (< 250 g/l)

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

## 16. Other information

### Hazardous Materials Identification System (HMIS)

Health: 2

Flammability: 3

Physical Hazard: 0

### NFPA Hazard Ratings

Health: 2

Flammability: 3

Reactivity: 0

Unique Hazard:

Revision date: 11/21/2023

Revision No: 1,8

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association


GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%



**Safety Data Sheet**

according to 29 CFR 1910.1200(g)

**DINITROL 6085**

Revision date: 11/21/2023

Product code: 5303

Page 11 of 11

LD50: Lethal dose, 50%

**Other data**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*