

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL L-142

UFI: 65GA-XMMM-V008-7G47

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226
Asp. Tox. 1; H304
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Danger

Pictograms:



Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P280	Wear protective gloves and eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 2 of 11

P403+P235 water or shower.
Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.
Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H304

Precautionary statements

P405

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			50 - < 100 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
61789-86-4	calcium sulfonate			< 1 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	50 - < 100 %
		inhalation: LC50 = 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
61789-86-4	263-093-9	calcium sulfonate	< 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5000 mg/kg Skin Sens. 1B; H317: >= 10 - 100	

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 3 of 11

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂) Extinguishing powder. Water spray jet alcohol resistant foam.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 4 of 11

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation as well as local exhaust at critical locations. Use only outdoors or in a well-ventilated area.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

No special measures are necessary.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 5 of 11

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Consumer DNEL, long-term		oral	systemic	125 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	871 mg/m³
Consumer DNEL, long-term		inhalation	systemic	185 mg/m³
61789-86-4	calcium sulfonate			
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm²
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm²
Consumer DNEL, long-term		oral	systemic	0,8333 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m³

PNEC values

CAS No	Substance	
Environmental compartment	Value	
61789-86-4	calcium sulfonate	
Freshwater	1 mg/l	
Marine water	1 mg/l	
Freshwater sediment	226000000 mg/kg	
Marine sediment	226000000 mg/kg	
Secondary poisoning	16667 mg/kg	
Micro-organisms in sewage treatment plants (STP)	1000 mg/l	
Soil	271000000 mg/kg	

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Recommended eye protection articles :

Eye glasses with side protection (EN 166)

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 6 of 11

Hand protection

Recommended glove articles :

NBR (Nitrile rubber) - ($\geq 0,12$ mm), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	whitish
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point: not determined

Boiling point or initial boiling point and boiling range: 154-193 °C

Flammability: Flammable liquid and vapour.

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 7 vol. %

Flash point: 41 °C

Auto-ignition temperature: > 200 °C

Decomposition temperature: not determined

pH-Value: The study does not need to be conducted because the substance is known to be insoluble in water. < 20,5 mm²/s

Viscosity / kinematic: (at 40 °C) < 20,5 mm²/s

Water solubility: Immiscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: 3 hPa

Vapour pressure: 13 hPa

Density (at 20 °C): 0,75 - 0,79 g/cm³

Relative vapour density: not determined

Particle characteristics: not applicable

Test method

DIN 53213

DIN 51757

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not determined

Sustaining combustion:

No data available

Oxidizing properties

not determined

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 7 of 11

Other safety characteristics

Solvent content: 90,4%
Solid content: 8,0 - 10,0 %
Softening point: not determined
Viscosity / dynamic: 7 mPa·s
(at 20 °C)

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 5000 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 8 of 11

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
		80%		
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 9 of 11

No further relevant information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not mix with other wastes. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 10 of 11

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: no
Special Provisions: 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 90,40 %
paints and varnishes: 697,6 g/l
Information according to Directive P5c FLAMMABLE LIQUIDS
2012/18/EU (SEVESO III):

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

Safety Data Sheet

according to UK REACH Regulation

DINITROL L-142

Revision date: 15.05.2024

Product code: 21646

Page 11 of 11

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,9,15.

Abbreviations and acronyms

Flam. Liq: Flammable liquids

Asp. Tox: Aspiration hazard

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)