

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 3125 HS Spray

UFI: K54X-W1P5-500R-QRAU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229
Asp. Tox. 1; H304
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 2 of 12

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.
Restricted to professional users.

Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229

Precautionary statements

P210-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			20 - < 25 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas; H220 H280			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics			5 - < 10 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
	barium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)			1 - < 5 %
	939-718-2		01-2119980986-14	
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H332 H302 H315			

Full text of H and EUH statements: see section 16.

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	20 - < 25 %
		inhalation: LC50 = 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics	5 - < 10 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 4951 mg/kg	
	939-718-2	barium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	1 - < 5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 500 mg/kg	

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Change contaminated clothing.
Wash with plenty of water/Soap.
If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 4 of 12

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Handle and open container with care.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking.

Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 5 of 12

When using do not eat or drink.
Wash hands before breaks and after work.
Avoid contact with skin and eyes.
Remove contaminated, saturated clothing immediately.
Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
Do not keep the container sealed. Keep container dry.
Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Consumer DNEL, long-term		oral	systemic	125 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	871 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	185 mg/m ³

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.
If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye protection: not required.

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 6 of 12

Recommended eye protection articles :Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141),. Filter material/medium: AX

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	dark brown	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		-42 °C
Flammability:		not applicable
Lower explosion limits:		0,6 vol. %
Upper explosion limits:		10,9 vol. %
Flash point:		< - 20 °C
Auto-ignition temperature:		> 200 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		8.300 hPa
(at 20 °C)		
Density (at 20 °C):		0,802 g/cm³
Relative vapour density:		not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not determined

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 7 of 12

Other safety characteristics

Evaporation rate:	not determined
Solvent content:	51,1%
Solid content:	46,2%
Viscosity / dynamic:	not determined
Flow time:	not determined

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix tested

	Dose	Species	Source
LD50, oral	> 22698 - 27237 mg/kg		
LC50, inhalation (dust/mist) (4 h)	> 68,1 - 81,7 mg/l		

ATEmix calculated

ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 8 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 5000 mg/l	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
	barium bis (di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)				
	oral	LD50 500 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 9 of 12

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
		80%		
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN1950
 14.2. UN proper shipping name: AEROSOLS
 14.3. Transport hazard class(es): 2
 14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 10 of 12

Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Other applicable information (land transport)

E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Marine pollutant: no
 Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

E0

Passenger-LQ: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Gases under pressure

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 11 of 12

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 29, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes:	51,13 % 410,0 g/l
Information according to Directive 2012/18/EU (SEVESO III):	P3a FLAMMABLE AEROSOLS

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,8,9,11.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3125 HS Spray

Revision date: 16.05.2024

Product code: 21713

Page 12 of 12

Abbreviations and acronyms

Flam. Gas: Flammable gases
Aerosol: Aerosols
Compressed gas
Flam. Liq: Flammable liquids
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
STOT SE: Specific target organ toxicity - single exposure
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)