

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 1 of 15

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 4010 Spray

UFI: TA3X-U1S6-300T-3AH6

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Anti-corrosive coating

##### Uses advised against

No further relevant information available.

#### 1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Aerosol 1; H222-H229  
 Asp. Tox. 1; H304  
 STOT SE 3; H336  
 STOT RE 1; H372  
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  
 Hydrocarbons, C9-10, <2% aromatics  
 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Danger

##### Pictograms:



##### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 2 of 15

#### Precautionary statements

- |           |  |
|-----------|--|
| P210      | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P251      | Do not pierce or burn, even after use.   |
| P280      | Wear protective gloves and eye/face protection.  |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed.                               |
| P405      | Store locked up.   |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.                   |

#### Special labelling of certain mixtures

- |        |  |
|--------|--|
| EUH066 | Repeated exposure may cause skin dryness or cracking.  |
| EUH208 | Contains calcium sulfonate. May produce an allergic reaction.<br>Restricted to professional users. |

#### Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



#### Hazard statements

H222-H229-H372-H412

#### Precautionary statements

P210-P251-P410+P412

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 3 of 15

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			15 - < 20 %
	919-446-0		01-2119458049-33	
	Flam. Liq. 3, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H372 H304 H411 EUH066			
1174921-73-3	Hydrocarbons, C9-10, <2% aromatics			15 - < 20 %
	807-660-6		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			15 - < 20 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
106-97-8	butane (<0,1 % butadiene)			10 - < 15 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Press. Gas (Comp.); H220 H280			
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Press. Gas (Comp.); H220 H280			
75-28-5	isobutane			5 - < 10 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Press. Gas (Comp.); H220 H280			
61789-86-4	calcium sulfonate			5 - < 10 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			
	calcium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)			1 - < 5 %
	939-717-7		01-2119980985-16	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	919-446-0	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	15 - < 20 %
		dermal: LD50 = >3400 mg/kg; oral: LD50 = >15000 mg/kg	
1174921-73-3	807-660-6	Hydrocarbons, C9-10, <2% aromatics	15 - < 20 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 4951 mg/kg	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	15 - < 20 %
		inhalation: LC50 = 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
61789-86-4	263-093-9	calcium sulfonate	5 - < 10 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5000 mg/kg Skin Sens. 1B; H317: >= 10 - 100	
	939-717-7	calcium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	1 - < 5 %
		inhalation: LC50 = > 18 mg/l (vapours); dermal: LD50 = > 20000 mg/kg; oral: LD50 = >5000 mg/kg	

### Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w)

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 4010 Spray**

Revision date: 19.12.2023

Product code: 21703

Page 4 of 15

DMSO extract (IP 346)).

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately.

**After inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. If unconscious but breathing normally, place in recovery position and seek medical advice.

**After contact with skin**

Wash with plenty of water/Soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

**After contact with eyes**

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Disorientation Nausea, Dizziness, Headache.

**4.3. Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Flammable. Vapours can form explosive mixtures with air.

In case of fire may be liberated: Gases/vapours, toxic

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin, eyes and clothes.

Use personal protection equipment.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 4010 Spray**

Revision date: 19.12.2023

Product code: 21703

Page 5 of 15

**6.2. Environmental precautions**

- Do not allow uncontrolled discharge of product into the environment.
- Do not allow to enter into surface water or drains.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For containment**

- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
- Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

- Provide adequate ventilation.
- Clear contaminated areas thoroughly.
- Do not rinse down with water.

**Other information**

- No information available.

**6.4. Reference to other sections**

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

- If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

- Keep away from sources of ignition - No smoking.
- Take precautionary measures against static discharges.
- Vapours can form explosive mixtures with air.

**Advice on general occupational hygiene**

- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from food, drink and animal feedingstuffs.
- Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

- Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only.
- Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

- Not required.

**Further information on storage conditions**

- Keep container tightly closed.

**7.3. Specific end use(s)**

- No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 6 of 15

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

### DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
Worker DNEL, long-term	inhalation		systemic	330 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal		systemic	44 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	71 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal		systemic	26 mg/kg bw/day
Consumer DNEL, long-term	oral		systemic	26 mg/kg bw/day
1174921-73-3	Hydrocarbons, C9-10, <2% aromatics			
Consumer DNEL, long-term	oral		systemic	125 mg/kg bw/day
Worker DNEL, long-term	dermal		systemic	208 mg/kg bw/day
Consumer DNEL, long-term	dermal		systemic	125 mg/kg bw/day
Worker DNEL, long-term	inhalation		systemic	871 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation		systemic	185 mg/m <sup>3</sup>
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Consumer DNEL, long-term	oral		systemic	125 mg/kg bw/day
Worker DNEL, long-term	dermal		systemic	208 mg/kg bw/day
Consumer DNEL, long-term	dermal		systemic	125 mg/kg bw/day
Worker DNEL, long-term	inhalation		systemic	871 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation		systemic	185 mg/m <sup>3</sup>
61789-86-4	calcium sulfonate			
Worker DNEL, long-term	dermal		systemic	3,33 mg/kg bw/day
Worker DNEL, long-term	dermal		local	1,03 mg/cm <sup>2</sup>
Consumer DNEL, long-term	inhalation		systemic	2,9 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal		systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term	dermal		local	0,513 mg/cm <sup>2</sup>
Consumer DNEL, long-term	oral		systemic	0,8333 mg/kg bw/day
Worker DNEL, long-term	inhalation		systemic	11,75 mg/m <sup>3</sup>

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 7 of 15

### PNEC values

CAS No	Substance	
Environmental compartment		Value
61789-86-4	calcium sulfonate	
Freshwater		1 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber), Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

##### Skin protection

Wear anti-static footwear and clothing

##### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: AX (short-term)

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	transparent beige	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 8 of 15

Boiling point or initial boiling point and boiling range:	-44,5 °C
Flammability:	not applicable
Lower explosion limits:	not applicable
Upper explosion limits:	0,6 vol. %
Flash point:	10,9 vol. %
Auto-ignition temperature:	< -20 °C
Decomposition temperature:	> 200 °C
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	not applicable
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	8300 hPa
(at 20 °C)	
Density (at 20 °C):	0,736 g/cm <sup>3</sup>
Relative vapour density:	not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties	
not determined	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

##### Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	70,2 %
Solid content:	30,7%
Viscosity / dynamic:	not determined

##### Further Information

No information available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No further relevant information available.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

#### 10.5. Incompatible materials

Oxidising agent, strong

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 9 of 15

### 10.6. Hazardous decomposition products

Carbon monoxide

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	oral	LD50 >15000 mg/kg	Rat		
	dermal	LD50 >3400 mg/kg	Rat		
1174921-73-3	Hydrocarbons, C9-10, <2% aromatics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 5000 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
	calcium bis (di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 > 20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 18 mg/l	Rat		

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.  
Repeated exposure may cause skin dryness or cracking.

#### Sensitising effects

Based on available data, the classification criteria are not met.  
Contains calcium sulfonate. May produce an allergic reaction.

#### Carcinogenic/mutagenic/toxic effects for reproduction

## DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 10 of 15

Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); Hydrocarbons, C9-10, <2% aromatics; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

### STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

### Aspiration hazard

May be fatal if swallowed and enters airways.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Endocrine disrupting potential No information available.

#### Further information

There are no data available on the preparation/mixture itself.

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)					
	Acute fish toxicity	LL50 mg/l	10-30	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	4,6 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EL50 mg/l	10-22	48 h	Daphnia magna (Big water flea)	
	calcium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)					
	Acute fish toxicity	LC50 mg/l	> 0,28	96 h	fish	
	Acute crustacea toxicity	EC50 mg/l	> 0,27	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC mg/l	> 0,27	3 d		

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
		74,7 %	28	
	Leicht biologisch abbaubar			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
		80%		
	Readily biodegradable (according to OECD criteria).			

### 12.3. Bioaccumulative potential

The product has not been tested.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 11 of 15

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
75-28-5	isobutane	2,8

### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No further relevant information available.

### Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes. Do not allow to enter into surface water or drains.

List of proposed waste codes/waste designations in accordance with EWC:

#### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

#### List of Wastes Code - contaminated packaging

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

#### Contaminated packaging

Remove according to the regulations.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 12 of 15

Tunnel restriction code: D  
**Other applicable information (land transport)**  
 E0

### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Limited quantity: 1 L  
 Excepted quantity: E0

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Marine pollutant: no  
 Special Provisions: 63, 190, 277, 327, 344, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, FLAMMABLE  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203  
 IATA-max. quantity - Cargo: 150 kg

**Other applicable information (air transport)**  
 E0

Passenger-LQ: Y203

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 13 of 15

#### **14.6. Special precautions for user**

Warning : gas

#### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

#### **Other applicable information**

SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity of 1litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

### **SECTION 15: Regulatory information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 70,18 %  
516,5 g/l

Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

##### **Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

##### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

##### **Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

#### **15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

### **SECTION 16: Other information**

#### **Changes**

This data sheet contains changes from the previous version in section(s): 2,6,8,11,12,14,15.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 14 of 15

### Abbreviations and acronyms

Flam. Gas: Flammable gases  
Aerosol: Aerosols  
Press. Gas (Comp.): Compressed gas  
Flam. Liq: Flammable liquids  
Asp. Tox: Aspiration hazard  
Skin Irrit: Skin irritation  
Eye Irrit: Eye irritation  
Skin Sens: Skin sensitisation  
STOT SE: Specific target organ toxicity - single exposure  
STOT RE: Specific target organ toxicity - repeated exposure  
Aquatic Chronic: Chronic aquatic hazard  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"
STOT RE 1; H372	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH208 Contains calcium sulfonate. May produce an allergic reaction.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 4010 Spray

Revision date: 19.12.2023

Product code: 21703

Page 15 of 15

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*