

according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 1 of 11

1. Identification

Product identifier

DINITROL 4010 Spray

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

Supplier

Company name: DINOL U.S. Inc.

Street: 8500 Cotter Street, Lewis Center

Place: USA-43035 Ohio

Telephone: 740-548-1656 Telefax: 740-548-1657

E-mail: info@dinolus.com
Internet: www.dinol.com

Emergency phone number: 3E Company Emergency +1-866-404-4230

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Flammable aerosols: Flam. Aerosol 1 Gases under pressure: Compressed gas

Aspiration hazard: Asp. Tox. 1

Respiratory or skin sensitization: Skin Sens. 1

Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects) Specific target organ toxicity repeated or prolonged exposure: STOT RE 1

Label elements

29 CFR Part 1910.1200

Signal word: Danger

Pictograms:









Print date: 12/19/2023

Telefax: + 49 (0) 5281 9829860

Hazard statements

Extremely flammable aerosol Contains gas under pressure; may explode if heated May be fatal if swallowed and enters airways May cause an allergic skin reaction



Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 2 of 11

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

If on skin: Wash with plenty of Water and soap.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

Hazards not otherwise classified

No information available.

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Components	
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	17.43 %
1174921-73-3	Hydrocarbons, C9-10, <2% aromatics	
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	17.43 %
61789-86-4	calcium sulfonate	6.93 %
	calcium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	2.03 %

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

4. First-aid measures

Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Wash with plenty of water/Soap. Take off immediately all contaminated clothing and wash it before reuse. If



Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 3 of 11

skin irritation occurs: Get medical advice/attention.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

Most important symptoms and effects, both acute and delayed

Disorientation Nausea, Dizziness, Headache.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

Specific hazards arising from the chemical

Flammable. Vapors may form explosive mixtures with air.

In case of fire may be liberated: Gases/vapors, toxic

In case of fire: Wear self-contained breathing apparatus.

Special protective equipment and precautions for fire-fighters

Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Supress gases/vapors/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition.

Do not breathe gas/fume/vapor/spray.

Avoid contact with skin, eyes and clothes.

Use personal protection equipment.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.



according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 4 of 11

Do not rinse down with water.

Other information

No information available.

Reference to other sections

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fume/vapor/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No	Substance	ppm	mg/m³	f/cc	Category	Origin
75-28-5	Butane: isobutane	1000			STEL (15 min)	ACGIH-2023
106-97-8	Butane: n-butane	1000			STEL (15 min)	ACGIH-2023
75-28-5	Isobutane	800	1900		TWA (8 h)	REL
106-97-8	n-Butane	800	1900		TWA (8 h)	REL
74-98-6	Propane	1000	1800		TWA (8 h)	PEL
		1000	1800		TWA (8 h)	REL
		-	-		Asphyxiant	ACGIH-2023

Exposure controls



according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 5 of 11





Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber), Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: AX (short-term)

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Aerosol

Color: transparent beige Odor: characteristic Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

-44,5 °C

boiling range:

Flammability: not applicable

not applicable

Lower explosion limits: 0,6 vol. %
Upper explosion limits: 10,9 vol. %
Flash point: < -20 °C

Auto-ignition temperature: > 200 °C

Decomposition temperature: not determined
pH-Value: not determined
Viscosity / kinematic: not determined
Water solubility: not applicable

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined



Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 6 of 11

Vapor pressure: 8300 hPa

(at 20 °C)

Density (at 20 °C): 0,736 g/cm³
Relative vapour density: not determined

Other information

Information with regard to physical hazard classes

Explosive properties

not determined

Sustaining combustion: No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate:

Solvent separation test:

not determined

Further Information

No information available.

10. Stability and reactivity

Reactivity

No further relevant information available.

Chemical stability

Stability: Stable

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Hazardous reactions: Will not occur

No known hazardous reactions.

Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapors may form explosive mixtures with air.

Incompatible materials

Oxidizing agent, strong

Hazardous decomposition products

Carbon monoxide

11. Toxicological information

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 7 of 11

CAS No	Components									
	Exposure route	Dose		Species	Source	Method				
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)									
	oral	LD50 mg/kg	>15000	Rat						
	dermal	LD50 mg/kg	>3400	Rat						
1174921-73- 3	Hydrocarbons, C9-10, <2% aromatics									
	oral	LD50 mg/kg	4951	Rat						
	dermal	LD50 mg/kg	> 5000	Rabbit						
	inhalation (4 h) vapour	LC50	4951 mg/l	Rat						
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics									
	oral	LD50 mg/kg	> 5000	Rat						
	dermal	LD50 mg/kg	> 5000	Rabbit						
	inhalation (4 h) vapour	LC50	5000 mg/l	Rat						
61789-86-4	calcium sulfonate									
	oral	LD50 mg/kg	5000	Rat						
	dermal	LD50 mg/kg	> 2000	Rat						
	calcium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)									
	oral	LD50 mg/kg	>5000	Rat						
	dermal	LD50 mg/kg	> 20000	Rabbit						
	inhalation (4 h) vapour	LC50	> 18 mg/l	Rat						

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitizing effects

May cause an allergic skin reaction (calcium sulfonate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); Hydrocarbons, C9-10, <2% aromatics; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

Specific target organ toxicity (STOT) - repeated exposure

Causes damage to organs through prolonged or repeated exposure (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

Aspiration hazard

May be fatal if swallowed and enters airways

Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.



according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Product code: 21703 Revision date: 12/19/2023 Page 8 of 11

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information

Persistence and degradability

The product has not been tested.

Bioaccumulative potential

The product has not been tested.

Mobility in soil

There are no data available on the mixture itself.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No further relevant information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes. Do not allow to enter into surface water or drains.

List of proposed waste codes/waste designations in accordance with EWC:

Contaminated packaging

Remove according to the regulations.

14. Transport information

U.S. DOT 49 CFR 172.101

UN 1950 **UN number or ID number:**

Proper shipping name: Coating solution

Transport hazard class(es): Hazard label: 2.1



Marine transport (IMDG)

UN number or ID number: UN 1950 **UN proper shipping name: AEROSOLS**

Transport hazard class(es): Packing group: Hazard label: 2.1



2.1

Marine pollutant:

Special Provisions: 63, 190, 277, 327, 344, 959



according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 9 of 11

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1950

UN proper shipping name: AEROSOLS, FLAMMABLE

Transport hazard class(es):

Packing group:
Hazard label:

2.1

2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

Other applicable information (air transport)

E0

Passenger-LQ: Y203

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

Warning: gas

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Other applicable information

SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity of 1litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class

2.

15. Regulatory information

U.S. Regulations

National Inventory TSCA

Substance/product listed in the following inventories: TSCA

National regulatory information

SARA Section 311/312 Hazards:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (-): Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Hydrocarbons, C9-10, <2% aromatics (1174921-73-3): Fire hazard, Immediate (acute) health hazard Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (-): Fire hazard, Immediate (acute) health hazard

Butane (106-97-8): Fire hazard, Sudden release of pressure



according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 10 of 11

Propane (74-98-6): Fire hazard, Sudden release of pressure Isobutane (75-28-5): Fire hazard, Sudden release of pressure calcium sulfonate (61789-86-4): Immediate (acute) health hazard

calcium bis (di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) (-): Immediate (acute) health

hazard

Clean Air Act Section 112(r):

Butane (106-97-8): Threshold quantities = 10,000 lbs. Propane (74-98-6): Threshold quantities = 10,000 lbs. Isobutane (75-28-5): Threshold quantities = 10,000 lbs.

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Directive 2004/42/EC on VOC in 70,18 % paints and varnishes: 516,5 g/l

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

16. Other information

Hazardous Materials Identification System (HMIS)

Health: 0
Flammability: 4
Physical Hazard: 3

NFPA Hazard Ratings

Health: 0
Flammability: 4
Reactivity: 3
Unique Hazard: none



Print date: 12/19/2023

Changes

Revision date: 12/19/2023

Revision No: 1,6

This data sheet contains changes from the previous version in section(s): 2,6,8,11,12,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



according to 29 CFR 1910.1200(g)

DINITROL 4010 Spray

Revision date: 12/19/2023 Product code: 21703 Page 11 of 11

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)