

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 1 of 21

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 6110 Spray

UFI:

0Q3F-F0KD-7008-3RAW

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Bodyfiller/stopper

##### Uses advised against

No information available.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

##### Supplier

Company name: Leading Solvent Supplies Limited  
Street: Marston Business Park, Rudgate  
Place: GB Tockwith, York YO26 7QF  
E-mail: enquiries@leading-solvents.co.uk  
Internet: www.leading-solvents.co.uk

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Aerosol 1; H222-H229  
Eye Irrit. 2; H319  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

n-butyl acetate  
ethyl acetate  
acetone; propan-2-one; propanone  
butan-1-ol; n-butanol

Signal word:

Danger

Pictograms:



## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 2 of 21

#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves and eye/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Special labelling of certain mixtures

EUH208	Contains n-butyl acrylate. May produce an allergic reaction. Restricted to professional users.
--------	---

#### Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



#### Hazard statements

H222-H229

#### Precautionary statements

P210-P211-P251-P280-P410+P412

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 3 of 21

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
74-98-6	propane			10 - < 15 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			10 - < 15 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
123-86-4	n-butyl acetate			10 - < 15 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
141-78-6	ethyl acetate			10 - < 15 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
67-64-1	acetone; propan-2-one; propanone			10 - < 15 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
108-10-1	4-methylpentan-2-one; isobutyl methyl ketone			5 - < 10 %
	203-550-1		01-2119473980-30	
	Flam. Liq. 2, Carc. 2, Acute Tox. 4, Eye Irrit. 2, STOT SE 3; H225 H351 H332 H319 H336 EUH066			
1330-20-7	xylene			1 - < 5 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
-	cellulose nitrate; nitrocellulose			1 - < 5 %
	-	603-037-00-6		
	Expl. 1.1; H201			
71-36-3	butan-1-ol; n-butanol			1 - < 5 %
	200-751-6	603-004-00-6	01-2119484630-38	
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			
100-41-4	ethylbenzene			1 - < 5 %
	202-849-4	601-023-00-4	01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H332 H373 H304 H412			
141-32-2	n-butyl acrylate			< 1 %
	205-480-7	607-062-00-3	01-2119453155-43	
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 3; H226 H332 H315 H319 H317 H335 H412			

Full text of H and EUH statements: see section 16.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 4 of 21

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
Specific Conc. Limits, M-factors and ATE			
106-97-8	203-448-7	butane	10 - < 15 %
		inhalation: LC50 = 273000 ppm (gases)	
123-86-4	204-658-1	n-butyl acetate	10 - < 15 %
		inhalation: LC50 = > 21 mg/l (vapours); inhalation: LC50 = >21 mg/l (dusts or mists); dermal: LD50 = > 14112 mg/kg; oral: LD50 = 10760 mg/kg	
141-78-6	205-500-4	ethyl acetate	10 - < 15 %
		inhalation: LC50 = 50 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = 5620 mg/kg	
67-64-1	200-662-2	acetone; propan-2-one; propanone	10 - < 15 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800 mg/kg	
108-10-1	203-550-1	4-methylpentan-2-one; isobutyl methyl ketone	5 - < 10 %
		inhalation: ATE = 4500 ppm (gases); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	
1330-20-7	215-535-7	xylene	1 - < 5 %
		inhalation: LC50 = 20 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = 2000 mg/kg; oral: LD50 = 4300 mg/kg	
-	-	cellulose nitrate; nitrocellulose	1 - < 5 %
		oral: LD50 = >2000 mg/kg	
71-36-3	200-751-6	butan-1-ol; n-butanol	1 - < 5 %
		inhalation: LC50 = >17 mg/l (dusts or mists); dermal: LD50 = 3430 mg/kg; oral: LD50 = 2292 mg/kg	
100-41-4	202-849-4	ethylbenzene	1 - < 5 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
141-32-2	205-480-7	n-butyl acrylate	< 1 %
		inhalation: LC50 = 16 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = 2000 mg/kg; oral: LD50 = 3150 mg/kg	

### Further Information

The homogeneous mixing of this product is controlled by continuous physical tests. Formerly dusty raw materials are completely integrated into the liquid/pasty mass. Possible AGW-values for solid substances are therefore not given, as there is no longer any risk of inhalation of these substances (when handling this mixture).

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice.  
Never give anything by mouth to an unconscious person or a person with cramps.  
If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.  
If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After contact with skin

Change contaminated clothing.  
Wash with plenty of water/Soap.  
If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing. In case of eye irritation consult an ophthalmologist.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 6110 Spray**

Revision date: 11.04.2025

Product code: 5098

Page 5 of 21

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious).  
Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.  
Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

Nausea, Dizziness, Headache.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water fog.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.  
Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

**5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
Wear personal protection equipment.  
Avoid contact with skin, eyes and clothes.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).  
Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.  
Clear contaminated areas thoroughly.  
Do not rinse down with water.

**Other information**

No information available.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 6110 Spray**

Revision date: 11.04.2025

Product code: 5098

Page 6 of 21

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Handle and open container with care.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Take precautionary measures against static discharges.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking.

Heating causes rise in pressure with risk of bursting.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Do not keep the container sealed. Keep container dry.

Keep away from heat. Protect from direct sunlight.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 7 of 21

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-10-1	4-Methylpentan-2-one	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
71-36-3	Butan-1-ol	50	154		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
546-93-0	Magnesite, inhalable dust	-	10		TWA (8 h)	WEL
141-32-2	n-Butyl acrylate	1	5		TWA (8 h)	WEL
		5	26		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
13463-67-7	Titanium dioxide, total inhalable	-	10		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-10-1	4-methylpentan-2-one	4-methylpentan-2-one	20 µmol/L	urine	Post shift
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 8 of 21

### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
123-86-4	n-butyl acetate			
Worker DNEL, long-term		inhalation	systemic	48 mg/m³
Worker DNEL, acute		inhalation	systemic	600 mg/m³
Worker DNEL, long-term		inhalation	local	300 mg/m³
Worker DNEL, acute		inhalation	local	600 mg/m³
Consumer DNEL, long-term		inhalation	systemic	12 mg/m³
Consumer DNEL, acute		inhalation	systemic	300 mg/m³
Consumer DNEL, long-term		inhalation	local	35,7 mg/m³
Consumer DNEL, acute		inhalation	local	300 mg/m³
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	734 mg/m³
Worker DNEL, acute		inhalation	systemic	1468 mg/m³
Worker DNEL, long-term		inhalation	local	734 mg/m³
Worker DNEL, acute		inhalation	local	1468 mg/m³
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m³
Consumer DNEL, acute		inhalation	systemic	734 mg/m³
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m³
Worker DNEL, acute		inhalation	local	2420 mg/m³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m³
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
,				
108-10-1	4-methylpentan-2-one; isobutyl methyl ketone			
Worker DNEL, acute		inhalation	local	208 mg/m³
Worker DNEL, acute		inhalation	systemic	208 mg/m³
Worker DNEL, long-term		inhalation	local	83 mg/m³
Worker DNEL, long-term		inhalation	systemic	83 mg/m³
Worker DNEL, long-term		dermal	systemic	11,8 mg/kg bw/day
1330-20-7	xylene			
Worker DNEL, long-term		dermal	systemic	108 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	289 mg/m³
Worker DNEL, acute		inhalation	local	174 mg/m³
Worker DNEL, long-term		inhalation	systemic	77 mg/m³
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day



# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 9 of 21

Consumer DNEL, long-term	dermal	systemic	108 mg/kg bw/day
Consumer DNEL, acute	inhalation	systemic	174 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	local	174 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	systemic	14,8 mg/m <sup>3</sup>
13463-67-7	Titanium dioxide		
Worker DNEL, long-term	inhalation	local	10 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	700 mg/kg bw/day
71-36-3	butan-1-ol; n-butanol		
Worker DNEL, long-term	inhalation	local	310 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	3,125 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	55 mg/m <sup>3</sup>
100-41-4	ethylbenzene		
Worker DNEL, long-term	inhalation	systemic	77 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	293 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	15 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	1,6 mg/kg bw/day
546-93-0	Magnesium carbonate		
Consumer DNEL, long-term	oral	systemic	7,23 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	7,23 mg/kg bw/day
141-32-2	n-butyl acrylate		
Worker DNEL, acute	dermal	local	0,28 mg/cm <sup>2</sup>
Worker DNEL, long-term	dermal	local	0,28 mg/cm <sup>2</sup>
Worker DNEL, long-term	inhalation	local	11 mg/m <sup>3</sup>

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 10 of 21

### PNEC values

CAS No	Substance	
Environmental compartment		Value
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,0981 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,0903 mg/kg
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		0,20 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg
108-10-1	4-methylpentan-2-one; isobutyl methyl ketone	
Freshwater		0,6 mg/l
Marine water		0,06 mg/l
Freshwater sediment		8,27 mg/kg
Marine sediment		0,83 mg/kg
Micro-organisms in sewage treatment plants (STP)		27,5 mg/l
Soil		1,3 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
13463-67-7	Titanium dioxide	
Freshwater		0,184 mg/l
Marine water		0,0184 mg/l
Freshwater sediment		1000 mg/kg

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 11 of 21

Marine sediment	100 mg/kg
Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	100 mg/kg
71-36-3	butan-1-ol; n-butanol
Freshwater	0,082 mg/l
Marine water	0,0082 mg/l
Freshwater sediment	0,178 mg/kg
Marine sediment	0,0178 mg/kg
Micro-organisms in sewage treatment plants (STP)	2476 mg/l
Soil	0,015 mg/kg
100-41-4	ethylbenzene
Freshwater	0,1 mg/l
Marine water	0,01 mg/l
Freshwater sediment	13,7 mg/kg
Marine sediment	1,37 mg/kg
Secondary poisoning	0,02 mg/kg
Micro-organisms in sewage treatment plants (STP)	9,6 mg/l
Soil	2,68 mg/kg
141-32-2	n-butyl acrylate
Freshwater	0,00272 mg/l
Marine water	0,000272 mg/l
Freshwater sediment	0,0338 mg/kg
Marine sediment	0,00338 mg/kg
Micro-organisms in sewage treatment plants (STP)	3,5 mg/l
Soil	1 mg/kg

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protect skin by using skin protective cream.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 12 of 21

#### Skin protection

Wear anti-static footwear and clothing

#### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.  
gas filtering equipment (EN 141), Filter material/medium: A/P2

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	light grey	
Odour:	Solvent	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not applicable
Flammability:		not applicable
Lower explosion limits:		1,2 vol. %
Upper explosion limits:		11,5 vol. %
Flash point:		not applicable
Auto-ignition temperature:		365 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		3500 hPa
(at 20 °C)		
Density (at 20 °C):		0,80 g/cm <sup>3</sup>
Bulk density:		not applicable
Relative vapour density:		not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties

not determined

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

##### Other safety characteristics

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

78,9 %

Solid content:

22,4 %

Sublimation point:

not determined

Softening point:

not determined

Pour point:

not determined

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 6110 Spray**

Revision date: 11.04.2025

Product code: 5098

Page 13 of 21

Viscosity / dynamic:

not determined

Flow time:

not determined

**Further Information**

No information available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Keep away from heat. Ignition hazard.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

Carbon monoxide

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 5000 mg/kg; ATE (dermal) &gt; 5000 mg/kg; ATE (inhalation gas) &gt; 20000 ppm

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 14 of 21

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
106-97-8	butane				
	inhalation (4 h) gas	LC50 273000 ppm	Rat	GESTIS	
123-86-4	n-butyl acetate				
	oral	LD50 10760 mg/kg	Rat		
	dermal	LD50 > 14112 mg/kg	Rabbit		
	inhalation vapour	LC50 > 21 mg/l	Rat		
	inhalation (4 h) dust/mist	LC50 >21 mg/l	Rat		
141-78-6	ethyl acetate				
	oral	LD50 5620 mg/kg	Rat		
	dermal	LD50 >20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 50 mg/l	Rat		
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat	RTECS	
	dermal	LD50 7426-15800 mg/kg	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
108-10-1	4-methylpentan-2-one; isobutyl methyl ketone				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
	inhalation gas	ATE 4500 ppm			
1330-20-7	xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 20 mg/l	Rat		
	inhalation gas	ATE 4500 ppm			
-	cellulose nitrate; nitrocellulose				
	oral	LD50 >2000 mg/kg	Rat		
71-36-3	butan-1-ol; n-butanol				
	oral	LD50 2292 mg/kg	Rat	GESTIS	
	dermal	LD50 3430 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) dust/mist	LC50 >17 mg/l	Rat		
100-41-4	ethylbenzene				

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 15 of 21

	oral	LD50 mg/kg	3500	Rat	GESTIS	
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat		
	inhalation gas	ATE ppm	4500			
141-32-2	n-butyl acrylate					
	oral	LD50 mg/kg	3150	Rat	GESTIS	
	dermal	LD50 mg/kg	2000	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50	16 mg/l	Rat	GESTIS	
	inhalation gas	ATE ppm	4500			

#### Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

Contains n-butyl acrylate. May produce an allergic reaction.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Endocrine disrupting potential No information available.

#### Further information

There are no data available on the preparation/mixture itself.

## SECTION 12: Ecological information

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 16 of 21

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50 18 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 397 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 44 mg/l	48 h	Daphnia magna (Big water flea)		
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50 230 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 3300 mg/l		Desmodesmus subspicatus	48 h	
	Acute crustacea toxicity	EC50 717 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	EC50 2900 mg/l ( )		Pseudomonas putida	16 h	
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 5540 mg/l	96 h	Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 8800 mg/l	48 h	Daphnia Magna		
	Algae toxicity	NOEC 4740 mg/l	2 d	Selenastrum capricornutum		
108-10-1	4-methylpentan-2-one; isobutyl methyl ketone					
	Acute fish toxicity	LC50 505 - 540 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 400 mg/l	96 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 170 mg/l	48 h	Daphnia magna	IUCLID	
-	cellulose nitrate; nitrocellulose					
	Acute fish toxicity	LC50 >5000 mg/l	96 h	Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50 >10000 mg/l	72 h			
	Acute crustacea toxicity	EC50 >10000 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	EC50 >10000 mg/l ( )				
71-36-3	butan-1-ol; n-butanol					
	Acute fish toxicity	LC50 1740 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 >500 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 1980 mg/l	48 h		GESTIS	
	Acute bacteria toxicity	EC50 2250 mg/l ( )		Pseudomonas putida	16 h	
141-32-2	n-butyl acrylate					
	Acute fish toxicity	LC50 5,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		



## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 17 of 21

	Acute algae toxicity	ErC50	5,5 mg/l	96 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50	8,2 mg/l	48 h	Daphnia magna (Big water flea)		

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
123-86-4	n-butyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	83%	28	
	Readily biodegradable (according to OECD criteria).			
141-78-6	ethyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	100 %	28	
	Readily biodegradable (according to OECD criteria).			
67-64-1	acetone; propan-2-one; propanone			
	OECD 301 B	91%	28	
	Readily biodegradable (according to OECD criteria).			
-	cellulose nitrate; nitrocellulose			
	OECD 301 B	20%	28	
	Poorly biodegradable.			

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

##### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
123-86-4	n-butyl acetate	2,3
141-78-6	ethyl acetate	0,73
67-64-1	acetone; propan-2-one; propanone	-0,24
108-10-1	4-methylpentan-2-one; isobutyl methyl ketone	1,31
1330-20-7	xylene	3
-	cellulose nitrate; nitrocellulose	<0
71-36-3	butan-1-ol; n-butanol	0,88
100-41-4	ethylbenzene	3,15
141-32-2	n-butyl acrylate	2,36

##### BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		
1330-20-7	xylene	25,9	Oncorhynchus mykiss (Rainbow trout)	

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 18 of 21

#### 12.7. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

##### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

##### Contaminated packaging

Remove according to the regulations.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Transport category: 2  
 Tunnel restriction code: D

#### Other applicable information (land transport)

E0

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Marine pollutant: no  
 Special Provisions: 63, 190, 277, 327, 344, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

#### Air transport (ICAO-TI/IATA-DGR)

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 19 of 21

**14.1. UN number or ID number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

#### Other applicable information (air transport)

E0  
Passenger-LQ: Y203

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Warning: Gases under pressure

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

#### Other applicable information

Stowage Code:  
SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:  
SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 78,9 %  
paints and varnishes: 647,8 g/l

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

##### Additional information

Observe in addition any national regulations!  
Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

##### National regulatory information

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 20 of 21

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

#### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,8,9,15,16.

#### Abbreviations and acronyms

Expl: Explosives

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

Carc: Carcinogenicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

#### Relevant H and EUH statements (number and full text)

H201	Explosive; mass explosion hazard.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6110 Spray

Revision date: 11.04.2025

Product code: 5098

Page 21 of 21

H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains n-butyl acrylate. May produce an allergic reaction.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*