

according to UK REACH Regulation

DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 77 B Spray

```
UFI:
```

G71D-DM4X-D00D-PNFC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	
1.4. Emergency telephone	Giftnotruf Berlin: +49 30 30686 70	0 (Beratung in Deutsch und Englisch)
and the second sec		

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Asp. Tox. 1; H304 Repr. 1B; H360D STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 2-ethylhexanoic acid, manganese salt

Signal word:

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P251	Do not pierce or burn, even after use.



	DINITROL 77 B Spray	
Revision date: 16.05.2024	Product code: 21702	Page 2 of 15
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P405	Store locked up.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
Special labelling of cert	ain mixtures	
EUH066	Repeated exposure may cause skin dryness or cracking. Restricted to professional users.	
Additional advice on lat	belling	
The classification of t	the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.	
Labelling of packages w	vhere the contents do not exceed 125 ml	
Signal word:	Danger	
Pictograms:		
Hazard statements H222-H229-H360D-H	H412	
Precautionary statemen	its	
P210-P251-P280-P4		
<u>2.3. Other hazards</u> No information availa	able.	
SECTION 3: Composition	n/information on ingredients	

3.2. Mixtures



DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 3 of 15

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulati	on)		
	Hydrocarbons, C9-C11, n-alkan	es, isoalkanes, cyclics, <2%	aromatics	45 - < 50 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. T	ox. 1; H226 H336 H304 EU	H066	
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas	; H220 H280		
106-97-8	n-butane			10 - < 15 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1A, Compressed gas; H220 H280			
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether		< 1 %	
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H302 H315 H319			
15956-58-8	2-ethylhexanoic acid, manganes	e salt		< 1 %
	240-085-3		01-2119979087-23	
	Repr. 1B, Eye Irrit. 2, STOT RE 2, Aquatic Chronic 2; H360D H319 H373 H411			
25307-17-9	2,2'-(octadec-9-enylimino)biseth	anol		< 1 %
	246-807-3		01-2119510876-35	
	Acute Tox. 4, Skin Corr. 1B, Aqu	atic Acute 1, Aquatic Chror	ic 1; H302 H314 H400 H410	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	pecific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	45 - < 50 %
	inhalation: LC5 mg/kg	0 = 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000	
111-76-2	203-905-0	2-butoxyethanol; ethylene glycol monobutyl ether	< 1 %
	inhalation: ATE	3 mg/l (vapours); oral: ATE 1200 mg/kg	
25307-17-9	246-807-3	2,2'-(octadec-9-enylimino)bisethanol	< 1 %
	oral: LD50 = >3 Aquatic Chronic	300-2000 mg/kg Aquatic Acute 1; H400: M=10 c 1; H410: M=1	

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

according to UK REACH Regulation

DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 4 of 15

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

<u>4.2. Most important symptoms and effects, both acute and delayed</u> No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), alcohol resistant foam, Extinguishing powder

In case of major fire and large quantities: Water spray jet, alcohol resistant foam

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation. Clear contaminated areas thoroughly. Do not rinse down with water.



DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 5 of 15

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

No special measures are necessary.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2		butoxyacetic acid (creatinine)	240 mmol/mol		Post shift



DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type	DNEL type		Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2	2% aromatics		
Consumer DN	EL, long-term	oral	systemic	125 mg/kg bw/day
Worker DNEL	, long-term	dermal	systemic	208 mg/kg bw/day
Consumer DN	EL, long-term	dermal	systemic	125 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	871 mg/m³
Consumer DN	EL, long-term	inhalation	systemic	185 mg/m³
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether			
Consumer DN	EL, acute	oral	systemic	13,4 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	3,2 mg/kg bw/day
Worker DNEL	, long-term	dermal	systemic	75 mg/kg bw/day
Consumer DN	EL, acute	dermal	systemic	44,5 mg/kg bw/day
Consumer DN	EL, long-term	dermal	systemic	38 mg/kg bw/day
Worker DNEL	, acute	inhalation	local	246 mg/m ³
Worker DNEL	, long-term	inhalation	systemic	98 mg/m³
Consumer DN	EL, acute	inhalation	systemic	633 mg/m³
Worker DNEL	, acute	inhalation	systemic	633 mg/m³
Consumer DN	EL, acute	inhalation	local	123 mg/m ³
Consumer DN	EL, long-term	inhalation	systemic	49 mg/m³
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol			
Worker DNEL	, long-term	inhalation	systemic	2,122 mg/m ³
Worker DNEL	, long-term	dermal	systemic	0,3 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,745 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,214 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	0,214 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmental	compartment	Value	
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol		
Freshwater		0,000214 mg/l	
Marine water 0,0000		0,0000214 mg/l	
Freshwater sediment 1,692 mg/kg			
Marine sediment 0,1692 m		0,1692 mg/kg	
Secondary poisoning		2 mg/kg	
Soil		5 mg/kg	

8.2. Exposure controls



DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 7 of 15

DINOL GmbH



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Not required.

Recommended eye protection articles: Eye glasses with side protection (EN 166)

Hand protection

Not required.

Recommended glove articles NBR (Nitrile rubber) - (> = 0,12 mm), Breakthrough time:: 480 min. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Protective gloves have to be replaced at the first sign of deterioration. Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: AX

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	brown
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point: Boiling point or initial boiling point and	not determined -44 °C	
boiling range:		
Flammability:	not applicable	
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	10,9 vol. %	
Flash point:	< -20 °C	
Auto-ignition temperature:	> 200 °C	
Decomposition temperature:	not determined	
pH-Value:	The study does not need to be	
	conducted because the substance is	
	known to be insoluble in water.	
Viscosity / kinematic:	not determined	
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	

Test method



DINITROL 77 B Spray			
Revision date: 16.05.2024	Product code: 21702	Page 8 of 15	
Vapour pressure:	8300 hPa		
(at 20 °C)			
Vapour pressure:	17081 hPa		
(at 50 °C)			
Density (at 20 °C):	0,736 g/cm ³	DIN 51757	
Relative vapour density:	not determined		
9.2. Other information			
Information with regard to physical hazard class	es		
Explosive properties			
not determined			
Self-ignition temperature			
Solid:	not applicable		
Gas:	not applicable		
Oxidizing properties			
Not oxidising.			
Other safety characteristics			
Evaporation rate:	not determined		
Solvent content:	49,90 %		
Solid content:	35,90 %		
Viscosity / dynamic:	not determined		
Further Information			
No information available.			

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 87333 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 218,3 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to UK REACH Regulation

DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 9 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n	-alkanes, isoalkanes, cy	clics, <2% aromatics		
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 5000 mg/l	Rat		
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether				
	oral	ATE 1200 mg/kg			
	inhalation vapour	ATE 3 mg/l			
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol				
	oral	LD50 >300- 2000 mg/kg	Rat		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

May damage the unborn child. (2-ethylhexanoic acid, manganese salt) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



according to UK REACH Regulation

DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 10 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
111-76-2	2-butoxyethanol; ethylene	glycol monobutyl	ether			
	Acute fish toxicity	LC50 1490 mg/l	0 96 h	Lepomis macrochirus		
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol					
	Acute algae toxicity	ErC50 >0,0 mg/l)1-1 72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 >0,0 mg/l)1-1 48 h	Daphnia magna (Big water flea)		

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aro	matics		
		80%		
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether	0,81 (25°C)

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes. List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste



according to UK REACH Regulation

DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 11 of 15

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
	2
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	EO
Transport category:	2
Tunnel restriction code:	D
Other applicable information (land trans	port)
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Marine transport (IMDG)	
<u>14.1. UN number or ID number:</u>	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
	JAK.
	2
Marine pollutant:	no
Special Provisions:	63, 190, 277, 327, 344, 381, 959
1	,,,,,,,,,,



according to UK REACH Regulation

DINITROL 77 B Spray			
Revision date: 16.05.2024	Product code: 21	• •	Page 12 of 15
Limited quantity:	1000 mL		
Excepted quantity:	E0		
EmS:	F-D, S-U		
Air transport (ICAO-TI/IATA-DGR)			
14.1. UN number or ID number:	UN 1950		
14.2. UN proper shipping name:	AEROSOLS, FLAMMABLE		
14.3. Transport hazard class(es):	2.1		
<u>14.4. Packing group:</u>	-		
Hazard label:	2.1		
Special Provisions:	A145 A167 A802		
Limited quantity Passenger:	30 kg G		
Passenger LQ:	Y203		
Excepted quantity:	E0		
IATA-packing instructions - Passenger:	203		
IATA-max. quantity - Passenger:	75 kg		
IATA-packing instructions - Cargo:	203		
IATA-max. quantity - Cargo:	150 k	g	
Other applicable information (air transp E0	ort)		
Passenger-LQ: Y203			
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	No		
14.6. Special precautions for user Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximu 1 litre:Category B. For WASTE AERO		γ A. For AEROSOLS with a capacity abov ving quarters.	e
	ROSOLS with a capacity above	tion as for class 9. Stow "separated from" /e 1 litre: Segregation as for the appropria the appropriate	te
14.7. Maritime transport in bulk according	to IMO instruments		
not applicable			
Other applicable information			
Stowage Code:			
SW1 Protected from sources of heat.			
SW22 For AEROSOLS with a maximu		A. For AEROSOLS with a capacity abov	e

1 litre:Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



DINITROL 77 B Spray		
Revision date: 16.05.2024	Product code: 21702	Page 13 of 15
EU regulatory information		
Restrictions on use (REACH, annex XVII): Entry 3, Entry 29, Entry 40, Entry 75		
Directive 2004/42/EC on VOC in paints and varnishes:	72,9 % (536,544 g/l)	
Subcategory according to Directive 2004/42/EC:	Special finishes - All types, VOC limit value: 840 g/l	
Information according to Directive 2012/18/EU (SEVESO III):	P3a FLAMMABLE AEROSOLS	
Additional information		
Observe in addition any national regula Directive 98/24/EC of 7 April 1998 on th chemical agents at work Aerosol Directive (75/324/).	ations! he protection of the health and safety of workers from the risks related t	0
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juv work protection guideline' (94/33/EC). Observe employment restrictio under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	ns
Water hazard class (D):	3 - highly hazardous to water	
Additional information		
This mixture contains the following sub Candidate List according to Article 59 c	stances of very high concern (SVHC) which are included in the of REACH: none	
15.2. Chemical safety assessment		
For the following substances of this mix Hydrocarbons, C9-C11, n-alkanes, isoa	xture a chemical safety assessment has been carried out: alkanes, cyclics, <2% aromatics	

SECTION 16: Other information

DINOL GmbH



DINITROL 77 B Spray

Revision date: 16.05.2024

Product code: 21702

Page 14 of 15

Abbreviations and acronyms

Flam. Gas: Flammable gases Aerosol: Aerosols Compressed gas Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Irrit: Eye irritation Repr: Reproductive toxicity STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50% Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Repr. 1B; H360D	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.



according to UK REACH Regulation

DINITROL 77 B Spray

Product code: 21702

Page 15 of 15

Revision date: 16.05.2024

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)