

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 771 BLACK

Revision date: 03.01.2024

Product code: 80974

Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 771 BLACK

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Adhesives, sealants

##### Uses advised against

No further relevant information available.

#### 1.3. Details of the supplier of the safety data sheet

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

#### 2.2. Label elements

##### GB CLP Regulation

##### Special labelling of certain mixtures

EUH208 Contains trimethoxyvinylsilane; trimethoxy(vinyl)silane. May produce an allergic reaction.  
EUH210 Safety data sheet available on request.  
Restricted to professional users.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
52829-07-9	Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate			0,1 - < 1 %
	258-207-9		01-2119537297-32	
	Repr. 2, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2; H361f H318 H400 H411			
2768-02-7	trimethoxyvinylsilane; trimethoxy(vinyl)silane			1 - < 2,5 %
	220-449-8	014-049-00-0	01-2119513215-52	
	Flam. Liq. 3, Acute Tox. 4, Skin Sens. 1B; H226 H332 H317			

Full text of H and EUH statements: see section 16.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 771 BLACK

Revision date: 03.01.2024

Product code: 80974

Page 2 of 10

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
52829-07-9	258-207-9	Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0,1 - < 1 %
		inhalation: LC50 = 500 mg/l (vapours); dermal: LD50 = >3170 mg/kg; oral: LD50 = >2000 mg/kg	
2768-02-7	220-449-8	trimethoxyvinylsilane; trimethoxy(vinyl)silane	1 - < 2,5 %
		inhalation: LC50 = 16,8 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 3540 mg/kg; oral: LD50 = 7120-7236 mg/kg	

### Further Information

Full text of H- and EUH-statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice.  
Never give anything by mouth to an unconscious person or a person with cramps.  
If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

Change contaminated clothing.  
After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).  
Do NOT induce vomiting.  
Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.

### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder Water spray jet alcohol resistant foam.  
Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide

### 5.3. Advice for firefighters

Use suitable breathing apparatus.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 771 BLACK**

Revision date: 03.01.2024

Product code: 80974

Page 3 of 10

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

- Provide adequate ventilation.
- Wear personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Avoid breathing dust/fume/gas/mist/vapours/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

No special measures are necessary.

**6.3. Methods and material for containment and cleaning up****For containment**

- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
- Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

- Provide adequate ventilation.
- Clear contaminated areas thoroughly.
- Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on general occupational hygiene**

- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

No special measures are necessary.

**Hints on joint storage**

No further relevant information available.

**Further information on storage conditions**

storage temperature: 10 - 35 °C

**7.3. Specific end use(s)**

No further relevant information available.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 771 BLACK

Revision date: 03.01.2024

Product code: 80974

Page 4 of 10

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1317-65-3	Calcium carbonate, respirable	-	4		TWA (8 h)	WEL

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
52829-07-9	Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate			
Worker DNEL, acute		inhalation	systemic	2,82 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	1,6 mg/kg bw/day
2768-02-7	trimethoxyvinylsilane; trimethoxy(vinyl)silane			
Worker DNEL, long-term		inhalation	systemic	27,6 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	3,9 mg/kg bw/day

#### PNEC values

CAS No	Substance	Value
52829-07-9	Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	
Freshwater		0,018 mg/l
Marine water		0,0018 mg/l
Freshwater sediment		29 mg/kg
Marine sediment		2,9 mg/kg
Soil		5,9 mg/kg
2768-02-7	trimethoxyvinylsilane; trimethoxy(vinyl)silane	
Freshwater		0,33 mg/l
Marine water		0,033 mg/l
Micro-organisms in sewage treatment plants (STP)		13 mg/l
Soil		0,04 mg/l

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (DIN EN 166)

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 771 BLACK

Revision date: 03.01.2024

Product code: 80974

Page 5 of 10

#### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

#### Skin protection

Wear anti-static footwear and clothing

#### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: A/P2

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	black
Odour:	characteristic
Odour threshold:	not determined

#### Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not determined
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	not determined
Auto-ignition temperature:	not determined
Decomposition temperature:	not applicable
pH-Value:	not applicable
Viscosity / kinematic:	The study does not need to be conducted because the substance is known to be insoluble in water.

Water solubility: practically insoluble

Solubility in other solvents  
not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: not determined

Density (at 20 °C): 1,5 g/cm<sup>3</sup> DIN 51757

Relative vapour density: not determined

Particle characteristics: not applicable

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties  
not determined

Sustaining combustion: No data available

Oxidizing properties  
not determined

#### Other safety characteristics

Solid content: 97%

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 771 BLACK

Revision date: 03.01.2024

Product code: 80974

Page 6 of 10

Softening point: not determined  
Viscosity / dynamic: 17000000 - 32000000 mPa·s  
(at 20 °C)

#### Further Information

No information available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4. Conditions to avoid

Protect from moisture.  
exposure to cold. Do not freeze

#### 10.5. Incompatible materials

No further relevant information available.

#### 10.6. Hazardous decomposition products

Carbon monoxide

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### ATEmix tested

	Dose	Species	Source
LC50, inhalation (vapour)	736,7 mg/l		

##### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
52829-07-9	Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >3170 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 500 mg/l	Rat		
2768-02-7	trimethoxyvinylsilane; trimethoxy(vinyl)silane				
	oral	LD50 7120-7236 mg/kg	Rat		
	dermal	LD50 3540 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 16,8 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 771 BLACK

Revision date: 03.01.2024

Product code: 80974

Page 7 of 10

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

Contains trimethoxyvinylsilane; trimethoxy(vinyl)silane. May produce an allergic reaction.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Information on likely routes of exposure

No information available.

#### Specific effects in experiment on an animal

No information available.

#### Additional information on tests

No information available.

#### Practical experience

No information available.

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

Endocrine disrupting potential No information available.

#### Further information

There are no data available on the preparation/mixture itself.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

#### 12.2. Persistence and degradability

No further relevant information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
52829-07-9	Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate			
	OECD 303A	24	28	
	Moderately/partially biodegradable.			

#### 12.3. Bioaccumulative potential

No further relevant information available.

#### 12.4. Mobility in soil

No further relevant information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 771 BLACK

Revision date: 03.01.2024

Product code: 80974

Page 8 of 10

#### 12.7. Other adverse effects

No further relevant information available.

#### Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

##### List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

##### List of Wastes Code - contaminated packaging

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

##### Contaminated packaging

Dispose of waste according to applicable legislation.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

##### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

##### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

##### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

#### Inland waterways transport (ADN)

##### 14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

##### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

##### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

##### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

#### Marine transport (IMDG)

##### 14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

##### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

##### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

##### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine pollutant:

no

#### Air transport (ICAO-TI/IATA-DGR)

##### 14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

##### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

##### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

##### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

#### 14.6. Special precautions for user

not applicable



## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 771 BLACK

Revision date: 03.01.2024

Product code: 80974

Page 9 of 10

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes: 0,00 %  
0,00 g/l

##### Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

##### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2.

#### Abbreviations and acronyms

Flam. Liq: Flammable liquids  
Acute Tox: Acute toxicity  
Eye Dam: Eye damage  
Skin Sens: Skin sensitisation  
Repr: Reproductive toxicity  
Aquatic Acute: Acute aquatic hazard  
Aquatic Chronic: Chronic aquatic hazard  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

#### Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 771 BLACK**

Revision date: 03.01.2024

Product code: 80974

Page 10 of 10

H318	Causes serious eye damage.
H332	Harmful if inhaled.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains trimethoxyvinylsilane; trimethoxy(vinyl)silane. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*