

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 8530 Spray

UFI: 2G51-A3WT-100U-RY6V

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Paints and varnishes

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

Supplier

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229
 Eye Irrit. 2; H319
 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

acetone; propan-2-one; propanone
 n-butyl acetate
 2-methoxy-1-methylethyl acetate
 isopropanol (isopropyl alcohol)

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 2 of 17

H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe mist/vapours/spray.
P280 Wear protective gloves and eye protection/face protection.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229

Precautionary statements

P210-P211-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 3 of 17

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-64-1	acetone; propan-2-one; propanone			25 - < 50 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-86-4	n-butyl acetate			12,5 - < 20 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
74-98-6	propane			10 - < 12,5 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
108-65-6	2-methoxy-1-methylethyl acetate			5 - < 10 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3, STOT SE 3; H226 H336			
106-97-8	butane			5 - < 10 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
75-28-5	isobutane			5 - < 10 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
67-63-0	isopropanol (isopropyl alcohol)			< 2,5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
71-36-3	butan-1-ol; n-butanol			< 2,5 %
	200-751-6	603-004-00-6	01-2119484630-38	
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 4 of 17

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	25 - < 50 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800 mg/kg	
123-86-4	204-658-1	n-butyl acetate	12,5 - < 20 %
		inhalation: LC50 = > 21 mg/l (vapours); inhalation: LC50 = >21 mg/l (dusts or mists); dermal: LD50 = > 14112 mg/kg; oral: LD50 = 10760 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	5 - < 10 %
		inhalation: LC50 = 35,7 mg/l (vapours); oral: LD50 = 8500 mg/kg	
106-97-8	203-448-7	butane	5 - < 10 %
		inhalation: LC50 = 273000 ppm (gases)	
67-63-0	200-661-7	isopropanol (isopropyl alcohol)	< 2,5 %
		inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg	
71-36-3	200-751-6	butan-1-ol; n-butanol	< 2,5 %
		inhalation: LC50 = >17 mg/l (dusts or mists); dermal: LD50 = 3400 mg/kg; oral: LD50 = 790 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 5 of 17

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.
Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wear personal protection equipment.
Avoid contact with skin, eyes and clothes.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.
Clear contaminated areas thoroughly.
Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.
Do not spray on naked flames or any incandescent material.
Keep away from sources of ignition - No smoking.
Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 6 of 17

When using do not eat or drink.
Wash hands before breaks and after work.
Avoid contact with skin and eyes.
Remove contaminated, saturated clothing immediately.
Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Do not keep the container sealed. Keep container dry.
Keep in a cool, well-ventilated place.
Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
71-36-3	Butan-1-ol	50	154		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 7 of 17

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL, long-term	inhalation	systemic	1210 mg/m ³	
Worker DNEL, acute	inhalation	local	2420 mg/m ³	
Worker DNEL, long-term	dermal	systemic	186 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	200 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	62 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	62 mg/kg bw/day	
123-86-4	n-butyl acetate			
Worker DNEL, long-term	inhalation	systemic	48 mg/m ³	
Worker DNEL, acute	inhalation	systemic	600 mg/m ³	
Worker DNEL, long-term	inhalation	local	300 mg/m ³	
Worker DNEL, acute	inhalation	local	600 mg/m ³	
Consumer DNEL, long-term	inhalation	systemic	12 mg/m ³	
Consumer DNEL, acute	inhalation	systemic	300 mg/m ³	
Consumer DNEL, long-term	inhalation	local	35,7 mg/m ³	
Consumer DNEL, acute	inhalation	local	300 mg/m ³	
108-65-6	2-methoxy-1-methylethyl acetate			
Worker DNEL, long-term	inhalation	systemic	275 mg/m ³	
Worker DNEL, acute	inhalation	local	550 mg/m ³	
Worker DNEL, long-term	dermal	systemic	796 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	33 mg/m ³	
Consumer DNEL, acute	inhalation	local	33 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	320 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	36 mg/kg bw/day	
67-63-0	isopropanol (isopropyl alcohol)			
Consumer DNEL, long-term	inhalation	systemic	89 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day	
Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	500 mg/m ³	
71-36-3	butan-1-ol; n-butanol			
Worker DNEL, long-term	inhalation	local	310 mg/m ³	
Consumer DNEL, long-term	oral	systemic	3,125 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	55 mg/m ³	
1333-86-4	Carbon Black			
Worker DNEL, long-term	inhalation	systemic	2 mg/m ³	
Worker DNEL, long-term	inhalation	local	2 mg/m ³	

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 8 of 17

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,0981 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,0903 mg/kg
108-65-6	2-methoxy-1-methylethyl acetate	
Freshwater		0,635 mg/l
Marine water		0,0635 mg/l
Freshwater sediment		3,29 mg/kg
Marine sediment		0,329 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,290 mg/kg
67-63-0	isopropanol (isopropyl alcohol)	
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg
71-36-3	butan-1-ol; n-butanol	
Freshwater		0,082 mg/l
Marine water		0,0082 mg/l
Freshwater sediment		0,178 mg/kg
Marine sediment		0,0178 mg/kg
Micro-organisms in sewage treatment plants (STP)		2476 mg/l
Soil		0,015 mg/kg
1333-86-4	Carbon Black	
Freshwater		5 mg/l
Marine water		5 mg/l

8.2. Exposure controls

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 9 of 17



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber), Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: A2/P3

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	black	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not applicable
Flammability:		not applicable
Lower explosion limits:		1,2 vol. %
Upper explosion limits:		13,0 vol. %
Flash point:		not applicable
Auto-ignition temperature:		333 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 10 of 17

Vapour pressure:	3500 hPa
(at 20 °C)	
Density (at 20 °C):	0,7 g/cm ³
Relative vapour density:	not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
not determined	
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
not determined	

Other safety characteristics

Evaporation rate:	not applicable
Solvent separation test:	not determined
Solvent content:	91,9 %
	Water content : 0,3 %
Solid content:	7,60 %
Viscosity / dynamic:	not determined

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 11 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat	RTECS	
	dermal	LD50 7426-15800 mg/kg	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
123-86-4	n-butyl acetate				
	oral	LD50 10760 mg/kg	Rat		
	dermal	LD50 > 14112 mg/kg	Rabbit		
	inhalation vapour	LC50 > 21 mg/l	Rat		
	inhalation (4 h) dust/mist	LC50 >21 mg/l	Rat		
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 8500 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 35,7 mg/l	Rat		
106-97-8	butane				
	inhalation (4 h) gas	LC50 273000 ppm	Rat	GESTIS	
67-63-0	isopropanol (isopropyl alcohol)				
	oral	LD50 4570 mg/kg	Rat		
	dermal	LD50 13400 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 30 mg/l	Rat		
71-36-3	butan-1-ol; n-butanol				
	oral	LD50 790 mg/kg	Rat	GESTIS	
	dermal	LD50 3400 mg/kg	Rabbit	GSETIS	
	inhalation (4 h) dust/mist	LC50 >17 mg/l	Rat		

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone; n-butyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 12 of 17

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna	
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum	
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50	18 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	397 mg/l	72 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50	44 mg/l	48 h	Daphnia magna (Big water flea)	
71-36-3	butan-1-ol; n-butanol					
	Acute fish toxicity	LC50 mg/l	1740	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	>500	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	1980	48 h		GESTIS
	Acute bacteria toxicity	EC50 mg/l ()	2250		Pseudomonas putida	16 h

12.2. Persistence and degradability

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 13 of 17

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	acetone; propan-2-one; propanone			
	OECD 301 B	91%	28	
	Readily biodegradable (according to OECD criteria).			
123-86-4	n-butyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	83%	28	
	Readily biodegradable (according to OECD criteria).			
108-65-6	2-methoxy-1-methylethyl acetate			
	OECD 302 B	>90 %		
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
123-86-4	n-butyl acetate	2,3
108-65-6	2-methoxy-1-methylethyl acetate	0,56
106-97-8	butane	2,89
67-63-0	isopropanol (isopropyl alcohol)	0,05
71-36-3	butan-1-ol; n-butanol	0,88

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 14 of 17

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Marine pollutant: no
Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 15 of 17



Special Provisions:	A145 A167 A802	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y203	
Excepted quantity:	E0	
IATA-packing instructions - Passenger:		203
IATA-max. quantity - Passenger:		75 kg
IATA-packing instructions - Cargo:		203
IATA-max. quantity - Cargo:		150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Gases under pressure

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 91,9 % (683,4 g/l)

Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 16 of 17

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3,8,13,15,16.

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8530 Spray

Revision date: 20.11.2024

Product code: 34005

Page 17 of 17

EUH066

Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)