

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier

DINITROL 8550 Spray

UFI: 9U51-C3PD-800U-DAJ4

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

Paints and varnishes

1.3. Details of the supplier of the safety data sheet
Manufacturer

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

Supplier

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgegate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

1.4. **Emergency telephone number:** Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
GB CLP Regulation

Aerosol 1; H222-H229
 Skin Irrit. 2; H315
 Eye Dam. 1; H318
 STOT SE 3; H335 H336
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements
GB CLP Regulation
Hazard components for labelling

Hydrocarbons, C9, aromatics
 butan-1-ol; n-butanol
 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
 reaction mass of ethylbenzene and xylene

Signal word: Danger

Pictograms:


Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 2 of 17

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves and eye protection/face protection.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

Hazard statements

H222-H229-H318-H412

Precautionary statements

P210-P211-P251-P280-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients
3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 3 of 17

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
115-10-6	dimethyl ether			50 - < 75 %
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Liquefied gas; H220 H280			
128601-23-0	Hydrocarbons, C9, aromatics			10 - < 12,5 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
71-36-3	butan-1-ol; n-butanol			5 - < 10 %
	200-751-6	603-004-00-6	01-2119484630-38	
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	reaction mass of ethylbenzene and xylene			5 - < 10 %
	905-588-0		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
100-41-4	ethylbenzene			< 2,5 %
	202-849-4	601-023-00-4	01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H332 H373 H304 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
128601-23-0	918-668-5	Hydrocarbons, C9, aromatics	10 - < 12,5 %
		dermal: LD50 = > 3160 mg/kg; oral: LD50 = > 2000 mg/kg	
71-36-3	200-751-6	butan-1-ol; n-butanol	5 - < 10 %
		inhalation: LC50 = >17 mg/l (dusts or mists); dermal: LD50 = 3400 mg/kg; oral: LD50 = 790 mg/kg	
	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	5 - < 10 %
		inhalation: LC50 = > 20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = > 2000 mg/kg	
	905-588-0	reaction mass of ethylbenzene and xylene	5 - < 10 %
		inhalation: LC50 = 20 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4300 mg/kg	
100-41-4	202-849-4	ethylbenzene	< 2,5 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	

Further Information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 4 of 17

4.1. Description of first aid measures**General information**

In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 5 of 17

For containment

- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
- Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

- Provide adequate ventilation.
- Clear contaminated areas thoroughly.
- Do not rinse down with water.

Other information

- No information available.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

- Take precautionary measures against static discharges.
- Do not spray on naked flames or any incandescent material.
- Keep away from sources of ignition - No smoking.
- Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs.
- When using do not eat or drink.
- Wash hands before breaks and after work.
- Avoid contact with skin and eyes.
- Remove contaminated, saturated clothing immediately.
- Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Do not keep the container sealed. Keep container dry.
- Keep in a cool, well-ventilated place.
- Keep away from heat. Protect from direct sunlight.

7.3. Specific end use(s)

- No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 6 of 17

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
71-36-3	Butan-1-ol	50	154		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 7 of 17

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
128601-23-0	Hydrocarbons, C9, aromatics		
Worker DNEL, long-term	inhalation	systemic	150 mg/m ³
Worker DNEL, long-term	dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	32 mg/m ³
Consumer DNEL, long-term	dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	11 mg/kg bw/day
71-36-3	butan-1-ol; n-butanol		
Worker DNEL, long-term	inhalation	local	310 mg/m ³
Consumer DNEL, long-term	oral	systemic	3,125 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	55 mg/m ³
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Worker DNEL, long-term	inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day
	reaction mass of ethylbenzene and xylene		
Worker DNEL, long-term	inhalation	systemic	211 mg/m ³
Worker DNEL, long-term	inhalation	local	221 mg/m ³
Worker DNEL, acute	inhalation	systemic	442 mg/m ³
Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
Worker DNEL, acute	inhalation	local	289 mg/m ³
Consumer DNEL, long-term	oral	systemic	1,6 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	14,8 mg/m ³
Consumer DNEL, long-term	inhalation	local	65,3 mg/m ³
Consumer DNEL, acute	inhalation	systemic	260 mg/m ³
Consumer DNEL, acute	inhalation	local	260 mg/m ³
100-41-4	ethylbenzene		
Worker DNEL, long-term	inhalation	systemic	77 mg/m ³
Worker DNEL, long-term	inhalation	local	293 mg/m ³
Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	15 mg/m ³
Consumer DNEL, long-term	oral	systemic	1,6 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 8 of 17

PNEC values

CAS No	Substance	Value
Environmental compartment		
71-36-3	butan-1-ol; n-butanol	
Freshwater		0,082 mg/l
Marine water		0,0082 mg/l
Freshwater sediment		0,178 mg/kg
Marine sediment		0,0178 mg/kg
Micro-organisms in sewage treatment plants (STP)		2476 mg/l
Soil		0,015 mg/kg
reaction mass of ethylbenzene and xylene		
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,64 mg/kg
Marine sediment		12,64 mg/kg
Soil		2,31 mg/kg
100-41-4	ethylbenzene	
Freshwater		0,1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		13,7 mg/kg
Marine sediment		1,37 mg/kg
Secondary poisoning		0,02 mg/kg
Micro-organisms in sewage treatment plants (STP)		9,6 mg/l
Soil		2,68 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment
Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber), Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 9 of 17

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

 Work in well-ventilated zones or use proper respiratory protection.
 gas filtering equipment (EN 141), Filter material/medium: A2/P3

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	transparent	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not applicable
Flammability:		not applicable
Lower explosion limits:		0,7 vol. %
Upper explosion limits:		26,2 vol. %
Flash point:		not applicable
Auto-ignition temperature:		> 200 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure: (at 20 °C)		4000 hPa
Density (at 20 °C):		0,8 g/cm ³
Relative vapour density:		not determined

9.2. Other information
Information with regard to physical hazard classes

Explosive properties		not determined
Self-ignition temperature		
Solid:		not applicable
Gas:		not applicable
Oxidizing properties		not determined

Other safety characteristics

Evaporation rate:		not applicable
Solvent separation test:		not determined
Solvent content:		88,1 %
Solid content:		11,7 %
Viscosity / dynamic:		not determined

Further Information

No information available.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 10 of 17

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation gas) 19500 ppm

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 11 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
128601-23-0	Hydrocarbons, C9, aromatics				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 3160 mg/kg	Rabbit		
71-36-3	butan-1-ol; n-butanol				
	oral	LD50 790 mg/kg	Rat	GESTIS	
	dermal	LD50 3400 mg/kg	Rabbit	GSETIS	
	inhalation (4 h) dust/mist	LC50 >17 mg/l	Rat		
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 20 mg/l	Rat		
	reaction mass of ethylbenzene and xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 20 mg/l	Rat		
	inhalation gas	ATE 4500 ppm			
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation gas	ATE 4500 ppm			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Hydrocarbons, C9, aromatics; butan-1-ol; n-butanol)

May cause drowsiness or dizziness. (Hydrocarbons, C9, aromatics; butan-1-ol; n-butanol; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 12 of 17

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards
Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information
12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
128601-23-0	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h		
71-36-3	butan-1-ol; n-butanol					
	Acute fish toxicity	LC50 mg/l	1740	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	>500	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	1980	48 h		GESTIS
	Acute bacteria toxicity	EC50 mg/l ()	2250		Pseudomonas putida	16 h
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50 mg/l	10-100	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	30-100	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna (Big water flea)	
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss (Rainbow trout)	
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	OECD 301F	98%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 13 of 17

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1
71-36-3	butan-1-ol; n-butanol	0,88
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	3,4-5,2
100-41-4	ethylbenzene	3,15

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 14 of 17



Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1



Marine pollutant:	no
Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1



Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	No
----------------------------	----

14.6. Special precautions for user

Warning: Gases under pressure

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Stowage Code:
 SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 15 of 17

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 88,14 % (661,9 g/l)

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C9, aromatics

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 16.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 16 of 17

Abbreviations and acronyms

Flam. Gas: Flammable gases
 Aerosol: Aerosols
 Liquefied gas
 Flam. Liq: Flammable liquids
 Acute Tox: Acute toxicity
 Asp. Tox: Aspiration hazard
 Skin Irrit: Skin irritation
 Eye Dam: Eye damage
 Eye Irrit: Eye irritation
 STOT SE: Specific target organ toxicity - single exposure
 STOT RE: Specific target organ toxicity - repeated exposure
 Aquatic Chronic: Chronic aquatic hazard
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Dam. 1; H318	Bridging principle "Aerosols"
STOT SE 3; H335	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
 H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H229 Pressurised container: May burst if heated.
 H280 Contains gas under pressure; may explode if heated.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our

Safety Data Sheet

according to UK REACH Regulation

DINITROL 8550 Spray

Revision date: 20.11.2024

Product code: 34009

Page 17 of 17

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)