

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 1 of 10

1. Identification

Product identifier

DINITROL HIGH PERFORMANCE WAX

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

No further relevant information available.

Uses advised against

Corrosion inhibitor

Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980
E-mail: msds@dinol.com
Contact person: Labor
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

Supplier

Company name: DINOL U.S. Inc.
Street: 8500 Cotter Street, Lewis Center
Place: USA-43035 Ohio
Telephone: 740-548-1656
E-mail: info@dinolus.com
Internet: www.dinol.com

Telefax: 740-548-1657

Emergency phone number: 3E Company Emergency +1-866-404-4230

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Flammable liquids: Flam. Liq. 3
Serious eye damage/eye irritation: Eye Irrit. 2A
Respiratory or skin sensitization: Skin Sens. 1B
Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects)

Label elements

29 CFR Part 1910.1200

Signal word: Warning

Pictograms:



Hazard statements

Flammable liquid and vapor
Causes serious eye irritation
May cause an allergic skin reaction
May cause drowsiness or dizziness

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 2 of 10

Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin: Wash with plenty of water.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Wash contaminated clothing before reuse.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 In case of fire: Use Water spray jet, Extinguishing powder, Carbon dioxide (CO₂) to extinguish.
 Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

Hazards not otherwise classified

No information available.

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Components	Quantity
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	59 %
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	24 %
61789-86-4	calcium sulfonate	9 %
154518-38-4	Phosphorsäure, C11-14-Isoalkylester, C13-reich	1 %

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w)
 DMSO extract (IP 346)).

4. First-aid measures

Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.
 Never give anything by mouth to an unconscious person or a person with cramps.
 If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.
 After contact with skin, wash immediately with plenty of water and soap.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 3 of 10

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Do NOT induce vomiting.
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂) Extinguishing powder Water spray jet alcohol resistant foam

Unsuitable extinguishing media

Full water jet

Specific hazards arising from the chemical

No further relevant information available.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Suppress gases/vapors/mists with water spray jet.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.
Wear personal protection equipment.
Avoid contact with skin, eyes and clothes.
Avoid breathing dust/fume/gas/mist/vapors/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow uncontrolled discharge of product into the environment.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.
Clear contaminated areas thoroughly.
Do not rinse down with water.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 4 of 10

Other information

No information available.

Reference to other sections

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No special measures are necessary.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed. Keep away from heat.

8. Exposure controls/personal protection

Control parameters

Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 5 of 10

mentioned above together with the supplier of these gloves.
Protective gloves have to be replaced at the first sign of deterioration.
Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
gas filtering equipment (EN 141), Filter material/medium: A

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Color:	whitish transparent
Odor:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	136-164 °C	
Flammability:	not applicable	
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	7 vol. %	
Flash point:	29 °C	DIN 53213
Auto-ignition temperature:	> 200 °C	
Decomposition temperature:	not applicable	
pH-Value:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Viscosity / kinematic:	not determined	
Water solubility:	not applicable	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:	not determined	
Vapor pressure:	5 hPa	
(at 20 °C)		
Vapor pressure:	30 hPa	
(at 50 °C)		
Density (at 20 °C):	0,84 - 0,88 g/cm³	DIN 51757
Relative vapour density:	not determined	
Particle characteristics:	not applicable	

Other information

Information with regard to physical hazard classes

Explosive properties	
not determined	
Sustaining combustion:	No data available
Oxidizing properties	
not determined	

Other safety characteristics

Solvent content:	59 %
Solid content:	42 - 45 %
Softening point:	not determined

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 6 of 10

Viscosity / dynamic:
(at 20 °C)

370 mPa·s

Further Information

No information available.

10. Stability and reactivity**Reactivity**

No further relevant information available.

Chemical stability

Stability:

Stable

No hazardous reaction when handled and stored according to provisions.

Possibility of hazardous reactions

Hazardous reactions:

Will not occur

No known hazardous reactions.

Conditions to avoid

No further relevant information available.

Incompatible materials

No further relevant information available.

Hazardous decomposition products

Carbon monoxide

11. Toxicological information**Route(s) of Entry**

No information available.

Information on toxicological effects**Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 7 of 10

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
154518-38-4	Phosphorsäure, C11-14-Isoalkylester, C13-reich				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		

Irritation and corrosivity

Causes serious eye irritation

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

May cause an allergic skin reaction (calcium sulfonate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics;
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (OSHA): No ingredient of this mixture is listed.

Carcinogenicity (IARC): No ingredient of this mixture is listed.

Carcinogenicity (NTP): No ingredient of this mixture is listed.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

Information on other hazards

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 8 of 10

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information

Persistence and degradability

There are no data available on the mixture itself.

Bioaccumulative potential

There are no data available on the mixture itself.

Mobility in soil

There are no data available on the mixture itself.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No further relevant information available.

Further information

There are no data available on the mixture itself.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

This material and its container must be disposed of as hazardous waste.

Contaminated packaging

Dispose of waste according to applicable legislation.

14. Transport information

U.S. DOT 49 CFR 172.101

UN number or ID number:

UN 1139

Proper shipping name:

COATING SOLUTION

Transport hazard class(es):

3

Packing group:

III

Hazard label:

3



Marine transport (IMDG)

UN number or ID number:

UN 1139

UN proper shipping name:

coating solution

Transport hazard class(es):

3

Packing group:

III

Marine pollutant:

no

Limited quantity:

5L

EmS:

F-E,S-E

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number:

UN 1139

UN proper shipping name:

coating solution

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 9 of 10

Transport hazard class(es): 3

Packing group: III

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

Warning : Flammable liquids

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Other applicable information

Transport classification ADR/IMDG is based on packaging >30ltr(IMDG), >450ltr(ADR).

For other packaging units different classification can apply.

15. Regulatory information

U.S. Regulations

National Inventory TSCA

Substance/product listed in the following inventories: TSCA

National regulatory information

SARA Section 311/312 Hazards:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (-): Fire hazard, Immediate (acute) health hazard

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics (-): Fire hazard, Immediate (acute) health hazard

calcium sulfonate (61789-86-4): Immediate (acute) health hazard

Phosphorsäure, C11-14-Isoalkylester, C13-reich (154518-38-4): Immediate (acute) health hazard

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Directive 2004/42/EC on VOC in 59,01 %

paints and varnishes: 508,1 g/l

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

16. Other information

Changes

Revision date: 02/12/2024

Revision No: 1,3

This data sheet contains changes from the previous version in section(s): 2,8,9.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL HIGH PERFORMANCE WAX

Revision date: 02/12/2024

Product code: 20179

Page 10 of 10

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)