

DINITROL 6100 SPRAY-FILL^{2K}

Spray Filler AC Spray

DINITROL 6100 Spray-Fill 2K is an acrylic resin-based filler in aerosol packaging. The product has excellent filling properties, dries quickly, is easy to sand and can be used with most repair lacquers.

- » Grey
- » Ideal to fill scratches, scrapes and other minor damage before paintwork
- » Good quick cosmetic repair





Equipment

DINITROL INDUSTRIAL NITRILE GLOVES XLArt. No. 1734100

DINITROL 6100 Spray-Fill^{2K}

Art. No.SizePackageColor13042400 mlSpray canGrey



08.2024



DINITROL 6100 SPRAY-FILL^{2K}

Technical Details

Product description

DINITROL 6100 Spray-Fill 2K is an acrylic resinbased filler in aerosol packaging. The product has excellent filling properties, dries quickly, is easy to file and can be used with most repair lacquers.

Application

DINITROL 6100 Spray-Fill 2K is used to level scratches, scrapes and other minor damage to paintwork.

Pre-Treatment Substrates

The surface to be treated must be clean and free from oil and grease. Edges of adjacent surfaces should be sanded with fine sand-paper. Unprocessed surfaces must be covered. At a distance of 20 to 30 cm spray the filler thinly in the cloister. If necessary, spray several times, with the previous layer dried before each application.

Over-Coating

After drying, the filler can be sanded and painted. If the filler is used in a thin layer as a primer, the surface need not be sanded before painting. For additional information, please consult DINOL GmbH

Technical Data

Colour	white
Base	Polyester
Density	1,7 g/cm³
Processing time	approx. 5 minutes
Flash point	31°C
Storage time	12 months (15°C and 25°C)
Available in	2,5 kg Can, 9,7 kg Can

Hazards identification
2.1. Classification of the substance or mixture
GB CLP Regulation

Aerosol 1; H222-H229; Acute Tox. 4; H332; Skin Irrit. 2; H315; Eye Irrit. 2; H319; STOT SE 3; H335; STOT RE 2; H373

For all relevant safety advices please read the material safety data sheet or the packaging label.