

DINITROL 7660 SILIOFF^{NORM}

Cleaning agent / silicone remover

DINITROL 7660 Silioff Norm is a quick-drying cleaning agent and silicone remover, for all cleaning tasks prior to painting.

- » Transparent
- » Professional cleaning and degreasing before painting
- » Long flash off time
- » High level of cleaning power
- » Reduces pretreatment and rework



Equipment

DINITROL INDUSTRIAL NITRILE GLOVES XL
Art. No. 1734100

DINITROL 7450

Art. No.	Size	Package	Color
14180	1 L	Canister	Transparent

DINITROL 7660 SILIOFF^{NORM}

Technical Details

Product description

DINITROL 7660 Silioff Norm is a quick-drying detergent and silicone remover for all cleaning jobs before painting

Application

Apply the silicone remover to the area to be cleaned directly before painting and wipe off with a clean, lint-free cloth. Allow the cleaned area to dry thoroughly before painting.

!! Non-volatilised silicone remover residues may cause bubbles in the paint during forced drying afterwards!!

With DINITROL 7660 Silioff Norm, sanding dust from leveling compounds or fillers and oil dusts (silicone), which are often the cause of paint runout problems, can be easily removed from the surfaces to be painted.

DINITROL 7660 Silioff Norm is also suitable as a quick-drying degreasing agent for metallic surfaces.

For additional information, please consult DINOL GmbH.

Technical Data

Colour	colourless transparent (clear)
Odour	benzene-like
Density	0.74 g/ml
Flash point	approx. 2°C
Initial bonding point	80°C
Storage	24 months (between 15 – 25°C)
Available in	5 L canister

Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation
Flam. Liq. 2; H225; Asp. Tox. 1; H304;
STOT SE 3; H336; Aquatic Chronic 2; H411

For all relevant safety advices please read the material safety data sheet or the packaging label.