

DINITROL 8550 Clearcoat 1K

Clear Lacquer Spray, transparent


DINITROL 8550 Clearcoat 1K Spray is an acrylic lacquer to seal lacquered surface. Also ideal for wheel rims.

» Transparent

» Decorative transparent protection
(small areas) after the application
DINITROL 8510 – 8540

» Fast curing within 25 minutes (20°C)

» Fast further processing



Equipment

DINITROL Industrial Nitrile Gloves XL
Art. No. 1734100

DINITROL 8550 Clearcoat 1K

Art. No.	Size	Package	Color
14071	400 ml	Spray can	Transparent

DINITROL 8550 Clearcoat 1K

Technical Details

Product Description

DINITROL 8550 Clearcoat 1K Spray is an acrylic lacquer for sealing lacquered surfaces.

Application

DINITROL 8550 Clearcoat 1K Spray is ideal for wheel rims. High-pigmented silver lacquer which may display good adhesion but are susceptible to ageing can be perfectly sealed with Clear Lacquer Spray.

Pre-Treatment Substrates

The substrate must be clean and free from grease, dust and rust. For use on solvent- or water-based basecoats or pre-treated old or original paintwork. In general, do not overpaint synthetic resin paints. We recommend spraying after shaking the can and checking the compatibility with the respective substrate and colour.

The substrate must be finely sanded, cleaned with silicone remover, pre-painted if necessary and free of dust.

For additional information, please consult DINITROL GmbH.

Technical Data

Colour	colourless
Base	Acrylic resin
Density	0,798 g/ml
Flash point	< - 19°C
Heat resistance	> 80°C
Propellant	Propane / butane
Drying time – Touch dry at 20°C	approx. 25 min. / 40 µ
Storage	24 months – cool and dry
Hazard indication	highly flammable
Available in	400 ml spray can

Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229; Skin Irrit. 2; H315; Eye Dam. 1; H318; STOT SE 3; H335; STOT SE 3; H336; Aquatic Chronic 3; H412

For all relevant safety advices please read the material safety data sheet or the packaging label.