

according to UK REACH Regulation

## **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**DINITROL 1000 Airmix** 

UFI: RA9A-HMPN-100M-88GU

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Anti-corrosive coating

## 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

Supplier

Company name:

Street:

Marston Business Park, Rudgate
Place:

GB Tockwith, York YO26 7QF

E-mail:

enquiries@leading-solvents.co.uk
Internet:

www.leading-solvents.co.uk

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

# **GB CLP Regulation**

# Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Danger

Pictograms:







# **Hazard statements**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.



according to UK REACH Regulation

# **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 2 of 12

# **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves and eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

## Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains calcium sulfonate. May produce an allergic reaction.

Restricted to professional users.

# Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:







### **Hazard statements**

H304

## **Precautionary statements**

P405

## 2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

# Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			55 - < 60 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
61789-86-4	calcium sulfonate			1 - < 5 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	55 - < 60 %
	inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
61789-86-4	263-093-9	calcium sulfonate	1 - < 5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5000 mg/kg Skin Sens. 1B; H317: >= 10 - 100		

## **Further Information**

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w)



according to UK REACH Regulation

### **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 3 of 12

DMSO extract (IP 346)).

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

### After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

## After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

# 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

## Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder. Water fog.

# Unsuitable extinguishing media

High power water jet.

# 5.2. Special hazards arising from the substance or mixture

No further relevant information available.

# 5.3. Advice for firefighters

Use appropriate respiratory protection.

## **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Print date: 05.05.2025



# **Safety Data Sheet**

according to UK REACH Regulation

## **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 4 of 12

### For emergency responders

For further specification, refer to section 8 of the SDS.

### 6.2. Environmental precautions

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

# 6.3. Methods and material for containment and cleaning up

## For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

#### For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

#### Other information

No information available.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

# Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

## Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs, Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

## 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Protect from sunlight.

# Hints on joint storage

Not required.

# Further information on storage conditions

maximum storage temperature : < 30 °C minimum storage temperature : > 5 °C

# 7.3. Specific end use(s)

No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters



according to UK REACH Regulation

# **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 5 of 12

## **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics	s, <2% aromatics		
Worker DNE	, long-term	dermal	systemic	208 mg/kg bw/day
Worker DNE	_, long-term	inhalation	systemic	871 mg/m³
Consumer D	NEL, long-term	inhalation	systemic	185 mg/m³
Consumer D	NEL, long-term	dermal	systemic	125 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	125 mg/kg bw/day
,				
61789-86-4	calcium sulfonate			
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNE	Worker DNEL, long-term		local	1,03 mg/cm²
Consumer D	NEL, long-term	inhalation	systemic	2,9 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm <sup>2</sup>
Consumer DNEL, long-term		oral	systemic	0,8333 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m³

### **PNEC** values

CAS No	Substance		
Environmenta	Environmental compartment		
61789-86-4	61789-86-4 calcium sulfonate		
Freshwater		1 mg/l	
Marine water		1 mg/l	
Freshwater sediment		226000000 mg/kg	
Marine sediment		226000000 mg/kg	
Secondary poisoning		16667 mg/kg	
Micro-organisms in sewage treatment plants (STP)		1000 mg/l	
Soil		271000000 mg/kg	

# 8.2. Exposure controls







# Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment



according to UK REACH Regulation

## **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 6 of 12

## Eye/face protection

Eye glasses with side protection (DIN EN 166)

### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min. NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

Thickness of the glove material: > 0,12 mm

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

## Skin protection

Wear anti-static footwear and clothing

## Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141). Filter material/medium: A

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: beige
Odour: characteristic
Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

not determined

154 - 193 °C

boiling range:

Flammability: Flammable liquid and vapour.

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 7,0 vol. %

Flash point: 36 °C DIN EN ISO 2719

Auto-ignition temperature: > 200 °C

Decomposition temperature: not determined
pH-Value: not determined
Viscosity / kinematic: < 20,5 mm²/s

(at 40 °C)

Water solubility: Immiscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 3 hPa

(at 20 °C)

Vapour pressure: 13 hPa

(at 50 °C)

Density (at 20 °C): 0,83 - 0,87 g/cm³ DIN 51757

Relative vapour density: not determined Particle characteristics: not applicable

# 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties not determined



according to UK REACH Regulation

## **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 7 of 12

Sustained combustibility:

No data available

Oxidizing properties not determined

Other safety characteristics

Solvent content: 48,4 %
Solid content: 48 - 52 %
Softening point: not determined
Viscosity / dynamic: not determined

Flow time: 14 - 16 s 4 DIN EN ISO 2431

(at 23 °C)

**Further Information** 

No information available.

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

## 10.4. Conditions to avoid

No further relevant information available.

### 10.5. Incompatible materials

No information available.

# 10.6. Hazardous decomposition products

No known hazardous decomposition products.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

## Acute toxicity

Based on available data, the classification criteria are not met.

## **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	AS No Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >5000 mg/l	Rat		
61789-86-4	6-4 calcium sulfonate				
	oral	LD50 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	) Rat		



according to UK REACH Regulation

### **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 8 of 12

## Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

### Sensitising effects

Based on available data, the classification criteria are not met. Contains calcium sulfonate. May produce an allergic reaction.

## Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

May be fatal if swallowed and enters airways.

## Information on likely routes of exposure

No information available.

# Specific effects in experiment on an animal

No information available.

#### Additional information on tests

No information available.

### **Practical experience**

No information available.

# 11.2. Information on other hazards

## **Endocrine disrupting properties**

Endocrine disrupting potential No information available.

### **Further information**

There are no data available on the preparation/mixture itself.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Based on available data, the classification criteria are not met.

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	OECD 301F	> 60 %	28		
	Readily biodegradable (according to OECD criteria).				

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

# 12.4. Mobility in soil

There are no data available on the mixture itself.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.



according to UK REACH Regulation

# **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 9 of 12

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No information available.

#### **Further information**

There are no data available on the mixture itself.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

### **Disposal recommendations**

Dispose of waste according to applicable legislation.

Do not mix with other wastes.

### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

## Contaminated packaging

Dispose according to legislation.

## **SECTION 14: Transport information**

# Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1139

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

# Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: Coating solution

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



according to UK REACH Regulation

## **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 10 of 12



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

EmS:

No
955

L

Et

E1

En

F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75



according to UK REACH Regulation

## **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 11 of 12

Directive 2004/42/EC on VOC in 48,37 % paints and varnishes: 401,5 g/l

Information according to Directive

2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

### **Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

## **Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

# Changes

This data sheet contains changes from the previous version in section(s): 2,8,9,15,16.

### Abbreviations and acronyms

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method
Asp. Tox. 1; H304	Calculation method

## Relevant H and EUH statements (number and full text)

H226	Flammable	liquid and	vapour.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains calcium sulfonate. May produce an allergic reaction.



according to UK REACH Regulation

## **DINITROL 1000 Airmix**

Revision date: 30.04.2025 Product code: 21639 Page 12 of 12

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)