

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3641 A-80

Revision date: 09.04.2025

Product code: 21652

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking				
1.1. Product identifier DINITROL 3641 A-80				
UFI:	39NA-AM1F-700X-XY33			
1.2. Relevant identified uses of th	e substance or mixture and uses advi	ised against		
Use of the substance/mixture Corrosion inhibitor				
Uses advised against No further relevant informat	ion available.			
1.3. Details of the supplier of the	safety data sheet			
Manufacturer Company name: Street: Place: Telephone: E-mail: Contact person:	DINOL GmbH Pyrmonter Strasse 76 D-32676 Luegde + 49 (0) 5281 982980 msds@dinol.com Labor	Telefax: + 49 (0) 5281 9829860		
Responsible Department:	msds@dinol.com			
Supplier Company name: Street: Place: E-mail: Internet: 1.4. Emergency telephone number:	Leading Solvent Supplies Limited Marston Business Park, Rudgate GB Tockwith, York YO26 7QF enquiries@leading-solvents.co.uk www.leading-solvents.co.uk Giftnotruf Berlin: +49 30 30686 70			
SECTION 2: Hazards identifica	ition			

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Signal word:

Pictograms:



Hazard statements H226

Flammable liquid and vapour.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

DINITROL 3641 A-80 Revision date: 09.04.2025 Product code: 21652 Page 2 of 11 water or shower. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Special labelling of certain mixtures EUH208 Contains calcium sulfonate. May produce an allergic reaction. Restricted to professional users. Labelling of packages where the contents do not exceed 125 ml Signal word: Warning Pictograms:

2.3. Other hazards

Hydrocarbons : This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP. (< 0,1 % Benzene)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)		
64742-65-0	Distillates (petroleum), solvent-dew	/axed heavy paraffinic; Baseoil - unsp	pecified	45 - < 50 %
	265-169-7		01-2119471299-27	
	Asp. Tox. 1; H304			
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha			15 - < 20 %
	265-150-3		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox	. 1; H226 H336 H304		
61789-86-4	calcium sulfonate			1 - < 5 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
64742-48-9	265-150-3	Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	15 - < 20 %
	inhalation: LC50 = > 10 mg/l (vapours); dermal: LD50 = > 3000 mg/kg; oral: LD50 = > 5000 mg/kg		
61789-86-4	263-093-9	calcium sulfonate	1 - < 5 %
dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5000 mg/kg_Skin Sens. 1B; H317: >= 10 - 100			

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures



Safety Data Sheet

according to UK REACH Regulation

DINITROL 3641 A-80

Revision date: 09.04.2025

Product code: 21652

Page 3 of 11

General information

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately. Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder. Water spray jet alcohol resistant foam.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up



Safety Data Sheet

according to UK REACH Regulation

DINITROL 3641 A-80

Revision date: 09.04.2025

Product code: 21652

Page 4 of 11

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly. Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals. Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No special measures are necessary.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place.

maximum storage temperature : < 30 °C minimum storage temperature : > 5 °C

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1317-65-3	Calcium carbonate, inhalable dust	-	10		TWA (8 h)	WEL



DINITROL 3641 A-80

Revision date: 09.04.2025

Product code: 21652

Page 5 of 11

DNEL/DMEL values

CAS No	Substance			-
DNEL type		Exposure route	Effect	Value
61789-86-4	calcium sulfonate			
Worker DNEL,	long-term	dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm ²
Consumer DN	EL, long-term	inhalation	systemic	2,9 mg/m³
Consumer DN	EL, long-term	dermal	systemic	1,667 mg/kg bw/day
Consumer DN	EL, long-term	dermal	local	0,513 mg/cm ²
Consumer DN	EL, long-term	oral	systemic	0,8333 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	11,75 mg/m³

PNEC values

CAS No	Substance			
Environmenta	Environmental compartment Value			
61789-86-4	calcium sulfonate			
Freshwater		1 mg/l		
Marine water		1 mg/l		
Freshwater sediment 226000		226000000 mg/kg		
Marine sediment		226000000 mg/kg		
Secondary poisoning 1		16667 mg/kg		
Micro-organisms in sewage treatment plants (STP)		1000 mg/l		
Soil		271000000 mg/kg		

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

Thickness of the glove material : > 0,12 mm

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

DINOL

Safety Data Sheet

according to UK REACH Regulation

DINITROL 3641 A-80

Revision date: 09.04.2025

Product code: 21652

Page 6 of 11

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1. Information on basic physical an Physical state:	Liquid		
Colour:	light brown		
Odour:	characteristic		
Odour threshold:	not determined		
			Test method
Melting point/freezing point:		not determined	rest method
Boiling point or initial boiling point a	nd	150 °C	
boiling range:		150 C	
Flammability:		not determined	
Lower explosion limits:		0,6 vol. %	
Upper explosion limits:		6,5 vol. %	
Flash point:			DIN EN ISO 2719
Auto-ignition temperature:		42 C 230 °C	DIN EN 130 27 19
Decomposition temperature:		not determined	
pH-Value:		not determined	
Viscosity / kinematic:		not determined	
•			
Water solubility:		Immiscible	
Solubility in other solvents			
not determined Partition coefficient n-octanol/water		not determined	
Vapour pressure:		1,0 hPa	
(at 20 °C)		1,0 III a	
Density (at 20 °C):		1,04 - 1,08 g/cm³	DIN 51757
Relative vapour density:		not determined	2
Particle characteristics:		not applicable	
9.2. Other information			
	al barand alasasa		
Information with regard to physic Explosive properties	ai nazaro classes		
not determined			
Sustained combustibility:		No data available	
Oxidizing properties			
not determined			
Other safety characteristics			
Solvent content:		19,1 %	
Solid content:		78 - 82 %	
Softening point:		not determined	
Viscosity / dynamic:		not determined	
Flow time:		60 - 70 s	4 DIN EN ISO 2431
(at 23 °C)			
Further Information			

DINITROL 3641 A-80

Revision date: 09.04.2025

Product code: 21652

Page 7 of 11

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

Based on available data, the classification criteria are not met.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha					
	oral	LD50 mg/kg	> 5000	Rat		
	dermal	LD50 mg/kg	> 3000	Rabbit		
	inhalation (4 h) vapour	LC50	> 10 mg/l	Rat		
61789-86-4	calcium sulfonate					
	oral	LD50 mg/kg	5000	Rat		
	dermal	LD50 mg/kg	> 2000	Rat		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met. Contains calcium sulfonate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

DINITROL 3641 A-80 Product code: 21652

Revision date: 09.04.2025

Page 8 of 11

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

Based on available data, the classification criteria are not met.

Additional information on tests

Based on available data, the classification criteria are not met.

Practical experience

No further relevant information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Other information

No further relevant information available.

Further information

No further relevant information available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No further relevant information available.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of Wastes Code - residues/unused products



DINITROL 3641 A-80

Revision date: 09.04.2025

Product code: 21652

Page 9 of 11

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label:	UN 1139 COATING SOLUTION 3 III 3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
<u>14.1. UN number or ID number:</u>	UN 1139
14.2. UN proper shipping name:	Coating solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 1139
14.2. UN proper shipping name:	Coating solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	Ш
Hazard label:	3
Marine pollutant:	no
Special Provisions:	955



Revision date: 09.04.2025	DINITROL 3 Product coo		Page 10 of 11	
Limited quantity:	5 L		r ugo ro or rr	
Excepted quantity:	E1			
EmS:	F-E, S-E			
Air transport (ICAO-TI/IATA-DGR)				
<u>14.1. UN number or ID number:</u> 14.2. UN proper shipping name:	UN 1139 Coating solution			
14.3. Transport hazard class(es):	3			
14.4. Packing group:	 -			
Hazard label:	3			
Special Provisions:	A3			
Limited quantity Passenger:	10 L			
Passenger LQ: Excepted quantity:	Y344 E1			
IATA-packing instructions - Passenger:		355		
IATA-max. quantity - Passenger:		60 L		
IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:		366 220 L		
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	No			
14.6. Special precautions for user				
Warning: Flammable liquids				
14.7. Maritime transport in bulk according to not applicable	o IMO instruments			
SECTION 15: Regulatory information				
15.1. Safety, health and environmental regu	lations/legislation spec	cific for the substance or mixture		
EU regulatory information				
Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40				
Directive 2004/42/EC on VOC in	19,11 %			
paints and varnishes: Information according to Directive	208,3 g/l			
2012/18/EU (SEVESO III):	P5c FLAMMABLE LI	20105		
Additional information				
Observe in addition any national regula Directive 98/24/EC of 7 April 1998 on t chemical agents at work		Ith and safety of workers from the risks related to	1	
National regulatory information				
Employment restrictions:	Observe restrictions t	o employment for juveniles according to the 'juve	nile	
	under the Maternity F	line' (94/33/EC). Observe employment restriction Protection Directive (92/85/EEC) for expectant or	S	
Water hazard class (D):	nursing mothers. 1 - slightly hazardous	to water		
Additional information				
This mixture contains the following sub Candidate List according to Article 59 (ncern (SVHC) which are included in the		

Candidate List according to Article 59 of REACH: none

DINOL GmbH

DINITROL 3641 A-80

Revision date: 09.04.2025

Product code: 21652

Page 11 of 11

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,8,9,16.

Abbreviations and acronyms

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard Skin Sens: Skin sensitisation STOT SE: Specific target organ toxicity - single exposure ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
EUH208	Contains calcium sulfonate. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)