

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

DINITROL 425 UV White

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives, sealants

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980
E-mail: msds@dinol.com
Contact person: Labor
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

Supplier

Company name: Leading Solvent Supplies Limited
Street: Marston Business Park, Rudgate
Place: GB Tockwith, York YO26 7QF
E-mail: enquiries@leading-solvents.co.uk
Internet: www.leading-solvents.co.uk

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements**GB CLP Regulation****Special labelling of certain mixtures**

EUH204 Contains isocyanates. May produce an allergic reaction.
EUH210 Safety data sheet available on request.
EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Restricted to professional users.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 2 of 12

Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|------------|--|--------------|------------------|-----------------|
| | EC No | Index No | REACH No | |
| | Classification (GB CLP Regulation) | | | |
| | reaction mass of ethylbenzene and xylene | | | 1 - < 10 % |
| | 905-588-0 | | 01-2119488216-32 | |
| | Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304 | | | |
| 13463-67-7 | titanium dioxide | | | 1 - < 10 % |
| | 236-675-5 | 022-006-00-2 | 01-2119489379-17 | |
| | Carc. 2; H351 | | | |
| 101-68-8 | diphenylmethane-4,4'-diisocyanate | | | 0,025 - < 0,1 % |
| | 202-966-0 | 615-005-00-9 | 01-2119457014-47 | |
| | Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373 | | | |
| 26471-62-5 | 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate | | | 0,025 - < 0,1 % |
| | 247-722-4 | 615-006-00-4 | 01-2119454791-34 | |
| | Carc. 2, Acute Tox. 1, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, Aquatic Chronic 3; H351 H330 H315 H319 H334 H317 H335 H412 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|------------|-----------|---|-----------------|
| | | Specific Conc. Limits, M-factors and ATE | |
| | 905-588-0 | reaction mass of ethylbenzene and xylene | 1 - < 10 % |
| | | inhalation: LC50 = 20 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4300 mg/kg | |
| 101-68-8 | 202-966-0 | diphenylmethane-4,4'-diisocyanate | 0,025 - < 0,1 % |
| | | inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >9400 mg/kg; oral: LD50 = >2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100 | |
| 26471-62-5 | 247-722-4 | 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate | 0,025 - < 0,1 % |
| | | inhalation: ATE = 0,05 mg/l (vapours); inhalation: ATE = 0,005 mg/l (dusts or mists); dermal: LD50 = > 12200 mg/kg Resp. Sens. 1; H334: >= 0,1 - 100 | |

Further Information

The homogeneous mixing of this product is controlled by continuous physical tests. Formerly dusty raw materials are completely integrated into the liquid/pasty mass. Possible AGW-values for solid substances are therefore not given, as there is no longer any risk of inhalation of these substances (when handling this mixture).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 3 of 12

After contact with skin

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleansing agent and water. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Do NOT induce vomiting.
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Hydrogen chloride (HCl), Nitrogen oxides (NO_x), Sulphur oxides, Carbon monoxide

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.
Wear personal protection equipment.
Avoid contact with skin, eyes and clothes.
Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 4 of 12

For cleaning up

Provide adequate ventilation.
Clear contaminated areas thoroughly.
Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air. Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
When using do not eat or drink.
Wash hands before breaks and after work.
Avoid contact with skin and eyes.
Remove contaminated, saturated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Protect from moisture.

Hints on joint storage

Store away from foodstuffs.

Further information on storage conditions

Keep container tightly closed and dry. Keep in a cool, well-ventilated place.
Protect against: Frost, Heat, UV-radiation/sunlight.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|------------|---|-----|-------------------|-----------|---------------|--------|
| - | Isocyanates, all (as -NCO) Except methyl isocyanate | - | 0.02 | | TWA (8 h) | WEL |
| | | - | 0.07 | | STEL (15 min) | WEL |
| 13463-67-7 | Titanium dioxide, total inhalable | - | 10 | | TWA (8 h) | WEL |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 5 of 12

DNEL/DMEL values

| CAS No | Substance | | | |
|--------------------------|--|----------------|----------|------------------|
| DNEL type | | Exposure route | Effect | Value |
| | reaction mass of ethylbenzene and xylene | | | |
| Worker DNEL, long-term | | inhalation | systemic | 211 mg/m³ |
| Worker DNEL, long-term | | inhalation | local | 221 mg/m³ |
| Worker DNEL, acute | | inhalation | systemic | 442 mg/m³ |
| Worker DNEL, long-term | | dermal | systemic | 180 mg/kg bw/day |
| Worker DNEL, acute | | inhalation | local | 289 mg/m³ |
| Consumer DNEL, long-term | | oral | systemic | 1,6 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 14,8 mg/m³ |
| Consumer DNEL, long-term | | inhalation | local | 65,3 mg/m³ |
| Consumer DNEL, acute | | inhalation | systemic | 260 mg/m³ |
| Consumer DNEL, acute | | inhalation | local | 260 mg/m³ |
| 101-68-8 | diphenylmethane-4,4'-diisocyanate | | | |
| Worker DNEL, long-term | | inhalation | local | 0,05 mg/m³ |
| Worker DNEL, acute | | inhalation | local | 0,10 mg/m³ |
| Consumer DNEL, long-term | | inhalation | local | 0,025 mg/m³ |
| Consumer DNEL, acute | | inhalation | local | 0,05 mg/m³ |
| 26471-62-5 | 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate | | | |
| Worker DNEL, long-term | | inhalation | local | 0,035 mg/m³ |
| Worker DNEL, acute | | inhalation | local | 0,14 mg/m³ |
| Worker DNEL, long-term | | inhalation | systemic | 0,035 mg/m³ |
| Worker DNEL, acute | | inhalation | systemic | 0,14 mg/m³ |

PNEC values

| CAS No | Substance | |
|--|--|--|
| Environmental compartment | Value | |
| | reaction mass of ethylbenzene and xylene | |
| Freshwater | 0,327 mg/l | |
| Marine water | 0,327 mg/l | |
| Freshwater sediment | 12,64 mg/kg | |
| Marine sediment | 12,64 mg/kg | |
| Soil | 2,31 mg/kg | |
| 101-68-8 | diphenylmethane-4,4'-diisocyanate | |
| Freshwater | 1,0 mg/l | |
| Marine water | 0,1 mg/l | |
| Micro-organisms in sewage treatment plants (STP) | 1,0 mg/l | |
| Soil | 1,0 mg/kg | |
| 26471-62-5 | 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate | |
| Freshwater | 0,0125 mg/l | |
| Marine water | 0,00125 mg/l | |
| Micro-organisms in sewage treatment plants (STP) | 1 mg/l | |
| Soil | 1 mg/kg | |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 6 of 12

8.2. Exposure controls



Appropriate engineering controls

The usual precautionary measures are to be adhered to when handling chemicals.
Provide adequate ventilation. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):
FKM (fluoro rubber) - (0,7mm), Breakthrough time:: 240 min.
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
Protective gloves have to be replaced at the first sign of deterioration.
Protect skin by using skin protective cream.

Skin protection

Protective clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
short-term :
gas filtering equipment (EN 141)., Filter material/medium: A2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | | |
|---|--|------------------------|
| Physical state: | Paste | |
| Colour: | white | |
| Odour: | like: Solvent | |
| Odour threshold: | not determined | |
| Melting point/freezing point: | | not determined |
| Boiling point or initial boiling point and boiling range: | | not determined |
| Flammability: | | not applicable |
| Lower explosion limits: | | not determined |
| Upper explosion limits: | | not determined |
| Flash point: | | not applicable |
| Auto-ignition temperature: | | not self-igniting |
| Decomposition temperature: | | not determined |
| pH-Value: | | not determined |
| Water solubility: | The study does not need to be conducted because the substance is known to be insoluble in water. | |
| Solubility in other solvents | | |
| not determined | | |
| Partition coefficient n-octanol/water: | | not determined |
| Vapour pressure: | | not determined |
| Density (at 20 °C): | | 1,37 g/cm ³ |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 7 of 12

Relative vapour density:

not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not determined

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Other safety characteristics

Evaporation rate:

not determined

Solvent content:

6,00 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product has not been tested.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with : Alcohol, Amines, Acid, alkali

After contact with water: Formation of: Methanol, Carbon dioxide.

Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Protect from moisture.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Possible in traces: Isocyanates.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 12,5 mg/l

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 8 of 12

| CAS No | Chemical name | | | | |
|------------|--|--------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| | reaction mass of ethylbenzene and xylene | | | | |
| | oral | LD50 4300 mg/kg | Rat | | |
| | dermal | LD50 > 2000 mg/kg | Rabbit | | |
| | inhalation (4 h) vapour | LC50 20 mg/l | Rat | | |
| | inhalation dust/mist | ATE 1,5 mg/l | | | |
| 101-68-8 | diphenylmethane-4,4'-diisocyanate | | | | |
| | oral | LD50 >2000 mg/kg | Rat | | |
| | dermal | LD50 >9400 mg/kg | Rabbit | | |
| | inhalation vapour | ATE 11 mg/l | | | |
| | inhalation dust/mist | ATE 1,5 mg/l | | | |
| 26471-62-5 | 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate | | | | |
| | dermal | LD50 > 12200 mg/kg | Rabbit | | |
| | inhalation vapour | ATE 0,05 mg/l | | | |
| | inhalation dust/mist | ATE 0,005 mg/l | | | |

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains isocyanates. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 9 of 12

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | | |
|------------|--|--------------------|-----------|-------------------------------------|--------|--------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 101-68-8 | diphenylmethane-4,4'-diisocyanate | | | | | |
| | Acute fish toxicity | LC50 >1000 mg/l | 96 h | Danio rerio (zebrafish) | | |
| | Acute algae toxicity | ErC50 >1640 mg/l | 72 h | Scenedesmus subspicatus | | |
| | Crustacea toxicity | NOEC >10 mg/l | 21 d | Daphnia magna (Big water flea) | | |
| | Acute bacteria toxicity | EC50 >100 mg/l () | 3 h | Activated sludge | | |
| 26471-62-5 | 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate | | | | | |
| | Acute fish toxicity | LC50 133 mg/l | 96 h | Oncorhynchus mykiss (Rainbow trout) | | |
| | Acute algae toxicity | ErC50 4300 mg/l | 96 h | Chlorella vulgaris | | |
| | Acute bacteria toxicity | EC50 >100 mg/l () | 3 h | Activated sludge | | |

12.2. Persistence and degradability

There are no data available on the mixture itself.

| CAS No | Chemical name | | | |
|----------|--|-------|----|--------|
| | Method | Value | d | Source |
| | Evaluation | | | |
| 101-68-8 | diphenylmethane-4,4'-diisocyanate | | | |
| | OECD 302C | 0% | 28 | |
| | Not readily biodegradable (according to OECD criteria) | | | |

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

BCF

| CAS No | Chemical name | BCF | Species | Source |
|----------|-----------------------------------|-----|-------------------------------|--------|
| 101-68-8 | diphenylmethane-4,4'-diisocyanate | 200 | Cyprinus carpio (Common Carp) | |

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 10 of 12

Further information

There are no data available on the preparation/mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.
List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|--|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Marine transport (IMDG)

| | |
|--|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Marine pollutant: no

Air transport (ICAO-TI/IATA-DGR)

| | |
|--|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

Other applicable information

Fire test in accordance with 33.2.1.4 "Manual of test and criteria" (recommendations on the TRANSPORT OF DANGEROUS GOODS [United Nations]): burn rate: $\leq 2, 2 \text{ mm / s}$ (no hazardous goods according to class 4.1 [ADR])

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 11 of 12

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 52, Entry 75

| | |
|------------------------------------|--|
| Directive 2004/42/EC on VOC in | 6,67 % |
| paints and varnishes: | 91,38 g/l |
| Subcategory according to Directive | Bodyfiller/stopper - All types, VOC limit value: 250 g/l |
| 2004/42/EC: | |

| | |
|------------------------------------|--|
| Information according to Directive | Not subject to 2012/18/EU (SEVESO III) |
| 2012/18/EU (SEVESO III): | |

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

| | |
|--------------------------|---|
| Employment restrictions: | Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. |
|--------------------------|---|

| | |
|-------------------------|----------------------------------|
| Water hazard class (D): | 2 - obviously hazardous to water |
|-------------------------|----------------------------------|

Additional information

The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,15.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 425 UV White

Revision date: 21.01.2025

Product code: 80030

Page 12 of 12

Abbreviations and acronyms

Flam. Liq: Flammable liquids
 Acute Tox: Acute toxicity
 Asp. Tox: Aspiration hazard
 Skin Irrit: Skin irritation
 Eye Irrit: Eye irritation
 Resp. Sens: Respiratory sensitisation
 Skin Sens: Skin sensitisation
 Carc: Carcinogenicity
 STOT SE: Specific target organ toxicity - single exposure
 STOT RE: Specific target organ toxicity - repeated exposure
 Aquatic Chronic: Chronic aquatic hazard
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

| | |
|--------|--|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH204 | Contains isocyanates. May produce an allergic reaction. |
| EUH210 | Safety data sheet available on request. |
| EUH212 | Warning! Hazardous respirable dust may be formed when used. Do not breathe dust. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)