

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 442 black

UFI: Q55F-20A4-E00P-CJ80

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

1.3. Details of the supplier of the safety data sheet

Manufacturer

| | | |
|-------------------------|----------------------|--------------------------------|
| Company name: | DINOL GmbH | |
| Street: | Pyrmonter Strasse 76 | |
| Place: | D-32676 Luegde | |
| Telephone: | + 49 (0) 5281 982980 | Telefax: + 49 (0) 5281 9829860 |
| E-mail: | msds@dinol.com | |
| Contact person: | Labor | |
| Responsible Department: | msds@dinol.com | |

Supplier

| | |
|---------------|----------------------------------|
| Company name: | Leading Solvent Supplies Limited |
| Street: | Marston Business Park, Rudgate |
| Place: | GB Tockwith, York YO26 7QF |
| E-mail: | enquiries@leading-solvents.co.uk |
| Internet: | www.leading-solvents.co.uk |

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226
 Skin Irrit. 2; H315
 Eye Irrit. 2; H319
 Skin Sens. 1; H317
 STOT SE 3; H335
 STOT RE 2; H373
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

xylene
 Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
 Fatty acids, C18-unsatd. , trimers, compds. with oleylamine
 Fatty acids, tall-oil, compds. with oleylamine
 Cobalt bis(2-ethylhexanoate)

Signal word: Warning

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 2 of 18

Pictograms:



Hazard statements

| | |
|------|--------------------------------------------------------------------|
| H226 | Flammable liquid and vapour. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H412 | Harmful to aquatic life with long lasting effects. |

Precautionary statements

| | |
|-----------|------------------------------------------------------------------------------------------------|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |
| P370+P378 | In case of fire: Use water to extinguish. |
| P403+P235 | Store in a well-ventilated place. Keep cool. |

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



Hazard statements

H317-H412

Precautionary statements

P280

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 3 of 18

Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|------------------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (GB CLP Regulation) | | | |
| | reaction mass of ethylbenzene and xylene | | | 20 - < 25 % |
| | 905-588-0 | | 01-2119488216-32 | |
| | Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304 | | | |
| 123-86-4 | n-butyl acetate | | | 5 - < 10 % |
| | 204-658-1 | 607-025-00-1 | 01-2119485493-29 | |
| | Flam. Liq. 3, STOT SE 3; H226 H336 EUH066 | | | |
| | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | | | 5 - < 10 % |
| | 919-446-0 | | 01-2119458049-33 | |
| | Flam. Liq. 3, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H372 H304 H411 EUH066 | | | |
| 1330-20-7 | xylene | | | 1 - < 5 % |
| | 215-535-7 | 601-022-00-9 | 01-2119488216-32 | |
| | Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412 | | | |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | 1 - < 5 % |
| | 919-857-5 | | 01-2119463258-33 | |
| | Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066 | | | |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | | | 1 - < 5 % |
| | 203-603-9 | 607-195-00-7 | 01-2119475791-29 | |
| | Flam. Liq. 3, STOT SE 3; H226 H336 | | | |
| 100-41-4 | ethylbenzene | | | 1 - < 5 % |
| | 202-849-4 | 601-023-00-4 | 01-2119489370-35 | |
| | Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304 | | | |
| | Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | | | 1 - < 5 % |
| | 918-668-5 | | 01-2119455851-35 | |
| | Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 | | | |
| 147900-93-4 | Fatty acids, C18-unsatd., trimers, compds. with oleylamine | | | < 1 % |
| | | | 01-2119971821-33 | |
| | Acute Tox. 4, Skin Sens. 1, STOT RE 2, Aquatic Chronic 2; H302 H317 H373 H411 | | | |
| 85711-55-3 | Fatty acids, tall-oil, compds. with oleylamine | | | < 1 % |
| | 288-315-1 | | 01-2119974148-28 | |
| | Eye Dam. 1, Skin Sens. 1A, STOT RE 2; H318 H317 H373 | | | |
| 136-52-7 | Cobalt bis(2-ethylhexanoate) | | | < 0.1 % |
| | 205-250-6 | | 01-2119524678-29 | |
| | Repr. 2, Eye Irrit. 2, Skin Sens. 1A, Aquatic Chronic 3; H361f H319 H317 H412 | | | |

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 4 of 18

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|-------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| | | Specific Conc. Limits, M-factors and ATE | |
| | 905-588-0 | reaction mass of ethylbenzene and xylene | 20 - < 25 % |
| | | inhalation: LC50 = 20 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4300 mg/kg | |
| 123-86-4 | 204-658-1 | n-butyl acetate | 5 - < 10 % |
| | | inhalation: LC50 = > 21 mg/l (vapours); inhalation: LC50 = >21 mg/l (dusts or mists); dermal: LD50 = > 14112 mg/kg; oral: LD50 = 10760 mg/kg | |
| | 919-446-0 | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | 5 - < 10 % |
| | | dermal: LD50 = >3400 mg/kg; oral: LD50 = >15000 mg/kg | |
| 1330-20-7 | 215-535-7 | xylene | 1 - < 5 % |
| | | inhalation: LC50 = 10-20 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 8700 mg/kg | |
| | 919-857-5 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | 1 - < 5 % |
| | | inhalation: LC50 = 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg | |
| 108-65-6 | 203-603-9 | 2-methoxy-1-methylethyl acetate | 1 - < 5 % |
| | | inhalation: LC50 = 35,7 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = 8500 mg/kg | |
| 100-41-4 | 202-849-4 | ethylbenzene | 1 - < 5 % |
| | | inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg | |
| | 918-668-5 | Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | 1 - < 5 % |
| | | inhalation: LC50 = >6193 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = 3492 mg/kg | |
| 147900-93-4 | | Fatty acids, C18-unsatd. , trimers, compds. with oleylamine | < 1 % |
| | | oral: LD50 = > 1570 mg/kg | |
| 85711-55-3 | 288-315-1 | Fatty acids, tall-oil, compds. with oleylamine | < 1 % |
| | | oral: LD50 = > 2000 mg/kg | |
| 136-52-7 | 205-250-6 | Cobalt bis(2-ethylhexanoate) | < 0.1 % |
| | | dermal: LD50 = >2000 mg/kg; oral: LD50 = 3129 mg/kg | |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious but breathing normally, place in recovery position and seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

Wash with plenty of water/Soap.

If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 5 of 18

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 6 of 18

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Do not store together with: Oxidizing agents. Strong acid, strong alkalis

7.3. Specific end use(s)

Anti-corrosive coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|------------|-------------------------|-----|-------------------|-----------|---------------|--------|
| 108-65-6 | 1-Methoxypropyl acetate | 50 | 274 | | TWA (8 h) | WEL |
| | | 100 | 548 | | STEL (15 min) | WEL |
| 123-86-4 | Butyl acetate | 150 | 724 | | TWA (8 h) | WEL |
| | | 200 | 966 | | STEL (15 min) | WEL |
| 100-41-4 | Ethylbenzene | 100 | 441 | | TWA (8 h) | WEL |
| | | 125 | 552 | | STEL (15 min) | WEL |
| 14807-96-6 | Talc respirable dust | - | 1 | | TWA (8 h) | WEL |
| 1330-20-7 | Xylene: mixed isomers | 50 | 220 | | TWA (8 h) | WEL |
| | | 100 | 441 | | STEL (15 min) | WEL |

Biological Monitoring Guidance Values (EH40)

| CAS No | Substance | Parameter | Value | Test material | Sampling time |
|-----------|-------------------------------------|-----------------------------------|--------------|---------------|---------------|
| 1330-20-7 | Xylene, o-, m-, p- or mixed isomers | methyl hippuric acid (creatinine) | 650 mmol/mol | urine | Post shift |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 7 of 18

DNEL/DMEL values

| CAS No | Substance | | | |
|--------------------------|-------------------------------------------------------------------------|----------------|----------|------------------|
| DNEL type | | Exposure route | Effect | Value |
| | reaction mass of ethylbenzene and xylene | | | |
| Worker DNEL, long-term | | inhalation | systemic | 211 mg/m³ |
| Worker DNEL, long-term | | inhalation | local | 221 mg/m³ |
| Worker DNEL, acute | | inhalation | systemic | 442 mg/m³ |
| Worker DNEL, long-term | | dermal | systemic | 180 mg/kg bw/day |
| Worker DNEL, acute | | inhalation | local | 289 mg/m³ |
| Consumer DNEL, long-term | | oral | systemic | 1,6 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 14,8 mg/m³ |
| Consumer DNEL, long-term | | inhalation | local | 65,3 mg/m³ |
| Consumer DNEL, acute | | inhalation | systemic | 260 mg/m³ |
| Consumer DNEL, acute | | inhalation | local | 260 mg/m³ |
| 123-86-4 | n-butyl acetate | | | |
| Worker DNEL, long-term | | inhalation | systemic | 48 mg/m³ |
| Worker DNEL, acute | | inhalation | systemic | 600 mg/m³ |
| Worker DNEL, long-term | | inhalation | local | 300 mg/m³ |
| Worker DNEL, acute | | inhalation | local | 600 mg/m³ |
| Consumer DNEL, long-term | | inhalation | systemic | 12 mg/m³ |
| Consumer DNEL, acute | | inhalation | systemic | 300 mg/m³ |
| Consumer DNEL, long-term | | inhalation | local | 35,7 mg/m³ |
| Consumer DNEL, acute | | inhalation | local | 300 mg/m³ |
| | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | | | |
| Worker DNEL, long-term | | inhalation | systemic | 330 mg/m³ |
| Worker DNEL, long-term | | dermal | systemic | 44 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 71 mg/m³ |
| Consumer DNEL, long-term | | dermal | systemic | 26 mg/kg bw/day |
| Consumer DNEL, long-term | | oral | systemic | 26 mg/kg bw/day |
| 1330-20-7 | xylene | | | |
| Consumer DNEL, long-term | | oral | systemic | 1,6 mg/kg bw/day |
| Worker DNEL, long-term | | dermal | systemic | 180 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | systemic | 108 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 77 mg/m³ |
| Consumer DNEL, long-term | | inhalation | systemic | 14,8 mg/m³ |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | |
| Consumer DNEL, long-term | | oral | systemic | 125 mg/kg bw/day |
| Worker DNEL, long-term | | dermal | systemic | 208 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | systemic | 125 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 871 mg/m³ |
| Consumer DNEL, long-term | | inhalation | systemic | 185 mg/m³ |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | | | |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 8 of 18

| | | | |
|--------------------------|-----------------------------------------------------------------------------------|----------|-----------------------|
| Worker DNEL, long-term | dermal | systemic | 153,5 mg/kg bw/day |
| Worker DNEL, acute | inhalation | local | 550 mg/m ³ |
| Worker DNEL, long-term | inhalation | systemic | 275 mg/m ³ |
| 100-41-4 | ethylbenzene | | |
| Worker DNEL, long-term | inhalation | systemic | 77 mg/m ³ |
| Worker DNEL, acute | inhalation | local | 293 mg/m ³ |
| Worker DNEL, long-term | dermal | systemic | 180 mg/kg bw/day |
| Consumer DNEL, long-term | inhalation | systemic | 15 mg/m ³ |
| Consumer DNEL, long-term | oral | systemic | 1,6 mg/kg bw/day |
| , | | | |
| | Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | | |
| Consumer DNEL, long-term | oral | systemic | 11 mg/kg bw/day |
| Worker DNEL, long-term | dermal | systemic | 25 mg/kg bw/day |
| Consumer DNEL, long-term | dermal | systemic | 11 mg/kg bw/day |
| Worker DNEL, long-term | inhalation | systemic | 150 mg/m ³ |
| Consumer DNEL, long-term | inhalation | systemic | 32 mg/m ³ |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 9 of 18

PNEC values

| CAS No | Substance | |
|---------------------------|--------------------------------------------------|--------------|
| Environmental compartment | | Value |
| | reaction mass of ethylbenzene and xylene | |
| | Freshwater | 0,327 mg/l |
| | Marine water | 0,327 mg/l |
| | Freshwater sediment | 12,64 mg/kg |
| | Marine sediment | 12,64 mg/kg |
| | Soil | 2,31 mg/kg |
| 123-86-4 | n-butyl acetate | |
| | Freshwater | 0,18 mg/l |
| | Marine water | 0,018 mg/l |
| | Freshwater sediment | 0,981 mg/kg |
| | Marine sediment | 0,0981 mg/kg |
| | Micro-organisms in sewage treatment plants (STP) | 35,6 mg/l |
| | Soil | 0,0903 mg/kg |
| 1330-20-7 | xylene | |
| | Freshwater | 0,327 mg/l |
| | Marine water | 0,327 mg/l |
| | Freshwater sediment | 12,46 mg/kg |
| | Marine sediment | 12,46 mg/kg |
| | Micro-organisms in sewage treatment plants (STP) | 6,58 mg/l |
| | Soil | 2,31 mg/kg |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | |
| | Freshwater | 0,635 mg/l |
| | Marine water | 0,0635 mg/l |
| | Freshwater sediment | 3,29 mg/kg |
| | Marine sediment | 0,329 mg/kg |
| | Micro-organisms in sewage treatment plants (STP) | 100 mg/l |
| | Soil | 0,29 mg/kg |
| 100-41-4 | ethylbenzene | |
| | Freshwater | 0,1 mg/l |
| | Marine water | 0,01 mg/l |
| | Freshwater sediment | 13,7 mg/kg |
| | Marine sediment | 1,37 mg/kg |
| | Secondary poisoning | 0,02 mg/kg |
| | Micro-organisms in sewage treatment plants (STP) | 9,6 mg/l |
| | Soil | 2,68 mg/kg |

8.2. Exposure controls



Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 10 of 18

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber) Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: A/P2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | | |
|-----------------------------------------------------------|--------------------------------------------------------------------------------------------------|-----------------|
| Physical state: | Liquid | |
| Colour: | black | |
| Odour: | characteristic | |
| Odour threshold: | not determined | |
| Melting point/freezing point: | | not determined |
| Boiling point or initial boiling point and boiling range: | | 124 °C |
| Flammability: | | not applicable |
| Lower explosion limits: | | 1,0 vol. % |
| Upper explosion limits: | | 7,0 vol. % |
| Flash point: | | 24 °C |
| Auto-ignition temperature: | | 210 °C |
| Decomposition temperature: | | not determined |
| pH-Value: | | not applicable |
| Viscosity / kinematic: | | not determined |
| Water solubility: | The study does not need to be conducted because the substance is known to be insoluble in water. | |
| Solubility in other solvents | not determined | |
| Partition coefficient n-octanol/water: | | not determined |
| Vapour pressure: | | 6,0 hPa |
| (at 20 °C) | | |
| Density (at 20 °C): | | 1,16-1,20 g/cm³ |
| Relative vapour density: | | not determined |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 11 of 18

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not determined

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

44,6 %

Solid content:

53-57 %

Sublimation point:

not determined

Softening point:

not determined

Pour point:

not determined

Viscosity / dynamic:

1800-2500 mPa·s

(at 20 °C)

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 12 of 18

| CAS No | Chemical name | | | | |
|-----------|-----------------------------------------------------------------------------------|--------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| | reaction mass of ethylbenzene and xylene | | | | |
| | oral | LD50 4300 mg/kg | Rat | | |
| | dermal | LD50 > 2000 mg/kg | Rabbit | | |
| | inhalation (4 h) vapour | LC50 20 mg/l | Rat | | |
| | inhalation dust/mist | ATE 1,5 mg/l | | | |
| 123-86-4 | n-butyl acetate | | | | |
| | oral | LD50 10760 mg/kg | Rat | | |
| | dermal | LD50 > 14112 mg/kg | Rabbit | | |
| | inhalation vapour | LC50 > 21 mg/l | Rat | | |
| | inhalation (4 h) dust/mist | LC50 >21 mg/l | Rat | | |
| | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | | | | |
| | oral | LD50 >15000 mg/kg | Rat | | |
| | dermal | LD50 >3400 mg/kg | Rat | | |
| 1330-20-7 | xylene | | | | |
| | oral | LD50 8700 mg/kg | Rat | | |
| | dermal | LD50 2000 mg/kg | Rabbit | | |
| | inhalation (4 h) vapour | LC50 10-20 mg/l | Rat | | |
| | inhalation dust/mist | ATE 1,5 mg/l | | | |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | |
| | oral | LD50 > 5000 mg/kg | Rat | | |
| | dermal | LD50 > 5000 mg/kg | Rabbit | | |
| | inhalation (4 h) vapour | LC50 5000 mg/l | Rat | | |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | | | | |
| | oral | LD50 8500 mg/kg | Rat | | |
| | dermal | LD50 >5000 mg/kg | Rabbit | | |
| | inhalation (4 h) vapour | LC50 35,7 mg/l | Rat | | |
| 100-41-4 | ethylbenzene | | | | |
| | oral | LD50 3500 mg/kg | Rat | GESTIS | |
| | dermal | LD50 15400 mg/kg | Rabbit | GESTIS | |
| | inhalation (4 h) vapour | LC50 17,2 mg/l | Rat | | |
| | inhalation dust/mist | ATE 1,5 mg/l | | | |
| | Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | | | | |

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 13 of 18

| | | | | | | |
|-------------|------------------------------------------------------------|---------------|--------|--------|--|--|
| | oral | LD50 mg/kg | 3492 | Rat | | |
| | dermal | LD50 mg/kg | >3160 | Rabbit | | |
| | inhalation vapour | LC50 mg/l | >6193 | Rat | | |
| 147900-93-4 | Fatty acids,C18-unsatd. , trimers, compds. with oleylamine | | | | | |
| | oral | LD50 mg/kg | > 1570 | Rat | | |
| 85711-55-3 | Fatty acids, tall-oil, compds. with oleylamine | | | | | |
| | oral | LD50 mg/kg | > 2000 | Rat | | |
| 136-52-7 | Cobalt bis(2-ethylhexanoate) | | | | | |
| | oral | LD50 mg/kg | 3129 | Rat | | |
| | dermal | LD50 mg/kg | >2000 | Rat | | |

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Fatty acids,C18-unsatd. , trimers, compds. with oleylamine; Fatty acids, tall-oil, compds. with oleylamine; Cobalt bis(2-ethylhexanoate))

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (reaction mass of ethylbenzene and xylene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (reaction mass of ethylbenzene and xylene; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 14 of 18

| CAS No | Chemical name | | | | | |
|-----------|-------------------------------------------------------------------------|-----------------|-----------|--------------------------------------|--------|--------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 123-86-4 | n-butyl acetate | | | | | |
| | Acute fish toxicity | LC50 18 mg/l | 96 h | Pimephales promelas (fathead minnow) | | |
| | Acute algae toxicity | ErC50 397 mg/l | 72 h | Selenastrum capricornutum | | |
| | Acute crustacea toxicity | EC50 44 mg/l | 48 h | Daphnia magna (Big water flea) | | |
| | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | | | | | |
| | Acute fish toxicity | LL50 10-30 mg/l | 96 h | Oncorhynchus mykiss (Rainbow trout) | | |
| | Acute algae toxicity | ErC50 4,6 mg/l | 72 h | Pseudokirchneriella subcapitata | | |
| | Acute crustacea toxicity | EL50 10-22 mg/l | 48 h | Daphnia magna (Big water flea) | | |
| 1330-20-7 | xylene | | | | | |
| | Acute fish toxicity | LC50 86 mg/l | 96 h | Leuciscus idus (golden orfe) | | |
| | Acute algae toxicity | ErC50 2-8 mg/l | | Selenastrum capricornutum | | |
| | Acute crustacea toxicity | EC50 1-10 mg/l | 48 h | | | |
| 100-41-4 | ethylbenzene | | | | | |
| | Acute fish toxicity | LC50 80 mg/l | 96 h | fish | GESTIS | |
| | Acute algae toxicity | ErC50 5 mg/l | 72 h | alga | GESTIS | |
| | Acute crustacea toxicity | EC50 4,75 mg/l | 48 h | | GESTIS | |

12.2. Persistence and degradability

There are no data available on the mixture itself.

| CAS No | Chemical name | | | |
|----------|-------------------------------------------------------------------------|--------|----|--------|
| | Method | Value | d | Source |
| | Evaluation | | | |
| 123-86-4 | n-butyl acetate | | | |
| | OECD 301D/ EEC 92/69/V, C.4-E | 83% | 28 | |
| | Readily biodegradable (according to OECD criteria). | | | |
| | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | | | |
| | | 74,7 % | 28 | |
| | Leicht biologisch abbaubar | | | |
| | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | |
| | | 80% | | |
| | Readily biodegradable (according to OECD criteria). | | | |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | | | |
| | OECD 302 B | >90 % | | |
| | Readily biodegradable (according to OECD criteria). | | | |

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 15 of 18

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|----------|---------------------------------|---------|
| 123-86-4 | n-butyl acetate | 2,3 |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 0,56 |
| 100-41-4 | ethylbenzene | 3,15 |

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 1139

14.2. UN proper shipping name:

Coating solution

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Classification code:

F1

Special Provisions:

640E

Limited quantity:

5 L

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 16 of 18

Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E
Other applicable information (land transport)
E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: no
Special Provisions: 955
Limited quantity: 5 L
EmS: F-E, S-E
Other applicable information (marine transport)
E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

Other applicable information (air transport)

E1
Passenger-LQ: Y344

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 28, Entry 40, Entry 75

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 17 of 18

| | |
|-------------------------------------------------------------|-----------------------|
| Directive 2004/42/EC on VOC in paints and varnishes: | 44,6 % |
| Information according to Directive 2012/18/EU (SEVESO III): | 530 g/l |
| | P5c FLAMMABLE LIQUIDS |

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

| | |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Employment restrictions: | Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| | |
|-------------------------|----------------------------------|
| Water hazard class (D): | 2 - obviously hazardous to water |
|-------------------------|----------------------------------|

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 7,16.

Abbreviations and acronyms

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 black

Revision date: 20.11.2024

Product code: 5115

Page 18 of 18

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Flam. Liq. 3; H226 | On basis of test data |
| Skin Irrit. 2; H315 | Calculation method |
| Eye Irrit. 2; H319 | Calculation method |
| Skin Sens. 1; H317 | Calculation method |
| STOT SE 3; H335 | Calculation method |
| STOT RE 2; H373 | Calculation method |
| Aquatic Chronic 3; H412 | Calculation method |

Relevant H and EUH statements (number and full text)

| | |
|--------|--------------------------------------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361f | Suspected of damaging fertility. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)