

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 1 of 16

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 443 Spray

UFI: 19A1-P3K1-600K-S2UG

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Paints and varnishes

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

##### Supplier

Company name: Leading Solvent Supplies Limited  
Street: Marston Business Park, Rudgate  
Place: GB Tockwith, York YO26 7QF  
E-mail: enquiries@leading-solvents.co.uk  
Internet: www.leading-solvents.co.uk

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Aerosol 1; H222-H229  
Eye Irrit. 2; H319  
Aquatic Acute 1; H400  
Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

Signal word: Danger

Pictograms:



##### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H410 Very toxic to aquatic life with long lasting effects.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 2 of 16

#### Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe mist/vapours/spray.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Special labelling of certain mixtures

Restricted to professional users.

#### Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



#### Hazard statements

H222-H229

#### Precautionary statements

P210-P211-P251-P410+P412

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 3 of 16

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
7440-66-6	zinc powder - zinc dust (stabilized)			25 - < 50%
	231-175-3	030-001-01-9	01-2119467174-37	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
115-10-6	dimethyl ether			25 - < 50%
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Liquefied gas; H220 H280			
67-64-1	acetone; propan-2-one; propanone			5 - < 10%
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
128601-23-0	Hydrocarbons, C9, aromatics			5 - < 10 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411			
	reaction mass of ethylbenzene and xylene			5 - < 10 %
	905-588-0		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
1314-13-2	zinc oxide			< 2,5 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	5 - < 10%
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800 mg/kg	
128601-23-0	918-668-5	Hydrocarbons, C9, aromatics	5 - < 10 %
		inhalation: LC50 = 10,2 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >6800 mg/kg	
	905-588-0	reaction mass of ethylbenzene and xylene	5 - < 10 %
		inhalation: LC50 = 20 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4300 mg/kg	
1314-13-2	215-222-5	zinc oxide	< 2,5 %
		inhalation: LC50 = > 2500 mg/l (dusts or mists); oral: LD50 = > 7950 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice.

##### After inhalation

Remove casualty to fresh air and keep warm and at rest.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 4 of 16

If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After contact with skin

Change contaminated clothing.

Wash with plenty of water/Soap.

If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. In case of eye irritation consult an ophthalmologist.

#### After ingestion

Let water be drunken in little sips (dilution effect).

Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, alcohol resistant foam.

Co-ordinate fire-fighting measures to the fire surroundings.

##### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

#### 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

##### For emergency responders

For further specification, refer to section 8 of the SDS.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 443 Spray**

Revision date: 20.11.2024

Product code: 34061

Page 5 of 16

**For cleaning up**

Provide adequate ventilation.  
Clear contaminated areas thoroughly.  
Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.  
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Take precautionary measures against static discharges.  
Do not spray on naked flames or any incandescent material.  
Keep away from sources of ignition - No smoking.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Heating causes rise in pressure with risk of bursting.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.  
Remove contaminated, saturated clothing immediately.  
Do not breathe gas/vapour/aerosol.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.  
Do not keep the container sealed. Keep container dry.  
Keep away from heat. Protect from direct sunlight.

**Hints on joint storage**

Not required.

**Further information on storage conditions**

Keep container tightly closed.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

Safety Data Sheet

according to UK REACH Regulation

DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 6 of 16

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 7 of 16

#### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m³
Worker DNEL, acute		inhalation	local	2420 mg/m³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m³
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
,				
128601-23-0	Hydrocarbons, C9, aromatics			
Worker DNEL, long-term		inhalation	systemic	150 mg/m³
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m³
Consumer DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	11 mg/kg bw/day
,				
	reaction mass of ethylbenzene and xylene			
Worker DNEL, long-term		inhalation	systemic	211 mg/m³
Worker DNEL, long-term		inhalation	local	221 mg/m³
Worker DNEL, acute		inhalation	systemic	442 mg/m³
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day
Worker DNEL, acute		inhalation	local	289 mg/m³
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	14,8 mg/m³
Consumer DNEL, long-term		inhalation	local	65,3 mg/m³
Consumer DNEL, acute		inhalation	systemic	260 mg/m³
Consumer DNEL, acute		inhalation	local	260 mg/m³
1314-13-2	zinc oxide			
Worker DNEL, long-term		inhalation	systemic	5 mg/m³
Worker DNEL, long-term		inhalation	local	0,5 mg/m³
Worker DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,5 mg/m³
Consumer DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,83 mg/kg bw/day
,				

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 8 of 16

#### PNEC values

CAS No	Substance	
Environmental compartment		Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg
reaction mass of ethylbenzene and xylene		
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,64 mg/kg
Marine sediment		12,64 mg/kg
Soil		2,31 mg/kg
1314-13-2	zinc oxide	
Freshwater		0,0206 mg/l
Marine water		0,0061 mg/l
Freshwater sediment		117,8 mg/kg
Marine sediment		56,5 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,100 mg/l
Soil		35,6 mg/kg

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time:: 120 min.

Butyl caoutchouc (butyl rubber), Breakthrough time:: 120 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

##### Skin protection

Wear anti-static footwear and clothing



## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 9 of 16

#### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.  
gas filtering equipment (EN 141), Filter material/medium: A2/P3

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	grey	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not applicable
Flammability:		not applicable
Lower explosion limits:		3,3 vol. %
Upper explosion limits:		26,2 vol. %
Flash point:		not applicable
Auto-ignition temperature:		> 400 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		4000 hPa
(at 20 °C)		
Density (at 20 °C):		1,1 g/cm <sup>3</sup>
Relative vapour density:		not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties	
not determined	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
not determined	

##### Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	59,2 %
Solid content:	40,7 %
Viscosity / dynamic:	not determined

##### Further Information

No information available.

### SECTION 10: Stability and reactivity

## DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 10 of 16

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

Hazardous decomposition products: none

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 5000 mg/kg; ATE (inhalation gas) &gt; 50000 ppm

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat	RTECS	
	dermal	LD50 7426-15800 mg/kg	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
128601-23-0	Hydrocarbons, C9, aromatics				
	oral	LD50 >6800 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 10,2 mg/l	Rat		
	reaction mass of ethylbenzene and xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 20 mg/l	Rat		
	inhalation gas	ATE 4500 ppm			
1314-13-2	zinc oxide				
	oral	LD50 > 7950 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 > 2500 mg/l	Rat		

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 11 of 16

#### Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

Endocrine disrupting potential No information available.

#### Further information

There are no data available on the preparation/mixture itself.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna	
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum	
128601-23-0	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50	9,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	2,9 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	3,2 mg/l	48 h	Daphnia magna (Big water flea)	
1314-13-2	zinc oxide					
	Acute fish toxicity	LC50 mg/l	1120	96 h	fish	GESTIS
	Acute crustacea toxicity	EC50 mg/l	12,3	48 h		GESTIS

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 12 of 16

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	acetone; propan-2-one; propanone			
	OECD 301 B	91%	28	
	Readily biodegradable (according to OECD criteria).			

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1
67-64-1	acetone; propan-2-one; propanone	-0,24

#### BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

##### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

##### Contaminated packaging

Remove according to the regulations.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number or ID number:

UN 1950

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 13 of 16

### 14.2. UN proper shipping name:

AEROSOLS, ENVIRONMENTALLY HAZARDOUS

### 14.3. Transport hazard class(es):

2

### 14.4. Packing group:

-

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

Transport category:

2

Tunnel restriction code:

D

### Marine transport (IMDG)

#### 14.1. UN number or ID number:

UN 1950

#### 14.2. UN proper shipping name:

AEROSOLS (zinc powder - zinc dust (stabilized), Solvent naphtha (petroleum), light arom.), MARINE POLLUTANT

#### 14.3. Transport hazard class(es):

2.1

#### 14.4. Packing group:

-

Hazard label:

2.1



Marine pollutant:

yes

Special Provisions:

63, 190, 277, 327, 344, 959

Limited quantity:

1000 mL

Excepted quantity:

E0

EmS:

F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

#### 14.1. UN number or ID number:

UN 1950

#### 14.2. UN proper shipping name:

AEROSOLS, flammable

#### 14.3. Transport hazard class(es):

2.1

#### 14.4. Packing group:

-

Hazard label:

2.1



Special Provisions:

A145 A167 A802

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y203

Excepted quantity:

E0

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes



Danger releasing substance:

zinc powder - zinc dust (stabilized)

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 14 of 16

#### **14.6. Special precautions for user**

Warning: Gases under pressure

#### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

#### **Other applicable information**

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 59,2 %

paints and varnishes: 648,3 g/l

Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

Information according to Directive 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

Additional information: P3a

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

##### **Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

##### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

##### **Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

#### **15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C9, aromatics

### SECTION 16: Other information

#### **Changes**

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 443 Spray

Revision date: 20.11.2024

Product code: 34061

Page 15 of 16

This data sheet contains changes from the previous version in section(s): 2,9,15,16.

#### Abbreviations and acronyms

Flam. Gas: Flammable gases  
Aerosol: Aerosols  
Liquefied gas  
Flam. Liq: Flammable liquids  
Acute Tox: Acute toxicity  
Asp. Tox: Aspiration hazard  
Skin Irrit: Skin irritation  
Eye Irrit: Eye irritation  
STOT SE: Specific target organ toxicity - single exposure  
STOT RE: Specific target organ toxicity - repeated exposure  
Aquatic Acute: Acute aquatic hazard  
Aquatic Chronic: Chronic aquatic hazard  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

#### Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 443 Spray**

Revision date: 20.11.2024

Product code: 34061

Page 16 of 16

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*