

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 447 Spray**

Revision date: 20.11.2024

Product code: 30447

Page 1 of 21

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

DINITROL 447 Spray

UFI: S676-0VAK-400X-U5V9

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Anti-corrosive coating

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

**Supplier**

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

**1.4. Emergency telephone number:** Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 1; H222-H229  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
Skin Sens. 1; H317  
STOT SE 3; H336  
STOT RE 2; H373  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol  
Rosin, colophony

**Signal word:** Danger

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 2 of 21

#### Pictograms:



#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves and eye protection/face protection.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Special labelling of certain mixtures

Restricted to professional users.

#### Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

#### Pictograms:



#### Hazard statements

H222-H229-H317-H412

#### Precautionary statements

P210-P211-P251-P280-P410+P412

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 3 of 21

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
1330-20-7	xylene			10 - < 15 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			10 - < 15 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
141-78-6	ethyl acetate			10 - < 15 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			1 - < 5 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
64-17-5	Ethanol			1 - < 5 %
	200-578-6		01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
	reaction mass of ethylbenzene and xylene			1 - < 5 %
	905-588-0		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
25085-50-1	Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol			1 - < 5 %
	Skin Sens. 1; H317			
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			< 1 %
	919-446-0		01-2119458049-33	
	Flam. Liq. 3, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H372 H304 H411 EUH066			
8050-09-7	Rosin, colophony			< 1 %
	232-475-7	650-015-00-7	01-2119480418-32	
	Skin Sens. 1; H317			
1330-20-7	xylene			< 1 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
100-41-4	ethylbenzene			< 1 %
	202-849-4	601-023-00-4	01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 4 of 21

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	10 - < 15 %
		inhalation: ATE = 4500 ppm (gases); dermal: LD50 = >1700 mg/kg; oral: LD50 = 4300 mg/kg	
	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	10 - < 15 %
		inhalation: LC50 = > 20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = > 2000 mg/kg	
141-78-6	205-500-4	ethyl acetate	10 - < 15 %
		inhalation: LC50 = 50 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = 5620 mg/kg	
	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	1 - < 5 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = 5000 mg/kg; oral: LD50 = 4951 mg/kg	
64-17-5	200-578-6	Ethanol	1 - < 5 %
		inhalation: LC50 = > 50 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
	905-588-0	reaction mass of ethylbenzene and xylene	1 - < 5 %
		inhalation: LC50 = 20 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4300 mg/kg	
	919-446-0	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	< 1 %
		dermal: LD50 = >3400 mg/kg; oral: LD50 = >15000 mg/kg	
8050-09-7	232-475-7	Rosin, colophony	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 2800 mg/kg	
1330-20-7	215-535-7	xylene	< 1 %
		inhalation: LC50 = 10-20 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = 2000 mg/kg; oral: LD50 = 8700 mg/kg	
100-41-4	202-849-4	ethylbenzene	< 1 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

###### After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

###### After contact with skin

Change contaminated clothing.

Wash with plenty of water/Soap.

If skin irritation occurs: Get medical advice/attention.

###### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. In case of eye irritation consult an ophthalmologist.

###### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 5 of 21

#### **4.2. Most important symptoms and effects, both acute and delayed**

Nausea, Dizziness, Headache.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water fog.

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

#### **5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

##### **For emergency responders**

For further specification, refer to section 8 of the SDS.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

##### **For cleaning up**

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

##### **Other information**

No information available.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### SECTION 7: Handling and storage

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 6 of 21

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Handle and open container with care.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

##### Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking.

Heating causes rise in pressure with risk of bursting.

##### Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Do not keep the container sealed. Keep container dry.

Keep away from heat. Protect from direct sunlight.

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
8050-09-7	Rosin-based solder flux fume	-	0.05		TWA (8 h)	WEL
		-	0.15		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 447 Spray**

Revision date: 20.11.2024

Product code: 30447

Page 7 of 21

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 8 of 21

### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1330-20-7	xylene			
Worker DNEL, long-term		dermal	systemic	108 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	289 mg/m³
Worker DNEL, acute		inhalation	local	174 mg/m³
Worker DNEL, long-term		inhalation	systemic	77 mg/m³
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	108 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	174 mg/m³
Consumer DNEL, acute		inhalation	local	174 mg/m³
Consumer DNEL, long-term		inhalation	systemic	14,8 mg/m³
,				
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	734 mg/m³
Worker DNEL, acute		inhalation	systemic	1468 mg/m³
Worker DNEL, long-term		inhalation	local	734 mg/m³
Worker DNEL, acute		inhalation	local	1468 mg/m³
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m³
Consumer DNEL, acute		inhalation	systemic	734 mg/m³
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m³
Worker DNEL, long-term		dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	125 mg/kg bw/day
64-17-5	Ethanol			
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m³
Worker DNEL, long-term		inhalation	systemic	950 mg/m³
Worker DNEL, acute		inhalation	local	1900 mg/m³
Consumer DNEL, acute		inhalation	local	950 mg/m³

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 9 of 21

reaction mass of ethylbenzene and xylene			
Worker DNEL, long-term	inhalation	systemic	211 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	221 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	442 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
Worker DNEL, acute	inhalation	local	289 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	1,6 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	14,8 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	260 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	local	260 mg/m <sup>3</sup>
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
Worker DNEL, long-term	inhalation	systemic	330 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	44 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	71 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	26 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day
8050-09-7 Rosin, colophony			
Worker DNEL, long-term	inhalation	systemic	117 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	17 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	35 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	10 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	10 mg/kg bw/day
,			
1330-20-7 xylene			
Consumer DNEL, long-term	oral	systemic	1,6 mg/kg bw/day
Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	108 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	77 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	systemic	14,8 mg/m <sup>3</sup>
1333-86-4 Carbon Black			
Worker DNEL, long-term	inhalation	systemic	2 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	2 mg/m <sup>3</sup>
100-41-4 ethylbenzene			
Worker DNEL, long-term	inhalation	systemic	77 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	293 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	15 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	1,6 mg/kg bw/day
,			

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 10 of 21

#### PNEC values

CAS No	Substance	
Environmental compartment		Value
1330-20-7	xylene	
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		0,20 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg
64-17-5	Ethanol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
	reaction mass of ethylbenzene and xylene	
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,64 mg/kg
Marine sediment		12,64 mg/kg
Soil		2,31 mg/kg
8050-09-7	Rosin, colophony	
Freshwater		0,005 mg/l
Marine water		0,0005 mg/l
Freshwater sediment		0,007 mg/kg
Marine sediment		0,0007 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		21,4 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 11 of 21

Micro-organisms in sewage treatment plants (STP)	6,58 mg/l
Soil	2,31 mg/kg
1333-86-4	Carbon Black
Freshwater	5 mg/l
Marine water	5 mg/l
100-41-4	ethylbenzene
Freshwater	0,1 mg/l
Marine water	0,01 mg/l
Freshwater sediment	13,7 mg/kg
Marine sediment	1,37 mg/kg
Secondary poisoning	0,02 mg/kg
Micro-organisms in sewage treatment plants (STP)	9,6 mg/l
Soil	2,68 mg/kg

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber), Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

##### Skin protection

Wear anti-static footwear and clothing

##### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: A/P2

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	black
Odour:	characteristic
Odour threshold:	not determined

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 12 of 21

#### Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-11,7 °C
Flammability:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	15 vol. %
Flash point:	-80 °C
Auto-ignition temperature:	200 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Density (at 20 °C):

0,96 g/cm<sup>3</sup> DIN 51757

Relative vapour density:

not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties

not determined

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

##### Other safety characteristics

Evaporation rate:

not determined

Solvent content:

68,8 %

Solid content:

31,2 %

Viscosity / dynamic:

not determined

##### Further Information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

### 10.5. Incompatible materials

No information available.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 447 Spray**

Revision date: 20.11.2024

Product code: 30447

Page 13 of 21

**10.6. Hazardous decomposition products**

Carbon monoxide

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 5000 mg/kg; ATE (inhalation gas) &gt; 20000 ppm

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 14 of 21

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	oral	LD50 mg/kg 4300	Rat	GESTIS	
	dermal	LD50 mg/kg >1700	Rabbit	GESTIS	
	inhalation gas	ATE ppm 4500			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 mg/kg > 2000	Rat		
	dermal	LD50 mg/kg >2000	Rabbit		
	inhalation (4 h) vapour	LC50 > 20 mg/l	Rat		
141-78-6	ethyl acetate				
	oral	LD50 mg/kg 5620	Rat		
	dermal	LD50 mg/kg >20000	Rabbit		
	inhalation (4 h) vapour	LC50 50 mg/l	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 mg/kg 4951	Rat		
	dermal	LD50 mg/kg 5000	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
64-17-5	Ethanol				
	oral	LD50 mg/kg 10470	Rat		
	dermal	LD50 mg/kg > 2000	Rabbit		
	inhalation (4 h) vapour	LC50 > 50 mg/l	Rat		
	reaction mass of ethylbenzene and xylene				
	oral	LD50 mg/kg 4300	Rat		
	dermal	LD50 mg/kg > 2000	Rabbit		
	inhalation (4 h) vapour	LC50 20 mg/l	Rat		
	inhalation gas	ATE ppm 4500			
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	oral	LD50 mg/kg >15000	Rat		
	dermal	LD50 mg/kg >3400	Rat		
8050-09-7	Rosin, colophony				
	oral	LD50 mg/kg 2800	Rat		

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 15 of 21

	dermal	LD50 mg/kg	>2000	Rat		
1330-20-7	xylene					
	oral	LD50 mg/kg	8700	Rat		
	dermal	LD50 mg/kg	2000	Rabbit		
	inhalation (4 h) vapour	LC50 mg/l	10-20	Rat		
	inhalation gas	ATE ppm	4500			
100-41-4	ethylbenzene					
	oral	LD50 mg/kg	3500	Rat	GESTIS	
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat		
	inhalation gas	ATE ppm	4500			

#### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. (Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol; Rosin, colophony)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

Endocrine disrupting potential No information available.

#### Further information

There are no data available on the preparation/mixture itself.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 16 of 21

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1330-20-7	xylene					
	Acute fish toxicity	LC50 780 mg/l	96 h			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50 10-100 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 30-100 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 > 1 - 10 mg/l	48 h	Daphnia magna (Big water flea)		
	Fish toxicity	NOEC 2,045 mg/l	28 d	Oncorhynchus mykiss (Rainbow trout)		
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna (Big water flea)		
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50 230 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 3300 mg/l		Desmodesmus subspicatus	48 h	
	Acute crustacea toxicity	EC50 717 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	EC50 2900 mg/l ( )		Pseudomonas putida	16 h	
64-17-5	Ethanol					
	Acute algae toxicity	ErC50 275 mg/l	72 h	Chlorella vulgaris		
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)		
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)					
	Acute fish toxicity	LL50 10-30 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 4,6 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EL50 10-22 mg/l	48 h	Daphnia magna (Big water flea)		
8050-09-7	Rosin, colophony					
	Acute algae toxicity	ErC50 400-410 mg/l	72 h	Scenedesmus subspicatus		
	Fish toxicity	NOEC >1 mg/l	4 d	Danio rerio (zebrafish)		
	Acute bacteria toxicity	EC50 >10000 mg/l ( )	3 h	Activated sludge		
1330-20-7	xylene					
	Acute fish toxicity	LC50 86 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 2-8 mg/l		Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 1-10 mg/l	48 h			
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50 80 mg/l	96 h	fish	GESTIS	
	Acute algae toxicity	ErC50 5 mg/l	72 h	alga	GESTIS	

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 17 of 21

	Acute crustacea toxicity	EC50 mg/l	4,75	48 h		GESTIS	
--	--------------------------	--------------	------	------	--	--------	--

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	OECD 301F	98%	28	
	Readily biodegradable (according to OECD criteria).			
141-78-6	ethyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	100 %	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
		74,7 %	28	
	Leicht biologisch abbaubar			

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

##### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1330-20-7	xylene	3
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	3,4-5,2
141-78-6	ethyl acetate	0,73
100-41-4	ethylbenzene	3,15

##### BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	25,9	Oncorhynchus mykiss (Rainbow trout)	

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

##### List of Wastes Code - residues/unused products

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 18 of 21

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

### Contaminated packaging

Remove according to the regulations.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

### Other applicable information (land transport)

E0

### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 19 of 21



Special Provisions: 63, 190, 277, 327, 344, 381, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

#### Air transport (ICAO-TI/ATA-DGR)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, FLAMMABLE  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203  
 IATA-max. quantity - Cargo: 150 kg

#### Other applicable information (air transport)

E0  
 Passenger-LQ: Y203

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Warning: Gases under pressure

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

#### Other applicable information

Stowage Code:  
 SW1 Protected from sources of heat.  
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:  
 SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):  
 Entry 28, Entry 29, Entry 40, Entry 75

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 20 of 21

Directive 2004/42/EC on VOC in  
paints and varnishes:

68,8 % (565 g/l)

#### Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

#### National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

#### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

160223

#### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 7,8,9,15,16.

#### Abbreviations and acronyms

Aerosol: Aerosols

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 447 Spray

Revision date: 20.11.2024

Product code: 30447

Page 21 of 21

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
Skin Sens. 1; H317	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
STOT RE 2; H373	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*