

DINITROL 4941 (60-900L)

Revision date: 24.03.2025

Product code: 21671

Page 1 of 9

1. Identification

Product identifier

DINITROL 4941 (60-900L)

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980
E-mail: msds@dinol.com
Contact person: Labor
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

Supplier

Company name: DINOL U.S. Inc.
Street: 8500 Cotter Street, Lewis Center
Place: USA-43035 Ohio
Telephone: 740-548-1656
E-mail: info@dinolus.com
Internet: www.dinol.com

Telefax: 740-548-1657

Emergency telephone number: 3E Company Emergency +1-866-404-4230

2. Hazard identification

Classification of the substance or mixture

WHMIS 2015

Flammable liquids: Flam. Liq. 3

Specific target organ toxicity - single exposure: STOT SE 3 (narcotic effects)

Label elements

WHMIS 2015

Signal word: Warning

Pictograms:



Hazard statements

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use non-sparking tools.

DINITROL 4941 (60-900L)

Revision date: 24.03.2025

Product code: 21671

Page 2 of 9

Take action to prevent static discharges.
 Avoid breathing dust/fume/gas/mist/vapours/spray.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 In case of fire: Use water to extinguish.
 Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

Special labelling of certain mixtures

Restricted to professional users.

Other hazards

No information available.

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	30 - < 60% (*)

(*) The actual concentration is withheld as a trade secret.

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w)
 DMSO extract (IP 346)).

4. First-aid measures

Description of first aid measures

General information

If unconscious but breathing normally, place in recovery position and seek medical advice.
 Never give anything by mouth to an unconscious person or a person with cramps.
 In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.
 Wash with plenty of water/Soap.
 If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
 Call a physician immediately.
 Put victim at rest, cover with a blanket and keep warm.
 Do NOT induce vomiting.

Most important symptoms and effects, whether acute or delayed

Nausea, Dizziness, Headache.

Indication of immediate medical attention and special treatment needed

No information available.

DINITROL 4941 (60-900L)

Revision date: 24.03.2025

Product code: 21671

Page 3 of 9

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.**Unsuitable extinguishing media**

High power water jet.

Specific hazards arising from the hazardous product

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

Special protective equipment and precautions for fire-fighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by

DINITROL 4941 (60-900L)

Revision date: 24.03.2025

Product code: 21671

Page 4 of 9

technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.
Keep away from sources of ignition - No smoking.
Vapours are heavier than air and will spread at floor level.
Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
When using do not eat or drink.
Wash hands before breaks and after work.
Avoid contact with skin and eyes.
Remove contaminated, saturated clothing immediately.
Do not breathe gas/vapour/aerosol.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
Keep container dry.
Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

8. Exposure controls/Personal protection

Control parameters

Exposure limits (ACGIH)

CAS No	Chemical name	ppm	mg/m ³	F/ml	Category	Origin
64-17-5	Ethanol	1000	1880		STEL (15 min)	ACGIH-2024

Exposure controls



Appropriate engineering controls

Provide adequate ventilation.
If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Recommended glove articles :
FKM (fluoro rubber), Breakthrough time::
PVA (Polyvinyl alcohol), Breakthrough time::
NBR (Nitrile rubber), Breakthrough time::
Butyl caoutchouc (butyl rubber) Breakthrough time::
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

DINITROL 4941 (60-900L)

Revision date: 24.03.2025

Product code: 21671

Page 5 of 9

mentioned above together with the supplier of these gloves.
Protective gloves have to be replaced at the first sign of deterioration.
Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
gas filtering equipment (EN 141), Filter material/medium: A

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	black
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	154 - 193 °C	
Flammability:	not applicable	
Lower explosive limits:	0,7 vol. %	
Upper explosive limits:	6,0 vol. %	
Flash point:	36 °C	DIN 53213
Auto-ignition temperature:	> 200 °C	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	3 hPa	
(at 20 °C)		
Vapour pressure:	13 hPa	
(at 50 °C)		
Density (at 20 °C):	1,10 - 1,14 g/cm³	DIN 51757
Relative vapour density:	not determined	

Other information

Information with regard to physical hazard classes

Explosive properties	
not determined	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
not determined	

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	not determined

DINITROL 4941 (60-900L)

Revision date: 24.03.2025

Product code: 21671

Page 6 of 9

Solvent content: 31,4 %
Solid content: 66 - 70 %
Viscosity / dynamic: 2200 mPa·s
(at 20 °C)

Further Information

No information available.

10. Stability and reactivity

Reactivity

No hazardous reaction when handled and stored according to provisions.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid

Keep away from heat.

Incompatible materials

No information available.

Hazardous decomposition products

Carbon monoxide

11. Toxicological information

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 mg/kg	> 5000	Rat	
	dermal	LD50 mg/kg	> 5000	Rabbit	
	inhalation (4 h) vapour	LC50 mg/l	> 5000	Rat	

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

DINITROL 4941 (60-900L)

Revision date: 24.03.2025

Product code: 21671

Page 7 of 9

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information

Persistence and degradability

There are no data available on the mixture itself.

Bioaccumulative potential

There are no data available on the mixture itself.

Mobility in soil

There are no data available on the mixture itself.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

Contaminated packaging

Remove according to the regulations.

14. Transport information

Canadian TDG

UN number:

UN 1139

Proper shipping name:

Coating solution

Safety Data Sheet

according to WHMIS

DINITROL 4941 (60-900L)

Revision date: 24.03.2025

Product code: 21671

Page 8 of 9

Hazard classes: 3
Packing group: III
 Hazard label: 3
 Limited quantity: 5L



Marine transport (IMDG)

UN number or ID number: UN 1139
United Nations proper shipping name: COATING SOLUTION
Transport hazard class(es): 3
Packing group: III
 Hazard label: 3



Marine pollutant: no
 Special Provisions: 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1139
United Nations proper shipping name: COATING SOLUTION
name:
Transport hazard class(es): 3
Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

15. Regulatory information

Canadian regulations

DSL/NDSL inventory status

Substance/product listed in the following inventories: DSL/NDSL

Directive 2004/42/EC on VOC in 31,84 %
 paints and varnishes: 356,6 g/l

Safety Data Sheet

according to WHMIS

DINITROL 4941 (60-900L)

Revision date: 24.03.2025

Product code: 21671

Page 9 of 9

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

666728

16. Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,9,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)