

# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 4941 (60-900L)

UFI: 3S5C-GMJP-100Y-XGYG

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Anti-corrosive coating

#### Uses advised against

No further relevant information available.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

**Supplier** 

Company name:

Street:

Marston Business Park, Rudgate
Place:

GB Tockwith, York YO26 7QF

E-mail:

enquiries@leading-solvents.co.uk

www.leading-solvents.co.uk

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Flam. Liq. 3; H226 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

# **GB CLP Regulation**

### Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Warning

Pictograms:





## **Hazard statements**

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.



according to UK REACH Regulation

# **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 2 of 12

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take action to prevent static discharges.

P280 Wear protective gloves and eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

# Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:





#### 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

# Relevant ingredients

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	919-857-5		01-2119463258-33		
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066				
64-17-5	ethanol, ethyl alcohol				
	200-578-6	603-002-00-5	01-2120063206-63		
	Flam. Liq. 2; H225				

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
	inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
64-17-5	200-578-6	ethanol, ethyl alcohol	1 - < 5 %
	inhalation: LC	inhalation: LC50 = 20000 mg/l (vapours); oral: LD50 = 7060 mg/kg	

### **Further Information**

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures



according to UK REACH Regulation

# **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 3 of 12

#### **General information**

If unconscious but breathing normally, place in recovery position and seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

In all cases of doubt, or when symptoms persist, seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

### After contact with skin

Change contaminated clothing.

Wash with plenty of water/Soap.

If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. In case of eye irritation consult an ophthalmologist.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

# 4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water fog.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

#### 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

## Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

## For emergency responders

For further specification, refer to section 8 of the SDS.

# 6.2. Environmental precautions

Do not allow to enter into surface water or drains.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 4 of 12

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

### For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

#### Other information

No information available.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

# Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

#### Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

# Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Keep away from heat.Protect from direct sunlight.

#### Hints on joint storage

Not required.

#### Further information on storage conditions

Keep container tightly closed.

### 7.3. Specific end use(s)

Anti-corrosive coating

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters



according to UK REACH Regulation

# **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 5 of 12

# **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

## **DNEL/DMEL values**

CAS No	Substance			
DNEL type	•	Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	% aromatics		
Consumer DN	IEL, long-term	oral	systemic	125 mg/kg bw/day
Worker DNEL	, long-term	dermal	systemic	208 mg/kg bw/day
Consumer DN	IEL, long-term	dermal	systemic	125 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	871 mg/m³
Consumer DNEL, long-term		inhalation	systemic	185 mg/m³
64-17-5	ethanol, ethyl alcohol			
Worker DNEL	, long-term	inhalation	systemic	950 mg/m³
Worker DNEL, acute		inhalation	local	1900 mg/m³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m³
Consumer DNEL, acute		inhalation	local	950 mg/m³
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day

### PNEC values

OAO Na	Outstance	
CAS No	Substance	
Environmental	compartment	Value
64-17-5	ethanol, ethyl alcohol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		0,72 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg

# 8.2. Exposure controls





# Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn

Individual protection measures, such as personal protective equipment



according to UK REACH Regulation

## **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 6 of 12

### Eye/face protection

Eye glasses with side protection (EN 166)

#### Hand protection

Recommended glove articles:

FKM (fluoro rubber), Breakthrough time:: PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber) Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

### Skin protection

Wear anti-static footwear and clothing

### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: black
Odour: characteristic
Odour threshold: not determined

Test method

Print date: 24.03.2025

Melting point/freezing point:

Boiling point or initial boiling point and

154 - 193 °C

boiling range:

Flammability: not applicable
Lower explosion limits: 0,7 vol. %
Upper explosion limits: 6,0 vol. %

Flash point: 36 °C DIN 53213

Auto-ignition temperature: > 200 °C

Decomposition temperature: not determined

pH-Value: not determined

Water solubility: The study does not need to be conducted

because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 3 hPa

(at 20 °C)

Vapour pressure: 13 hPa

(at 50 °C)

Density (at 20 °C): 1,10 - 1,14 g/cm³ DIN 51757

Relative vapour density: not determined

# 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties not determined



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 7 of 12

Sustaining combustion:

No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties not determined

Other safety characteristics

Evaporation rate: not determined Solvent separation test: not determined Solvent content: 31,4 % Solid content: 66 - 70 % Viscosity / dynamic: 2200 mPa·s

(at 20 °C)

**Further Information** 

No information available.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

## 10.4. Conditions to avoid

Keep away from heat.

# 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

Carbon monoxide

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

# Acute toxicity

Based on available data, the classification criteria are not met.

# ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 8 of 12

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	oral	LD50 > 50 mg/kg	000	Rat		
	dermal	LD50 > 50 mg/kg	000	Rabbit		
	inhalation (4 h) vapour	LC50 > 50 mg/l	000	Rat		
64-17-5	ethanol, ethyl alcohol					
	oral	LD50 706 mg/kg	60	Rat		
	inhalation (4 h) vapour	LC50 200 mg/l	000	Rat		

# Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Information on likely routes of exposure

No information available.

# Specific effects in experiment on an animal

No information available.

### Additional information on tests

No information available.

### **Practical experience**

No information available.

# 11.2. Information on other hazards

# **Endocrine disrupting properties**

Endocrine disrupting potential No information available.

### **Further information**

There are no data available on the preparation/mixture itself.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

#### 12.2. Persistence and degradability



according to UK REACH Regulation

# **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 9 of 12

There are no data available on the mixture itself.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation	•			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
		80%			
	Readily biodegradable (according to OECD criteria).				

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

# 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### **Further information**

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## **Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

# List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

#### Contaminated packaging

Remove according to the regulations.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



according to UK REACH Regulation

# **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 10 of 12



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 113914.2. UN proper shipping name:Coating solution

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Marine pollutant: no
Special Provisions: 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1139

14.2. UN proper shipping name: COATING SOLUTION

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366



# **Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 4941 (60-900L)** 

Revision date: 24.03.2025 Product code: 21671 Page 11 of 12

IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 31,84 % paints and varnishes: 356.6 g/l

Information according to Directive

2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

### **Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

**Additional information** 

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

666728

# 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

## Changes

This data sheet contains changes from the previous version in section(s): 2,9,15,16.



# **Safety Data Sheet**

according to UK REACH Regulation

## **DINITROL 4941 (60-900L)**

Revision date: 24.03.2025 Product code: 21671 Page 12 of 12

### Abbreviations and acronyms

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method

## Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)