

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 4941 / CAR

UFI: K57G-5SKE-F50K-67G2

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Anti-corrosive coating

##### Uses advised against

No further relevant information available.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

##### Supplier

Company name: Leading Solvent Supplies Limited  
Street: Marston Business Park, Rudgate  
Place: GB Tockwith, York YO26 7QF  
E-mail: enquiries@leading-solvents.co.uk  
Internet: www.leading-solvents.co.uk

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Flam. Liq. 3; H226  
STOT SE 3; H336  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics  
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified  
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Warning

##### Pictograms:



# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 2 of 12

### Hazard statements

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P280	Wear protective gloves and eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

### Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking. Restricted to professional users.
--------	--

### Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



### Hazard statements

H412

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			20 - < 25 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified			10 - < 15 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			5 - < 10 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304			
108-32-7	propylene carbonate			1 - < 5 %
	203-572-1	607-194-00-1	01-2119537232-48	
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 3 of 12

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	20 - < 25 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = 5000 mg/kg; oral: LD50 = 4951 mg/kg	
	918-668-5	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	10 - < 15 %
		inhalation: LC50 = >6193 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = 3492 mg/kg	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	5 - < 10 %
		dermal: LD50 = >3000 mg/kg; oral: LD50 = > 5000 mg/kg	
108-32-7	203-572-1	propylene carbonate	1 - < 5 %
		dermal: LD50 = > 20000 mg/kg; oral: LD50 = 33520 mg/kg	

#### Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice.  
Never give anything by mouth to an unconscious person or a person with cramps.  
If unconscious but breathing normally, place in recovery position and seek medical advice.

##### After inhalation

Remove casualty to fresh air and keep warm and at rest.

##### After contact with skin

Change contaminated clothing.  
After contact with skin, wash immediately with plenty of water and soap.

##### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing. Seek medical advice immediately.

##### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).  
Do NOT induce vomiting.  
Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.

#### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

In case of fire, use sand, extinguishing powder or alcohol resistant foam.

##### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, toxic

#### 5.3. Advice for firefighters

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 4941 / CAR**

Revision date: 29.04.2025

Product code: 20091

Page 4 of 12

Wear respiratory protection.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation as well as local exhaust at critical locations. Use only in well-ventilated areas.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

No special measures are necessary.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 5 of 12

### Hints on joint storage

Not required.

### Further information on storage conditions

Keep container tightly closed.

### 7.3. Specific end use(s)

Not required.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
DNEL type				
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	125 mg/kg bw/day
	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified			
Consumer DNEL, long-term		oral	systemic	11 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	150 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	32 mg/m <sup>3</sup>
108-32-7	propylene carbonate			
Worker DNEL, long-term		inhalation	systemic	70,56 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	20 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	20 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	17,4 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	10 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	10 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	10 mg/kg bw/day

#### PNEC values

CAS No	Substance	Value
Environmental compartment		
108-32-7	propylene carbonate	
Freshwater		0,9 mg/l
Marine water		0,9 mg/l
Micro-organisms in sewage treatment plants (STP)		7400 mg/l
Soil		0,81 mg/kg

### 8.2. Exposure controls

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 6 of 12



### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Eye glasses with side protection (EN 166)

#### Hand protection

Recommended glove articles :

FKM (fluoro rubber), Breakthrough time:: 480 min.

NBR (Nitrile rubber), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

#### Skin protection

Wear anti-static footwear and clothing

#### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: A

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	black
Odour:	characteristic
Odour threshold:	not determined

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	165 - 181 °C
Flammability:	not determined
Lower explosion limits:	0,8 vol. %
Upper explosion limits:	6 vol. %
Flash point:	36 °C DIN 53213
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	> 20,5 mm²/s
Water solubility:	not applicable
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	5 hPa
(at 20 °C)	

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 7 of 12

Vapour pressure: (at 50 °C)	30 hPa
Density (at 20 °C):	1,01 - 1,05 g/cm <sup>3</sup> DIN 51757
Relative vapour density:	not determined
Particle characteristics:	not applicable

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties

not determined

Sustained combustibility:

No data available

Oxidizing properties

not determined

##### Other safety characteristics

Solvent content:

org. Lösemittel 37,5 %

Wassergehalt 0,1 %

Solid content:

58,5 - 63,5 %

Softening point:

not determined

Viscosity / dynamic:

1400 - 3500 mPa·s

(at 20 °C)

##### Further Information

No information available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No further relevant information available.

#### 10.2. Chemical stability

No known hazardous decomposition products.

#### 10.3. Possibility of hazardous reactions

No known hazardous decomposition products.

#### 10.4. Conditions to avoid

No further relevant information available.

#### 10.5. Incompatible materials

No further relevant information available.

#### 10.6. Hazardous decomposition products

Carbon monoxide

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 8 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified				
	oral	LD50 3492 mg/kg	Rat		
	dermal	LD50 >3160 mg/kg	Rabbit		
	inhalation vapour	LC50 >6193 mg/l	Rat		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rat		
108-32-7	propylene carbonate				
	oral	LD50 33520 mg/kg	Rat	GESTIS	
	dermal	LD50 > 20000 mg/kg	Rabbit	GESTIS	

### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Information on likely routes of exposure

No information available.

### Specific effects in experiment on an animal

No information available.

### Additional information on tests

No information available.

### Practical experience

No information available.



## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 9 of 12

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

Endocrine disrupting potential No information available.

##### Further information

There are no data available on the preparation/mixture itself.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-32-7	propylene carbonate					
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna (Big water flea)	

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
108-32-7	propylene carbonate			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	83,5-87,7 %	29	
	Readily biodegradable (according to OECD criteria).			

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

##### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-32-7	propylene carbonate	-0,41

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No further relevant information available.

##### Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 10 of 12

### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

### Contaminated packaging

Dispose of waste according to applicable legislation.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L  
Excepted quantity: E1  
Transport category: 3  
Hazard No: 30  
Tunnel restriction code: D/E

### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** Coating solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L  
Excepted quantity: E1

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 11 of 12

Marine pollutant: no  
Special Provisions: 955  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-E, S-E

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1139  
**14.2. UN proper shipping name:** COATING SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### Other applicable information

Transport classification ADR/IMDG is based on packaging >30ltr(IMDG), >450ltr(ADR).  
For other packaging units different classification can apply.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 37,86 %  
paints and varnishes: 390,0 g/l  
Information according to Directive P5c FLAMMABLE LIQUIDS  
2012/18/EU (SEVESO III):

#### Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 4941 / CAR

Revision date: 29.04.2025

Product code: 20091

Page 12 of 12

Water hazard class (D): 2 - obviously hazardous to water

### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

55220

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Abbreviations and acronyms

Flam. Liq: Flammable liquids  
 Asp. Tox: Aspiration hazard  
 Eye Irrit: Eye irritation  
 STOT SE: Specific target organ toxicity - single exposure  
 Aquatic Chronic: Chronic aquatic hazard  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*