

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 1 of 15

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 535

UFI: UXNT-R95E-N00X-TRWG

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Adhesion promoter

##### Uses advised against

No further relevant information available.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

##### Supplier

Company name: Leading Solvent Supplies Limited  
Street: Marston Business Park, Rudgate  
Place: GB Tockwith, York YO26 7QF  
E-mail: enquiries@leading-solvents.co.uk  
Internet: www.leading-solvents.co.uk

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Flam. Liq. 2; H225  
Eye Irrit. 2; H319  
Skin Sens. 1; H317  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

n-butyl acetate  
butanone; ethyl methyl ketone  
ethyl acetate

Signal word: Danger

##### Pictograms:



## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 2 of 15

#### Hazard statements

- |      |                                      |
|------|--------------------------------------|
| H225 | Highly flammable liquid and vapour.  |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation.       |
| H336 | May cause drowsiness or dizziness.   |

#### Precautionary statements

- |                |  |
|----------------|--|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P241           | Use explosion-proof electrical/ventilating/lighting equipment.   |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.                                    |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.                           |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P405           | Store locked up.   |

#### Special labelling of certain mixtures

- |        |  |
|--------|--|
| EUH066 | Repeated exposure may cause skin dryness or cracking.  |
| EUH204 | Contains isocyanates. May produce an allergic reaction.<br>Restricted to professional users. |

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



#### Hazard statements

H317

#### Precautionary statements

P280

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 3 of 15

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
123-86-4	n-butyl acetate			30 - < 35 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
108-65-6	2-methoxy-1-methylethyl acetate			30 - < 35 %
	203-603-9	607-195-00-7		
	Flam. Liq. 3; H226			
78-93-3	butanone; ethyl methyl ketone			15 - < 20 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
141-78-6	ethyl acetate			5 - < 10 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
26426-91-5	Benzene, 2,4-diisocyanato-1-methyl-, polymer with 1,6-diisocyanatohexane			5 - < 10 %
	927-271-6			
	Eye Irrit. 2, Skin Sens. 1; H319 H317			
4151-51-3	Tris(p-isocyanatophenyl) thiophosphate			1 - < 5 %
	223-981-9		01-2119948848-16	
	Acute Tox. 4; H302			
82985-35-1	Bis(trimethoxysilylpropyl)amine			1 - < 5 %
	280-084-5		01-2119969956-12	
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
123-86-4	204-658-1	n-butyl acetate	30 - < 35 %
		inhalation: LC50 = > 21 mg/l (vapours); inhalation: LC50 = >21 mg/l (dusts or mists); dermal: LD50 = > 14112 mg/kg; oral: LD50 = 10760 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	30 - < 35 %
		dermal: LD50 = 7500 mg/kg; oral: LD50 = 8532 mg/kg	
78-93-3	201-159-0	butanone; ethyl methyl ketone	15 - < 20 %
		dermal: LD50 = 6480 mg/kg; oral: LD50 = 2740 mg/kg	
141-78-6	205-500-4	ethyl acetate	5 - < 10 %
		inhalation: LC50 = 50 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = 5620 mg/kg	
26426-91-5	927-271-6	Benzene, 2,4-diisocyanato-1-methyl-, polymer with 1,6-diisocyanatohexane	5 - < 10 %
		oral: LD50 = > 5000 mg/kg	
4151-51-3	223-981-9	Tris(p-isocyanatophenyl) thiophosphate	1 - < 5 %
		oral: ATE = 500 mg/kg	

### Further Information

Full text of H- and EUH-statements: see section 16.

### SECTION 4: First aid measures

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 535**

Revision date: 25.11.2024

Product code: 11001

Page 4 of 15

**4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical advice.  
Never give anything by mouth to an unconscious person or a person with cramps.  
If unconscious but breathing normally, place in recovery position and seek medical advice.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

Change contaminated clothing.  
After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious).  
Do NOT induce vomiting.  
Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.

**4.2. Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder. Water fog.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

No further relevant information available.

**5.3. Advice for firefighters**

No further relevant information available.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.  
Wear personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Avoid breathing dust/fume/gas/mist/vapours/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 535**

Revision date: 25.11.2024

Product code: 11001

Page 5 of 15

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on general occupational hygiene**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.

**Hints on joint storage**

Not required.

**Further information on storage conditions**

maximum storage temperature : < 40 °C

minimum storage temperature : > 4 °C

storage temperature: : 4 - 40 °C

**7.3. Specific end use(s)**

No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 6 of 15

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL

### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
123-86-4	n-butyl acetate			
Worker DNEL, long-term		inhalation	systemic	48 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	600 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	300 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	600 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	12 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	300 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	35,7 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	300 mg/m <sup>3</sup>
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	734 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	1468 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	734 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	1468 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	734 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
1333-86-4	Carbon Black			
Worker DNEL, long-term		inhalation	systemic	2 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	2 mg/m <sup>3</sup>

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 7 of 15

#### PNEC values

CAS No	Substance	
Environmental compartment		Value
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,0981 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,0903 mg/kg
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		0,20 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg
1333-86-4	Carbon Black	
Freshwater		5 mg/l
Marine water		5 mg/l

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

##### Individual protection measures, such as personal protective equipment

###### Eye/face protection

Eye glasses with side protection (DIN EN 166)

###### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

###### Skin protection

Wear anti-static footwear and clothing

###### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.  
gas filtering equipment (EN 141). Filter material/medium : A

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 8 of 15

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	black	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		79 - 80,5 °C
Flammability:		not applicable
Lower explosion limits:		1,8 vol. %
Upper explosion limits:		11,5 vol. %
Flash point:		- 4 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not applicable
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		completely miscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		105 hPa
(at 20 °C)		
Density (at 20 °C):		0,98 - 0,99 g/cm³
Relative vapour density:		not determined
Particle characteristics:		not applicable

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties  
not determined

Oxidizing properties  
not determined

#### Other safety characteristics

Solvent content: 78,7 %

Softening point: not determined

Viscosity / dynamic: not determined

#### Further Information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

No further relevant information available.



## DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 9 of 15

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix tested

	Dose	Species	Source
LD50, oral	24534 mg/kg		

#### ATEmix calculated

ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
123-86-4	n-butyl acetate				
	oral	LD50 10760 mg/kg	Rat		
	dermal	LD50 > 14112 mg/kg	Rabbit		
	inhalation vapour	LC50 > 21 mg/l	Rat		
	inhalation (4 h) dust/mist	LC50 >21 mg/l	Rat		
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 8532 mg/kg	Rat	RTECS	
	dermal	LD50 7500 mg/kg	Rabbit		
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 2740 mg/kg	Rat		
	dermal	LD50 6480 mg/kg	Rabbit		
141-78-6	ethyl acetate				
	oral	LD50 5620 mg/kg	Rat		
	dermal	LD50 >20000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 50 mg/l	Rat		
26426-91-5	Benzene, 2,4-diisocyanato-1-methyl-, polymer with 1,6-diisocyanatohexane				
	oral	LD50 > 5000 mg/kg	Rat		
4151-51-3	Tris(p-isocyanatophenyl) thiophosphate				
	oral	ATE 500 mg/kg			

#### Irritation and corrosivity

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 535**

Revision date: 25.11.2024

Product code: 11001

Page 10 of 15

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

May cause an allergic skin reaction. (Benzene, 2,4-diisocyanato-1-methyl-, polymer with 1,6-diisocyanatohexane)

Contains isocyanates. May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (n-butyl acetate)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No information available.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

No information available.

**Practical experience**

No information available.

**11.2. Information on other hazards****Endocrine disrupting properties**

Endocrine disrupting potential No information available.

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 11 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50	18 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	397 mg/l	72 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50	44 mg/l	48 h	Daphnia magna (Big water flea)	
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50	161 mg/l	96 h	Pimephales promelas	
	Acute crustacea toxicity	EC50	408 mg/l	48 h	Daphnia magna	
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	3300 mg/l		Desmodesmus subspicatus	48 h
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	EC50	2900 mg/l ( )		Pseudomonas putida	16 h

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
123-86-4	n-butyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	83%	28	
	Readily biodegradable (according to OECD criteria).			
141-78-6	ethyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	100 %	28	
	Readily biodegradable (according to OECD criteria).			

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
123-86-4	n-butyl acetate	2,3
108-65-6	2-methoxy-1-methylethyl acetate	0,43
78-93-3	butanone; ethyl methyl ketone	0,29
141-78-6	ethyl acetate	0,73

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 12 of 15

No information available.

### Further information

There are no data available on the mixture itself.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Dispose of waste according to applicable legislation.

Do not mix with other wastes.

#### Contaminated packaging

Dispose according to legislation.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	RESIN SOLUTION
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

### Inland waterways transport (ADN)

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E2

### Marine transport (IMDG)

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	RESIN SOLUTION
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 13 of 15

Marine pollutant: no  
Special Provisions: -  
Limited quantity: 5 L  
Excepted quantity: E2  
EmS: F-E, S-E

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1866  
**14.2. UN proper shipping name:** RESIN SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 78,72 %  
771,5 - 779,4 g/l  
Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

#### Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

#### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 535

Revision date: 25.11.2024

Product code: 11001

Page 14 of 15

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 16.

### Abbreviations and acronyms

Flam. Liq: Flammable liquids  
 Acute Tox: Acute toxicity  
 Skin Irrit: Skin irritation  
 Eye Dam: Eye damage  
 Eye Irrit: Eye irritation  
 Skin Sens: Skin sensitisation  
 STOT SE: Specific target organ toxicity - single exposure  
 Aquatic Chronic: Chronic aquatic hazard  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H336	Calculation method

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.  
 EUH204 Contains isocyanates. May produce an allergic reaction.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 535**

Revision date: 25.11.2024

Product code: 11001

Page 15 of 15

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*