DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 1 of 11

1. Identification

Product identifier

DINITROL 538 PLUS

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesion promoter

Details of the supplier of the safety data sheet

Manufacturer

	Wanulaclurei		
	Company name:	DINOL GmbH	
	Street:	Pyrmonter Strasse 76	
	Place:	D-32676 Luegde	
	Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
	E-mail:	msds@dinol.com	
	Contact person:	Labor	
	Responsible Department:	msds@dinol.com	
	Supplier		
	Company name:	DINOL U.S. Inc.	
	Street:	8500 Cotter Street, Lewis Center	
	Place:	USA-43035 Ohio	
	Telephone:	740-548-1656	Telefax: 740-548-1657
	E-mail:	info@dinolus.com	
	Internet:	www.dinol.com	
<u>E</u>	<u>mergency telephone number:</u>	3E Company Emergency +1-866-404-4230	

2. Hazard identification

Classification of the substance or mixture

WHMIS 2015

Flammable liquids: Flam. Liq. 2 Serious eye damage/eye irritation: Eye Irrit. 2A Respiratory or skin sensitization: Resp. Sens. 1 Respiratory or skin sensitization: Skin Sens. 1 Carcinogenicity: Carc. 2 Specific target organ toxicity - single exposure: STOT SE 3 (narcotic effects)

Label elements

WHMIS 2015

Signal word:

Pictograms:





Hazard statements

Highly flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness. Suspected of causing cancer.

DINOL

Safety Data Sheet

according to WHMIS

DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 2 of 11

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

Wear respiratory protection.

IF ON SKIN: Wash with plenty of water.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use Water spray jet, Extinguishing powder, Carbon dioxide (CO2) to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Other hazards

Endocrine disrupting properties: butanone; ethyl methyl ketone. No information available.

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Chemical name	Quantity
78-93-3	butanone; ethyl methyl ketone	45 - < 70% (*)
108-65-6	2-methoxy-1-methylethyl acetate	5 - < 10% (*)
28182-81-2	Hexamethylene diisocyanate, oligomers	5 - < 10% (*)
1333-86-4	Carbon Black	3 - < 7% (*)
123-86-4	n-butyl acetate	1 - < 5% (*)
1330-20-7	xylene	1 - < 5% (*)
100-41-4	ethylbenzene	0.1 - < 1% (*)
9016-87-9	Diphenylmethanediisocyanate, isomeres and homologues	0.1 - < 1% (*)

(*) The actual concentration is withheld as a trade secret.

Further Information

Full text of H- and EUH-statements: see section 16.

4. First-aid measures

Description of first aid measures

DINOL

Safety Data Sheet

according to WHMIS

DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 3 of 11

General information

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately. Put victim at rest, cover with a blanket and keep warm.

Most important symptoms and effects, whether acute or delayed

No information available.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Extinguishing powder. Water spray jet In case of major fire and large quantities: Water spray jet, alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

Specific hazards arising from the hazardous product

No further relevant information available.

Special protective equipment and precautions for fire-fighters

No special measures are necessary.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

DINOL

Safety Data Sheet

according to WHMIS

DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 4 of 11

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation. Clear contaminated areas thoroughly. Do not rinse down with water.

Other information

No information available.

Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals. Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

maximum storage temperature: < 40°C minimum storage temperature: > 4°C storage temperature: 4 - 40°C

8. Exposure controls/Personal protection

Control parameters

DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 5 of 11

Exposure limits (ACGIH)

CAS No	Chemical name	ppm	mg/m³	F/ml	Category	Origin
1333-86-4	Carbon black (inhalable fraction)		3		TWA (8 h)	ACGIH-2024
100-41-4	Ethyl benzene	20			TWA (8 h)	ACGIH-2024
78-93-3	Methyl ethyl ketone	75			TWA (8 h)	ACGIH-2024
		150			STEL (15 min)	ACGIH-2024
123-86-4	n-Butyl acetate	50	238		TWA (8 h)	ACGIH-2024
		150	712		STEL (15 min)	ACGIH-2024
1330-20-7	Xylene: mixed isomers	20			TWA (8 h)	ACGIH-2024

Biological limit values

CAS No	Chemical name	Parameter	Value	Test material	Sampling time
78-93-3	METHYL ETHYL KETONE (ACGIH 2024)	Methyl ethyl ketone	2 mg/L	urine	End of shift
1330-20-7	XYLENES (technical or commercial grade) (ACGIH 2024)	Methylhippuric acids (creatinine)	0.3 g/g	urine	End of shift
100-41-4	ETHYLBENZENE (ACGIH 2024)	Sum of mandelic acid and phenylglyoxylic acid (creatinine)	0.15 g/g	urine	End of shift

Exposure controls







Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A

DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 6 of 11

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	black
Odour:	characteristic
Odour threshold:	not determined
Melting point/freezing point:	not determined
Boiling point or initial boiling point and	79 - 80,5 °C
boiling range:	
Flammability:	Highly flammable liquid and vapour.
Lower explosive limits:	1,8 vol. %
Upper explosive limits:	11,5 vol. %
Flash point:	- 4 °C
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	Immiscible
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	105 hPa
(at 20 °C)	
Density (at 20 °C):	0,92 - 0,93 g/cm³
Relative vapour density:	not determined
Particle characteristics:	not applicable
Other information	
Information with regard to physical haz	zard classes
Explosive properties	
The product is: not explosive In use	, may form flammable/explosive vapour-air mixture.

Self-ignition temperature		-		•	
Solid:					not applicable
Gas:					not applicable
Oxidizing properties					
not determined					

Other safety characteristics

Evaporation rate: Solvent content: Softening point: Viscosity / dynamic:

Further Information

No information available.

10. Stability and reactivity

Reactivity

No further relevant information available.

Chemical stability

No hazardous reaction when handled and stored according to provisions.

Possibility of hazardous reactions

not determined

not determined

not determined

72.3 %

DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 7 of 11

No known hazardous reactions.

Conditions to avoid

No further relevant information available.

Incompatible materials

No further relevant information available.

Hazardous decomposition products

No known hazardous decomposition products.

11. Toxicological information

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix tested

	Dose	Species	Source
LD50, dermal	150638 mg/kg	Rabbit	
LC50, inhalation (vapour) (4 h)	130 mg/l		

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (inhalation dust/mist) > 12,5 mg/l



DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 8 of 11

CAS No	No Chemical name								
	Route of exposure	Dose		Species	Source	Method			
78-93-3	butanone; ethyl methyl ketone								
	oral	LD50 mg/kg	3300	Rat					
	dermal	LD50 mg/kg	5000	Rabbit					
	inhalation (4 h) vapour	LC50	12 mg/l	Rat					
108-65-6	2-methoxy-1-methylethyl	acetate		_					
	oral	LD50 mg/kg	8500	Rat					
	inhalation (4 h) vapour	LC50	35,7 mg/l	Rat					
28182-81-2	Hexamethylene diisocya	nate, oligor	ners						
	oral	LD50 mg/kg	>5000	Rat					
	inhalation (4 h) vapour	LC50	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						
1333-86-4	Carbon Black								
	oral	LD50 mg/kg	> 15400	Rat	GESTIS				
	dermal	LD50 mg/kg	> 3000	Rabbit	GESTIS				
123-86-4	n-butyl acetate								
	oral	LD50 mg/kg	10760	Rat					
	dermal	LD50 mg/kg	> 14112	Rabbit					
	inhalation vapour	LC50	> 21 mg/l	Rat					
	inhalation (4 h) dust/mist	LC50	>21 mg/l	Rat					
1330-20-7	xylene				-	-			
	dermal	ATE mg/kg	1100						
	inhalation vapour	ATE	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						
100-41-4	ethylbenzene								
	oral	LD50 mg/kg	3500	Rat	GESTIS				
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS				
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat					
	inhalation dust/mist	ATE	1,5 mg/l						
9016-87-9	Diphenylmethanediisocy	anate, isom	eres and hom	nologues					
	oral	LD50 mg/kg	>10000	Rat					
	dermal	LD50 mg/kg	>9400	Rabbit					
	inhalation vapour	ATE	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						



Safety Data Sheet

according to WHMIS

DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 9 of 11

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Diphenylmethanediisocyanate,

isomeres and homologues)

May cause an allergic skin reaction. (Hexamethylene diisocyanate, oligomers; Diphenylmethanediisocyanate, isomeres and homologues)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Carbon Black; ethylbenzene; Diphenylmethanediisocyanate, isomeres and homologues)

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (butanone; ethyl methyl ketone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

Information on other hazards

Endocrine disrupting properties

Endocrine disrupting properties: butanone; ethyl methyl ketone.

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information

Persistence and degradability

No further relevant information available.

Bioaccumulative potential

No further relevant information available.

Mobility in soil

No further relevant information available.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No further relevant information available.

Further information

There are no data available on the mixture itself.



DINITROL 538 PLUS

Revision date: 13.01.2025

Product code: 10730

Page 10 of 11

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

Contaminated packaging

Remove according to the regulations.

14. Transport information

Canadian TDG

UN number:	
Proper shipping name:	
Hazard classes:	
Packing group:	
Hazard label:	
Limited quantity:	

UN 1866 Resin solution 3 II 3 5 L

UN 1866

3

Ш

3

no

5 L

E2

3 11 3

A3 1 L Y341 E2

F-E, S-E

UN 1866

RESIN SOLUTION

RESIN SOLUTION

Marine transport (IMDG) <u>UN number or ID number:</u> <u>United Nations proper shipping</u> <u>name:</u> <u>Transport hazard class(es):</u> <u>Packing group:</u> Hazard label:

Marine pollutant: Special Provisions: Limited quantity: Excepted quantity: EmS:

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number:	
United Nations proper shipping	
<u>name:</u>	
Transport hazard class(es):	
Packing group:	
Hazard label:	

Special Provisions:
Limited quantity Passenger:
Passenger LQ:
Excepted quantity:
IATA-packing instructions - Passenger:

353



	DINITROL 538 PLUS					
Revision date: 13.01.2025	Product code: 10730	Page 11 of 11				
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	5 L 364 60 L					
Environmental hazards						
ENVIRONMENTALLY HAZARDOUS:	No					
15. Regulatory information						
Canadian regulations						
DSL/NDSL inventory status Substance/product listed in the followi	ng inventories: DSL/NDSL					
Directive 2004/42/EC on VOC in paints and varnishes:	72,34 % 665,5 - 672,8 g/l					
Additional information						
This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none						
16. Other information						
Changes This data sheet contains changes from the previous version in section(s): 2,3,7,8,9,11,16.						

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)