

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 6090**

Revision date: 20.11.2024

Product code: 5010

Page 1 of 14

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

DINITROL 6090

UFI: S4VE-W0UF-800Q-VQ27

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Bodyfiller/stopper

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
E-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

**Supplier**

Company name:	Leading Solvent Supplies Limited
Street:	Marston Business Park, Rudgate
Place:	GB Tockwith, York YO26 7QF
E-mail:	enquiries@leading-solvents.co.uk
Internet:	www.leading-solvents.co.uk

**1.4. Emergency telephone number:** Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 3; H226  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
Skin Sens. 1; H317  
Repr. 2; H361d  
STOT SE 3; H335  
STOT RE 1; H372  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

styrene  
Hydrocarbons, C9, aromatics  
Silicon dioxide  
Maleic anhydride

**Signal word:** Danger

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 2 of 14

#### Pictograms:



#### Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.

#### Special labelling of certain mixtures

Restricted to professional users.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

#### Pictograms:



#### Hazard statements

H317-H361d-H372-H412

#### Precautionary statements

P260-P280

#### 2.3. Other hazards

Endocrine disrupting properties: styrene.  
No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 3 of 14

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
100-42-5	styrene			20 - < 25 %
	202-851-5	601-026-00-0	01-2119457861-32	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H226 H361d H332 H315 H319 H335 H372 H304 H412			
128601-23-0	Hydrocarbons, C9, aromatics			1 - < 5 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
14808-60-7	Silicon dioxide			1 - < 5 %
	238-878-4			
	STOT RE 1; H372			
108-31-6	Maleic anhydride			< 0.1 %
	203-571-6		01-2119472428-31	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1A, STOT RE 1; H302 H314 H318 H334 H317 H372 EUH071			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
100-42-5	202-851-5	styrene	20 - < 25 %
	inhalation: LC50 = 11,8 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = > 5000 mg/kg		
128601-23-0	918-668-5	Hydrocarbons, C9, aromatics	1 - < 5 %
	dermal: LD50 = > 3160 mg/kg; oral: LD50 = > 2000 mg/kg		
108-31-6	203-571-6	Maleic anhydride	< 0.1 %
	dermal: LD50 = 2620 mg/kg; oral: LD50 = 1090 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100		

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

#### After inhalation

Provide fresh air. In case of irregular breathing or respiratory arrest provide artificial respiration.

If unconscious but breathing normally, place in recovery position and seek medical advice.

In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 6090**

Revision date: 20.11.2024

Product code: 5010

Page 4 of 14

physician immediately. Put victim at rest, cover with a blanket and keep warm.

**4.2. Most important symptoms and effects, both acute and delayed**

Nausea, Dizziness, Headache.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water fog.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

**5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

**For emergency responders**

For further specification, refer to section 8 of the SDS.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

**Other information**

No information available.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 5 of 14

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Vapours may form explosive mixtures with air.

#### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place.

#### Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

#### Further information on storage conditions

Keep container tightly closed and in a well-ventilated place. Keep container dry.

Protect from direct sunlight.

storage temperature: 15 - 25 °C

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
7429-90-5	Aluminium metal, inhalable dust	-	10		TWA (8 h)	WEL
108-31-6	Maleic anhydride	-	1		TWA (8 h)	WEL
		-	3		STEL (15 min)	WEL
100-42-5	Styrene	100	430		TWA (8 h)	WEL
		250	1080		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 6 of 14

#### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
100-42-5	styrene			
Worker DNEL, acute		inhalation	local	289 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	306 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	85 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	local	406 mg/person/day
Consumer DNEL, acute		inhalation	local	182,75 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	174,25 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	10,2 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2,1 mg/kg bw/day
7429-90-5	aluminium powder (stabilised)			
Worker DNEL, long-term		inhalation	systemic	3,72 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	3,72 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	3,95 mg/kg bw/day
128601-23-0	Hydrocarbons, C9, aromatics			
Worker DNEL, long-term		inhalation	systemic	150 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	11 mg/kg bw/day

#### PNEC values

CAS No	Substance		
Environmental compartment			Value
100-42-5	styrene		
Freshwater			0,028 mg/l
Marine water			0,014 mg/l
Freshwater sediment			0,614 mg/kg
Marine sediment			0,307 mg/kg
Micro-organisms in sewage treatment plants (STP)			5 mg/l
Soil			0,2 mg/kg
7429-90-5	aluminium powder (stabilised)		
Freshwater			0,0749 mg/l
Micro-organisms in sewage treatment plants (STP)			20 mg/l

#### 8.2. Exposure controls

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 7 of 14



#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Eye glasses with side protection (EN 166)

##### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time:: 480 min.

NBR (Nitrile rubber), Breakthrough time:: 30 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

##### Skin protection

Wear anti-static footwear and clothing

##### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: A

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	silver grey
Odour:	characteristic
Odour threshold:	not determined

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	145 °C
Flammability:	not applicable
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	8,9 vol. %
Flash point:	31 °C DIN 51755
Auto-ignition temperature:	480 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 8 of 14

Vapour pressure: (at 20 °C)	6,7 hPa
Density (at 20 °C):	1,45 g/cm <sup>3</sup> ISO 2811
Relative vapour density:	not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties  
not determined

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties  
not determined

##### Other safety characteristics

Evaporation rate: not determined

Solvent separation test: <3 % (ADR/RID)

Solvent content: 20,8 %

Solid content: 79,2 %

Sublimation point: not determined

Softening point: not determined

Pour point: not determined

Viscosity / dynamic:  
(at 20 °C) 80000 - 90000 mPa·s

##### Further Information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

In case of warming: Danger of polymerisation

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

Carbon monoxide

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 5 mg/l



# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
100-42-5	styrene				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 11,8 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
128601-23-0	Hydrocarbons, C9, aromatics				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 3160 mg/kg	Rabbit		
108-31-6	Maleic anhydride				
	oral	LD50 1090 mg/kg	Rat		
	dermal	LD50 2620 mg/kg	Rabbit		

### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

### Sensitising effects

May cause an allergic skin reaction. (Maleic anhydride)

### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (styrene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause respiratory irritation. (styrene)

### STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (styrene)

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Endocrine disrupting properties

Endocrine disrupting properties: styrene.

Endocrine disrupting potential No information available.

### Further information

There are no data available on the preparation/mixture itself.

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
100-42-5	styrene					
	Acute fish toxicity	LC50 mg/l	4,02	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	4,9 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	4,7 mg/l	48 h	Daphnia magna (Big water flea)	
	Fish toxicity	NOEC mg/l	1,01	21 d	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	EC50 ( )	500 mg/l	0,5 h		
128601-23-0	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h		

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
100-42-5	styrene			
		70,9%	28	
	Readily biodegradable (according to OECD criteria).			

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

##### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-42-5	styrene	2,96

##### BCF

CAS No	Chemical name	BCF	Species	Source
100-42-5	styrene	74		

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 11 of 14

### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

### Contaminated packaging

Remove according to the regulations.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Special Provisions: 640E  
Limited quantity: 5 L  
Transport category: 3  
Hazard No: 30  
Tunnel restriction code: D/E

### Other applicable information (land transport)

E1

No good of class 3 according to ADR/RID chapter 2.2.3.1.5.

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: no  
Special Provisions: 223, 955  
Limited quantity: 5 L  
EmS: F-E, S-E

### Other applicable information (marine transport)

E1

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 12 of 14

Transport in accordance with paragraph 2.3.2.5 of the IMDG Code.

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 10 L  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

### Other applicable information (air transport)

E1  
Passenger-LQ: Y344

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

Warning: Flammable liquids

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes: 20,8 % (< 250 g/l)

Subcategory according to Directive 2004/42/EC: Bodyfiller/stopper - All types, VOC limit value: 250 g/l

#### Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

#### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6090

Revision date: 20.11.2024

Product code: 5010

Page 13 of 14

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 16.

#### Abbreviations and acronyms

Flam. Liq: Flammable liquids  
 Acute Tox: Acute toxicity  
 Asp. Tox: Aspiration hazard  
 Skin Corr: Skin corrosion  
 Skin Irrit: Skin irritation  
 Eye Dam: Eye damage  
 Eye Irrit: Eye irritation  
 Resp. Sens: Respiratory sensitisation  
 Skin Sens: Skin sensitisation  
 Repr: Reproductive toxicity  
 STOT SE: Specific target organ toxicity - single exposure  
 STOT RE: Specific target organ toxicity - repeated exposure  
 Aquatic Chronic: Chronic aquatic hazard  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 1; H372	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 6090**

Revision date: 20.11.2024

Product code: 5010

Page 14 of 14

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*