

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 1 of 14

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

DINITROL 6100 Spray

UFI: 0DKD-N314-J00S-D46T

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Bodyfiller/stopper

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name: DINOL GmbH  
Street: Pyrmonter Strasse 76  
Place: D-32676 Luegde  
Telephone: + 49 (0) 5281 982980  
E-mail: msds@dinol.com  
Contact person: Labor  
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

##### Supplier

Company name: Leading Solvent Supplies Limited  
Street: Marston Business Park, Rudgate  
Place: GB Tockwith, York YO26 7QF  
E-mail: enquiries@leading-solvents.co.uk  
Internet: www.leading-solvents.co.uk

#### 1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Aerosol 1; H222-H229  
Acute Tox. 4; H332  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
STOT SE 3; H335  
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

reaction mass of ethylbenzene and xylene

Signal word: Danger

Pictograms:



##### Hazard statements

H222 Extremely flammable aerosol.

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 2 of 14

H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

P201	Obtain special instructions before use.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Special labelling of certain mixtures

EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Restricted to professional users.
--------	---

### Labelling of packages where the contents do not exceed 125 ml

Signal word:

Danger

Pictograms:



### Hazard statements

H222-H229

### Precautionary statements

P251-P410+P412

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 3 of 14

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	reaction mass of ethylbenzene and xylene			20 - < 25 %
	905-588-0		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
74-98-6	propane			12,5 - < 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			12,5 - < 20 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
75-28-5	isobutane			10 - < 12,5 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
67-64-1	acetone; propan-2-one; propanone			5 - < 10 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
13463-67-7	titanium dioxide			2,5 - < 5 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	905-588-0	reaction mass of ethylbenzene and xylene	20 - < 25 %
		inhalation: LC50 = 20 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4300 mg/kg	
106-97-8	203-448-7	butane	12,5 - < 20 %
		inhalation: LC50 = 273000 ppm (gases)	
67-64-1	200-662-2	acetone; propan-2-one; propanone	5 - < 10 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800 mg/kg	

### Further Information

The homogeneous mixing of this product is controlled by continuous physical tests. Formerly dusty raw materials are completely integrated into the liquid/pasty mass. Possible AGW-values for solid substances are therefore not given, as there is no longer any risk of inhalation of these substances (when handling this mixture).

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

## DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 4 of 14

If unconscious but breathing normally, place in recovery position and seek medical advice.

### After contact with skin

Wash with plenty of water/Soap. Change contaminated clothing.

If skin irritation occurs: Get medical advice/attention.

### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. In case of eye irritation consult an ophthalmologist.

### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

### 4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water fog.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

### 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

#### For emergency responders

Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 5 of 14

#### For cleaning up

Provide adequate ventilation.  
Clear contaminated areas thoroughly.  
Do not rinse down with water.

#### Other information

No information available.

#### 6.4. Reference to other sections

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.  
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

##### Advice on protection against fire and explosion

Take precautionary measures against static discharges.  
Do not spray on naked flames or any incandescent material.  
Keep away from sources of ignition - No smoking.  
Heating causes rise in pressure with risk of bursting.

##### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.  
When using do not eat or drink.  
Wash hands before breaks and after work.  
Avoid contact with skin and eyes.  
Remove contaminated, saturated clothing immediately.  
Do not breathe gas/vapour/aerosol.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Do not keep the container sealed. Keep container dry.  
Keep in a cool, well-ventilated place.  
Keep away from heat. Protect from direct sunlight.

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, total inhalable	-	10		TWA (8 h)	WEL

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 6 of 14

### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	reaction mass of ethylbenzene and xylene			
Worker DNEL, long-term		inhalation	systemic	211 mg/m³
Worker DNEL, long-term		inhalation	local	221 mg/m³
Worker DNEL, acute		inhalation	systemic	442 mg/m³
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day
Worker DNEL, acute		inhalation	local	289 mg/m³
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	14,8 mg/m³
Consumer DNEL, long-term		inhalation	local	65,3 mg/m³
Consumer DNEL, acute		inhalation	systemic	260 mg/m³
Consumer DNEL, acute		inhalation	local	260 mg/m³
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m³
Worker DNEL, acute		inhalation	local	2420 mg/m³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m³
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day

### PNEC values

CAS No	Substance	
Environmental compartment	Value	
	reaction mass of ethylbenzene and xylene	
Freshwater	0,327 mg/l	
Marine water	0,327 mg/l	
Freshwater sediment	12,64 mg/kg	
Marine sediment	12,64 mg/kg	
Soil	2,31 mg/kg	
67-64-1	acetone; propan-2-one; propanone	
Freshwater	10,6 mg/l	
Marine water	1,06 mg/l	
Freshwater sediment	30,4 mg/kg	
Marine sediment	3,04 mg/kg	
Micro-organisms in sewage treatment plants (STP)	100 mg/l	
Soil	29,5 mg/kg	

### 8.2. Exposure controls



## DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 7 of 14

### Appropriate engineering controls

Provide adequate ventilation.  
If handled uncovered, arrangements with local exhaust ventilation should be used if possible.  
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Eye glasses with side protection (EN 166)

#### Hand protection

Tested protective gloves must be worn (EN ISO 374):  
FKM (fluoro rubber), Breakthrough time::  
PVA (Polyvinyl alcohol), Breakthrough time::  
NBR (Nitrile rubber), Breakthrough time::  
Butyl caoutchouc (butyl rubber), Breakthrough time::  
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
Protective gloves have to be replaced at the first sign of deterioration.  
Protect skin by using skin protective cream.

#### Skin protection

Wear anti-static footwear and clothing

#### Respiratory protection

2Work in well-ventilated zones or use proper respiratory protection.  
gas filtering equipment (EN 141)., Filter material/medium: A2/P3

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	grey	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not applicable
Flammability:		not applicable
Lower explosion limits:		1,0 vol. %
Upper explosion limits:		10,9 vol. %
Flash point:		not applicable
Auto-ignition temperature:		365 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		3500 hPa
(at 20 °C)		
Density (at 20 °C):		0,8 g/cm³
Relative vapour density:		not determined

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 8 of 14

#### **9.2. Other information**

##### **Information with regard to physical hazard classes**

Explosive properties

not determined

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

##### **Other safety characteristics**

Evaporation rate:

not applicable

Solvent separation test:

not determined

Solvent content:

75,6 %

Solid content:

24,2 %

Viscosity / dynamic:

not determined

##### **Further Information**

No information available.

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

#### **10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

#### **10.3. Possibility of hazardous reactions**

No known hazardous reactions.

#### **10.4. Conditions to avoid**

Keep away from heat. Ignition hazard.

#### **10.5. Incompatible materials**

No information available.

#### **10.6. Hazardous decomposition products**

Carbon monoxide

### **SECTION 11: Toxicological information**

#### **11.1. Information on hazard classes as defined in GB CLP Regulation**

##### **Acute toxicity**

Harmful if inhaled.

##### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) 9300 ppm



# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	reaction mass of ethylbenzene and xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 20 mg/l	Rat		
	inhalation gas	ATE 4500 ppm			
106-97-8	butane				
	inhalation (4 h) gas	LC50 273000 ppm	Rat	GESTIS	
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat	RTECS	
	dermal	LD50 7426-15800 mg/kg	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		

### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause respiratory irritation. (reaction mass of ethylbenzene and xylene)

### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (reaction mass of ethylbenzene and xylene)

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Endocrine disrupting properties

Endocrine disrupting potential No information available.

### Further information

There are no data available on the preparation/mixture itself.

## SECTION 12: Ecological information

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna	
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum	

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	acetone; propan-2-one; propanone			
	OECD 301 B	91%	28	
	Readily biodegradable (according to OECD criteria).			

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
67-64-1	acetone; propan-2-one; propanone	-0,24

#### BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

##### List of Wastes Code - residues/unused products

# Safety Data Sheet

according to UK REACH Regulation

## DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 11 of 14

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

### Contaminated packaging

Remove according to the regulations.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Marine pollutant: no  
Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 12 of 14

Hazard label:

2.1



Special Provisions:

A145 A167 A802

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y203

Excepted quantity:

E0

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

#### 14.6. Special precautions for user

Warning: Gases under pressure

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

#### Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes:

75,6 %

578,4 g/l

Subcategory according to Directive  
2004/42/EC:

Special finishes - All types, VOC limit value: 840 g/l

Information according to Directive  
2012/18/EU (SEVESO III):

P3a FLAMMABLE AEROSOLS

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

##### Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

##### National regulatory information

## Safety Data Sheet

according to UK REACH Regulation

### DINITROL 6100 Spray

Revision date: 11.04.2025

Product code: 38127

Page 13 of 14

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

#### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,8,15,16.

#### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Carc: Carcinogenicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Acute Tox. 4; H332	Bridging principle "Aerosols"
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H335	Bridging principle "Aerosols"
STOT RE 2; H373	Bridging principle "Aerosols"

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.

**Safety Data Sheet**

according to UK REACH Regulation

**DINITROL 6100 Spray**

Revision date: 11.04.2025

Product code: 38127

Page 14 of 14

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*