

according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 1 of 13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**DINITROL 7250 Spray** 

UFI: WFH9-TVDC-X00A-NRW4

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

detergent

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

**Supplier** 

Company name:

Street:

Marston Business Park, Rudgate
Place:

GB Tockwith, York YO26 7QF

E-mail:

enquiries@leading-solvents.co.uk
Internet:

www.leading-solvents.co.uk

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

Aerosol 1; H222-H229 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

## **GB CLP Regulation**

Signal word: Danger

Pictograms:





## **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.



according to UK REACH Regulation

**DINITROL 7250 Spray** 

Revision date: 26.06.2025 Product code: 30566 Page 2 of 13

P251 Do not pierce or burn, even after use.
P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves and eye protection/face protection.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





**Hazard statements** 

H222-H229

**Precautionary statements** 

P210-P211-P251-P410+P412

## 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP	Regulation)		
67-63-0	isopropanol (isopropyl a	alcohol)		12,5 - < 20 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2	, STOT SE 3; H225 H319 H336		
74-98-6	propane			2,5 - < 5 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied	gas; H220 H280		
106-97-8	butane			2,5 - < 5 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied	gas; H220 H280	•	
75-28-5	isobutane	2,5 - < 5 %		
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied	gas; H220 H280	•	
107-98-2	1-methoxy-2-propanol;	monopropylene glycol methyl ether		< 2,5 %
	203-539-1	603-064-00-3	01-2119457435-35	
	Flam. Liq. 3, STOT SE	3; H226 H336	•	
1336-21-6	Ammonia	< 0,5 %		
	215-647-6	007-001-01-2	01-2119982985-14	
	Skin Corr. 1B, Eye Dam			

Full text of H and EUH statements: see section 16.



## **Safety Data Sheet**

according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	imits, M-factors and ATE	
67-63-0	200-661-7	isopropanol (isopropyl alcohol)	12,5 - < 20 %
	inhalation: LC5	0 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg	
106-97-8	203-448-7	butane	2,5 - < 5 %
	inhalation: LC5	0 = 273000 ppm (gases)	
107-98-2	203-539-1	1-methoxy-2-propanol; monopropylene glycol methyl ether	< 2,5 %
	dermal: LD50 =	>>2000 mg/kg; oral: LD50 = > 5000 mg/kg	
1336-21-6	215-647-6	Ammonia	< 0,5 %
	STOT SE 3; H3	35: >= 5 - 100	

### Labelling for contents according to Regulation (EC) No 648/2004

5 % - < 15 % aliphatic hydrocarbons.

#### **Further Information**

Full text of H- and EUH-statements: see section 16.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

## After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

## After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water fog.

Co-ordinate fire-fighting measures to the fire surroundings.

### Unsuitable extinguishing media

High power water jet.

## 5.2. Special hazards arising from the substance or mixture

No information available.

### 5.3. Advice for firefighters



## **Safety Data Sheet**

according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 4 of 13

Use water spray jet to protect personnel and to cool endangered containers.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

#### For emergency responders

For further specification, refer to section 8 of the SDS.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

#### For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

#### Other information

No information available.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

## Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking.

Heating causes rise in pressure with risk of bursting.

### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities



according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 5 of 13

## Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Do not keep the container sealed. Keep container dry.

Keep away from heat. Protect from direct sunlight.

## Hints on joint storage

Not required.

## Further information on storage conditions

Keep container tightly closed.

## 7.3. Specific end use(s)

No information available.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
7664-41-7	Ammonia, anhydrous	25	18		TWA (8 h)	WEL
		35	25		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-63-0	67-63-0 isopropanol (isopropyl alcohol)			
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	500 mg/m³



according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 6 of 13

#### **PNEC values**

CAS No	Cubatana			
CAS NO	Substance			
Environmen	tal compartment	Value		
67-63-0	isopropanol (isopropyl alcohol)			
Freshwater		140,9 mg/l		
Marine water	or .	140,9 mg/l		
Freshwater sediment		552 mg/kg		
Marine sediment		552 mg/kg		
Secondary poisoning		160 mg/kg		
Micro-organisms in sewage treatment plants (STP)		2251 mg/l		
Soil		28 mg/kg		

## 8.2. Exposure controls







### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

Eye glasses with side protection (EN 166)

#### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

Thickness of the glove material: > 0,12 mm

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

## Skin protection

Wear anti-static footwear and clothing

### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A2/P3

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not applicable

boiling range:



according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 7 of 13

Flammability: not applicable Lower explosion limits: 2,0 vol. % Upper explosion limits: 12.0 vol. % Flash point: not applicable Auto-ignition temperature: 425 °C Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: completely miscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 3500 hPa

(at 20 °C)

Density (at 20 °C): 0,9 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

## 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties not determined

Self-ignition temperature

Solid: not applicable Gas: not applicable

Oxidizing properties not determined

Evaporation rate:

Other safety characteristics

Solvent content: 25,0 %, water: 74,5 %
Solid content: 0,1
Softening point: not determined
Viscosity / dynamic: not determined

## **Further Information**

No information available.

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

# 10.5. Incompatible materials

No information available.

## 10.6. Hazardous decomposition products

No known hazardous decomposition products.

not determined



## **Safety Data Sheet**

according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 8 of 13

### **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
67-63-0	isopropanol (isopropyl al	cohol)					
	oral	LD50 mg/kg	4570	Rat			
	dermal	LD50 mg/kg	13400	Rabbit			
	inhalation (4 h) vapour	LC50	30 mg/l	Rat			
106-97-8	butane						
	inhalation (4 h) gas	LC50 ppm	273000	Rat	GESTIS		
107-98-2	1-methoxy-2-propanol; m	nonopropylen	e glycol met	hyl ether			
	oral	LD50 mg/kg	> 5000	Rat	IUCLID		
	dermal	LD50 mg/kg	>2000	Rabbit			

#### Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### Information on likely routes of exposure

No information available.

#### Specific effects in experiment on an animal

No information available.

## Additional information on tests

No information available.

#### **Practical experience**

No information available.

### 11.2. Information on other hazards



## **Safety Data Sheet**

according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 9 of 13

## **Endocrine disrupting properties**

Endocrine disrupting potential No information available.

#### **Further information**

There are no data available on the preparation/mixture itself.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d] Species	Source	Method
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether				
	Acute fish toxicity	LC50 4600 - 10000 mg/l	96 h Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h Daphnia magna	IUCLID	

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	isopropanol (isopropyl alcohol)	0,05
106-97-8	butane	2,89
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437
1336-21-6	Ammonia	-1,38

## 12.4. Mobility in soil

There are no data available on the mixture itself.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No information available.

## **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## **Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

### List of Wastes Code - residues/unused products



according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 10 of 13

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND

INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately

collected fractions (except 15 01); Solvents; hazardous waste

List of Wastes Code - contaminated packaging

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND 150104

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED: packaging (including separately

collected municipal packaging waste); metallic packaging

Contaminated packaging

Remove according to the regulations.

### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 14.2. UN proper shipping name: **AEROSOLS** 

14.3. Transport hazard class(es): 2 14.4. Packing group: Hazard label: 2.1



Classification code:

**Special Provisions:** 190 327 344 625

Limited quantity: 1 I Excepted quantity: F٥ Transport category: 2 Tunnel restriction code: D

Inland waterways transport (ADN)

UN 1950 14.1. UN number or ID number: 14.2. UN proper shipping name: **AEROSOLS** 

14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: 2.1



Classification code:

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

UN 1950 14.1. UN number or ID number: 14.2. UN proper shipping name: **AEROSOLS** 

14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: 2.1



2.1

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL



according to UK REACH Regulation

**DINITROL 7250 Spray** 

Revision date: 26.06.2025 Product code: 30566 Page 11 of 13

Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Warning: Gases under pressure

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

## Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 25 % (229 g/l)

paints and varnishes:

Information according to Directive P3a FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

### Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work



according to UK REACH Regulation

## **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 12 of 13

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

**Additional information** 

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 4,6,8,16.

#### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols Liquefied gas

Flam. Liq: Flammable liquids Skin Corr: Skin corrosion Eye Dam: Eye damage Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure		
Aerosol 1; H222-H229	On basis of test data		
Eye Irrit. 2; H319	Bridging principle "Aerosols"		

### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.



## **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 7250 Spray**

Revision date: 26.06.2025 Product code: 30566 Page 13 of 13

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)