

Safety Data Sheet

according to UK REACH Regulation

DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 77 B Spray

UFI:

WA1D-VMUA-P00W-A01E

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

1.3. Details of the supplier of the safety data sheet

Manufacturer

	Wallulaclulei		
	Company name:	DINOL GmbH	
	Street:	Pyrmonter Strasse 76	
	Place:	D-32676 Luegde	
	Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
	E-mail:	msds@dinol.com	
	Contact person:	Labor	
	Responsible Department:	msds@dinol.com	
	Supplier		
	Company name:	Leading Solvent Supplies Limited	
	Street:	Marston Business Park, Rudgate	
	Place:	GB Tockwith, York YO26 7QF	
	E-mail:	enquiries@leading-solvents.co.uk	
	Internet:	www.leading-solvents.co.uk	
<u>1.</u>	4. Emergency telephone	Giftnotruf Berlin: +49 30 30686 700 (Beratung	in Deutsch und Englisch)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Pictograms: Danger



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.



DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 2 of 14

Precautionary state	ements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking. Restricted to professional users.

Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7. Labelling of packages where the contents do not exceed 125 ml

Signal word:	Danger
Pictograms:	



Hazard statements

H222-H229-H412 Precautionary statements P210-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 3 of 14

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)	Classification (GB CLP Regulation)		
	Hydrocarbons, C9-C11, n-alkanes,	isoalkanes, cyclics, <2% aromatics		25 - < 50 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox	. 1; H226 H336 H304 EUH066		
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas; H			
106-97-8	n-butane			10 - < 15 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1A, Compressed gas; H			
111-76-2	2-butoxyethanol; ethylene glycol m	onobutyl ether		< 1 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 3, Acute Tox. 4, Skin Irr	319		
25307-17-9	2,2'-(9-Octadecenylimino)bisethand	bl		< 1 %
	246-807-3		01-2119510876-35	
	Acute Tox. 4, Skin Corr. 1, Aquatic Chronic 1; H302 H314 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc	Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	25 - < 50 %
	inhalation: LC50 = 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
111-76-2	11-76-2 203-905-0 2-butoxyethanol; ethylene glycol monobutyl ether		< 1 %
	inhalation: A	E 3 mg/l (vapours); oral: ATE 1200 mg/kg	
25307-17-9	246-807-3	2,2'-(9-Octadecenylimino)bisethanol	< 1 %
	oral: LD50 =	>300 - 2000 mg/kg Aguatic Chronic 1; H410: M=1	

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 4 of 14

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), alcohol resistant foam , Extinguishing powder In case of major fire and large quantities: Water spray jet, alcohol resistant foam

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation. Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8

DINOL GmbH

DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 5 of 14

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

No special measures are necessary.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	,	butoxyacetic acid (creatinine)	240 mmol/mol		Post shift



DINOL GmbH

DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 6 of 14

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkan	es, cyclics, <2% aromatics		
Consumer DN	NEL, long-term	oral	systemic	125 mg/kg bw/day
Worker DNEL	., long-term	dermal	systemic	208 mg/kg bw/day
Consumer DN	NEL, long-term	dermal	systemic	125 mg/kg bw/day
Worker DNEL	., long-term	inhalation	systemic	871 mg/m³
Consumer DN	NEL, long-term	inhalation	systemic	185 mg/m³
111-76-2	2-butoxyethanol; ethylene glycol monobutyl	ether		
Consumer DN	IEL, acute	oral	systemic	13,4 mg/kg bw/day
Consumer DN	NEL, long-term	oral	systemic	3,2 mg/kg bw/day
Worker DNEL	., long-term	dermal	systemic	75 mg/kg bw/day
Consumer DN	NEL, acute	dermal	systemic	44,5 mg/kg bw/day
Consumer DN	NEL, long-term	dermal	systemic	38 mg/kg bw/day
Worker DNEL	., acute	inhalation	local	246 mg/m ³
Worker DNEL	., long-term	inhalation	systemic	98 mg/m³
Consumer DN	NEL, acute	inhalation	systemic	633 mg/m³
Worker DNEL	., acute	inhalation	systemic	633 mg/m³
Consumer DN	NEL, acute	inhalation	local	123 mg/m ³
Consumer DN	NEL, long-term	inhalation	systemic	49 mg/m³
25307-17-9	2,2'-(9-Octadecenylimino)bisethanol			
Consumer DN	IEL, long-term	oral	systemic	0,179 mg/kg bw/day
Worker DNEL	., long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DN	IEL, long-term	dermal	systemic	0,179 mg/kg bw/day
Worker DNEL	., long-term	inhalation	systemic	1,76 mg/m ³
Consumer DN	NEL, long-term	inhalation	systemic	0,621 mg/m ³

CAS No Substance Environmental compartment Value 25307-17-9 2,2'-(9-Octadecenylimino)bisethanol 0,000214 mg/l Freshwater 0,000021 mg/l Marine water Freshwater sediment 1,692 mg/kg Marine sediment 0,1692 mg/kg Micro-organisms in sewage treatment plants (STP) 1,5 mg/l

8.2. Exposure controls

DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 7 of 14



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn

Individual protection measures, such as personal protective equipment

Eye/face protection

Not required.

Recommended eye protection articles: Eye glasses with side protection (EN 166)

Hand protection

Not required.

Recommended glove articles NBR (Nitrile rubber) - (> = 0,12 mm), Breakthrough time:: 480 min. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Protective gloves have to be replaced at the first sign of deterioration. Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: AX

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	brown
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point: Boiling point or initial boiling point and	not determined -44 °C	
boiling range:		
Flammability:	not applicable	
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	10,9 vol. %	
Flash point:	< -20 °C	
Auto-ignition temperature:	> 200 °C	
Decomposition temperature:	not determined	
pH-Value:	The study does not need to be	
	conducted because the substance is	
	known to be insoluble in water.	
Viscosity / kinematic:	not determined	
Water solubility:	practically insoluble	
Solubility in other solvents not determined		
Partition coefficient n-octanol/water:	not determined	

Test method



Revision date: 18.03.2025 Product code: 21702 Page 8 of 14 Vapour pressure: 8300 hPa (at 20 °C) 17081 hPa Vapour pressure: 17081 hPa (at 50 °C) 0,736 g/cm³ DIN 51757 Density (at 20 °C): 0,736 g/cm³ DIN 51757 Relative vapour density: not determined 92. Other information Information with regard to physical hazard classes Explosive properties not determined Self-ignition temperature Solid: Gas: not applicable Oxidizing properties not applicable Not oxidising. Other safety characteristics Evaporation rate: not determined	DINITROL 77 B Spray					
(at 20 °C) 17081 hPa (at 50 °C) 0,736 g/cm³ DIN 51757 Density (at 20 °C): 0,736 g/cm³ DIN 51757 Relative vapour density: not determined 9.2. Other information Information with regard to physical hazard classes Explosive properties not determined Self-ignition temperature Solid: Solid: not applicable Gas: not applicable Oxidizing properties not applicable Not oxidising. Other safety characteristics	Revision date: 18.03.2025	Product code: 21702	Page 8 of 14			
Vapour pressure:17081 hPa(at 50 °C)0,736 g/cm³ DIN 51757Density (at 20 °C):0,736 g/cm³ DIN 51757Relative vapour density:not determined9.2. Other informationInformation with regard to physical hazard classesExplosive propertiesnot determinednot determinedSelf-ignition temperatureSolid:not applicableGas:not applicableOxidizing propertiesnot applicableNot oxidising.Other safety characteristics		8300 hPa				
Density (at 20 °C): 0,736 g/cm³ DIN 51757 Relative vapour density: not determined 9.2. Other information Information with regard to physical hazard classes Explosive properties not determined Self-ignition temperature Solid: Gas: not applicable Oxidizing properties not applicable Not oxidising. Other safety characteristics	Vapour pressure:	17081 hPa				
9.2. Other information Information with regard to physical hazard classes Explosive properties not determined Self-ignition temperature Solid: not applicable Gas: not applicable Oxidizing properties Not oxidising. Other safety characteristics		0,736 g/cm³	DIN 51757			
Information with regard to physical hazard classes Explosive properties not determined Self-ignition temperature Solid: not applicable Gas: not applicable Oxidizing properties not applicable Not oxidising. Other safety characteristics	Relative vapour density:	not determined				
Explosive properties not determined Self-ignition temperature Solid: not applicable Gas: not applicable Oxidizing properties Not oxidising. Other safety characteristics	9.2. Other information					
not determined Self-ignition temperature Solid: not applicable Gas: not applicable Oxidizing properties not applicable Not oxidising. Verticable Other safety characteristics Verticable	Information with regard to physical hazard classes					
Self-ignition temperature not applicable Solid: not applicable Gas: not applicable Oxidizing properties Not oxidising. Other safety characteristics Verticable						
Solid: not applicable Gas: not applicable Oxidizing properties not applicable Not oxidising. Vother safety characteristics						
Gas: not applicable Oxidizing properties Not oxidising. Other safety characteristics						
Oxidizing properties Not oxidising. Other safety characteristics						
Not oxidising. Other safety characteristics		not applicable				
Other safety characteristics						
Evaporation rate: not determined						
	•					
Solvent content: 49,90 %						
Solid content: 35,90 % Viscosity / dynamic: not determined						
·····		not determined				
Further Information	Further Information					
No information available.	No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 50000 ppm



DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, r	n-alkanes, isoalkanes, cy	clics, <2% aromatics	•	
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 5000 mg/l	Rat		
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether				
	oral	ATE 1200 mg/kg			
	inhalation vapour	ATE 3 mg/l			
25307-17-9	2,2'-(9-Octadecenylimino)bisethanol				
	oral	LD50 >300 - 2000 mg/kg	Rat		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity Dose [h] [d] Species Source Method					
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether					
	Acute fish toxicity	LC50 1490 mg/l	96 h	Lepomis macrochirus		

12.2. Persistence and degradability

There are no data available on the mixture itself.



DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 10 of 14

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	80%				
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether	0,81 (25°C)

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes. List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-

Revision date: 18.03.2025	DINITROL 77 B Spray Product code: 21702	Page 11 of 14
Hazard label:	2.1	
Classification code:	5F	
Special Provisions:	190 327 344 625	
Limited quantity:	1L	
Excepted quantity:	EO	
Transport category: Tunnel restriction code:	2 D	
Other applicable information (land tran E0	-	
Inland waterways transport (ADN)		
14.1. UN number or ID number:	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
14.3. Transport hazard class(es):	2	
14.4. Packing group:	-	
Hazard label:	2.1	
	<u>.</u>	
	2	
Classification code:	5F	
Special Provisions:	190 327 344 625	
Limited quantity:	1 L	
Excepted quantity:	E0	
Marine transport (IMDG)		
<u>14.1. UN number or ID number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
<u>14.3. Transport hazard class(es):</u> 14.4. Packing group:	2.1	
Hazard label:	- 2.1	
	2	
Marine pollutant:	no	
Special Provisions:	63, 190, 277, 327, 344, 381, 959	
Limited quantity: Excepted quantity:	1000 mL E0	
EmS:	F-D, S-U	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 1950	
14.2. UN proper shipping name:	AEROSOLS, FLAMMABLE	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
	<u>.</u>	
	2	
Special Provisions:	A145 A167 A802	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y203	
Revision No: 1,6 - Replaces version: 1,5	GB - en	Print date: 18.03.2025



	DINITROL 77 B Spray	
Revision date: 18.03.2025	Product code: 21702	Page 12 of 14
Excepted quantity:	E0	
IATA-packing instructions - Passenger:	203	
IATA-max. quantity - Passenger:	75 kg	
IATA-packing instructions - Cargo:	203	
IATA-max. quantity - Cargo:	150 kg	
Other applicable information (air transpo	rt)	
E0		
Passenger-LQ: Y203		
14.5. Environmental hazards		

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre:Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre:Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information	
Restrictions on use (REACH, annex XVII):	
Entry 29, Entry 40, Entry 75	
Directive 2004/42/EC on VOC in	72,9 % (536,544 g/l)
paints and varnishes:	
Subcategory according to Directive 2004/42/EC:	Special finishes - All types, VOC limit value: 840 g/l
Information according to Directive	P3a FLAMMABLE AEROSOLS
2012/18/EU (SEVESO III):	
Additional information	

Observe in addition any national regulations! Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work Aerosol Directive (75/324/).



DINITROL 77 B Spray

Revision date: 18.03.2025

Product code: 21702

Page 13 of 14

National regulatory information

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

Employment restrictions:

3 - highly hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronyms

Dieviations and actonyms	
Flam. Gas: Flammable gases	
Aerosol: Aerosols	
Compressed gas	
Flam. Liq: Flammable liquids	
Acute Tox: Acute toxicity	
Asp. Tox: Aspiration hazard	
Skin Irrit: Skin irritation	
Skin Corr: Skin corrosion	
Eye Irrit: Eye irritation	
STOT SE: Specific target organ toxicity - single exposure	
Aquatic Chronic: Chronic aquatic hazard	
ADR: Accord européen sur le transport des marchandises dangereuses par Rou	ıte
(European Agreement concerning the International Carriage of Dangerous Good	ls by Road)
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonized System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service	
LC50: Lethal concentration, 50%	
LD50: Lethal dose, 50%	

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.

DINITROL 77 B Spray				
Revision date: 18.03.2025	Product code: 21702	Page 14 of 14		
H314	Causes severe skin burns and eye damage.			
H315	Causes skin irritation.			
H319	Causes serious eye irritation.			
H331	Toxic if inhaled.			
H336	May cause drowsiness or dizziness.			
H410	Very toxic to aquatic life with long lasting effects.			
H412	Harmful to aquatic life with long lasting effects.			
EUH066	Repeated exposure may cause skin dryness or cracking.			
Eurther Information				

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)