Telefax: + 49 (0) 5281 9829860

Telefax: 740-548-1657



Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 1 of 10

1. Identification

Product identifier

DINITROL 77 B Spray

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Anti-corrosive coating

Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

Supplier

Company name: DINOL U.S. Inc.

Street: 8500 Cotter Street, Lewis Center

Place: USA-43035 Ohio Telephone: 740-548-1656

E-mail: info@dinolus.com Internet: www.dinol.com

Emergency phone number: 3E Company Emergency +1-866-404-4230

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Flammable aerosols: Flam. Aerosol 1 Gases under pressure: Compressed gas Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2A

Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects)

Label elements

29 CFR Part 1910.1200

Signal word: Danger

Pictograms:







Hazard statements

Extremely flammable aerosol

Contains gas under pressure; may explode if heated Causes skin irritation and serious eye irritation

May cause drowsiness or dizziness

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.



according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 2 of 10

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eve irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Restricted to professional users.

Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

Hazards not otherwise classified

No information available.

3. Composition/information on ingredients

<u>Mixtures</u>

Hazardous components

CAS No	Components	
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	25 - < 50 %
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether	0.9 %
25307-17-9	2,2'-(9-Octadecenylimino)bisethanol	< 1 %

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

4. First-aid measures

Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

Print date: 03/20/2025



Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 3 of 10

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), alcohol resistant foam, Extinguishing powder In case of major fire and large quantities: Water spray jet, alcohol resistant foam

Unsuitable extinguishing media

High power water jet.

Specific hazards arising from the chemical

No further relevant information available.

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Supress gases/vapors/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/fume/vapor/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow to enter into surface water or drains.

Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

Reference to other sections

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13

7. Handling and storage

Precautions for safe handling



according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 4 of 10

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fume/vapor/spray.

Advice on protection against fire and explosion

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

No special measures are necessary.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No	Substance	ppm	mg/m³	f/cc	Category	Origin
111-76-2	2-Butoxyethanol (EGBE)	20	97		TWA (8 h)	ACGIH-2024
111-76-2	2-Butoxyethanol	50	240		TWA (8 h)	PEL
		5	24		TWA (8 h)	REL
75-28-5	Butane: isobutane	1000	2370		STEL (15 min)	ACGIH-2024
106-97-8	Butane: n-butane	1000	2370		STEL (15 min)	ACGIH-2024
75-28-5	Isobutane	800	1900		TWA (8 h)	REL
106-97-8	n-Butane	800	1900		TWA (8 h)	REL
74-98-6	Propane	1000	1800		TWA (8 h)	PEL
		1000	1800		TWA (8 h)	REL
		-	-		Asphyxiant	ACGIH-2024

Biological Exposure Indices (BEI-ACGIH)

CAS No	Substance	Determinant	Value	Test material	Sampling time
111-76-2		Butoxyacetic acid (BAA) (with hydrolysis, creatinine)	200 mg/g	urine	End of shift

Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.



according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 5 of 10

Individual protection measures, such as personal protective equipment

Eye/face protection

Not required.

Recommended eye protection articles: Eye glasses with side protection (EN 166)

Hand protection

Not required.

Recommended glove articles

NBR (Nitrile rubber) - (> = 0,12 mm), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: AX

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Aerosol Color: brown Odor: characteristic Odour threshold: not determined

Test method

Melting point/freezing point: not determined Boiling point or initial boiling point and

-44 °C

boiling range:

Flammability: not applicable Lower explosion limits: 0,6 vol. % 10,9 vol. % Upper explosion limits: < -20 °C Flash point: > 200 °C Auto-ignition temperature: Decomposition temperature: not determined pH-Value:

The study does not need to be conducted because the substance is

known to be insoluble in water.

Viscosity / kinematic: not determined Water solubility: practically insoluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapor pressure: 8300 hPa

(at 20 °C)

Vapor pressure: 17081 hPa

(at 50 °C)

Density (at 20 °C): 0,736 g/cm3 DIN 51757

Relative vapour density: not determined

Other information

Information with regard to physical hazard classes



according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 6 of 10

Explosive properties

not determined

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate: not determined Solvent content: 49,90 % Solid content: 35,90 % Viscosity / dynamic: not determined

Further InformationNo information available.

10. Stability and reactivity

Reactivity

No hazardous reaction when handled and stored according to provisions.

Chemical stability

Stability: Stable

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Hazardous reactions: Will not occur

No known hazardous reactions.

Conditions to avoid

No further relevant information available.

Incompatible materials

No information available.

Hazardous decomposition products

Carbon monoxide

11. Toxicological information

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 50000 ppm



according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 7 of 10

CAS No	Components					
	Exposure route	Dose	Species	Source	Method	
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	oral	LD50 > 5000 mg/kg	Rat			
	dermal	LD50 > 5000 mg/kg	Rabbit			
	inhalation (4 h) vapour	LC50 5000 mg/l	Rat			
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether					
	oral	ATE 1200 mg/kg				
	inhalation vapour	ATE 3 mg/l				
25307-17-9	-9 2,2'-(9-Octadecenylimino)bisethanol					
	oral	LD50 >300 - 2000 mg/kg	Rat			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation

Serious eye damage/eye irritation: Causes serious eye irritation

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (IARC): 2-Butoxyethanol (CAS 111-76-2) is listed in group 3.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information

Persistence and degradability

There are no data available on the mixture itself.

Bioaccumulative potential

There are no data available on the mixture itself.

Mobility in soil

There are no data available on the mixture itself.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No information available.



according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 8 of 10

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

Contaminated packaging

Remove according to the regulations.

14. Transport information

U.S. DOT 49 CFR 172.101

<u>UN number or ID number:</u> UN 1950 <u>Proper shipping name:</u> AEROSOLS

Transport hazard class(es):
Hazard label:
2.1
2.1



Marine transport (IMDG)

<u>UN number or ID number:</u> UN 1950 <u>UN proper shipping name:</u> AEROSOLS

Transport hazard class(es):2.1Packing group:-Hazard label:2.1



Marine pollutant: no

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1950

<u>UN proper shipping name:</u> AEROSOLS, FLAMMABLE

Transport hazard class(es):2.1Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger: 203



according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 9 of 10

IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

F0

Passenger-LQ: Y203

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre:Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

15. Regulatory information

U.S. Regulations

National Inventory TSCA

Substance/product listed in the following inventories: TSCA

National regulatory information

SARA Section 311/312 Hazards:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (-): Fire hazard, Immediate (acute)

health hazard

Propane (74-98-6): Fire hazard, Sudden release of pressure Butane (106-97-8): Fire hazard, Sudden release of pressure Isobutane (75-28-5): Fire hazard, Sudden release of pressure

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2): Immediate (acute) health hazard

2,2'-(9-Octadecenylimino)bisethanol (25307-17-9): Immediate (acute) health hazard

Clean Air Act Section 112(r):

Propane (74-98-6): Threshold quantities = 10,000 lbs. Butane (106-97-8): Threshold quantities = 10,000 lbs. Isobutane (75-28-5): Threshold quantities = 10,000 lbs.

State Regulations



according to 29 CFR 1910.1200(g)

DINITROL 77 B Spray

Revision date: 03/18/2025 Product code: 21702 Page 10 of 10

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Directive 2004/42/EC on VOC in

72.9 % (536,544 g/l)

paints and varnishes:

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

16. Other information

Hazardous Materials Identification System (HMIS)

Health: 0 Flammability: 4 Physical Hazard: 3

NFPA Hazard Ratings

Health: 0 Flammability: 4 Reactivity: 3

Unique Hazard:

Changes

Revision date: 03/18/2025

Revision No: 1.6

This data sheet contains changes from the previous version in section(s): 2,11.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

USA - en

Print date: 03/20/2025