

according to UK REACH Regulation

# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 1 of 17

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

DINITROL 8020 Spray Black

UFI:

T5F9-0XTS-G00W-JYNQ

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

## Paints and varnishes

## 1.3. Details of the supplier of the safety data sheet

## Manufacturer

	Manulaciulei		
	Company name:	DINOL GmbH	
	Street:	Pyrmonter Strasse 76	
	Place:	D-32676 Luegde	
	Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
	E-mail:	msds@dinol.com	
	Contact person:	Labor	
	Responsible Department:	msds@dinol.com	
	Supplier		
	Company name:	Leading Solvent Supplies Limited	
	Street:	Marston Business Park, Rudgate	
	Place:	GB Tockwith, York YO26 7QF	
	E-mail:	enquiries@leading-solvents.co.uk	
	Internet:	www.leading-solvents.co.uk	
<u>1.4</u>	. Emergency telephone	Giftnotruf Berlin: +49 30 30686 700 (Beratung	in Deutsch und Englisch)
	-		

### number:

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Aerosol 1; H222-H229 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

Danger

## 2.2. Label elements

## **GB CLP Regulation**

### Hazard components for labelling

acetone; propan-2-one; propanone n-butyl acetate 2-methoxy-1-methylethyl acetate butan-1-ol; n-butanol

Signal word:

# Pictograms:



## Hazard statements H222

Extremely flammable aerosol.

according to UK REACH Regulation

DINITROL 8020 Spray Black							
Revision date: 20.11.2024	Product code: 32802	Page 2 of 17					
H229	Pressurised container: May burst if heated.						
H319	Causes serious eye irritation.						
H336	May cause drowsiness or dizziness.						
Precautionary statement	ts						
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.						
P211	Do not spray on an open flame or other ignition source.						
P251	Do not pierce or burn, even after use.						
P280	Wear protective gloves and eye/face protection.						
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.						
P337+P313	If eye irritation persists: Get medical advice/attention.						
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.						
Special labelling of certa	ain mixtures						
EUH066	Repeated exposure may cause skin dryness or cracking.						
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Restricted to professional users.						
l abelling of packages w	where the contents do not exceed 125 ml						
Signal word:	Danger						
Pictograms:							
Hazard statements H222-H229							
Precautionary statement	ts						
P210-P211-P251-P4	10+P412						
2.3. Other hazards							

No information available.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures



# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 3 of 17

# **Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Reg	gulation)		
67-64-1	acetone; propan-2-one; pro	panone		25 - < 50 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, ST	OT SE 3; H225 H319 H336 EUH0	66	
115-10-6	dimethyl ether			12,5 - < 20 %
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Liquefied gas	; H220 H280		
123-86-4	n-butyl acetate			10 - < 12,5 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H	226 H336 EUH066	÷	
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas	; H220 H280	·	
108-65-6	2-methoxy-1-methylethyl ad	5 - < 10 %		
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3, STOT SE 3; H	I226 H336		
106-97-8	butane	5 - 10 %		
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas	; H220 H280		
75-28-5	isobutane			5 - < 10 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas	; H220 H280	·	
13463-67-7	titanium dioxide			< 2,5 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351		·	
71-36-3	butan-1-ol; n-butanol			< 2,5 %
	200-751-6	603-004-00-6	01-2119484630-38	
	Flam. Liq. 3, Acute Tox. 4, H318 H335 H336			

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

## **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 4 of 17

CAS No	EC No	Chemical name	Quantity
	Specific Conc	Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	25 - < 50 %
	inhalation: LC mg/kg	50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800	
123-86-4	204-658-1	n-butyl acetate	10 - < 12,5 %
		50 = > 21 mg/l (vapours); inhalation: LC50 = >21 mg/l (dusts or mists); dermal: 12 mg/kg; oral: LD50 = 10760 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	5 - < 10 %
	inhalation: LC	50 = 35,7 mg/l (vapours); oral: LD50 = 8500 mg/kg	
106-97-8	203-448-7	butane	5 - 10 %
	inhalation: LC	50 = 273000 ppm (gases)	
13463-67-7	236-675-5	titanium dioxide	< 2,5 %
	dermal: LD50	= > 10000 mg/kg; oral: LD50 = > 20000 mg/kg	
71-36-3	200-751-6	butan-1-ol; n-butanol	< 2,5 %
	inhalation: LC mg/kg	:50 = >17 mg/l (dusts or mists); dermal: LD50 = 3400 mg/kg; oral: LD50 = 790	

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

## **General information**

In all cases of doubt, or when symptoms persist, seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

## After contact with skin

If skin irritation occurs: Get medical advice/attention.

## After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately. Put victim at rest, cover with a blanket and keep warm.

## 4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

# 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water fog.

## Unsuitable extinguishing media

High power water jet.

## 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.



# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 5 of 17

# Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

## 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

## Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

## General advice

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

## For emergency responders

For further specification, refer to section 8 of the SDS.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### For cleaning up

Provide adequate ventilation. Clear contaminated areas thoroughly. Do not rinse down with water.

## Other information

No information available.

## 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

## Advice on protection against fire and explosion

Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

## Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

# DINOL

# Safety Data Sheet

according to UK REACH Regulation

# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 6 of 17

Avoid contact with skin and eyes. Remove contaminated, saturated clothing immediately. Do not breathe gas/vapour/aerosol.

# 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Do not keep the container sealed. Keep container dry. Keep in a cool, well-ventilated place. Keep away from heat. Protect from direct sunlight.

# 7.3. Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
71-36-3	Butan-1-ol	50	154		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, total inhalable	-	10		TWA (8 h)	WEL



# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 7 of 17

# **DNEL/DMEL** values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL	, long-term	inhalation	systemic	1210 mg/m <sup>3</sup>
Worker DNEL	, acute	inhalation	local	2420 mg/m <sup>3</sup>
Worker DNEL	, long-term	dermal	systemic	186 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	200 mg/m <sup>3</sup>
Consumer DN	IEL, long-term	dermal	systemic	62 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	62 mg/kg bw/day
,				
123-86-4	n-butyl acetate			
Worker DNEL	, long-term	inhalation	systemic	48 mg/m³
Worker DNEL	, acute	inhalation	systemic	600 mg/m³
Worker DNEL	, long-term	inhalation	local	300 mg/m <sup>3</sup>
Worker DNEL	, acute	inhalation	local	600 mg/m³
Consumer DN	IEL, long-term	inhalation	systemic	12 mg/m³
Consumer DN	EL, acute	inhalation	systemic	300 mg/m <sup>3</sup>
Consumer DN	IEL, long-term	inhalation	local	35,7 mg/m³
Consumer DN	IEL, acute	inhalation	local	300 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate			
Worker DNEL	, long-term	inhalation	systemic	275 mg/m³
Worker DNEL	, acute	inhalation	local	550 mg/m³
Worker DNEL	, long-term	dermal	systemic	796 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	33 mg/m³
Consumer DN	EL, acute	inhalation	local	33 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	320 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	36 mg/kg bw/day
71-36-3	butan-1-ol; n-butanol			
Worker DNEL	, long-term	inhalation	local	310 mg/m <sup>3</sup>
Consumer DN	IEL, long-term	oral	systemic	3,125 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	local	55 mg/m³



# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 8 of 17

**DINOL GmbH** 

## **PNEC** values

CAS No	Substance	
Environment	tal compartment	Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine wate	r	1,06 mg/l
Freshwater s	sediment	30,4 mg/kg
Marine sedir	nent	3,04 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	100 mg/l
Soil		29,5 mg/kg
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Marine wate	r	0,018 mg/l
Freshwater s	sediment	0,981 mg/kg
Marine sedir	nent	0,0981 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	35,6 mg/l
Soil		0,0903 mg/kg
108-65-6	2-methoxy-1-methylethyl acetate	
Freshwater		0,635 mg/l
Marine wate	r	0,0635 mg/l
Freshwater s	sediment	3,29 mg/kg
Marine sedir	nent	0,329 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	100 mg/l
Soil		0,290 mg/kg
71-36-3	butan-1-ol; n-butanol	
Freshwater		0,082 mg/l
Marine wate	r	0,0082 mg/l
Freshwater s	sediment	0,178 mg/kg
Marine sedir	nent	0,0178 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	2476 mg/l
Soil		0,015 mg/kg

# 8.2. Exposure controls







## Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

# Individual protection measures, such as personal protective equipment

## Eye/face protection

Eye glasses with side protection (EN 166)

# DINOL

# Safety Data Sheet

according to UK REACH Regulation

# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 9 of 17

## Hand protection

Tested protective gloves must be worn (EN ISO 374): FKM (fluoro rubber), Breakthrough time:: PVA (Polyvinyl alcohol), Breakthrough time:: NBR (Nitrile rubber), Breakthrough time:: Butyl caoutchouc (butyl rubber), Breakthrough time:: For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Protective gloves have to be replaced at the first sign of deterioration. Protect skin by using skin protective cream.

## Skin protection

Physical state

Wear anti-static footwear and clothing

# **Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A2/P3

Aerosol

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	black	
Odour:	characteristic	
Odour threshold:	not determined	
		Test method
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and	not applicable	
boiling range:		
Flammability:	not applicable	
Lower explosion limits:	1,2 vol. %	
Upper explosion limits:	26,2 vol. %	
Flash point:	not applicable	ASTM D 92
Auto-ignition temperature:	240 °C	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	The study does not need to be conducted	
	because the substance is known to be	
	insoluble in water.	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	4000 hPa	
(at 20 °C)		
Density (at 20 °C):	0,8 g/cm³	
Relative vapour density:	not determined	
9.2. Other information		
Information with regard to physical haz	ard classes	
Explosive properties		
not determined		
Self-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	

# DINOL

# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

not applicable

not determined 89,3 %

not determined

9.6 %

Page 10 of 17

Oxidizing properties not determined

## Other safety characteristics

Evaporation rate: Solvent separation test: Solvent content: Solid content: Viscosity / dynamic:

## Further Information

No information available.

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

No known hazardous reactions.

# 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

## 10.5. Incompatible materials

No information available.

# 10.6. Hazardous decomposition products

Carbon monoxide

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

## Acute toxicity

Based on available data, the classification criteria are not met.

# ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm



# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 11 of 17

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-64-1	acetone; propan-2-one; p	propanone				
	oral	LD50 mg/kg	5800	Rat	RTECS	
	dermal	LD50 15800 mg/kg	7426- )	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50	76 mg/l	Rat		
123-86-4	n-butyl acetate			_		
	oral	LD50 mg/kg	10760	Rat		
	dermal	LD50 mg/kg	> 14112	Rabbit		
	inhalation vapour	LC50	> 21 mg/l	Rat		
	inhalation (4 h) dust/mist	LC50	>21 mg/l	Rat		
108-65-6	2-methoxy-1-methylethyl	acetate				
	oral	LD50 mg/kg	8500	Rat		
	inhalation (4 h) vapour	LC50	35,7 mg/l	Rat		
106-97-8	butane					
	inhalation (4 h) gas	LC50 ppm	273000	Rat	GESTIS	
13463-67-7	titanium dioxide					
	oral	LD50 mg/kg	> 20000	Rat		
	dermal	LD50 mg/kg	> 10000	Rabbit		
71-36-3	butan-1-ol; n-butanol					
	oral	LD50 mg/kg	790	Rat	GESTIS	
	dermal	LD50 mg/kg	3400	Rabbit	GSETIS	
	inhalation (4 h) dust/mist		>17 mg/l	Rat		

## Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation. Skin corrosion/irritation: Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

# Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

## STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 12 of 17

# Aspiration hazard

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards

# Endocrine disrupting properties

Endocrine disrupting potential No information available.

## Further information

There are no data available on the preparation/mixture itself.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
67-64-1	acetone; propan-2-one; propanone								
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss				
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna				
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum				
123-86-4	6-4 n-butyl acetate								
	Acute fish toxicity	LC50	18 mg/l	96 h	Pimephales promelas (fathead minnow)				
	Acute algae toxicity	ErC50	397 mg/l	72 h	Selenastrum capricornutum				
	Acute crustacea toxicity	EC50	44 mg/l	48 h	Daphnia magna (Big water flea)				
71-36-3	butan-1-ol; n-butanol								
	Acute fish toxicity	LC50 mg/l	1740	96 h	Pimephales promelas (fathead minnow)				
	Acute algae toxicity	ErC50 mg/l	>500	72 h	Scenedesmus subspicatus				
	Acute crustacea toxicity	EC50 mg/l	1980	48 h		GESTIS			
	Acute bacteria toxicity	EC50 mg/l()	2250		Pseudomonas putida	16 h			

## 12.2. Persistence and degradability

There are no data available on the mixture itself.



according to UK REACH Regulation

# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 13 of 17

CAS No	Chemical name						
	Method	Value		d	Source		
	Evaluation						
67-64-1	acetone; propan-2-one; propanone						
	OECD 301 B	91%		28			
	Readily biodegradable (according to OECD criteria).						
123-86-4	n-butyl acetate						
	OECD 301D/ EEC 92/69/V, C.4-E	83%		28			
	Readily biodegradable (according to OECD criteria).						
108-65-6	2-methoxy-1-methylethyl acetate						
	OECD 302 B	>90 %					
	Readily biodegradable (according to OECD criteria).						

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
115-10-6	dimethyl ether	0,1
123-86-4	n-butyl acetate	2,3
108-65-6	2-methoxy-1-methylethyl acetate	0,56
106-97-8	butane	2,89
71-36-3	butan-1-ol; n-butanol	0,88
	4	

## BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

# 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects

No information available.

## **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes. List of proposed waste codes/waste designations in accordance with EWC:

## List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste



# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 14 of 17

# List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

## List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

## Contaminated packaging

Remove according to the regulations.

## **SECTION 14: Transport information**

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Marine pollutant:	no
Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1

according to UK REACH Regulation

# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 15 of 17

2	
A145 A167 A802	
30 kg G	
Y203	
E0	
	203
	75 kg
	203
	150 kg
	30 kg G Y203

# 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Gases under pressure

# 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre:Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# EU regulatory information

	EU regulatory information	
	Restrictions on use (REACH, annex XVII):	
	Entry 28, Entry 40, Entry 75	
	Directive 2004/42/EC on VOC in paints and varnishes:	89,3 % (674,4 g/l)
	Subcategory according to Directive 2004/42/EC:	Special finishes - All types, VOC limit value: 840 g/l
Marketing and use of explosives precursors (Regulation (EU) 2019/1148):		s (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

#### Additional information

Observe in addition any national regulations! Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

## National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.



# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 16 of 17

**DINOL GmbH** 

Water hazard class (D):

1 - slightly hazardous to water

## Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 2,3,9,15,16.

# Abbreviations and acronyms

Flam. Gas: Flammable gases Aerosol: Aerosols Liquefied gas Flam. Lig: Flammable liquids Acute Tox: Acute toxicity Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation Carc: Carcinogenicity STOT SE: Specific target organ toxicity - single exposure ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration. 50% LD50: Lethal dose, 50%

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

## Relevant H and EUH statements (number and full text)

Н	220	Extremely flammable gas.
Н	222	Extremely flammable aerosol.
Н	225	Highly flammable liquid and vapour.
Н	226	Flammable liquid and vapour.
Н	229	Pressurised container: May burst if heated.
Н	280	Contains gas under pressure; may explode if heated.
Н	1302	Harmful if swallowed.
Н	315	Causes skin irritation.
Н	318	Causes serious eye damage.
Н	1319	Causes serious eye irritation.
Н	335	May cause respiratory irritation.
Н	1336	May cause drowsiness or dizziness.
Н	1351	Suspected of causing cancer.
E	UH066	Repeated exposure may cause skin dryness or cracking.
E	UH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe



according to UK REACH Regulation

# **DINITROL 8020 Spray Black**

Revision date: 20.11.2024

Product code: 32802

Page 17 of 17

spray or mist.

# **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)