

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 1 of 17

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**DINITROL 8020 Spray Grey** 

UFI: NMRD-NWK0-N003-N6DJ

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Paints and varnishes

### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

**Supplier** 

Company name:

Street:

Marston Business Park, Rudgate
Place:

GB Tockwith, York YO26 7QF

E-mail:

enquiries@leading-solvents.co.uk
Internet:

www.leading-solvents.co.uk

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# **GB CLP Regulation**

Aerosol 1; H222-H229 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

# **GB CLP Regulation**

# Hazard components for labelling

acetone; propan-2-one; propanone

n-butyl acetate

2-methoxy-1-methylethyl acetate

butan-1-ol; n-butanol

Signal word: Danger

Pictograms:





# **Hazard statements**

H222 Extremely flammable aerosol.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 2 of 17

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves and eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

# Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe

spray or mist.

Restricted to professional users.

# Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





# **Hazard statements**

H222-H229

#### 2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures



according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 3 of 17

# Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP	Regulation)	•	
67-64-1	acetone; propan-2-one;	propanone		25 - < 50 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2,	STOT SE 3; H225 H319 H336 EUH	066	
115-10-6	dimethyl ether			12,5 - < 20 %
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Liquefied	gas; H220 H280		
123-86-4	n-butyl acetate			10 - < 12,5 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE	3; H226 H336 EUH066	•	
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied	gas; H220 H280		
108-65-6	2-methoxy-1-methylethy	5 - < 10 %		
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3, STOT SE	3; H226 H336		
13463-67-7	titanium dioxide			< 2,5 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351	•		
9004-70-0	Nitrocellulose			< 2,5 %
	Flam. Sol. 1; H228			
71-36-3	butan-1-ol; n-butanol			< 2,5 %
	200-751-6	603-004-00-6	01-2119484630-38	
	Flam. Liq. 3, Acute Tox. H318 H335 H336	4, Skin Irrit. 2, Eye Dam. 1, STOT SI	E 3, STOT SE 3; H226 H302 H315	

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc	Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	25 - < 50 %
	inhalation: LC mg/kg	C50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800	
123-86-4	204-658-1	n-butyl acetate	10 - < 12,5 %
		C50 = > 21 mg/l (vapours); inhalation: LC50 = >21 mg/l (dusts or mists); dermal: 12 mg/kg; oral: LD50 = 10760 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	5 - < 10 %
	inhalation: LC	C50 = 35,7 mg/l (vapours); oral: LD50 = 8500 mg/kg	
13463-67-7	236-675-5	titanium dioxide	< 2,5 %
	dermal: LD50	) = > 10000 mg/kg; oral: LD50 = > 20000 mg/kg	
71-36-3	200-751-6	butan-1-ol; n-butanol	< 2,5 %
	inhalation: LC mg/kg	250 = >17 mg/l (dusts or mists); dermal: LD50 = 3400 mg/kg; oral: LD50 = 790	

### **Further Information**

For full text of Hazard- and EU Hazard-statements: see SECTION 16.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 4 of 17

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

### After contact with skin

If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

### 4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water fog.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

# 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

# Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

# For emergency responders

For further specification, refer to section 8 of the SDS.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 5 of 17

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

# 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

### For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

#### Other information

No information available.

# 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

# Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

#### Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking.

Heating causes rise in pressure with risk of bursting.

### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Do not keep the container sealed. Keep container dry.

Keep in a cool, well-ventilated place.

Keep away from heat. Protect from direct sunlight.

### 7.3. Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters



according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 6 of 17

# **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
71-36-3	Butan-1-ol	50	154		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, total inhalable	-	10		TWA (8 h)	WEL



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 7 of 17

# **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL,	long-term	inhalation	systemic	1210 mg/m³
Worker DNEL,	acute	inhalation	local	2420 mg/m³
Worker DNEL,	long-term	dermal	systemic	186 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	200 mg/m³
Consumer DN	EL, long-term	dermal	systemic	62 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	62 mg/kg bw/day
,	1			
123-86-4	n-butyl acetate			
Worker DNEL,	long-term	inhalation	systemic	48 mg/m³
Worker DNEL,	acute	inhalation	systemic	600 mg/m³
Worker DNEL,	long-term	inhalation	local	300 mg/m³
Worker DNEL,	acute	inhalation	local	600 mg/m³
Consumer DN	EL, long-term	inhalation	systemic	12 mg/m³
Consumer DN	EL, acute	inhalation	systemic	300 mg/m³
Consumer DN	EL, long-term	inhalation	local	35,7 mg/m³
Consumer DN	EL, acute	inhalation	local	300 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate			
Worker DNEL,	long-term	inhalation	systemic	275 mg/m³
Worker DNEL,	acute	inhalation	local	550 mg/m³
Worker DNEL,	long-term	dermal	systemic	796 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	33 mg/m³
Consumer DN	EL, acute	inhalation	local	33 mg/m³
Consumer DN	EL, long-term	dermal	systemic	320 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	36 mg/kg bw/day
71-36-3	butan-1-ol; n-butanol			
Worker DNEL,	long-term	inhalation	local	310 mg/m <sup>3</sup>
Consumer DN	EL, long-term	oral	systemic	3,125 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	local	55 mg/m³



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 8 of 17

# **PNEC values**

CAS No	Substance	
Environmenta	al compartment	Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater s	ediment	30,4 mg/kg
Marine sedim	nent	3,04 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	100 mg/l
Soil		29,5 mg/kg
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Marine water		0,018 mg/l
Freshwater s	ediment	0,981 mg/kg
Marine sedim	nent	0,0981 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,0903 mg/kg
108-65-6	2-methoxy-1-methylethyl acetate	
Freshwater		0,635 mg/l
Marine water		0,0635 mg/l
Freshwater sediment		3,29 mg/kg
Marine sedim	nent	0,329 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	100 mg/l
Soil		0,290 mg/kg
71-36-3	butan-1-ol; n-butanol	
Freshwater		0,082 mg/l
Marine water		0,0082 mg/l
Freshwater s	ediment	0,178 mg/kg
Marine sediment		0,0178 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	2476 mg/l
Soil		0,015 mg/kg

# 8.2. Exposure controls







# Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

# Individual protection measures, such as personal protective equipment

# Eye/face protection

Eye glasses with side protection (EN 166)



according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 9 of 17

### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber), Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

#### Skin protection

Wear anti-static footwear and clothing

### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A2/P3

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: dark grey
Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not applicable

boiling range:

Flammability: not applicable Lower explosion limits: 1,2 vol. % Upper explosion limits: 26.2 vol. % not applicable Flash point: Auto-ignition temperature: 240 °C Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined The study does not need to be conducted Water solubility: because the substance is known to be

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 4000 hPa

(at 20 °C)

Density (at 20 °C): 0,8 g/cm³
Relative vapour density: not determined

#### 9.2. Other information

# Information with regard to physical hazard classes

Explosive properties not determined Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties not determined

insoluble in water.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 10 of 17

# Other safety characteristics

Evaporation rate:

Solvent separation test:

Solvent content:

Solid content:

Solid content:

Viscosity / dynamic:

not applicable
not determined
not determined

#### **Further Information**

No information available.

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

Carbon monoxide

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 11 of 17

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
67-64-1	acetone; propan-2-one; propanone						
	oral	LD50 mg/kg	5800	Rat	RTECS		
	dermal	LD50 15800 mg	7426- g/kg	Rabbit	IUCLID		
	inhalation (4 h) vapour	LC50	76 mg/l	Rat			
123-86-4	n-butyl acetate						
	oral	LD50 mg/kg	10760	Rat			
	dermal	LD50 mg/kg	> 14112	Rabbit			
	inhalation vapour	LC50	> 21 mg/l	Rat			
	inhalation (4 h) dust/mist	LC50	>21 mg/l	Rat			
108-65-6	2-methoxy-1-methylethyl acetate						
	oral	LD50 mg/kg	8500	Rat			
	inhalation (4 h) vapour	LC50	35,7 mg/l	Rat			
13463-67-7	titanium dioxide						
	oral	LD50 mg/kg	> 20000	Rat			
	dermal	LD50 mg/kg	> 10000	Rabbit			
71-36-3	butan-1-ol; n-butanol						
	oral	LD50 mg/kg	790	Rat	GESTIS		
	dermal	LD50 mg/kg	3400	Rabbit	GSETIS		
	inhalation (4 h) dust/mist	LC50	>17 mg/l	Rat			

### Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

# Sensitising effects

Based on available data, the classification criteria are not met.

# Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards



according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 12 of 17

# **Endocrine disrupting properties**

Endocrine disrupting potential No information available.

# **Further information**

There are no data available on the preparation/mixture itself.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; p	ropanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna		
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum		
123-86-4	n-butyl acetate						
	Acute fish toxicity	LC50	18 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50	397 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50	44 mg/l	48 h	Daphnia magna (Big water flea)		
71-36-3	butan-1-ol; n-butanol						
	Acute fish toxicity	LC50 mg/l	1740	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 mg/l	>500	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	1980	48 h		GESTIS	
	Acute bacteria toxicity	EC50 mg/l ( )	2250		Pseudomonas putida	16 h	

# 12.2. Persistence and degradability

There are no data available on the mixture itself.

11101	e are no data avaliable on the mixture itself.			
CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation		-	
67-64-1	acetone; propan-2-one; propanone			
	OECD 301 B	91%	28	
	Readily biodegradable (according to OECD criteria).			
123-86-4	n-butyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	83%	28	
	Readily biodegradable (according to OECD criteria).		-	
108-65-6	2-methoxy-1-methylethyl acetate			
	OECD 302 B	>90 %		
	Readily biodegradable (according to OECD criteria).			

# 12.3. Bioaccumulative potential

There are no data available on the mixture itself.



according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 13 of 17

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
115-10-6	dimethyl ether	0,1
123-86-4	n-butyl acetate	2,3
108-65-6	2-methoxy-1-methylethyl acetate	0,56
9004-70-0	Nitrocellulose	<0
71-36-3	butan-1-ol; n-butanol	0,88

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes. List of proposed waste codes/waste designations in accordance with EWC:

#### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

# List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

# List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

### Contaminated packaging

Remove according to the regulations.

# **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950



according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 14 of 17

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant: no

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Gases under pressure

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 15 of 17

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

#### Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 89,3 % (674,4 g/l)

paints and varnishes:

Subcategory according to Directive Special finishes - All types, VOC limit value: 840 g/l

2004/42/EC:

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

### **Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

# National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

#### **Additional information**

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,9,15,16.



according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Product code: 31802 Revision date: 20.11.2024 Page 16 of 17

### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols Liquefied gas

Flam. Liq: Flammable liquids Flam. Sol: Flammable solids Acute Tox: Acute toxicity Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation Carc: Carcinogenicity

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

# Classification for mixtures and used evaluation method according to GB CLP Regulation

Extremely flammable aerosol.

	<u> </u>
Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

# Relevant H and EUH statements (number and full text) Extremely flammable gas.

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

Repeated exposure may cause skin dryness or cracking. **EUH066** 

**EUH211** Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe

spray or mist.

# **Further Information**

H220

H222

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8020 Spray Grey**

Revision date: 20.11.2024 Product code: 31802 Page 17 of 17

(EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)