

according to UK REACH Regulation

# **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 1 of 17

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**DINITROL 8050 Spray** 

UFI: Y9JT-P291-1003-S2GP

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Paints and varnishes

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

**Supplier** 

Company name:

Street:

Marston Business Park, Rudgate
Place:

GB Tockwith, York YO26 7QF

E-mail:

enquiries@leading-solvents.co.uk
Internet:

www.leading-solvents.co.uk

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Aerosol 1; H222-H229 Eye Irrit. 2; H319 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

# **GB CLP Regulation**

## Hazard components for labelling

acetone; propan-2-one; propanone Hydrocarbons, C9, aromatics

Signal word:

Danger

Pictograms:





## **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



## **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 2 of 17

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





#### **Hazard statements**

H222-H229-H412

## **Precautionary statements**

P210-P251-P410+P412

#### 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures



according to UK REACH Regulation

# **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 3 of 17

## Relevant ingredients

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (GB CLP Regulation	on)	•			
67-64-1	acetone; propan-2-one; propano	ne		25 - < 50 %		
	200-662-2	606-001-00-8	01-2119471330-49			
	Flam. Liq. 2, Eye Irrit. 2, STOT S	E 3; H225 H319 H336 EUH	166			
74-98-6	propane			12,5 - < 20 %		
	200-827-9	601-003-00-5	01-2119486944-21			
	Flam. Gas 1, Liquefied gas; H22	0 H280	•			
106-97-8	butane			10 - < 12,5 %		
	203-448-7	601-004-00-0	01-2119474691-32			
	Flam. Gas 1, Liquefied gas; H22	0 H280	•			
75-28-5	isobutane			10 - < 12,5 %		
	200-857-2	601-004-00-0	01-2119485395-27			
	Flam. Gas 1, Liquefied gas; H22	0 H280	•			
1330-20-7	xylene			5 - < 10 %		
	215-535-7	601-022-00-9	01-2119488216-32			
	Flam. Liq. 3, Acute Tox. 4, Acute	Tox. 4, Skin Irrit. 2; H226 H	332 H312 H315			
128601-23-0	Hydrocarbons, C9, aromatics			2,5 - < 5 %		
	918-668-5		01-2119455851-35			
	Flam. Liq. 3, STOT SE 3, STOT H411	SE 3, Asp. Tox. 1, Aquatic C	hronic 2; H226 H335 H336 H304			
100-41-4	ethylbenzene	2,5 - < 5 %				
	202-849-4	601-023-00-4	01-2119489370-35			
	Flam. Liq. 2, Acute Tox. 4, STOT	RE 2, Asp. Tox. 1; H225 H3	32 H373 H304			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
67-64-1	200-662-2 acetone; propan-2-one; propanone				
	inhalation: LC5 mg/kg	50 = 76 mg/l (vapours); dermal: LD50 = 7426-15800 mg/kg; oral: LD50 = 5800			
106-97-8	203-448-7	butane	10 - < 12,5 %		
	inhalation: LC5	50 = 273000 ppm (gases)			
1330-20-7	215-535-7	xylene	5 - < 10 %		
		50 = 6350 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = al: LD50 = 8700 mg/kg			
128601-23-0	918-668-5	Hydrocarbons, C9, aromatics	2,5 - < 5 %		
	inhalation: LC5 mg/kg	50 = 10,2 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >6800			
100-41-4	202-849-4	ethylbenzene	2,5 - < 5 %		
	1	50 = 17,2 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = oral: LD50 = 3500 mg/kg			

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures



according to UK REACH Regulation

## **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 4 of 17

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After contact with skin

If skin irritation occurs: Get medical advice/attention.

## After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. In case of eye irritation consult an ophthalmologist.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

#### 4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water fog.

## Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

## 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

## For emergency responders

For further specification, refer to section 8 of the SDS.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up



according to UK REACH Regulation

## **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 5 of 17

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

#### For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

#### Other information

No information available.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means

#### Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking.

Heating causes rise in pressure with risk of bursting.

## Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Do not keep the container sealed. Keep container dry.

Keep in a cool, well-ventilated place.

Keep away from heat. Protect from direct sunlight.

#### 7.3. Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters



according to UK REACH Regulation

# **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 6 of 17

# **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

# **Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol		Post shift



according to UK REACH Regulation

# **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 7 of 17

## **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
67-64-1	acetone; propan-2-one; propanone		•			
Worker DNEL,	long-term	inhalation	systemic	1210 mg/m³		
Worker DNEL,	acute	inhalation	local	2420 mg/m³		
Worker DNEL,	long-term	dermal	systemic	186 mg/kg bw/day		
Consumer DNI	EL, long-term	inhalation	systemic	200 mg/m³		
Consumer DNI	EL, long-term	dermal	systemic	62 mg/kg bw/day		
Consumer DNI	EL, long-term	oral	systemic	62 mg/kg bw/day		
,						
1330-20-7	xylene	·	·			
Worker DNEL,	long-term	dermal	systemic	108 mg/kg bw/day		
Worker DNEL,	acute	inhalation	systemic	289 mg/m³		
Worker DNEL,	acute	inhalation	local	174 mg/m³		
Worker DNEL,	long-term	inhalation	systemic	77 mg/m³		
Consumer DNI	EL, long-term	oral	systemic	1,6 mg/kg bw/day		
Consumer DNI	EL, long-term	dermal	systemic	108 mg/kg bw/day		
Consumer DNI	EL, acute	inhalation	systemic	174 mg/m³		
Consumer DNI	EL, acute	inhalation	local	174 mg/m³		
Consumer DNI	EL, long-term	inhalation	systemic	14,8 mg/m³		
,						
128601-23-0	Hydrocarbons, C9, aromatics					
Worker DNEL,	long-term	inhalation	systemic	150 mg/m³		
Worker DNEL,	long-term	dermal	systemic	25 mg/kg bw/day		
Consumer DNI	EL, long-term	inhalation	systemic	32 mg/m³		
Consumer DNI	EL, long-term	dermal	systemic	11 mg/kg bw/day		
Consumer DNI	EL, long-term	oral	systemic	11 mg/kg bw/day		
j						
100-41-4	ethylbenzene					
Worker DNEL,	long-term	inhalation	systemic	77 mg/m³		
Worker DNEL, long-term		inhalation	local	293 mg/m³		
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day		
Consumer DNI	EL, long-term	inhalation	systemic	15 mg/m³		
Consumer DNI	EL, long-term	oral	systemic	1,6 mg/kg bw/day		



according to UK REACH Regulation

# **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 8 of 17

#### **PNEC values**

CAS No	Substance			
Environment	al compartment	Value		
67-64-1	acetone; propan-2-one; propanone			
Freshwater	reshwater			
Marine water	T	1,06 mg/l		
Freshwater s	sediment	30,4 mg/kg		
Marine sedin	nent	3,04 mg/kg		
Micro-organia	sms in sewage treatment plants (STP)	100 mg/l		
Soil		29,5 mg/kg		
1330-20-7	xylene	·		
Freshwater	•	0,327 mg/l		
Marine water		0,327 mg/l		
Freshwater s	sediment	12,46 mg/kg		
Marine sedin	nent	12,46 mg/kg		
Micro-organia	sms in sewage treatment plants (STP)	6,58 mg/l		
Soil		2,31 mg/kg		
100-41-4	ethylbenzene	·		
Freshwater		0,1 mg/l		
Marine water	r	0,01 mg/l		
Freshwater sediment		13,7 mg/kg		
Marine sediment 1,37 m		1,37 mg/kg		
Secondary poisoning 0,02 mg/kg				
Micro-organia	sms in sewage treatment plants (STP)	9,6 mg/l		
Soil		2,68 mg/kg		

# 8.2. Exposure controls







## Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

Eye glasses with side protection (EN 166)

#### Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time::

PVA (Polyvinyl alcohol), Breakthrough time::

NBR (Nitrile rubber), Breakthrough time::

Butyl caoutchouc (butyl rubber), Breakthrough time::

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.



according to UK REACH Regulation

## **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 9 of 17

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

## Skin protection

Wear anti-static footwear and clothing

#### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A/P2

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol Colour: silver grey Odour: like: Solvent Odour threshold: not determined

Test method

Melting point/freezing point: not determined Boiling point or initial boiling point and not applicable

boiling range:

Flammability: not applicable Lower explosion limits: 1,5 vol. % Upper explosion limits: 13.0 vol. % Flash point: not applicable

365 °C DIN 51794 Auto-ignition temperature:

Decomposition temperature: not determined pH-Value: not determined not determined Viscosity / kinematic: The study does not need to be conducted Water solubility: because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 3500 hPa

(at 20 °C)

Density (at 20 °C): 0,7 g/cm<sup>3</sup> Relative vapour density: not determined

## 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties not determined Self-ignition temperature

> Solid: not applicable not applicable Gas:

Oxidizing properties not determined

Other safety characteristics

Evaporation rate: not applicable Solvent separation test: not determined Solvent content: 96,4 % Solid content: 3,6 % Viscosity / dynamic: not determined



## **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 10 of 17

#### **Further Information**

No information available.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

#### 10.5. Incompatible materials

No information available.

## 10.6. Hazardous decomposition products

Carbon monoxide

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation gas) > 20000 ppm



## **Safety Data Sheet**

according to UK REACH Regulation

## **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 11 of 17

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-64-1	acetone; propan-2-one; p	oropanone			•	
	oral	LD50 mg/kg	5800	Rat	RTECS	
	dermal	LD50 15800 mg/k	7426- sg	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50	76 mg/l	Rat		
106-97-8	butane					
	inhalation (4 h) gas	LC50 ppm	273000	Rat	GESTIS	
1330-20-7	xylene					
	oral	LD50 mg/kg	8700	Rat		
	dermal	LD50 mg/kg	2000	Rabbit		
	inhalation (4 h) vapour	LC50	6350 mg/l	Rat		
	inhalation gas	ATE ppm	4500			
128601-23-0	Hydrocarbons, C9, arom	atics				
	oral	LD50 mg/kg	>6800	Rat		
	dermal	LD50 mg/kg	>2000	Rabbit		
	inhalation (4 h) vapour	LC50	10,2 mg/l	Rat		
100-41-4	ethylbenzene	_				
	oral	LD50 mg/kg	3500	Rat	GESTIS	
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat		
	inhalation gas	ATE ppm	4500			

## Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

# Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

## STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards



according to UK REACH Regulation

# **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 12 of 17

## **Endocrine disrupting properties**

Endocrine disrupting potential No information available.

# **Further information**

There are no data available on the preparation/mixture itself.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; p	ropanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia Magna		
	Algae toxicity	NOEC mg/l	4740	2 d	Selenastrum capricornutum		
1330-20-7	xylene						
	Acute fish toxicity	LC50 mg/l	13,5	96 h	Daphnia magna (Big water flea)		
	Acute crustacea toxicity	EC50	7,4 mg/l	48 h	fish		
128601-23-0	Hydrocarbons, C9, aroma	tics					
	Acute fish toxicity	LC50	9,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50	2,9 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50	3,2 mg/l	48 h	Daphnia magna (Big water flea)		

## 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
67-64-1	acetone; propan-2-one; propanone				
	OECD 301 B	91%	28		
	Readily biodegradable (according to OECD criteria).				

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	
106-97-8	butane	2,89
1330-20-7	xylene	3
100-41-4	ethylbenzene	3,15



## **Safety Data Sheet**

according to UK REACH Regulation

# Revision date: 20.11.2024 Product code: 31615 Page 13 of 17

#### BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		
1330-20-7	xylene	,	Oncorhynchus mykiss (Rainbow trout)	

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

#### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

## List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

#### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

#### Contaminated packaging

Remove according to the regulations.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1





according to UK REACH Regulation

DINITROL 8050 Spray

Revision date: 20.11.2024 Product code: 31615 Page 14 of 17

Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant: no

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

 14.3. Transport hazard class(es):
 2.1

 14.4. Packing group:

 Hazard label:
 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Gases under pressure

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from"



## **Safety Data Sheet**

according to UK REACH Regulation

## **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 15 of 17

class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 96,4 % (670,1 g/l)

paints and varnishes:

Subcategory according to Directive

2004/42/EC:

Special finishes - All types, VOC limit value: 840 g/l

Information according to Directive P3a FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant

disappearances and thefts should be reported to the relevant national contact point.

#### **Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

## National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

#### Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

## 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: Hydrocarbons, C9, aromatics

## **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 3,8,9,11,12,15,16.



according to UK REACH Regulation

## **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 16 of 17

#### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols Liquefied gas

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure				
Aerosol 1; H222-H229	On basis of test data				
Eye Irrit. 2; H319	Bridging principle "Aerosols"				
STOT SE 3; H336	Bridging principle "Aerosols"				
Aquatic Chronic 3; H412	Calculation method				

## Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Further Information**

**EUH066** 

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Repeated exposure may cause skin dryness or cracking.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL 8050 Spray**

Revision date: 20.11.2024 Product code: 31615 Page 17 of 17

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)