

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 1 of 10

1. Identification

Product identifier

DINITROL HIGH PERFORMANCE WAX SPRAY

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980
E-mail: msds@dinol.com
Contact person: Labor
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

Supplier

Company name: DINOL U.S. Inc.
Street: 8500 Cotter Street, Lewis Center
Place: USA-43035 Ohio
Telephone: 740-548-1656
E-mail: info@dinolus.com
Internet: www.dinol.com

Telefax: 740-548-1657

Emergency telephone number: 3E Company Emergency +1-866-404-4230

2. Hazard identification

Classification of the substance or mixture

WHMIS 2015

Gases under pressure: Compressed gas
Serious eye damage/eye irritation: Eye Irrit. 2A
Respiratory or skin sensitization: Skin Sens. 1B
Specific target organ toxicity - single exposure: STOT SE 3 (narcotic effects)
Aspiration hazard: Asp. Tox. 1

Label elements

WHMIS 2015

Signal word: Danger

Pictograms:



Hazard statements

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Harmful if inhaled.
Causes serious eye irritation.
May cause an allergic skin reaction.

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 2 of 10

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Contaminated work clothing should not be allowed out of the workplace.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

IF ON SKIN: Wash with plenty of water.

Do NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Specific treatment (see on this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

Other hazards

No information available.

3. Composition/information on ingredients

Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	30 - < 60 % (*)
74-98-6	propane	7 - < 13 % (*)
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	5 - < 10 % (*)
109-66-0	pentane	5 - < 10 % (*)
61789-86-4	calcium sulfonate	1 - < 5 % (*)

(*) The actual concentration is withheld as a trade secret.

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w)

DMSO extract (IP 346)).

4. First-aid measures

Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 3 of 10

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Change contaminated clothing.

Wash with plenty of water/Soap.

If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

Most important symptoms and effects, whether acute or delayed

No further relevant information available.

Indication of immediate medical attention and special treatment needed

No further relevant information available.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Extinguishing powder Water spray jet alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

Specific hazards arising from the hazardous product

No further relevant information available.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Wear personal protection equipment. Avoid contact with skin, eyes and clothes.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow to enter into surface water or drains.

Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 4 of 10

For cleaning up

Provide adequate ventilation.
Clear contaminated areas thoroughly.
Do not rinse down with water.

Other information

No information available.

Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.
Remove contaminated, saturated clothing immediately.
Do not breathe gas/vapour/aerosol.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
Do not keep the container sealed. Keep container dry.
Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

8. Exposure controls/Personal protection

Control parameters

Exposure limits (ACGIH)

CAS No	Chemical name	ppm	mg/m ³	Category	Origin
75-28-5	Butane: isobutane	1000	2370	STEL (15 min)	ACGIH-2024
106-97-8	Butane: n-butane	1000	2370	STEL (15 min)	ACGIH-2024
109-66-0	Pentane: n-pentane	1000	2950	TWA (8 h)	ACGIH-2024
74-98-6	Propane	-	-	Asphyxiant	ACGIH-2024

Exposure controls

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 5 of 10



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Recommended glove articles :

FKM (fluoro rubber) penetration time (maximum wearing period): 480 min.

NBR (Nitrile rubber) penetration time (maximum wearing period): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: A/X

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	whitish transparent
Odour:	characteristic
Odour threshold:	not determined

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-44,5 °C
Flammability:	not applicable
Lower explosive limits:	0,6 vol. %
Upper explosive limits:	10,9 vol. %
Flash point:	-97 °C DIN 53213
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 6 of 10

Vapour pressure:	3500 hPa
(at 20 °C)	
Density (at 20 °C):	0,7 g/cm ³ DIN 51757
Relative vapour density:	not determined

Other information

Information with regard to physical hazard classes

Explosive properties	
not determined	
Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
not determined	

Other safety characteristics

Evaporation rate:	not determined
Solvent content:	77,5 %
Solid content:	20,6 %
Viscosity / dynamic:	not determined

Further Information

No information available.

10. Stability and reactivity

Reactivity

No further relevant information available.

Chemical stability

No hazardous reaction when handled and stored according to provisions.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid

No further relevant information available.

Incompatible materials

No further relevant information available.

Hazardous decomposition products

Carbon monoxide

11. Toxicological information

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 4,545 mg/l

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 7 of 10

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 4951 mg/kg	Rat		
	dermal	LD50 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
109-66-0	pentane				
	oral	LD50 >5000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 25,3 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

May cause an allergic skin reaction. (calcium sulfonate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information

Persistence and degradability

No further relevant information available.

Bioaccumulative potential

No further relevant information available.

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 8 of 10

Mobility in soil

No further relevant information available.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No further relevant information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

Contaminated packaging

Dispose of waste according to applicable legislation.

14. Transport information

Canadian TDG

UN number:

UN 1950

Proper shipping name:

AEROSOLS

Hazard classes:

2.1

Hazard label:

2.1



Limited quantity:

1 L

Marine transport (IMDG)

UN number or ID number:

UN 1950

United Nations proper shipping name:

AEROSOLS

Transport hazard class(es):

2.1

Packing group:

-

Hazard label:

2.1



Marine pollutant:

no

Special Provisions:

63, 190, 277, 327, 344, 959

Limited quantity:

1000 mL

Excepted quantity:

E0

EmS:

F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number:

UN 1950

United Nations proper shipping name:

AEROSOLS, flammable

name:

Transport hazard class(es):

2.1

Packing group:

-

Safety Data Sheet

according to WHMIS

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 9 of 10

Hazard label:

2.1



Special Provisions:

A145 A167 A802

Limited quantity Passenger:

30 kg G

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

Other applicable information (air transport)

E0

Passenger-LQ: Y203

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

15. Regulatory information

Canadian regulations

DSL/NDSL inventory status

Substance/product listed in the following inventories: DSL/NDSL

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

16. Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Further Information

The above information describes exclusively the safety requirements of the product and is based on our

Safety Data Sheet

according to WHMIS

DINITROL HIGH PERFORMANCE WAX SPRAY

Revision date: 20.05.2025

Product code: 20180

Page 10 of 10

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)