

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL ML Spray

UFI: AR6D-SMAC-0002-0GRG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH
Street: Pyrmonter Strasse 76
Place: D-32676 Luegde
Telephone: + 49 (0) 5281 982980
E-mail: msds@dinol.com
Contact person: Labor
Responsible Department: msds@dinol.com

Telefax: + 49 (0) 5281 9829860

Supplier

Company name: Leading Solvent Supplies Limited
Street: Marston Business Park, Rudgate
Place: GB Tockwith, York YO26 7QF
E-mail: enquiries@leading-solvents.co.uk
Internet: www.leading-solvents.co.uk

1.4. Emergency telephone number:

Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 2 of 14

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe mist/vapours/spray.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

- EUH208 Contains calcium sulfonate. May produce an allergic reaction.
Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229

Precautionary statements

P210-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			50 - < 55 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas; H220 H280			
106-97-8	n-butane			10 - < 15 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1A, Compressed gas; H220 H280			
61789-86-4	calcium sulfonate			1 - < 5 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether			< 1 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H302 H315 H319			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	50 - < 55 %
		inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
61789-86-4	263-093-9	calcium sulfonate	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5000 mg/kg Skin Sens. 1B; H317: >= 10 - 100	
111-76-2	203-905-0	2-butoxyethanol; ethylene glycol monobutyl ether	< 1 %
		inhalation: ATE 3 mg/l (vapours); oral: ATE 1200 mg/kg	

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Wash with plenty of water/Soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 4 of 14

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.
Clear contaminated areas thoroughly.
Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.
Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 5 of 14

Anti-corrosive coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 6 of 14

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Consumer DNEL, long-term		oral	systemic	125 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	871 mg/m³
Consumer DNEL, long-term		inhalation	systemic	185 mg/m³
61789-86-4	calcium sulfonate			
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm²
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm²
Consumer DNEL, long-term		oral	systemic	0,8333 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m³
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether			
Consumer DNEL, acute		oral	systemic	13,4 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	3,2 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	75 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	44,5 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	38 mg/kg bw/day
Worker DNEL, acute		inhalation	local	246 mg/m³
Worker DNEL, long-term		inhalation	systemic	98 mg/m³
Consumer DNEL, acute		inhalation	systemic	633 mg/m³
Worker DNEL, acute		inhalation	systemic	633 mg/m³
Consumer DNEL, acute		inhalation	local	123 mg/m³
Consumer DNEL, long-term		inhalation	systemic	49 mg/m³

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 7 of 14

PNEC values

CAS No	Substance	
Environmental compartment		Value
61789-86-4	calcium sulfonate	
Freshwater		1 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Recommended glove articles

NBR (Nitrile rubber) - (> = 0,12 mm), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141), Filter material/medium: AX

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	brown
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-44 °C

Test method

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 8 of 14

Flammability:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	< - 20 °C
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents
not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure:

8300 hPa

(at 20 °C)

Density (at 20 °C):

0,75 g/cm³ DIN 51757

Relative vapour density:

not determined

Particle characteristics:

not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not determined

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

65,3 %

Solid content:

36,2%

Softening point:

not determined

Viscosity / dynamic:

not determined

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 9 of 14

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 50000 ppm

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 5000 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether				
	oral	ATE 1200 mg/kg			
	inhalation vapour	ATE 3 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains calcium sulfonate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 10 of 14

Additional information on tests

No information available.

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether					
	Acute fish toxicity	LC50 mg/l	1490	96 h	Lepomis macrochirus	

12.2. Persistence and degradability

No further relevant information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
		80%		
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

No further relevant information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether	0,81 (25°C)

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No further relevant information available.

Further information

No further relevant information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 11 of 14

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 12 of 14



Marine pollutant: no
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Limited quantity Passenger: 1 L
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning : gas

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.
Category C, Clear of living quarters.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 13 of 14

Entry 29, Entry 40, Entry 75

Directive 2004/42/EC on VOC in
paints and varnishes:
Information according to Directive
2012/18/EU (SEVESO III):

65,3 %
490,0 g/l
P3a FLAMMABLE AEROSOLS

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

55230

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 6,8,9,11,15.

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Compressed gas

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Safety Data Sheet

according to UK REACH Regulation

DINITROL ML Spray

Revision date: 14.04.2025

Product code: 21708

Page 14 of 14

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
STOT SE 3; H336	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains calcium sulfonate. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)