DINOL

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL ML Spray

Revision date: 04/14/2025

Product code: 21708

Page 1 of 10

1. Identification

Product identifier

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

DINITROL ML Spray

Anti-corrosive coating

Uses advised against

No further relevant information available.

Details of the supplier of the safety data sheet

Manufacturer

	Wallulaciulei		
	Company name:	DINOL GmbH	
Street:		Pyrmonter Strasse 76	
	Place:	D-32676 Luegde	
	Telephone:	+ 49 (0) 5281 982980	Telefax:+49 (0) 5281 9829860
	E-mail:	msds@dinol.com	
	Contact person:	Labor	
	Responsible Department:	msds@dinol.com	
	Supplier		
	Company name:	DINOL U.S. Inc.	
	Street:	8500 Cotter Street, Lewis Center	
	Place:	USA-43035 Ohio	
	Telephone:	740-548-1656	Telefax: 740-548-1657
	E-mail:	info@dinolus.com	
	Internet:	www.dinol.com	
E	mergency phone number:	3E Company Emergency +1-866-404-4230	

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200


Flammable aerosols: Flam. Aerosol 1 Gases under pressure: Compressed gas Respiratory or skin sensitization: Skin Sens. 1 Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects) Aspiration hazard: Asp. Tox. 1

Label elements

29 CFR Part 1910.1200

Signal word:

Pictograms:



Hazard statements

Extremely flammable aerosol Contains gas under pressure; may explode if heated May be fatal if swallowed and enters airways May cause an allergic skin reaction May cause drowsiness or dizziness

Danger



according to 29 CFR 1910.1200(g)

DINITROL ML Spray

Revision date: 04/14/2025

Product code: 21708

Page 2 of 10

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Hazards not otherwise classified

No information available.

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	CAS No Components	
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	54.6 %
61789-86-4	calcium sulfonate	2.9 %
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether	0.9 %

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

4. First-aid measures

Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Wash with plenty of water/Soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Call a physician immediately. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

No further relevant information available.



according to 29 CFR 1910.1200(g)

DINITROL ML Spray

Revision date: 04/14/2025

Product code: 21708

Page 3 of 10

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

Specific hazards arising from the chemical

No further relevant information available.

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Supress gases/vapors/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fume/vapor/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For emergency responders

For further specification, refer to section 8 of the SDS.

Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Do not allow to enter into surface water or drains.

Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation. Clear contaminated areas thoroughly. Do not rinse down with water.

Other information

No information available.

Reference to other sections

Safe handling: see section 7 Personal protection equipment (PPE): see section 8 Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fume/vapor/spray.



according to 29 CFR 1910.1200(g)

DINITROL ML Spray

Revision date: 04/14/2025

Product code: 21708

Page 4 of 10

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No	Substance	ppm	mg/m³	f/cc	Category	Origin
111-76-2	2-Butoxyethanol (EGBE)	20	97		TWA (8 h)	ACGIH-2024
111-76-2	2-Butoxyethanol	50	240		TWA (8 h)	PEL
		5	24		TWA (8 h)	REL
75-28-5	Butane: isobutane	1000	2370		STEL (15 min)	ACGIH-2024
106-97-8	Butane: n-butane	1000	2370		STEL (15 min)	ACGIH-2024
75-28-5	Isobutane	800	1900		TWA (8 h)	REL
106-97-8	n-Butane	800	1900		TWA (8 h)	REL
74-98-6	Propane	1000	1800		TWA (8 h)	PEL
		1000	1800		TWA (8 h)	REL
		-	-		Asphyxiant	ACGIH-2024
						1

Biological Exposure Indices (BEI-ACGIH)

CAS No	Substance	Determinant	Value	Test material	Sampling time
111-76-2	2-BUTOXYETHANOL	Butoxyacetic acid (BAA) (with hydrolysis, creatinine)	200 mg/g	urine	End of shift

Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.



according to 29 CFR 1910.1200(g)

Revision date: 04/14/2025

DINITROL ML Spray Product code: 21708

Page 5 of 10

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eve/face protection

Eye glasses with side protection (EN 166)

Hand protection

Recommended glove articles NBR (Nitrile rubber) - (> = 0,12 mm), Breakthrough time:: 480 min. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Protective gloves have to be replaced at the first sign of deterioration. Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: AX

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Color:	Aerosol
•	brown
Odor: Odour threshold:	characteristic not determined
Odour threshold.	not determined
Melting point/freezing point:	not determined
Boiling point or initial boiling point and	-44 °C
boiling range:	
Flammability:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	< - 20 °C
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted
	because the substance is known to be
	insoluble in water.
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapor pressure:	8300 hPa
(at 20 °C)	6300 m a
Density (at 20 °C):	0.75 g/cm³
Relative vapour density:	not determined
Particle characteristics:	not applicable
Other information	
Information with record to physical her	

Information with regard to physical hazard classes Explosive properties not determined

Test method

DIN 51757

according to 29 CFR 1910.1200(g)

	DINITROL ML Spray	
Revision date: 04/14/2025	Product code: 21708	Page 6 of 10
Sustained combustibility:	No data available	
Self-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	
Oxidizing properties Not oxidising.		
Other safety characteristics		
Evaporation rate:	not determined	
Solvent separation test:	not determined	
Solvent content:	65,3 %	
Solid content:	36,2%	
Softening point:	not determined	
Viscosity / dynamic:	not determined	
Further Information		
No information available.		
10. Stability and reactivity		
<u>Reactivity</u> No further relevant information avail <u>Chemical stability</u>	able.	
Stability:	Stable	
The product is stable under storage		
Possibility of hazardous reactions		
Hazardous reactions:	Will not occur	
No known hazardous reactions.		
<u>Conditions to avoid</u> Keep away from sources of heat (e. mixtures with air.	g. hot surfaces), sparks and open flames. Vapors may forr	n explosive
Incompatible materials No information available.		
Hazardous decomposition products		
Carbon monoxide		
11. Toxicological information		
Route(s) of Entry No information available.		
Information on toxicological effects		
Acute toxicity		
Based on available data, the classifi	cation criteria are not met.	
ATEmix calculated ATE (oral) > 2000 mg/kg; ATE (dern	nal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm	



according to 29 CFR 1910.1200(g)

DINITROL ML Spray

Revision date: 04/14/2025

Product code: 21708

Page 7 of 10

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 5000 mg/l	Rat		
61789-86-4	calcium sulfonate				
	oral	LD50 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether				
	oral ATE 1200 mg/kg inhalation vapour ATE 3 mg/l				

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

May cause an allergic skin reaction (calcium sulfonate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (OSHA):	No ingredient of this mixture is listed.
Carcinogenicity (IARC):	2-Butoxyethanol (CAS 111-76-2) is listed in group 3.
Carcinogenicity (NTP):	No ingredient of this mixture is listed.

Aspiration hazard

May be fatal if swallowed and enters airways

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

12. Ecological information

DINITROL ML Spray

Revision date: 04/14/2025

Product code: 21708

Page 8 of 10

Persistence and degradability

No further relevant information available.

Bioaccumulative potential

No further relevant information available.

Mobility in soil

No further relevant information available.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No further relevant information available.

Further information

No further relevant information available.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes. List of proposed waste codes/waste designations in accordance with EWC:

Contaminated packaging

Remove according to the regulations.

14. Transport information

U.S. DOT 49 CFR 172.101

<u>UN number or ID number:</u> <u>Proper shipping name:</u> <u>Transport hazard class(es):</u> <u>Packing group:</u> Hazard label:	UN 1139 Coating solution 3 III 3
Marine transport (IMDC)	3
Marine transport (IMDG)	UN 1950
UN number or ID number:	
UN proper shipping name:	AEROSOLS
<u>Transport hazard class(es):</u>	2.1
Packing group:	-
Hazard label:	2.1
Marine pollutant:	no
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U
Air transport (ICAO-TI/IATA-DGR) <u>UN number or ID number:</u> <u>UN proper shipping name:</u>	UN 1950 AEROSOLS, FLAMMABLE



according to 29 CFR 1910.1200(g)

Revision date: 04/14/2025	DINITROL ML Spray Product code: 21708	Page 9 of 10		
<u>Transport hazard class(es):</u> <u>Packing group:</u> Hazard label:	2.1 - 2.1			
Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	1 L Y203 E0 203 75 kg 203 150 kg			
Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	No			
ENVIRONMENTALLY HAZARDOUS: No Special precautions for user Warning : gas Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable Other applicable information SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. Category C, Clear of living quarters.				
15. Regulatory information				
U.S. Regulations				
National Inventory TSCA All components of the product are publicly listed or excluded. National regulatory information SARA Section 311/312 Hazards: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (-): Fire hazard, Immediate (acute)				

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (-): Fire hazard, Immediate (acute) health hazard Propane (74-98-6): Fire hazard, Sudden release of pressure Butane (106-97-8): Fire hazard, Sudden release of pressure Isobutane (75-28-5): Fire hazard, Sudden release of pressure calcium sulfonate (61789-86-4): Immediate (acute) health hazard 2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2): Immediate (acute) health hazard Clean Air Act Section 112(r): Propane (74-98-6): Threshold quantities = 10,000 lbs.

Butane (106-97-8): Threshold quantities = 10,000 lbs.

DINOL

Safety Data Sheet

according to 29 CFR 1910.1200(g)

DINITROL ML Spray

Revision date: 04/14/2025

Product code: 21708

Page 10 of 10

Isobutane (75-28-5): Threshold quantities = 10,000 lbs.

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Directive 2004/42/EC on VOC in 65,3 % paints and varnishes: 490,0 g/l

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

55230

16. Other information

Hazardous Materials Identification System (HMIS)				
Health:	0			
Flammability:	4			
Physical Hazard:	3			
NFPA Hazard Ratings				
Health:	0			
Flammability:	4			
Reactivity:	3			
Unique Hazard:	none			
Changes				
Revision date:	04/14/2025			
Revision No:	1,4			



This data sheet contains changes from the previous version in section(s): 6,8,9,11,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)