

# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 1 of 14

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**DINITROL** Penetrant LT Spray

UFI: 6D0D-AM7Y-A00F-27MQ

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Anti-corrosive coating

#### Uses advised against

No further relevant information available.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

E-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

**Supplier** 

Company name:

Street:

Marston Business Park, Rudgate
Place:

GB Tockwith, York YO26 7QF

E-mail:

enquiries@leading-solvents.co.uk

www.leading-solvents.co.uk

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Aerosol 1; H222-H229 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

# **GB CLP Regulation**

#### Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Danger

Pictograms:





## **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 2 of 14

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains calcium sulfonate. May produce an allergic reaction.

Restricted to professional users.

#### Additional advice on labelling

The classification of the aerosol was carried out according to EC 1272/2008, Annex 1, point 1.1.3.7.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





# **Hazard statements**

H222-H229

# **Precautionary statements**

P210-P211-P251-P410+P412

# 2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures



according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 3 of 14

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)		•	
	Hydrocarbons, C9-C11, n-alkanes,	isoalkanes, cyclics, <2% aromatics	3	50 - < 55 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox	. 1; H226 H336 H304 EUH066		
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas; H	220 H280		
106-97-8	n-butane		10 - < 15 %	
	203-448-7		01-2119474691-32	
	Flam. Gas 1A, Compressed gas; H	220 H280		
61789-86-4	calcium sulfonate			1 - < 5 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317	•	•	
111-76-2	2-butoxyethanol; ethylene glycol me	onobutyl ether		< 1 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H302 H315 H319			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

opcome co.	101 <b>=</b> 1111110, 111 14	0.010 4114 7.11	
CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	50 - < 55 %
	inhalation: LC mg/kg	50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000	
61789-86-4	263-093-9	calcium sulfonate	1 - < 5 %
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = 5000 mg/kg	
111-76-2	203-905-0	2-butoxyethanol; ethylene glycol monobutyl ether	< 1 %
_	inhalation: AT	E 3 mg/l (vapours); oral: ATE 1200 mg/kg	

# **Further Information**

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

## **General information**

Remove contaminated, saturated clothing immediately.

#### After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After contact with skin

Wash with plenty of water/Soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

# After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 4 of 14

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Call a physician immediately. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

# 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media

Carbon dioxide (CO2), Extinguishing powder, Water spray jet In case of major fire and large quantities: Water spray jet, alcohol resistant foam

### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

No further relevant information available.

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

# For emergency responders

For further specification, refer to section 8 of the SDS.

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Do not allow to enter into surface water or drains.

## 6.3. Methods and material for containment and cleaning up

### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

# For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

### Other information

No information available.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13



according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 5 of 14

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

## Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Hints on joint storage

Not required.

# Further information on storage conditions

Keep container tightly closed.

#### 7.3. Specific end use(s)

No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### **Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	,	butoxyacetic acid (creatinine)	240 mmol/mol		Post shift



according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 6 of 14

# **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyc	lics, <2% aromatics	•	
Consumer DN	NEL, long-term	oral	systemic	125 mg/kg bw/day
Worker DNEL	_, long-term	dermal	systemic	208 mg/kg bw/day
Consumer DN	NEL, long-term	dermal	systemic	125 mg/kg bw/day
Worker DNEL	_, long-term	inhalation	systemic	871 mg/m³
Consumer DN	NEL, long-term	inhalation	systemic	185 mg/m³
61789-86-4	calcium sulfonate			
Worker DNEL	_, long-term	dermal	systemic	3,33 mg/kg bw/day
Worker DNEL	_, long-term	dermal	local	1,03 mg/cm <sup>2</sup>
Consumer DN	NEL, long-term	inhalation	systemic	2,9 mg/m³
Consumer DN	NEL, long-term	dermal	systemic	1,667 mg/kg bw/day
Consumer DN	NEL, long-term	dermal	local	0,513 mg/cm <sup>2</sup>
Consumer DN	NEL, long-term	oral	systemic	0,8333 mg/kg bw/day
Worker DNEL	_, long-term	inhalation	systemic	11,75 mg/m³
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether			
Consumer DN	NEL, acute	oral	systemic	13,4 mg/kg bw/day
Consumer DN	NEL, long-term	oral	systemic	3,2 mg/kg bw/day
Worker DNEL	_, long-term	dermal	systemic	75 mg/kg bw/day
Consumer DN	NEL, acute	dermal	systemic	44,5 mg/kg bw/day
Consumer DN	NEL, long-term	dermal	systemic	38 mg/kg bw/day
Worker DNEL	_, acute	inhalation	local	246 mg/m³
Worker DNEL	_, long-term	inhalation	systemic	98 mg/m³
Consumer DN	NEL, acute	inhalation	systemic	633 mg/m³
Worker DNEL		inhalation	systemic	633 mg/m³
Consumer DN	NEL, acute	inhalation	local	123 mg/m³
Consumer DN	NEL, long-term	inhalation	systemic	49 mg/m³



according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 7 of 14

#### **PNEC values**

CAS No	Substance	
Environmen	tal compartment	Value
61789-86-4	calcium sulfonate	
Freshwater		1 mg/l
Marine water	or .	1 mg/l
Freshwater	sediment	226000000 mg/kg
Marine sedi	ment	226000000 mg/kg
Secondary p	poisoning	16667 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	1000 mg/l
Soil		271000000 mg/kg

#### 8.2. Exposure controls



### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

### Individual protection measures, such as personal protective equipment

# Eye/face protection

Not required.

Recommended eye protection articles: Eye glasses with side protection (EN 166)

# **Hand protection**

Hand protection is not required.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

# Skin protection

Wear anti-static footwear and clothing

# **Respiratory protection**

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: AX

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: light beige
Odour: characteristic
Odour threshold: not determined

Test method

Melting point/freezing point: not determined



according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 8 of 14

Boiling point or initial boiling point and

-42 °C

boiling range:

Flammability: not applicable Lower explosion limits: 0,6 vol. % Upper explosion limits: 10,9 vol. %

Flash point: < - 20 °C DIN 53213

Auto-ignition temperature: > 200 °C
Decomposition temperature: not determined

pH-Value: The study does not need to be

conducted because the substance is known to be insoluble in water.

Viscosity / kinematic: not determined
Water solubility: practically insoluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 8300 hPa

(at 20 °C)

Density (at 20 °C): 0,818 g/cm<sup>3</sup> DIN 51757

Relative vapour density: not determined

## 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

The product is: not explosive.. In use, may form flammable/explosive vapour-air mixture.

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate:

Solvent separation test:

not determined
not determined
not determined
not determined
20,5 %
Solid content:

Viscosity / dynamic:

not determined
not determined

Further Information

No information available.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No further relevant information available.

# 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

# 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

# 10.5. Incompatible materials

No information available.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 9 of 14

#### 10.6. Hazardous decomposition products

Carbon monoxide

## **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix** calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name	Chamical name				
CAS NO	Chemical hame					
	Exposure route	Dose	Species	Source	Method	
	Hydrocarbons, C9-C11, ı	n-alkanes, isoalkanes, c	yclics, <2% aromatics			
	oral	LD50 > 5000 mg/kg	Rat			
	dermal	LD50 > 5000 mg/kg	Rabbit			
	inhalation (4 h) vapour	LC50 > 5000 mg/l	Rat			
61789-86-4	calcium sulfonate					
	oral	LD50 5000 mg/kg	Rat			
	dermal	LD50 > 2000 mg/kg	Rat			
111-76-2	2-butoxyethanol; ethylen	e glycol monobutyl ethe	r			
·	oral	ATE 1200 mg/kg				
•	inhalation vapour	ATE 3 mg/l				

### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

### Sensitising effects

Based on available data, the classification criteria are not met.

Contains calcium sulfonate. May produce an allergic reaction.

# Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Information on likely routes of exposure

No information available.

# Specific effects in experiment on an animal

No information available.



# **Safety Data Sheet**

according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 10 of 14

#### Additional information on tests

No information available.

#### **Practical experience**

No information available.

#### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

Endocrine disrupting potential No information available.

#### **Further information**

There are no data available on the preparation/mixture itself.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose	[h]   [d] Species	Source	Method			
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether							
	Acute fish toxicity	LC50 1490 mg/l	96 h Lepomis macrochirus					

#### 12.2. Persistence and degradability

No further relevant information available.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation		-		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
		80%			
	Readily biodegradable (according to OECD criteria).				

# 12.3. Bioaccumulative potential

No further relevant information available.

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
111-76-2	2-butoxyethanol; ethylene glycol monobutyl ether	0,81 (25°C)

#### 12.4. Mobility in soil

No further relevant information available.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No further relevant information available.

#### **Further information**

No further relevant information available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods



according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 11 of 14

#### **Disposal recommendations**

Dispose of waste according to applicable legislation. Do not mix with other wastes. List of proposed waste codes/waste designations in accordance with EWC:

#### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

#### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

#### Contaminated packaging

Remove according to the regulations.

### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS14.3. Transport hazard class(es):2

14.4. Packing group:
Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity:

Excepted quantity:

Transport category:

Tunnel restriction code:

D

Other applicable information (land transport)

E0

### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 12 of 14



Marine pollutant:

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U
Segregation group: bromates

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 1 L
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

Other applicable information (air transport)

E0

Passenger-LQ: Y203

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Warning: Flammable liquids

# 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

#### Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information



according to UK REACH Regulation

# **DINITROL Penetrant LT Spray**

Revision date: 30.04.2025 Product code: 21701 Page 13 of 14

Restrictions on use (REACH, annex XVII): Entry 3, Entry 29, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 71,52 % paints and varnishes: 585,1 g/l

Information according to Directive

P3a FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

#### **Additional information**

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to

chemical agents at work

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

**Additional information** 

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

#### **SECTION 16: Other information**

## Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols Compressed gas

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
STOT SE 3; H336	Bridging principle "Aerosols"

### Relevant H and EUH statements (number and full text)



# **Safety Data Sheet**

according to UK REACH Regulation

	DINITROL Penetrant LT Spray	
Revision date: 30.04.2025	Product code: 21701	Page 14 of 14
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H226	Flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H336	May cause drowsiness or dizziness.	
EUH066	Repeated exposure may cause skin dryness or cracking.	
EUH208	Contains calcium sulfonate. May produce an allergic reaction.	
Further Information		
present-day knowled	on describes exclusively the safety requirements of the product and is based on our ge. The information is intended to give you advice about the safe handling of the product data sheet, for storage, processing, transport and disposal. The information cannot be	

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.